

Bayesian Cluster Tool

Generated by Doxygen 1.9.1

Tue Jul 4 2023 15:21:44

1 Todo List	1
2 Class Index	3
2.1 Class List	3
3 File Index	5
3.1 File List	5
4 Class Documentation	7
4.1 AuxConfiguration Class Reference	7
4.1.1 Detailed Description	8
4.1.2 Constructor & Destructor Documentation	8
4.1.2.1 AuxConfiguration() [1/2]	8
4.1.2.2 AuxConfiguration() [2/2]	9
4.1.3 Member Function Documentation	9
4.1.3.1 ClusterR()	9
4.1.3.2 ClusterT()	9
4.1.3.3 configFile()	10
4.1.3.4 FromVector()	10
4.1.3.5 inputFile()	10
4.1.3.6 outputFile()	11
4.1.3.7 SetConfigFile()	11
4.1.3.8 SetInputFile()	11
4.1.3.9 SetOutputFile()	12
4.1.3.10 SetValidate()	12
4.1.3.11 validate()	12
4.2 Cluster Class Reference	13
4.2.1 Detailed Description	14
4.2.2 Constructor & Destructor Documentation	14
4.2.2.1 Cluster() [1/4]	14
4.2.2.2 Cluster() [2/4]	14
4.2.2.3 Cluster() [3/4]	15
4.2.2.4 Cluster() [4/4]	15
4.2.3 Member Function Documentation	15
4.2.3.1 GetParent()	15
4.2.3.2 operator+=(())	16
4.2.3.3 operator=() [1/2]	16
4.2.3.4 operator=() [2/2]	17
4.2.3.5 UpdateLogScore()	17
4.3 ClusterWrapper Struct Reference	17
4.3.1 Detailed Description	18
4.3.2 Member Function Documentation	18
4.3.2.1 operator<()	18

4.3.2.2 operator==()	18
4.4 Data Class Reference	19
4.4.1 Detailed Description	20
4.4.2 Constructor & Destructor Documentation	21
4.4.2.1 Data() [1/3]	21
4.4.2.2 Data() [2/3]	21
4.4.2.3 Data() [3/3]	21
4.4.3 Member Function Documentation	22
4.4.3.1 CalculateLocalizationScore()	22
4.4.3.2 dPhi()	22
4.4.3.3 dR()	23
4.4.3.4 dR2()	23
4.4.3.5 operator<()	24
4.4.3.6 operator=() [1/2]	24
4.4.3.7 operator=() [2/2]	24
4.4.3.8 Preprocess()	25
4.4.3.9 PreprocessLocalizationScores()	25
4.5 DataProxy Class Reference	26
4.5.1 Detailed Description	27
4.5.2 Constructor & Destructor Documentation	27
4.5.2.1 DataProxy() [1/3]	27
4.5.2.2 DataProxy() [2/3]	27
4.5.2.3 DataProxy() [3/3]	28
4.5.3 Member Function Documentation	28
4.5.3.1 Clusterize() [1/2]	28
4.5.3.2 Clusterize() [2/2]	28
4.5.3.3 GetCluster()	29
4.5.3.4 operator=() [1/2]	29
4.5.3.5 operator=() [2/2]	29
4.6 GSLInterpolator Class Reference	30
4.6.1 Detailed Description	31
4.6.2 Constructor & Destructor Documentation	31
4.6.2.1 GSLInterpolator() [1/5]	31
4.6.2.2 GSLInterpolator() [2/5]	31
4.6.2.3 GSLInterpolator() [3/5]	32
4.6.2.4 GSLInterpolator() [4/5]	32
4.6.2.5 GSLInterpolator() [5/5]	32
4.6.3 Member Function Documentation	34
4.6.3.1 Deriv()	34
4.6.3.2 Deriv2()	34
4.6.3.3 Eval()	35
4.6.3.4 Evaluate()	35

4.6.3.5 Integ()	36
4.6.3.6 operator=() [1/2]	37
4.6.3.7 operator=() [2/2]	37
4.6.3.8 SetData() [1/2]	38
4.6.3.9 SetData() [2/2]	38
4.7 LocalizationFile Class Reference	39
4.7.1 Detailed Description	39
4.7.2 Constructor & Destructor Documentation	39
4.7.2.1 LocalizationFile() [1/3]	39
4.7.2.2 LocalizationFile() [2/3]	40
4.7.2.3 LocalizationFile() [3/3]	40
4.7.3 Member Function Documentation	40
4.7.3.1 data()	40
4.7.3.2 ExtractRols() [1/3]	41
4.7.3.3 ExtractRols() [2/3]	41
4.7.3.4 ExtractRols() [3/3]	42
4.7.3.5 operator=() [1/2]	42
4.7.3.6 operator=() [2/2]	43
4.8 ManualRol Struct Reference	43
4.8.1 Detailed Description	43
4.9 Cluster::Parameter Struct Reference	44
4.9.1 Detailed Description	44
4.9.2 Member Function Documentation	44
4.9.2.1 alt_log_score()	45
4.9.2.2 log_score()	45
4.9.2.3 operator+=()	45
4.10 ProgressBar Class Reference	46
4.10.1 Detailed Description	47
4.10.2 Constructor & Destructor Documentation	47
4.10.2.1 ProgressBar()	47
4.10.3 Member Function Documentation	47
4.10.3.1 operator++()	47
4.11 ProgressTimer Struct Reference	48
4.11.1 Detailed Description	48
4.11.2 Constructor & Destructor Documentation	48
4.11.2.1 ProgressTimer()	48
4.12 Rol Class Reference	49
4.12.1 Detailed Description	50
4.12.2 Constructor & Destructor Documentation	50
4.12.2.1 Rol() [1/3]	50
4.12.2.2 Rol() [2/3]	51
4.12.2.3 Rol() [3/3]	51

4.12.3 Member Function Documentation	51
4.12.3.1 Clusterize()	51
4.12.3.2 data()	52
4.12.3.3 getArea()	52
4.12.3.4 getCentreX()	52
4.12.3.5 getCentreY()	53
4.12.3.6 id()	53
4.12.3.7 operator=() [1/2]	53
4.12.3.8 operator=() [2/2]	54
4.12.3.9 Preprocess()	54
4.12.3.10 ScanRT()	54
4.12.3.11 SetArea()	55
4.12.3.12 SetCentre()	55
4.13 Rolproxy Class Reference	56
4.13.1 Detailed Description	57
4.13.2 Constructor & Destructor Documentation	57
4.13.2.1 Rolproxy() [1/3]	57
4.13.2.2 Rolproxy() [2/3]	58
4.13.2.3 Rolproxy() [3/3]	58
4.13.3 Member Function Documentation	58
4.13.3.1 CheckClusterization()	58
4.13.3.2 Clusterize()	59
4.13.3.3 GetData()	59
4.13.3.4 operator=() [1/2]	60
4.13.3.5 operator=() [2/2]	60
4.13.3.6 ScanRT()	60
4.13.3.7 UpdateLogScore()	61
4.13.3.8 ValidateLogScore()	61
4.14 ScanConfiguration Class Reference	62
4.14.1 Detailed Description	64
4.14.2 Constructor & Destructor Documentation	64
4.14.2.1 ScanConfiguration() [1/5]	64
4.14.2.2 ScanConfiguration() [2/5]	65
4.14.2.3 ScanConfiguration() [3/5]	66
4.14.2.4 ScanConfiguration() [4/5]	66
4.14.2.5 ScanConfiguration() [5/5]	67
4.14.3 Member Function Documentation	67
4.14.3.1 alpha()	67
4.14.3.2 FromVector()	67
4.14.3.3 log_probability_sigma() [1/2]	68
4.14.3.4 log_probability_sigma() [2/2]	68
4.14.3.5 logAlpha()	68

4.14.3.6 logGammaAlpha()	69
4.14.3.7 logPb()	69
4.14.3.8 logPbDagger()	70
4.14.3.9 operator=() [1/2]	70
4.14.3.10 operator=() [2/2]	70
4.14.3.11 probability_sigma() [1/2]	71
4.14.3.12 probability_sigma() [2/2]	71
4.14.3.13 Rbounds()	71
4.14.3.14 SetAlpha()	72
4.14.3.15 SetPb()	72
4.14.3.16 SetRBins()	72
4.14.3.17 SetSigmaParameters()	73
4.14.3.18 SetTBins()	73
4.14.3.19 sigmabins() [1/2]	74
4.14.3.20 sigmabins() [2/2]	74
4.14.3.21 sigmabins2() [1/2]	74
4.14.3.22 sigmabins2() [2/2]	75
4.14.3.23 sigmacount()	75
4.14.3.24 sigmaspacing()	76
4.14.3.25 Tbounds()	76
4.15 ScanEntry Struct Reference	76
4.15.1 Detailed Description	77
4.15.2 Member Function Documentation	77
4.15.2.1 operator<()	77
4.15.2.2 operator==()	77
4.16 ScanConfiguration::tBounds Struct Reference	78
4.16.1 Detailed Description	78
5 File Documentation	79
5.1 include/BayesianClustering/API.hpp File Reference	79
5.1.1 Function Documentation	81
5.1.1.1 AutoRoi_Cluster_FullCallback()	81
5.1.1.2 AutoRoi_Cluster_SimpleCallback()	82
5.1.1.3 AutoRoi_Cluster_ToJson()	82
5.1.1.4 AutoRoi_Scan_FullCallback()	83
5.1.1.5 AutoRoi_Scan_SimpleCallback()	83
5.1.1.6 AutoRoi_Scan_ToJson()	83
5.1.1.7 ImageJRoi_Cluster_FullCallback()	84
5.1.1.8 ImageJRoi_Cluster_SimpleCallback()	84
5.1.1.9 ImageJRoi_Cluster_ToJson()	86
5.1.1.10 ImageJRoi_Scan_FullCallback()	86
5.1.1.11 ImageJRoi_Scan_SimpleCallback()	87

5.1.1.12 ImageJRoi_Scan_ToJson()	88
5.1.1.13 ManualRoi_Cluster_FullCallback()	88
5.1.1.14 ManualRoi_Cluster_SimpleCallback()	89
5.1.1.15 ManualRoi_Cluster_ToJson()	89
5.1.1.16 ManualRoi_Scan_FullCallback()	90
5.1.1.17 ManualRoi_Scan_SimpleCallback()	90
5.1.1.18 ManualRoi_Scan_ToJson()	91
5.2 include/BayesianClustering/Cluster.hpp File Reference	91
5.3 include/BayesianClustering/Configuration.hpp File Reference	92
5.4 include/BayesianClustering/Data.hpp File Reference	93
5.5 include/BayesianClustering/DataProxy.hpp File Reference	94
5.6 include/BayesianClustering/ImageJ_Roi.hpp File Reference	95
5.6.1 Function Documentation	95
5.6.1.1 DecodeBinaryRoi()	96
5.6.1.2 OpenRoiZipfile()	96
5.7 include/BayesianClustering/LocalizationFile.hpp File Reference	96
5.8 include/BayesianClustering/Precision.hpp File Reference	98
5.9 include/BayesianClustering/Roi.hpp File Reference	98
5.10 include/BayesianClustering/RoiProxy.hpp File Reference	99
5.11 include/Utilities/GSLInterpolator.hpp File Reference	100
5.12 include/Utilities/ListComprehension.hpp File Reference	100
5.12.1 Function Documentation	101
5.12.1.1 operator" () [1/3]	102
5.12.1.2 operator" () [2/3]	102
5.12.1.3 operator" () [3/3]	103
5.12.1.4 range()	103
5.13 include/Utilities/MemoryMonitoring.hpp File Reference	104
5.13.1 Function Documentation	104
5.13.1.1 mem_usage()	104
5.14 include/Utilities/ProgressBar.hpp File Reference	105
5.15 include/Utilities/Units.hpp File Reference	106
5.15.1 Function Documentation	107
5.15.1.1 operator""_micrometer() [1/2]	107
5.15.1.2 operator""_micrometer() [2/2]	107
5.15.1.3 operator""_nanometer() [1/2]	108
5.15.1.4 operator""_nanometer() [2/2]	108
5.15.1.5 StrToDist()	109
5.16 include/Utilities/Vectorize.hpp File Reference	109
5.16.1 Function Documentation	110
5.16.1.1 operator&&()	110
5.16.1.2 operator" " ()	111
5.16.2 Variable Documentation	111

5.16.2.1 Nthreads	111
5.17 src/BayesianClustering/API.cpp File Reference	112
5.17.1 Function Documentation	113
5.17.1.1 _ClusterCallback_Json_()	113
5.17.1.2 _FullClusterToSimpleCluster_()	114
5.17.1.3 _FullScanToSimpleScan_()	114
5.17.1.4 _ScanCallback_Json_()	115
5.17.1.5 AutoRoi_Cluster_FullCallback()	115
5.17.1.6 AutoRoi_Cluster_SimpleCallback()	116
5.17.1.7 AutoRoi_Cluster_ToJson()	116
5.17.1.8 AutoRoi_Scan_FullCallback()	117
5.17.1.9 AutoRoi_Scan_SimpleCallback()	117
5.17.1.10 AutoRoi_Scan_ToJson()	118
5.17.1.11 ImageJRoi_Cluster_FullCallback()	118
5.17.1.12 ImageJRoi_Cluster_SimpleCallback()	119
5.17.1.13 ImageJRoi_Cluster_ToJson()	119
5.17.1.14 ImageJRoi_Scan_FullCallback()	120
5.17.1.15 ImageJRoi_Scan_SimpleCallback()	120
5.17.1.16 ImageJRoi_Scan_ToJson()	121
5.17.1.17 ManualRoi_Cluster_FullCallback()	121
5.17.1.18 ManualRoi_Cluster_SimpleCallback()	122
5.17.1.19 ManualRoi_Cluster_ToJson()	122
5.17.1.20 ManualRoi_Scan_FullCallback()	123
5.17.1.21 ManualRoi_Scan_SimpleCallback()	123
5.17.1.22 ManualRoi_Scan_ToJson()	124
5.18 src/BayesianClustering/Cluster.cpp File Reference	124
5.18.1 Function Documentation	125
5.18.1.1 normal_cdf()	125
5.19 src/BayesianClustering/Configuration.cpp File Reference	125
5.20 src/BayesianClustering/Data.cpp File Reference	126
5.21 src/BayesianClustering/DataProxy.cpp File Reference	126
5.22 src/BayesianClustering/ImageJ_Roi.cpp File Reference	127
5.22.1 Function Documentation	127
5.22.1.1 DecodeBinaryRoi()	127
5.22.1.2 OpenRoiZipfile()	128
5.23 src/BayesianClustering/LocalizationFile.cpp File Reference	128
5.23.1 Function Documentation	129
5.23.1.1 __LoadCSV__()	129
5.23.1.2 __RecursiveSearch__()	130
5.24 src/BayesianClustering/Roi.cpp File Reference	130
5.25 src/BayesianClustering/Roiproxy.cpp File Reference	130
5.26 src/Cluster.cxx File Reference	131

5.26.1 Function Documentation	132
5.26.1.1 main()	132
5.26.1.2 ReportClusters()	132
5.27 src/PythonBindings/PythonBindings.cpp File Reference	132
5.27.1 Detailed Description	134
5.27.2 Macro Definition Documentation	134
5.27.2.1 ADAPT_CALLBACK_CONSTRUCTOR	135
5.27.2.2 ADAPTED_FN	135
5.27.2.3 EXPOSE_STRUCT	135
5.27.2.4 EXPOSE_VECTOR	136
5.27.2.5 FN	136
5.27.2.6 STRUCT_ARG	136
5.27.3 Function Documentation	137
5.27.3.1 CheckRols()	137
5.27.3.2 GetLocalizations()	137
5.27.3.3 GetRols()	138
5.27.3.4 ScanConfigurationConstructor()	138
5.28 src/Scan.cxx File Reference	139
5.28.1 Function Documentation	140
5.28.1.1 main()	140
5.29 src/Utilities/GSLInterpolator.cpp File Reference	141
5.30 src/Utilities/ProgressBar.cpp File Reference	141
5.31 src/Utilities/Units.cpp File Reference	141
5.31.1 Function Documentation	142
5.31.1.1 StrToDist()	142
5.32 src/Utilities/Vectorize.cpp File Reference	143
5.32.1 Variable Documentation	143
5.32.1.1 Nthreads	143
Index	145

Chapter 1

Todo List

Member [Data::CalculateLocalizationScore](#) (const std::vector< [Data](#) > &aData, const double &R, const double &aArea) const

Remind myself how this works and what the difference is with above

Member [Data::PreprocessLocalizationScores](#) (std::vector< [Data](#) > &aData, const [ScanConfiguration](#) &aScanConfig, const double &aArea)

Remind myself how this works and what the difference is with below

Member [LocalizationFile::ExtractRols](#) (const std::string &almageJfile, const double &aScale, const std::function< void([Rol](#) &) > &aCallback) const

Add ID back into [Rol](#)

Chapter 2

Class Index

2.1 Class List

Here are the classes, structs, unions and interfaces with brief descriptions:

AuxConfiguration	Class for storing the auxilliary configuration parameters	7
Cluster	A class representing a cluster	13
ClusterWrapper	A struct for storing extracted parameters from a cluster	17
Data	A class to store the raw data-points	19
DataProxy	A light-weight proxy for the raw data-points	26
GSLInterpolator	A utility wrapper around the GSL interpolator to give it a clean C++ interface	30
LocalizationFile	A class to store the raw data-points	39
ManualRol	A struct for storing the parameters of a manual Rol	43
Cluster::Parameter	A struct representing the cluster parameters	44
ProgressBar	A utility progress-bar	46
ProgressTimer	A utility code timer	48
Rol	A class which holds the raw Rol data and global parameters	49
Rolproxy	A lightweight wrapper for the Rol to store clusters for a given scan	56
ScanConfiguration	A class for storing the scan configuration parameters	62
ScanEntry	A struct for storing a result of an individual scan configuration	76
ScanConfiguration::tBounds	A struct to store the bounds of a scan in either R or T	78

Chapter 3

File Index

3.1 File List

Here is a list of all documented files with brief descriptions:

include/BayesianClustering/ API.hpp	79
include/BayesianClustering/ Cluster.hpp	91
include/BayesianClustering/ Configuration.hpp	92
include/BayesianClustering/ Data.hpp	93
include/BayesianClustering/ DataProxy.hpp	94
include/BayesianClustering/ ImageJ_Rol.hpp	95
include/BayesianClustering/ LocalizationFile.hpp	96
include/BayesianClustering/ Precision.hpp	98
include/BayesianClustering/ Rol.hpp	98
include/BayesianClustering/ Rolproxy.hpp	99
include/Utilities/ GSLInterpolator.hpp	100
include/Utilities/ ListComprehension.hpp	100
include/Utilities/ MemoryMonitoring.hpp	104
include/Utilities/ ProgressBar.hpp	105
include/Utilities/ Units.hpp	106
include/Utilities/ Vectorize.hpp	109
src/ Cluster.cxx	131
src/ GilTest.cxx	??
src/ Scan.cxx	139
src/ ZipTest.cxx	??
src/BayesianClustering/ API.cpp	112
src/BayesianClustering/ Cluster.cpp	124
src/BayesianClustering/ Configuration.cpp	125
src/BayesianClustering/ Data.cpp	126
src/BayesianClustering/ DataProxy.cpp	126
src/BayesianClustering/ ImageJ_Rol.cpp	127
src/BayesianClustering/ LocalizationFile.cpp	128
src/BayesianClustering/ Rol.cpp	130
src/BayesianClustering/ Rolproxy.cpp	130
src/PythonBindings/ PythonBindings.cpp	
Self-contained sourcefile for producing python-bindings	132
src/Utilities/ GSLInterpolator.cpp	141
src/Utilities/ ProgressBar.cpp	141
src/Utilities/ Units.cpp	141
src/Utilities/ Vectorize.cpp	143

Chapter 4

Class Documentation

4.1 AuxConfiguration Class Reference

Class for storing the auxilliary configuration parameters.

```
#include <Configuration.hpp>
```

Public Member Functions

- [AuxConfiguration](#) (int argc, char **argv)
Default constructor.
- [AuxConfiguration](#) (const std::vector< std::string > &aArgs)
Constructor which parses the parameters when passed in as commandline arguments.
- void [SetValidate](#) (const bool &aValidate)
Set whether to validate clusterization.
- void [SetInputFile](#) (const std::string &aFileName)
Setter for the input file.
- void [SetOutputFile](#) (const std::string &aFileName)
Setter for the output file.
- void [SetConfigFile](#) (const std::string &aFileName)
Setter for the config file.
- const bool & [validate](#) () const
Getter for whether or not to run the validation on the clustering.
- const std::string & [inputFile](#) () const
Getter for the input file.
- const std::string & [outputFile](#) () const
Getter for the output file.
- const std::string & [configFile](#) () const
Getter for the config file.
- const double & [ClusterR](#) () const
Getter for the R value for a clusterization pass.
- const double & [ClusterT](#) () const
Getter for the T value for a clusterization pass.

Public Attributes

- bool [mValidate](#)
Whether or not to run the validation on the clustering.
- std::string [mInputFile](#)
The input [RoI](#) file.
- std::string [mOutputFile](#)
The output file.
- std::string [mConfigFile](#)
The config file.
- double [mClusterR](#)
The value of R for clustering.
- double [mClusterT](#)
The value of T for clustering.

Private Member Functions

- void [FromVector](#) (const std::vector< std::string > &aArgs)
Parse the parameters when passed in as commandline arguments.

4.1.1 Detailed Description

Class for storing the auxilliary configuration parameters.

Definition at line 284 of file Configuration.hpp.

4.1.2 Constructor & Destructor Documentation

4.1.2.1 AuxConfiguration() [1/2]

```
AuxConfiguration::AuxConfiguration (
    int argc,
    char ** argv )
```

Default constructor.

Constructor which parses the parameters when passed in as commandline arguments

Parameters

<i>argc</i>	The number of commandline arguments
<i>argv</i>	The commandline arguments

Definition at line 231 of file Configuration.cpp.

References FromVector().

4.1.2.2 AuxConfiguration() [2/2]

```
AuxConfiguration::AuxConfiguration (
    const std::vector< std::string > & aArgs )
```

Constructor which parses the parameters when passed in as commandline arguments.

Parameters

<i>aArgs</i>	The commandline arguments
--------------	---------------------------

Definition at line 240 of file Configuration.cpp.

References FromVector().

4.1.3 Member Function Documentation

4.1.3.1 ClusterR()

```
const double& AuxConfiguration::ClusterR ( ) const [inline]
```

Getter for the R value for a clusterization pass.

Returns

The R value for a clusterization pass

Definition at line 344 of file Configuration.hpp.

References mClusterR.

Referenced by main().

4.1.3.2 ClusterT()

```
const double& AuxConfiguration::ClusterT ( ) const [inline]
```

Getter for the T value for a clusterization pass.

Returns

The T value for a clusterization pass

Definition at line 351 of file Configuration.hpp.

References mClusterT.

Referenced by main().

4.1.3.3 configFile()

```
const std::string& AuxConfiguration::configFile ( ) const [inline]
```

Getter for the config file.

Returns

The name of the config file

Definition at line 337 of file Configuration.hpp.

References mConfigFile.

Referenced by main().

4.1.3.4 FromVector()

```
void AuxConfiguration::FromVector (
    const std::vector< std::string > & aArgs ) [private]
```

Parse the parameters when passed in as commandline arguments.

Parameters

<i>aArgs</i>	The commandline arguments
--------------	---------------------------

Definition at line 279 of file Configuration.cpp.

References mClusterR, mClusterT, Nthreads, SetConfigFile(), SetInputFile(), SetOutputFile(), SetValidate(), and StrToDist().

Referenced by AuxConfiguration().

4.1.3.5 inputFile()

```
const std::string& AuxConfiguration::inputFile ( ) const [inline]
```

Getter for the input file.

Returns

The name of the input [Rol](#) file

Definition at line 323 of file Configuration.hpp.

References mInputFile.

Referenced by main().

4.1.3.6 outputFile()

```
const std::string& AuxConfiguration::outputFile ( ) const [inline]
```

Getter for the output file.

Returns

The name of the output file

Definition at line 330 of file Configuration.hpp.

References mOutputFile.

Referenced by main().

4.1.3.7 SetConfigFile()

```
void AuxConfiguration::SetConfigFile (
    const std::string & aFileName )
```

Setter for the config file.

Parameters

<i>aFileName</i>	The name of the file
------------------	----------------------

Definition at line 267 of file Configuration.cpp.

References mConfigFile.

Referenced by FromVector().

4.1.3.8 SetInputFile()

```
void AuxConfiguration::SetInputFile (
    const std::string & aFileName )
```

Setter for the input file.

Parameters

<i>aFileName</i>	The name of the file
------------------	----------------------

Definition at line 254 of file Configuration.cpp.

References mInputFile.

Referenced by FromVector().

4.1.3.9 SetOutputFile()

```
void AuxConfiguration::SetOutputFile (
    const std::string & aFileName )
```

Setter for the output file.

Parameters

<i>aFileName</i>	The name of the file
------------------	----------------------

Definition at line 260 of file Configuration.cpp.

References mOutputFile.

Referenced by FromVector().

4.1.3.10 SetValidate()

```
void AuxConfiguration::SetValidate (
    const bool & aValidate )
```

Set whether to validate clusterization.

Parameters

<i>aValidate</i>	Whether to validate clusterization
------------------	------------------------------------

Definition at line 248 of file Configuration.cpp.

References mValidate.

Referenced by FromVector().

4.1.3.11 validate()

```
const bool& AuxConfiguration::validate ( ) const [inline]
```

Getter for whether or not to run the validation on the clustering.

Returns

Whether or not to run the validation on the clustering

Definition at line 316 of file Configuration.hpp.

References mValidate.

The documentation for this class was generated from the following files:

- include/BayesianClustering/Configuration.hpp
- src/BayesianClustering/Configuration.cpp

4.2 Cluster Class Reference

A class representing a cluster.

```
#include <Cluster.hpp>
```

Collaboration diagram for Cluster:

**Classes**

- struct [Parameter](#)
A struct representing the cluster parameters.

Public Member Functions

- [Cluster](#) (const std::size_t &aParamSize)
Default constructor.
- [Cluster](#) (const [Data](#) &aData, const std::vector< double > &aSigmapins2)
Construct a cluster from a single data-point.
- [Cluster](#) (const [Cluster](#) &aOther)=delete
Deleted copy constructor.
- [Cluster](#) & [operator=](#) (const [Cluster](#) &aOther)=delete
Deleted assignment operator.
- [Cluster](#) ([Cluster](#) &&aOther)=default
Default move constructor.
- [Cluster](#) & [operator=](#) ([Cluster](#) &&aOther)=default
Default move-assignment constructor.
- [~Cluster](#) ()
Default destructor.
- [Cluster](#) & [operator+=](#) (const [Cluster](#) &aOther)
Add another cluster to this one.
- [Cluster](#) * [GetParent](#) ()
Get a pointer to this cluster's ultimate parent.
- void [UpdateLogScore](#) (const [ScanConfiguration](#) &aScanConfig)
Update log-probability after a scan.

Public Attributes

- `std::vector< Parameter > mParams`
The collection of parameters, each corresponding to a different sigma hypothesis.
- `std::size_t mClusterSize`
The number of points in the current cluster.
- `std::size_t mLastClusterSize`
The number of points in the cluster on the previous scan iteration.
- `PRECISION mClusterScore`
The log-probability of the current cluster.
- `Cluster * mParent`
A pointer to the immediate parent of the current cluster.
- `std::vector< Data * > mData`
List of points in the cluster after clustering.

4.2.1 Detailed Description

A class representing a cluster.

Definition at line 16 of file Cluster.hpp.

4.2.2 Constructor & Destructor Documentation

4.2.2.1 Cluster() [1/4]

```
Cluster::Cluster (
    const std::size_t & aParamSize )
```

Default constructor.

Parameters

<code>aParamSize</code>	The number of sigma-bins
-------------------------	--------------------------

Definition at line 93 of file Cluster.cpp.

4.2.2.2 Cluster() [2/4]

```
Cluster::Cluster (
    const Data & aData,
    const std::vector< double > & aSigmas2 )
```

Construct a cluster from a single data-point.

Parameters

<i>aData</i>	A data-point with which to initialize the cluster
<i>aSigmbins2</i>	The sigma-bins for initializing clusters

Definition at line 99 of file Cluster.cpp.

References `mParams`, `Data::r2`, `Data::s`, `Data::x`, and `Data::y`.

4.2.2.3 Cluster() [3/4]

```
Cluster::Cluster (
    const Cluster & aOther ) [delete]
```

Deleted copy constructor.

Parameters

<i>aOther</i>	Anonymous argument
---------------	--------------------

4.2.2.4 Cluster() [4/4]

```
Cluster::Cluster (
    Cluster && aOther ) [default]
```

Default move constructor.

Parameters

<i>aOther</i>	Anonymous argument
---------------	--------------------

4.2.3 Member Function Documentation

4.2.3.1 GetParent()

```
Cluster * Cluster::GetParent ( )
```

Get a pointer to this cluster's ultimate parent.

Returns

A pointer to this cluster's ultimate parent

Definition at line 165 of file Cluster.cpp.

References GetParent(), and mParent.

Referenced by DataProxy::GetCluster(), and GetParent().

4.2.3.2 operator+=()

```
Cluster & Cluster::operator+= (
    const Cluster & aOther )
```

Add another cluster to this one.

Parameters

<i>aOther</i>	Another cluster of parameters to add to this one
---------------	--

Returns

Reference to this, for chaining calls

Definition at line 155 of file Cluster.cpp.

References mClusterSize, and mParams.

4.2.3.3 operator=() [1/2]

```
Cluster& Cluster::operator= (
    Cluster && aOther ) [default]
```

Default move-assignment constructor.

Returns

Reference to this, for chaining calls

Parameters

<i>aOther</i>	Anonymous argument
---------------	--------------------

4.2.3.4 operator=() [2/2]

```
Cluster& Cluster::operator= (
    const Cluster & aOther ) [delete]
```

Deleted assignment operator.

Returns

Reference to this, for chaining calls

Parameters

<i>aOther</i>	Anonymous argument
---------------	--------------------

4.2.3.5 UpdateLogScore()

```
void Cluster::UpdateLogScore (
    const ScanConfiguration & aScanConfig )
```

Update log-probability after a scan.

Parameters

<i>aScanConfig</i>	The configuration parameters for the scan
--------------------	---

Definition at line 124 of file Cluster.cpp.

References `ScanConfiguration::log_probability_sigma()`, `mClusterScore`, `mClusterSize`, `mLastClusterSize`, `mParams`, and `ScanConfiguration::sigmabins()`.

The documentation for this class was generated from the following files:

- include/BayesianClustering/[Cluster.hpp](#)
- src/BayesianClustering/[Cluster.cpp](#)

4.3 ClusterWrapper Struct Reference

A struct for storing extracted parameters from a cluster.

```
#include <API.hpp>
```

Public Member Functions

- bool `operator<` (const [ClusterWrapper](#) &aOther)
Comparison operator for sorting.
- bool `operator==` (const [ClusterWrapper](#) &aOther)
Equality operator required by boost python.

Public Attributes

- `std::size_t` [localizations](#)
The number of localizations in the cluster.
- `long double` [area](#)
The area of the spanning convex hull.
- `long double` [perimeter](#)
The perimeter of the spanning convex hull.
- `double` [centroid_x](#)
The x-position of the centroid.
- `double` [centroid_y](#)
The y-position of the centroid.

4.3.1 Detailed Description

A struct for storing extracted parameters from a cluster.

Definition at line 44 of file API.hpp.

4.3.2 Member Function Documentation

4.3.2.1 `operator<()`

```
bool ClusterWrapper::operator< (
    const ClusterWrapper & aOther ) [inline]
```

Comparison operator for sorting.

Returns

Whether we are smaller than the other

Parameters

<i>aOther</i>	Another ClusterWrapper to compare against
---------------	---

Definition at line 54 of file API.hpp.

References [area](#), [localizations](#), and [perimeter](#).

4.3.2.2 `operator==()`

```
bool ClusterWrapper::operator== (
    const ClusterWrapper & aOther ) [inline]
```

Equality operator required by boost python.

Returns

Whether we are equal to the other

Parameters

<i>aOther</i>	Another ClusterWrapper to compare against
---------------	---

Definition at line 64 of file API.hpp.

References `centroid_x`, and `centroid_y`.

The documentation for this struct was generated from the following file:


- `include/BayesianClustering/API.hpp`

4.4 Data Class Reference

A class to store the raw data-points.

```
#include <Data.hpp>
```

Collaboration diagram for Data:

**Public Member Functions**

- [Data](#) (const PRECISION &aX, const PRECISION &aY, const PRECISION &aS)
Constructor.
- [Data](#) (const [Data](#) &aOther)=delete
Deleted copy constructor.
- [Data](#) & **operator=** (const [Data](#) &aOther)=delete
Deleted assignment operator.
- [Data](#) ([Data](#) &&aOther)=default
Default move constructor.
- [Data](#) & **operator=** ([Data](#) &&aOther)=default

- *Default move-assignment constructor.*
- virtual `~Data ()`
 - *Destructor.*
- bool `operator<` (const `Data` &aOther) const
 - *Comparison operator for sorting data-points by distance from the origin.*
- PRECISION `dR2` (const `Data` &aOther) const
 - *Return the squared-distance of this data-points from another.*
- PRECISION `dR` (const `Data` &aOther) const
 - *Return the distance of this data-points from another.*
- PRECISION `dPhi` (const `Data` &aOther) const
 - *Return the angle between this data-points and another.*
- void `Preprocess` (std::vector< `Data` > &aData, const std::size_t &aIndex, const double &aMax2R, const double &aMax2R2, const std::vector< double > &aSigmabins2, `ProgressBar` &aProgressBar)
 - *All the necessary pre-processing to get this data-point ready for an RT-scan.*
- void `PreprocessLocalizationScores` (std::vector< `Data` > &aData, const `ScanConfiguration` &aScanConfig, const double &aArea)
 - *Calculate the localization score from the local neighbourhood.*
- PRECISION `CalculateLocalizationScore` (const std::vector< `Data` > &aData, const double &R, const double &aArea) const
 - *Calculate the localization score from the local neighbourhood.*

Public Attributes

- PRECISION `x`
 - *The x-position of the data-point.*
- PRECISION `y`
 - *The y-position of the data-point.*
- PRECISION `s`
 - *The sigma of the data-point.*
- PRECISION `r2`
 - *The squared radial distance of the data-point.*
- PRECISION `r`
 - *The radial distance of the data-point.*
- PRECISION `phi`
 - *The phi-position of the data-point.*
- std::vector< PRECISION > `mLocalizationScores`
 - *The localization scores, one per R-bin.*
- std::vector< std::pair< PRECISION, std::size_t > > `mNeighbours`
 - *The list of neighbours as a pair of squared-distance and index into the list of points.*
- `Cluster` * `mProtoCluster`
 - *A cluster containing only this data-point.*

4.4.1 Detailed Description

A class to store the raw data-points.

Definition at line 17 of file Data.hpp.

4.4.2 Constructor & Destructor Documentation

4.4.2.1 Data() [1/3]

```
Data::Data (
    const PRECISION & aX,
    const PRECISION & aY,
    const PRECISION & aS )
```

Constructor.

Parameters

<i>aX</i>	The x-position of the data-point in algorithm units
<i>aY</i>	The y-position of the data-point in algorithm units
<i>aS</i>	The sigma of the data-point in algorithm units

Definition at line 14 of file Data.cpp.

4.4.2.2 Data() [2/3]

```
Data::Data (
    const Data & aOther ) [delete]
```

Deleted copy constructor.

Parameters

<i>aOther</i>	Anonymous argument
---------------	--------------------

4.4.2.3 Data() [3/3]

```
Data::Data (
    Data && aOther ) [default]
```

Default move constructor.

Parameters

<i>aOther</i>	Anonymous argument
---------------	--------------------

4.4.3 Member Function Documentation

4.4.3.1 CalculateLocalizationScore()

```
PRECISION Data::CalculateLocalizationScore (
    const std::vector< Data > & aData,
    const double & R,
    const double & aArea ) const
```

Calculate the localization score from the local neighbourhood.

Todo Remind myself how this works and what the difference is with above

Parameters

<i>aData</i>	?
<i>R</i>	?
<i>aArea</i>	The area of the window for normalizing the log score

Returns

The localization score

Definition at line 106 of file Data.cpp.

References mNeighbours.

4.4.3.2 dPhi()

```
PRECISION Data::dPhi (
    const Data & aOther ) const [inline]
```

Return the angle between this data-points and another.

Returns

The angle between this data-points and another

Parameters

<i>aOther</i>	A data-point to compare against
---------------	---------------------------------

Definition at line 71 of file Data.hpp.

References phi.

4.4.3.3 dR()

```
PRECISION Data::dR (
    const Data & aOther ) const [inline]
```

Return the distance of this data-points from another.

Returns

The distance of this data-points from another

Parameters

<i>aOther</i>	A data-point to compare against
---------------	---------------------------------

Definition at line 63 of file Data.hpp.

References dR2().

4.4.3.4 dR2()

```
PRECISION Data::dR2 (
    const Data & aOther ) const [inline]
```

Return the squared-distance of this data-points from another.

Returns

The squared-distance of this data-points from another

Parameters

<i>aOther</i>	A data-point to compare against
---------------	---------------------------------

Definition at line 54 of file Data.hpp.

References x, and y.

Referenced by dR().

4.4.3.5 operator<()

```
bool Data::operator< (
    const Data & aOther ) const [inline]
```

Comparison operator for sorting data-points by distance from the origin.

Returns

Whether this data-point is closer to the origin than another

Parameters

<i>aOther</i>	A data-point to compare against
---------------	---------------------------------

Definition at line 46 of file Data.hpp.

References r.

4.4.3.6 operator=() [1/2]

```
Data& Data::operator= (
    const Data & aOther ) [delete]
```

Deleted assignment operator.

Returns

Reference to this, for chaining calls

Parameters

<i>aOther</i>	Anonymous argument
---------------	--------------------

4.4.3.7 operator=() [2/2]

```
Data& Data::operator= (
    Data && aOther ) [default]
```

Default move-assignment constructor.

Returns

Reference to this, for chaining calls

Parameters

<i>aOther</i>	Anonymous argument
---------------	--------------------

4.4.3.8 Preprocess()

```
void Data::Preprocess (
    std::vector< Data > & aData,
    const std::size_t & aIndex,
    const double & aMax2R,
    const double & aMax2R2,
    const std::vector< double > & aSigmabins2,
    ProgressBar & aProgressBar )
```

All the necessary pre-processing to get this data-point ready for an RT-scan.

Parameters

<i>aData</i>	The collection of data-points
<i>aIndex</i>	The index of the current data-point
<i>aMax2R</i>	Twice the maximum radius out to which we will cluster
<i>aMax2R2</i>	Square of twice the maximum radius out to which we will cluster
<i>aSigmabins2</i>	The sigma-bins for initializing clusters
<i>aProgressBar</i>	The progress bar to update

Definition at line 28 of file Data.cpp.

4.4.3.9 PreprocessLocalizationScores()

```
void Data::PreprocessLocalizationScores (
    std::vector< Data > & aData,
    const ScanConfiguration & aScanConfig,
    const double & aArea )
```

Calculate the localization score from the local neighbourhood.

Todo Remind myself how this works and what the difference is with below

Parameters

<i>aData</i>	?
<i>aScanConfig</i>	The configuration parameters for the scan
<i>aArea</i>	The area of the window for normalizing the log score

Definition at line 77 of file Data.cpp.

The documentation for this class was generated from the following files:


- [include/BayesianClustering/Data.hpp](#)
- [src/BayesianClustering/Data.cpp](#)

4.5 DataProxy Class Reference

A light-weight proxy for the raw data-points.

```
#include <DataProxy.hpp>
```

Collaboration diagram for DataProxy:



Public Member Functions

- [DataProxy](#) ([Data](#) &aData)
Default constructor.
- [DataProxy](#) (const [DataProxy](#) &aOther)=delete
Deleted copy constructor.
- [DataProxy](#) & [operator=](#) (const [DataProxy](#) &aOther)=delete
Deleted assignment operator.
- [DataProxy](#) ([DataProxy](#) &&aOther)=default
Default move constructor.
- [DataProxy](#) & [operator=](#) ([DataProxy](#) &&aOther)=default
Default move-assignment constructor.
- void [Clusterize](#) (const PRECISION &a2R2, [Rolproxy](#) &aRol)
Entry point clusterization function - a new cluster will be created.
- void [Clusterize](#) (const PRECISION &a2R2, [Rolproxy](#) &aRol, [Cluster](#) *aCluster, const std::size_t &d=0)
Recursive clusterization function.
- [Cluster](#) * [GetCluster](#) ()
Get a pointer to this data-proxy's ultimate parent cluster (or null if unclustered).

Public Attributes

- `Data * mData`
The data-point for which this is the proxy.
- `Cluster * mCluster`
This data-proxy's immediate parent cluster.
- `bool mExclude`
Whether this data-point is to be included in the clusterization.

4.5.1 Detailed Description

A light-weight proxy for the raw data-points.

Definition at line 18 of file DataProxy.hpp.

4.5.2 Constructor & Destructor Documentation

4.5.2.1 DataProxy() [1/3]

```
DataProxy::DataProxy (
    Data & aData )
```

Default constructor.

Parameters

<code>aData</code>	The data-point for which this is the proxy
--------------------	--

Definition at line 17 of file DataProxy.cpp.

4.5.2.2 DataProxy() [2/3]

```
DataProxy::DataProxy (
    const DataProxy & aOther ) [delete]
```

Deleted copy constructor.

Parameters

<code>aOther</code>	Anonymous argument
---------------------	--------------------

4.5.2.3 DataProxy() [3/3]

```
DataProxy::DataProxy (
    DataProxy && aOther ) [default]
```

Default move constructor.

Parameters

<i>aOther</i>	Anonymous argument
---------------	--------------------

4.5.3 Member Function Documentation

4.5.3.1 Clusterize() [1/2]

```
void DataProxy::Clusterize (
    const PRECISION & a2R2,
    RoIproxy & aRoI )
```

Entry point clusterization function - a new cluster will be created.

Parameters

<i>a2R2</i>	The clusterization radius
<i>aRoI</i>	The RoI-proxy in which we are running

Definition at line 23 of file DataProxy.cpp.

References mCluster, RoIproxy::mClusters, mData, mExclude, Cluster::mParams, and Data::mProtoCluster.

Referenced by Clusterize().

4.5.3.2 Clusterize() [2/2]

```
void DataProxy::Clusterize (
    const PRECISION & a2R2,
    RoIproxy & aRoI,
    Cluster * aCluster,
    const std::size_t & d = 0 )
```

Recursive clusterization function.

Parameters

<i>a2R2</i>	The clusterization radius
<i>aRoI</i>	The RoI-proxy in which we are running
<i>aCluster</i>	The cluster we are building
<i>d</i>	The recursion depth

Definition at line 34 of file DataProxy.cpp.

References Clusterize(), GetCluster(), Rolproxy::GetData(), mCluster, Cluster::mClusterSize, mData, mExclude, Data::mNeighbours, Cluster::mParent, Data::mProtoCluster, and RECURSION_LIMIT.

4.5.3.3 GetCluster()

```
Cluster* DataProxy::GetCluster ( ) [inline]
```

Get a pointer to this data-proxy's ultimate parent cluster (or null if unclustered).

Returns

A pointer to this data-proxy's ultimate parent cluster

Definition at line 53 of file DataProxy.hpp.

References Cluster::GetParent(), and mCluster.

Referenced by Clusterize().

4.5.3.4 operator=() [1/2]

```
DataProxy& DataProxy::operator= (
    const DataProxy & aOther ) [delete]
```

Deleted assignment operator.

Returns

Reference to this, for chaining calls

Parameters

<i>aOther</i>	Anonymous argument
---------------	--------------------

4.5.3.5 operator=() [2/2]

```
DataProxy& DataProxy::operator= (
    DataProxy && aOther ) [default]
```

Default move-assignment constructor.

Returns

Reference to this, for chaining calls

Parameters

<i>aOther</i>	Anonymous argument
---------------	--------------------

The documentation for this class was generated from the following files:

- include/BayesianClustering/[DataProxy.hpp](#)
- src/BayesianClustering/[DataProxy.cpp](#)

4.6 GSLInterpolator Class Reference

A utility wrapper around the GSL interpolator to give it a clean C++ interface.

```
#include <GSLInterpolator.hpp>
```

Public Member Functions

- [GSLInterpolator](#) (const gsl_interp_type *type, const unsigned int &ndata)
Empty splice constructor.
- [GSLInterpolator](#) (const gsl_interp_type *type, const std::vector< double > &x, const std::vector< double > &y)
Initialised splice constructor.
- [GSLInterpolator](#) (const gsl_interp_type *type, const std::map< double, double > &data)
Initialised splice constructor.
- virtual [~GSLInterpolator](#) ()
Destructor.
- [GSLInterpolator](#) (const [GSLInterpolator](#) &aOther)=delete
Deleted copy constructor.
- [GSLInterpolator](#) & [operator=](#) (const [GSLInterpolator](#) &aOther)=delete
Deleted assignment operator.
- [GSLInterpolator](#) ([GSLInterpolator](#) &&aOther)=default
Default move constructor.
- [GSLInterpolator](#) & [operator=](#) ([GSLInterpolator](#) &&aOther)=default
Default move-assignment constructor.
- bool [SetData](#) (const std::vector< double > &x, const std::vector< double > &y)
Set the spline data points.
- bool [SetData](#) (const unsigned int &ndata, const double *x, const double *y)
Set the spline data points.
- double [Evaluate](#) (const std::function< int(double &) > &aFunction, const std::string &aName)
Utility function that runs the GSL function that has been wrapped in a lambda below.
- double [Eval](#) (const double &x)
Evaluate the spline at the given x.
- double [Deriv](#) (const double &x)
The first derivative of the spline at the given x.
- double [Deriv2](#) (const double &x)
The second derivative of the spline at the given x.
- double [Integ](#) (const double &a, const double &b)
The integral over the spline between two bounds.

Private Attributes

- unsigned int [nErrors](#)
An error counter to suppress excess messages.
- gsl_interp_accel * [fAccel](#)
Underlying GSL machinery.
- gsl_spline * [fSpline](#)
Underlying GSL machinery for the spline itself.
- const gsl_interp_type * [fInterpType](#)
Underlying GSL machinery for the interpolation type.

4.6.1 Detailed Description

A utility wrapper around the GSL interpolator to give it a clean C++ interface.

Definition at line 20 of file `GSLInterpolator.hpp`.

4.6.2 Constructor & Destructor Documentation

4.6.2.1 GSLInterpolator() [1/5]

```
GSLInterpolator::GSLInterpolator (
    const gsl_interp_type * type,
    const unsigned int & ndata )
```

Empty splice constructor.

Parameters

<i>type</i>	The spline type
<i>ndata</i>	The number of points that will be added to the spline

Definition at line 9 of file `GSLInterpolator.cpp`.

References [fInterpType](#), and [fSpline](#).

4.6.2.2 GSLInterpolator() [2/5]

```
GSLInterpolator::GSLInterpolator (
    const gsl_interp_type * type,
    const std::vector< double > & x,
    const std::vector< double > & y )
```

Initialised splice constructor.

Parameters

<i>type</i>	The spline type
<i>x</i>	The points on the x-axis
<i>y</i>	The points on the y-axis

Definition at line 19 of file GSLInterpolator.cpp.

References fInterpType, fSpline, and SetData().

4.6.2.3 GSLInterpolator() [3/5]

```
GSLInterpolator::GSLInterpolator (
    const gsl_interp_type * type,
    const std::map< double, double > & data )
```

Initialised splice constructor.

Parameters

<i>type</i>	The spline type
<i>data</i>	Data points along the spline

Definition at line 32 of file GSLInterpolator.cpp.

References fInterpType, fSpline, and SetData().

4.6.2.4 GSLInterpolator() [4/5]

```
GSLInterpolator::GSLInterpolator (
    const GSLInterpolator & aOther ) [delete]
```

Deleted copy constructor.

Parameters

<i>aOther</i>	Anonymous argument
---------------	--------------------

4.6.2.5 GSLInterpolator() [5/5]

```
GSLInterpolator::GSLInterpolator (
    GSLInterpolator && aOther ) [default]
```

Default move constructor.

Parameters

<i>aOther</i>	Anonymous argument
---------------	--------------------

4.6.3 Member Function Documentation

4.6.3.1 Deriv()

```
double GSLInterpolator::Deriv (  
    const double & x ) [inline]
```

The first derivative of the spline at the given x.

Parameters

x	The x-coordinate at which to evaluate the derivative
---	--

Returns

The first derivative of the spline at the given x-coordinate

Definition at line 110 of file GSLInterpolator.hpp.

References Evaluate(), fAccel, and fSpline.

4.6.3.2 Deriv2()

```
double GSLInterpolator::Deriv2 (  
    const double & x ) [inline]
```

The second derivative of the spline at the given x.

Parameters

x	The x-coordinate at which to evaluate the derivative
---	--

Returns

The second derivative of the spline at the given x-coordinate

Definition at line 120 of file GSLInterpolator.hpp.

References Evaluate(), fAccel, and fSpline.

4.6.3.3 Eval()

```
double GSLInterpolator::Eval (
    const double & x ) [inline]
```

Evaluate the spline at the given x.

Parameters

x	The x-coordinate at which to evaluate the spline
---	--

Returns

The value of the spline at the given x-coordinate

Definition at line 100 of file GSLInterpolator.hpp.

References Evaluate(), fAccel, and fSpline.

Referenced by ScanConfiguration::FromVector(), and ScanConfiguration::ScanConfiguration().

4.6.3.4 Evaluate()

```
double GSLInterpolator::Evaluate (
    const std::function< int(double &) > & aFunction,
    const std::string & aName ) [inline]
```

Utility function that runs the GSL function that has been wrapped in a lambda below.

Parameters

<i>aFunction</i>	A lambda that will be evaluated
<i>aName</i>	The operation name for the debugging messages

Returns

The interpolated value

Definition at line 81 of file GSLInterpolator.hpp.

References fAccel, and nErrors.

Referenced by Deriv(), Deriv2(), Eval(), and Integ().

4.6.3.5 Integ()

```
double GSLInterpolator::Integ (  
    const double & a,  
    const double & b ) [inline]
```

The integral over the spline between two bounds.

Parameters

<i>a</i>	The lower bound of the integral
<i>b</i>	The upper bound of the integral

Returns

The integral over the spline between a and b

Definition at line 131 of file GSLInterpolator.hpp.

References Evaluate(), fAccel, and fSpline.

4.6.3.6 operator=() [1/2]

```
GSLInterpolator& GSLInterpolator::operator= (
    const GSLInterpolator & aOther ) [delete]
```

Deleted assignment operator.

Returns

Reference to this, for chaining calls

Parameters

<i>aOther</i>	Anonymous argument
---------------	--------------------

4.6.3.7 operator=() [2/2]

```
GSLInterpolator& GSLInterpolator::operator= (
    GSLInterpolator && aOther ) [default]
```

Default move-assignment constructor.

Returns

Reference to this, for chaining calls

Parameters

<i>aOther</i>	Anonymous argument
---------------	--------------------

4.6.3.8 SetData() [1/2]

```
bool GSLInterpolator::SetData (
    const std::vector< double > & x,
    const std::vector< double > & y ) [inline]
```

Set the spline data points.

Parameters

<i>x</i>	The x-coordinates of the datapoints
<i>y</i>	The y-coordinates of the datapoints

Returns

success or fail

Definition at line 64 of file GSLInterpolator.hpp.

Referenced by GSLInterpolator().

4.6.3.9 SetData() [2/2]

```
bool GSLInterpolator::SetData (
    const unsigned int & ndata,
    const double * x,
    const double * y )
```

Set the spline data points.

Parameters

<i>ndata</i>	The number of data points
<i>x</i>	Pointer to the first element of an array of x-coordinates
<i>y</i>	Pointer to the first element of an array of y-coordinates

Returns

success or fail

Definition at line 59 of file GSLInterpolator.cpp.

References fAccel, fInterpType, fSpline, and nErrors.

The documentation for this class was generated from the following files:

- include/Utilities/GSLInterpolator.hpp
- src/Utilities/GSLInterpolator.cpp

4.7 LocalizationFile Class Reference

A class to store the raw data-points.

```
#include <LocalizationFile.hpp>
```

Public Member Functions

- [LocalizationFile](#) (const std::string &aFilename)
Constructor.
- [LocalizationFile](#) (const [LocalizationFile](#) &aOther)=delete
Deleted copy constructor.
- [LocalizationFile](#) & operator= (const [LocalizationFile](#) &aOther)=delete
Deleted assignment operator.
- [LocalizationFile](#) ([LocalizationFile](#) &&aOther)=default
Default move constructor.
- [LocalizationFile](#) & operator= ([LocalizationFile](#) &&aOther)=default
Default move-assignment constructor.
- [~LocalizationFile](#) ()=default
Default destructor.
- void [ExtractRols](#) (const [ManualRol](#) &aRol, const std::function< void([Rol](#) &) > &aCallback) const
Manually extract an Rol.
- void [ExtractRols](#) (const std::function< void([Rol](#) &) > &aCallback) const
Automatically extract the Rols.
- void [ExtractRols](#) (const std::string &almageJfile, const double &aScale, const std::function< void([Rol](#) &) > &aCallback) const
Manually extract an Rol.
- const std::vector< [Data](#) > & [data](#) ()
Accessor to the raw data.

Private Attributes

- std::string [mFilename](#)
The localization file name.
- std::vector< [Data](#) > [mData](#)
The localizations in the file.

4.7.1 Detailed Description

A class to store the raw data-points.

Definition at line 25 of file LocalizationFile.hpp.

4.7.2 Constructor & Destructor Documentation

4.7.2.1 LocalizationFile() [1/3]

```
LocalizationFile::LocalizationFile (
    const std::string & aFilename )
```

Constructor.

Parameters

<i>aFilename</i>	The name of the localizations file
------------------	------------------------------------

Definition at line 75 of file LocalizationFile.cpp.

References `__LoadCSV__()`, `mData`, `Nthreads`, and `range()`.

4.7.2.2 LocalizationFile() [2/3]

```
LocalizationFile::LocalizationFile (
    const LocalizationFile & aOther ) [delete]
```

Deleted copy constructor.

Parameters

<i>aOther</i>	Anonymous argument
---------------	--------------------

4.7.2.3 LocalizationFile() [3/3]

```
LocalizationFile::LocalizationFile (
    LocalizationFile && aOther ) [default]
```

Default move constructor.

Parameters

<i>aOther</i>	Anonymous argument
---------------	--------------------

4.7.3 Member Function Documentation

4.7.3.1 data()

```
const std::vector< Data >& LocalizationFile::data ( ) [inline]
```

Accessor to the raw data.

Returns

Reference to the raw data

Definition at line 67 of file LocalizationFile.hpp.

References mData.

Referenced by CheckRols(), and GetLocalizations().

4.7.3.2 ExtractRols() [1/3]

```
void LocalizationFile::ExtractRols (
    const ManualRoI & aRoI,
    const std::function< void(RoI &) > & aCallback ) const
```

Manually extract an [RoI](#).

Parameters

<i>aRoI</i>	The manual RoI window
<i>aCallback</i>	A handler for each RoI found

Definition at line 107 of file LocalizationFile.cpp.

References ManualRoI::height, mData, RoI::SetArea(), RoI::SetCentre(), ManualRoI::width, ManualRoI::x, and ManualRoI::y.

Referenced by AutoRoi_Cluster_FullCallback(), AutoRoi_Scan_FullCallback(), AutoRoi_Scan_SimpleCallback(), CheckRols(), ImageJRoi_Cluster_FullCallback(), ImageJRoi_Scan_FullCallback(), ImageJRoi_Scan_SimpleCallback(), ManualRoi_Cluster_FullCallback(), ManualRoi_Scan_FullCallback(), and ManualRoi_Scan_SimpleCallback().

4.7.3.3 ExtractRols() [2/3]

```
void LocalizationFile::ExtractRols (
    const std::function< void(RoI &) > & aCallback ) const
```

Automatically extract the Rols.

Parameters

<i>aCallback</i>	A handler for each RoI found
------------------	--

Local record to store the size, the bounds and the datapoints

< The number of histogram cells in the [RoI](#)

< The mean X of the [RoI](#)

< The mean Y of the [RoI](#)

< The data points in the [RoI](#)

Definition at line 145 of file LocalizationFile.cpp.

References `__RecursiveSearch__()`, `mData`, `RoI::SetArea()`, and `RoI::SetCentre()`.

4.7.3.4 `ExtractRols()` [3/3]

```
void LocalizationFile::ExtractRoIs (
    const std::string & aImageJfile,
    const double & aScale,
    const std::function< void(RoI &) > & aCallback ) const
```

Manually extract an [RoI](#).

Parameters

<i>aImageJfile</i>	The name of an ImageJ RoI file
<i>aScale</i>	The size of the LSB in the ImageJ file
<i>aCallback</i>	A handler for each RoI found

Todo Add ID back into [RoI](#)

Definition at line 327 of file LocalizationFile.cpp.

References `mData`, `OpenRoiZipfile()`, `RoI::SetArea()`, and `RoI::SetCentre()`.

4.7.3.5 `operator=()` [1/2]

```
LocalizationFile& LocalizationFile::operator= (
    const LocalizationFile & aOther ) [delete]
```

Deleted assignment operator.

Returns

Reference to this, for chaining calls

Parameters

<i>aOther</i>	Anonymous argument
---------------	--------------------

4.7.3.6 operator=() [2/2]

```
LocalizationFile& LocalizationFile::operator= (
    LocalizationFile && aOther ) [default]
```

Default move-assignment constructor.

Returns

Reference to this, for chaining calls

Parameters

<i>aOther</i>	Anonymous argument
---------------	--------------------

The documentation for this class was generated from the following files:

- include/BayesianClustering/[LocalizationFile.hpp](#)
- src/BayesianClustering/[LocalizationFile.cpp](#)

4.8 ManualRol Struct Reference

A struct for storing the parameters of a manual [Rol](#).

```
#include <LocalizationFile.hpp>
```

Public Attributes

- double [x](#)
The x-centre of the [Rol](#).
- double [y](#)
The y-centre of the [Rol](#).
- double [width](#)
The width of the [Rol](#).
- double [height](#)
The height of the [Rol](#).

4.8.1 Detailed Description

A struct for storing the parameters of a manual [Rol](#).

Definition at line 15 of file [LocalizationFile.hpp](#).

The documentation for this struct was generated from the following file:

- include/BayesianClustering/[LocalizationFile.hpp](#)

4.9 Cluster::Parameter Struct Reference

A struct representing the cluster parameters.

```
#include <Cluster.hpp>
```

Public Member Functions

- [Parameter](#) ()
Default constructor.
- [Parameter](#) & [operator+=](#) (const [Parameter](#) &aOther)
Add another set of parameters to this set.
- double [log_score](#) () const
Convert the parameters to a log-probability.
- double [alt_log_score](#) () const
Sean's alternative function to calculate the log-score using only the A's and B's as per the original paper for debugging.

Public Attributes

- PRECISION [A](#)
[Parameter A](#) defined in the math.
- PRECISION [Bx](#)
[Parameter Bx](#) defined in the math.
- PRECISION [By](#)
[Parameter By](#) defined in the math.
- PRECISION [C](#)
[Parameter C](#) defined in the math.
- PRECISION [logF](#)
[Parameter logF](#) defined in the math.
- PRECISION [weightedCentreX](#)
Parameters added by Sean for validation.
- PRECISION [weightedCentreY](#)
Parameters added by Sean for validation.
- PRECISION [S2](#)
Parameters added by Sean for validation.

4.9.1 Detailed Description

A struct representing the cluster parameters.

Definition at line 21 of file Cluster.hpp.

4.9.2 Member Function Documentation

4.9.2.1 alt_log_score()

```
double Cluster::Parameter::alt_log_score ( ) const
```

Sean's alternative function to calculate the log-score using only the A's and B's as per the original paper for debugging.

Returns

the log-probability of this set of cluster parameters

Definition at line 47 of file Cluster.cpp.

References `normal_cdf()`.

4.9.2.2 log_score()

```
double Cluster::Parameter::log_score ( ) const
```

Convert the parameters to a log-probability.

Returns

the log-probability of this set of cluster parameters

Definition at line 72 of file Cluster.cpp.

References `normal_cdf()`.

4.9.2.3 operator+=()

```
Cluster::Parameter & Cluster::Parameter::operator+= (
    const Parameter & aOther )
```

Add another set of parameters to this set.

Parameters

<i>aOther</i>	Another set of parameters to add to this set
---------------	--

Returns

Reference to this, for chaining calls

Definition at line 37 of file Cluster.cpp.

References A, Bx, By, C, and logF.

The documentation for this struct was generated from the following files:

- include/BayesianClustering/[Cluster.hpp](#)
- src/BayesianClustering/[Cluster.cpp](#)

4.10 ProgressBar Class Reference

A utility progress-bar.

```
#include <ProgressBar.hpp>
```

Public Member Functions

- [ProgressBar](#) (const std::string &aLabel, const uint32_t &aMax)
Constructor.
- virtual [~ProgressBar](#) ()
Destructor.
- void [operator++](#) ()
Postfix increment.
- void [operator++](#) (int aDummy)
Prefix increment.

Private Member Functions

- void [print](#) ()
Update the screen.

Private Attributes

- float [mBlockSize](#)
The size of each increment.
- float [mNextThreshold](#)
The next threshold at which we will write a block to stdout.
- std::size_t [mCount](#)
The number of times we have incremented.
- std::chrono::high_resolution_clock::time_point [mStart](#)
A timer for end-of-task stats.
- std::mutex [mMutex](#)
A mutex for multi-threaded updates.
- std::string [mLabel](#)
The label for the start of the line.
- std::size_t [mPercent](#)
The current progress.

4.10.1 Detailed Description

A utility progress-bar.

Definition at line 8 of file ProgressBar.hpp.

4.10.2 Constructor & Destructor Documentation

4.10.2.1 ProgressBar()

```
ProgressBar::ProgressBar (
    const std::string & aLabel,
    const uint32_t & aMax )
```

Constructor.

Parameters

<i>aLabel</i>	A description of the task being timed
<i>aMax</i>	The number of calls equalling 100%

Definition at line 8 of file ProgressBar.cpp.

References mLabel, and print().

4.10.3 Member Function Documentation

4.10.3.1 operator++()

```
void ProgressBar::operator++ (
    int aDummy )
```

Prefix increment.

Parameters

<i>aDummy</i>	Anonymous argument
---------------	--------------------

Definition at line 39 of file ProgressBar.cpp.

References operator++().

The documentation for this class was generated from the following files:

- [include/Utilities/ProgressBar.hpp](#)
- [src/Utilities/ProgressBar.cpp](#)

4.11 ProgressTimer Struct Reference

A utility code timer.

```
#include <ProgressBar.hpp>
```

Public Member Functions

- [ProgressTimer](#) (const std::string &aLabel)
Constructor.
- virtual [~ProgressTimer](#) ()
Destructor.

Public Attributes

- std::chrono::high_resolution_clock::time_point [mStart](#)
A timer for end-of-task stats.

4.11.1 Detailed Description

A utility code timer.

Definition at line 49 of file `ProgressBar.hpp`.

4.11.2 Constructor & Destructor Documentation

4.11.2.1 ProgressTimer()

```
ProgressTimer::ProgressTimer (
    const std::string & aLabel )
```

Constructor.

Parameters

<i>aLabel</i>	A description of the task being timed
---------------	---------------------------------------

Definition at line 55 of file `ProgressBar.cpp`.

The documentation for this struct was generated from the following files:

- include/Utilities/ProgressBar.hpp
- src/Utilities/ProgressBar.cpp

4.12 RoI Class Reference

A class which holds the raw [RoI](#) data and global parameters.

```
#include <RoI.hpp>
```

Public Member Functions

- [RoI](#) (const std::string &id, std::vector< [Data](#) > &&aData)
Default Constructor.
- [RoI](#) (const [RoI](#) &aOther)=delete
Deleted copy constructor.
- [RoI](#) & operator= (const [RoI](#) &aOther)=delete
Deleted assignment operator.
- [RoI](#) ([RoI](#) &&aOther)=default
Default move constructor.
- [~RoI](#) ()
Default destructor.
- [RoI](#) & operator= ([RoI](#) &&aOther)=default
Default move-assignment constructor.
- void [Preprocess](#) (const double &aMaxR, const std::vector< double > &aSigmabins2)
All the necessary pre-processing to get the [RoI](#) ready for an RT-scan.
- void [ScanRT](#) (const [ScanConfiguration](#) &aScanConfig, const std::function< void([RoIproxy](#) &, const double &, const double &) > &aCallback)
Run the scan.
- void [Clusterize](#) (const double &R, const double &T, const std::function< void([RoIproxy](#) &) > &aCallback)
Run clusterization for a specific choice of R and T.
- void [SetCentre](#) (const double &aPhysicalCentreX, const double &aPhysicalCentreY)
Setter for the centre of the scan window.
- void [SetArea](#) (const double &aArea)
Setter for the size of the [RoI](#) window.
- const double & [getCentreX](#) () const
Getter for the x-coordinate of the physical centre.
- const double & [getCentreY](#) () const
Getter for the y-coordinate of the physical centre.
- const double & [getArea](#) () const
Getter for the height of the ROI window.
- const std::vector< [Data](#) > & [data](#) () const
Accessor to the raw data.
- const std::string & [id](#) () const
Accessor to the [RoI](#) ID.

Private Attributes

- `std::string mId`
The ID of the ROI.
- `std::vector< Data > mData`
The collection of raw data points.
- `double mPhysicalCentreX`
The x-coordinate of the centre of the window in physical units.
- `double mPhysicalCentreY`
The y-coordinate of the centre of the window in physical units.
- `double mArea`
The area of the window in physical units.

Friends

- class **Rolproxy**

4.12.1 Detailed Description

A class which holds the raw **Rol** data and global parameters.

Definition at line 17 of file Rol.hpp.

4.12.2 Constructor & Destructor Documentation

4.12.2.1 Rol() [1/3]

```
RoI::RoI (
    const std::string & aId,
    std::vector< Data > && aData )
```

Default Constructor.

Parameters

<i>aId</i>	The ID of the Rol
<i>aData</i>	The set of data-points in the Rol

Definition at line 17 of file Rol.cpp.

References `mData`.

4.12.2.2 RoI() [2/3]

```
RoI::RoI (
    const RoI & aOther ) [delete]
```

Deleted copy constructor.

Parameters

<i>aOther</i>	Anonymous argument
---------------	--------------------

4.12.2.3 RoI() [3/3]

```
RoI::RoI (
    RoI && aOther ) [default]
```

Default move constructor.

Parameters

<i>aOther</i>	Anonymous argument
---------------	--------------------

4.12.3 Member Function Documentation

4.12.3.1 Clusterize()

```
void RoI::Clusterize (
    const double & R,
    const double & T,
    const std::function< void(RoIproxy &) > & aCallback )
```

Run clusterization for a specific choice of R and T.

Parameters

<i>R</i>	The R parameter for clusterization
<i>T</i>	The T parameter for clusterization
<i>aCallback</i>	A callback for the clusterization results

Definition at line 58 of file RoI.cpp.

References `RoIproxy::Clusterize()`, and `Preprocess()`.

Referenced by `AutoRoi_Cluster_FullCallback()`, `ImageJRoi_Cluster_FullCallback()`, and `ManualRoi_Cluster_FullCallback()`.

4.12.3.2 `data()`

```
const std::vector< Data >& Roi::data ( ) const [inline]
```

Accessor to the raw data.

Returns

Reference to the raw data

Definition at line 113 of file `Roi.hpp`.

References `mData`.

Referenced by `CheckRols()`.

4.12.3.3 `getArea()`

```
const double& Roi::getArea ( ) const [inline]
```

Getter for the height of the ROI window.

Returns

The height of the ROI window

Definition at line 106 of file `Roi.hpp`.

References `mArea`.

Referenced by `RoiProxy::Clusterize()`, and `ScanRT()`.

4.12.3.4 `getCentreX()`

```
const double& Roi::getCentreX ( ) const [inline]
```

Getter for the x-coordinate of the physical centre.

Returns

The x-coordinate of the physical centre

Definition at line 79 of file `Roi.hpp`.

References `mPhysicalCentreX`.

4.12.3.5 getCentreY()

```
const double& RoI::getCentreY ( ) const [inline]
```

Getter for the y-coordinate of the physical centre.

Returns

The y-coordinate of the physical centre

Definition at line 85 of file RoI.hpp.

References `mPhysicalCentreY`.

4.12.3.6 id()

```
const std::string& RoI::id ( ) const [inline]
```

Accessor to the [RoI](#) ID.

Returns

Reference to the [RoI](#) ID

Definition at line 120 of file RoI.hpp.

References `mId`.

Referenced by `_FullClusterToSimpleCluster_()`, and `_FullScanToSimpleScan_()`.

4.12.3.7 operator=() [1/2]

```
RoI& RoI::operator= (
    const RoI & aOther ) [delete]
```

Deleted assignment operator.

Returns

Reference to this, for chaining calls

Parameters

<i>aOther</i>	Anonymous argument
---------------	--------------------

4.12.3.8 operator=() [2/2]

```
RoI& RoI::operator= (
    RoI && aOther ) [default]
```

Default move-assignment constructor.

Returns

Reference to this, for chaining calls

Parameters

<i>aOther</i>	Anonymous argument
---------------	--------------------

4.12.3.9 Preprocess()

```
void RoI::Preprocess (
    const double & aMaxR,
    const std::vector< double > & aSigmabins2 )
```

All the necessary pre-processing to get the [RoI](#) ready for an RT-scan.

Parameters

<i>aMaxR</i>	The maximum radius out to which we should pre-process
<i>aSigmabins2</i>	The number of sigma bins

Definition at line 35 of file RoI.cpp.

References mData, and range().

Referenced by Clusterize(), and ScanRT().

4.12.3.10 ScanRT()

```
void RoI::ScanRT (
    const ScanConfiguration & aScanConfig,
    const std::function< void(RoIproxy &, const double &, const double &) > & a←
    Callback )
```

Run the scan.

Parameters

<i>aScanConfig</i>	The configuration parameters for the scan
<i>aCallback</i>	A callback for each RT-scan result

Definition at line 44 of file RoI.cpp.

References `ScanConfiguration::tBounds::bins`, `getArea()`, `mData`, `Nthreads`, `Preprocess()`, `range()`, `ScanConfiguration::Rbounds()`, `ScanConfiguration::sigmabins2()`, and `ScanConfiguration::Tbounds()`.

Referenced by `_FullScanToSimpleScan_()`, `AutoRoi_Scan_FullCallback()`, `ImageJRoi_Scan_FullCallback()`, and `ManualRoi_Scan_FullCallback()`.

4.12.3.11 SetArea()

```
void RoI::SetArea (
    const double & aArea )
```

Setter for the size of the [RoI](#) window.

Parameters

<i>aArea</i>	The area of the RoI in physical units
--------------	---

Definition at line 85 of file RoI.cpp.

References `mArea`.

Referenced by `LocalizationFile::ExtractRols()`.

4.12.3.12 SetCentre()

```
void RoI::SetCentre (
    const double & aPhysicalCentreX,
    const double & aPhysicalCentreY )
```

Setter for the centre of the scan window.

Parameters

<i>aPhysicalCentreX</i>	The x-coordinate of the centre of the window in physical units (becomes 0 in algorithm units)
<i>aPhysicalCentreY</i>	The y-coordinate of the centre of the window in physical units (becomes 0 in algorithm units)

Definition at line 70 of file RoI.cpp.

References `mPhysicalCentreX`, and `mPhysicalCentreY`.

Referenced by `LocalizationFile::ExtractRols()`.

The documentation for this class was generated from the following files:


- `include/BayesianClustering/Rol.hpp`
- `src/BayesianClustering/Rol.cpp`

4.13 Rolproxy Class Reference

A lightweight wrapper for the [Rol](#) to store clusters for a given scan.

```
#include <Rolproxy.hpp>
```

Collaboration diagram for Rolproxy:



Public Member Functions

- [Rolproxy](#) ([Rol](#) &aRol)
Default constructor.
- [Rolproxy](#) (const [Rolproxy](#) &aOther)=delete
Deleted copy constructor.
- [Rolproxy](#) & operator= (const [Rolproxy](#) &aOther)=delete
Deleted assignment operator.
- [Rolproxy](#) ([Rolproxy](#) &&aOther)=default
Default move constructor.
- [Rolproxy](#) & operator= ([Rolproxy](#) &&aOther)=default
Default move-assignment constructor.
- [~Rolproxy](#) ()
Default destructor.
- void [CheckClusterization](#) (const double &R, const double &T)
Run validation tests on the clusters.
- void [ScanRT](#) (const [ScanConfiguration](#) &aScanConfig, const std::function< void([Rolproxy](#) &, const double &, const double &) > &aCallback, [ProgressBar](#) &aProgressBar, const uint8_t &aParallelization=1, const uint8_t &aOffset=0, const bool &aValidate=false)
Run an RT-scan.

- void [Clusterize](#) (const double &R, const double &T, const std::function< void([Rolproxy](#) &) > &aCallback)
Run clusterization for a specific choice of R and T.
- void [UpdateLogScore](#) (const [ScanConfiguration](#) &aScanConfig)
Update log-probability after a scan.
- void [ValidateLogScore](#) (const [ScanConfiguration](#) &aScanConfig)
Sean's validation code for testing when the running log-score fails.
- [DataProxy](#) & [GetData](#) (const std::size_t &aIndex)
Get the proxy for the Nth neighbour of this data-point.

Public Attributes

- std::vector< [DataProxy](#) > [mData](#)
The collection of lightweight data-point wrappers used by this [Rol](#) wrapper.
- std::vector< [Cluster](#) > [mClusters](#)
The collection of clusters found by this scan.
- std::size_t [mClusteredCount](#)
The number of clustered data-points.
- std::size_t [mBackgroundCount](#)
The number of background data-points.
- std::size_t [mClusterCount](#)
The number of non-Null clusters.
- double [mLogP](#)
The log-probability density associated with the last scan.
- const [Rol](#) & [mRol](#)
The underlying [Rol](#) this is a proxy to.

4.13.1 Detailed Description

A lightweight wrapper for the [Rol](#) to store clusters for a given scan.

Definition at line 19 of file Rolproxy.hpp.

4.13.2 Constructor & Destructor Documentation

4.13.2.1 Rolproxy() [1/3]

```

Rolproxy::Rolproxy (
    RolI & aRolI )

```

Default constructor.

Parameters

<i>aRol</i>	An Rol for which this is a lightweight proxy
-------------	--

Definition at line 17 of file Rolproxy.cpp.

References mClusters, Rol::mData, and mData.

4.13.2.2 Rolproxy() [2/3]

```
RoIproxy::RoIproxy (
    const RoIproxy & aOther ) [delete]
```

Deleted copy constructor.

Parameters

<i>aOther</i>	Anonymous argument
---------------	--------------------

4.13.2.3 Rolproxy() [3/3]

```
RoIproxy::RoIproxy (
    RoIproxy && aOther ) [default]
```

Default move constructor.

Parameters

<i>aOther</i>	Anonymous argument
---------------	--------------------

4.13.3 Member Function Documentation

4.13.3.1 CheckClusterization()

```
void RoIproxy::CheckClusterization (
    const double & R,
    const double & T )
```

Run validation tests on the clusters.

Parameters

<i>R</i>	The R of the last run scan
<i>T</i>	The T of the last run scan

Definition at line 34 of file Rolproxy.cpp.

References `GetData()`, `mBackgroundCount`, `mClusterCount`, `mClusters`, and `mData`.

4.13.3.2 Clusterize()

```
void RoIproxy::Clusterize (
    const double & R,
    const double & T,
    const std::function< void(RoIproxy &) > & aCallback )
```

Run clusterization for a specific choice of R and T.

Parameters

<i>R</i>	The R parameter for clusterization
<i>T</i>	The T parameter for clusterization
<i>aCallback</i>	A callback for the clusterization results

Definition at line 139 of file Rolproxy.cpp.

References `Rol::getArea()`, `mClusters`, `Rol::mData`, `mData`, and `mRol`.

Referenced by `Rol::Clusterize()`.

4.13.3.3 GetData()

```
DataProxy& RoIproxy::GetData (
    const std::size_t & aIndex ) [inline]
```

Get the proxy for the Nth neighbour of this data-point.

Returns

A reference to the neighbour data-proxy

Parameters

<i>aIndex</i>	The index of the neighbour we are looking for
---------------	---

Definition at line 74 of file Rolproxy.hpp.

References `mData`.

Referenced by `CheckClusterization()`, and `DataProxy::Clusterize()`.

4.13.3.4 operator=() [1/2]

```
RoIproxy& RoIproxy::operator= (
    const RoIproxy & aOther ) [delete]
```

Deleted assignment operator.

Returns

Reference to this, for chaining calls

Parameters

<i>aOther</i>	Anonymous argument
---------------	--------------------

4.13.3.5 operator=() [2/2]

```
RoIproxy& RoIproxy::operator= (
    RoIproxy && aOther ) [default]
```

Default move-assignment constructor.

Returns

Reference to this, for chaining calls

Parameters

<i>aOther</i>	Anonymous argument
---------------	--------------------

4.13.3.6 ScanRT()

```
void RoIproxy::ScanRT (
    const ScanConfiguration & aScanConfig,
    const std::function< void(RoIproxy &, const double &, const double &) > & a←
    Callback,
    ProgressBar & aProgressBar,
    const uint8_t & aParallelization = 1,
    const uint8_t & aOffset = 0,
    const bool & aValidate = false )
```

Run an RT-scan.

Parameters

<i>aScanConfig</i>	The configuration parameters for the scan
<i>aCallback</i>	A callback for each RT-scan result
<i>aProgressBar</i>	The progress bar to update
<i>aParallelization</i>	The stride with which we will iterate across RT parameters
<i>aOffset</i>	The starting point for the strides as we iterate across RT parameters
<i>aValidate</i>	Run validation of the score calculation

Definition at line 104 of file Rolproxy.cpp.

4.13.3.7 UpdateLogScore()

```
void RoIproxy::UpdateLogScore (
    const ScanConfiguration & aScanConfig )
```

Update log-probability after a scan.

Parameters

<i>aScanConfig</i>	The configuration parameters for the scan
--------------------	---

Definition at line 219 of file Rolproxy.cpp.

References `ScanConfiguration::alpha()`, `ScanConfiguration::logAlpha()`, `ScanConfiguration::logGammaAlpha()`, `ScanConfiguration::logPb()`, `ScanConfiguration::logPbDagger()`, `mBackgroundCount`, `mClusterCount`, `mClusteredCount`, `mClusters`, `mData`, `mLogP`, and `ScanConfiguration::sigmabins()`.

4.13.3.8 ValidateLogScore()

```
void RoIproxy::ValidateLogScore (
    const ScanConfiguration & aScanConfig )
```

Sean's validation code for testing when the running log-score fails.

Parameters

<i>aScanConfig</i>	The configuration parameters for the scan
--------------------	---

Definition at line 160 of file Rolproxy.cpp.

References `mClusters`, `mData`, `Cluster::mParams`, `Data::s`, `ScanConfiguration::sigmabins2()`, `ScanConfiguration::sigmacount()`, `Data::x`, and `Data::y`.

The documentation for this class was generated from the following files:


- [include/BayesianClustering/Rolproxy.hpp](#)
- [src/BayesianClustering/Rolproxy.cpp](#)

4.14 ScanConfiguration Class Reference

A class for storing the scan configuration parameters.

```
#include <Configuration.hpp>
```

Collaboration diagram for ScanConfiguration:



Classes

- [struct tBounds](#)
A struct to store the bounds of a scan in either R or T.

Public Member Functions

- [ScanConfiguration](#) (const std::string &aCfgFile)
Constructor which parses the parameters when passed in as commandline arguments.
- [ScanConfiguration](#) (const std::size_t &aSigmaBins, const double &aSigmaMin, const double &aSigmaMax, const std::function< double(const double &) > &aInterpolator, const std::size_t &aRbins, const double &aMinScanR, const double &aMaxScanR, const std::size_t &aTbins, const double &aMinScanT, const double &aMaxScanT, const double &aPB, const double &aAlpha)
Constructor which take the parameters directly.
- [ScanConfiguration](#) (const std::size_t &aSigmaBins, const double &aSigmaMin, const double &aSigmaMax, const std::map< double, double > &aInterpolator, const std::size_t &aRbins, const double &aMinScanR, const double &aMaxScanR, const std::size_t &aTbins, const double &aMinScanT, const double &aMaxScanT, const double &aPB, const double &aAlpha)
Constructor which take the parameters directly.
- [ScanConfiguration](#) (const [ScanConfiguration](#) &aOther)=delete
Deleted copy constructor.
- [ScanConfiguration](#) &operator= (const [ScanConfiguration](#) &aOther)=delete

- Deleted assignment operator.*
- [ScanConfiguration](#) ([ScanConfiguration](#) &&aOther)=default
- Default move constructor.*
- [ScanConfiguration](#) & operator= ([ScanConfiguration](#) &&aOther)=default
- Default move-assignment constructor.*
- [~ScanConfiguration](#) ()=default
- Default destructor.*
- void [SetSigmaParameters](#) (const std::size_t &aSigmaBins, const double &aSigmaMin, const double &aSigmaMax, const std::function< double(const double &) > &aInterpolator)
- Setter for the sigma-bins to be integrated over.*
- void [SetRBins](#) (const std::size_t &aRbins, const double &aMinScanR, const double &aMaxScanR)
- Setter for the R bins for the RT scan.*
- void [SetTBins](#) (const std::size_t &aTbins, const double &aMinScanT, const double &aMaxScanT)
- void [SetPb](#) (const double &aPB)
- Setter for the P_b parameter.*
- void [SetAlpha](#) (const double &aAlpha)
- Setter for the alpha parameter.*
- const std::size_t & [sigmacount](#) () const
- Getter for the sigma count.*
- const double & [sigmaspacing](#) () const
- Getter for the sigma spacing.*
- const std::vector< double > & [sigmabins](#) () const
- Getter for the values of sigma.*
- const std::vector< double > & [sigmabins2](#) () const
- Getter for the values of sigma squared.*
- const std::vector< double > & [probability_sigma](#) () const
- Getter for the probabilities of a given sigma.*
- const std::vector< double > & [log_probability_sigma](#) () const
- Getter for the log of the probabilities of a given sigma.*
- const double & [sigmabins](#) (const std::size_t &i) const
- Getter for the i'th value of sigma.*
- const double & [sigmabins2](#) (const std::size_t &i) const
- Getter for the i'th value of sigma squared.*
- const double & [probability_sigma](#) (const std::size_t &i) const
- Getter for the probability of the i'th value of sigma.*
- const double & [log_probability_sigma](#) (const std::size_t &i) const
- Getter for the log-probability of the i'th value of sigma.*
- const [tBounds](#) & [Rbounds](#) () const
- Getter for the bounds of R to scan.*
- const [tBounds](#) & [Tbounds](#) () const
- Getter for the bounds of T to scan.*
- const double & [logPb](#) () const
- Logarithm of the P_b parameter.*
- const double & [logPbDagger](#) () const
- Logarithm of the (1 - P_b) parameter.*
- const double & [alpha](#) () const
- Getter for the alpha parameter.*
- const double & [logAlpha](#) () const
- Getter for the logarithm of the alpha parameter.*
- const double & [logGammaAlpha](#) () const
- Getter for the logarithm of the gamma function of alpha parameter.*

Private Member Functions

- void [FromVector](#) (const std::vector< std::string > &aArgs)
Parse the parameters when passed in as commandline arguments.

Private Attributes

- std::size_t [mSigmacount](#)
The number of sigma bins.
- double [mSigmaspacing](#)
The spacing of sigma bins.
- std::vector< double > [mSigmabins](#)
The values of sigma.
- std::vector< double > [mSigmabins2](#)
The values of sigma squared.
- std::vector< double > [mProbabilitySigma](#)
The probability of a given sigma.
- std::vector< double > [mLogProbabilitySigma](#)
The log-probability of a gievn sigma.
- [tBounds](#) [mRbounds](#)
The bounds of R to scan.
- [tBounds](#) [mTbounds](#)
The bounds of T to scan.
- double [mAlpha](#)
The alpha parameter.
- double [mLogAlpha](#)
Logarithm of the alpha parameter.
- double [mLogGammaAlpha](#)
Logarithm of the gamma function of alpha parameter.
- double [mLogPb](#)
Logarithm of the P_b parameter.
- double [mLogPbDagger](#)
Logarithm of the(1- P_b) parameter.

4.14.1 Detailed Description

A class for storing the scan configuration parameters.

Definition at line 12 of file Configuration.hpp.

4.14.2 Constructor & Destructor Documentation

4.14.2.1 ScanConfiguration() [1/5]

```
ScanConfiguration::ScanConfiguration (
    const std::string & aCfgFile )
```

Constructor which parses the parameters when passed in as commandline arguments.

Parameters

<i>aCfgFile</i>	A Scan-parameter config file name
-----------------	-----------------------------------

Definition at line 41 of file Configuration.cpp.

References FromVector().

4.14.2.2 ScanConfiguration() [2/5]

```
ScanConfiguration::ScanConfiguration (
    const std::size_t & aSigmaBins,
    const double & aSigmaMin,
    const double & aSigmaMax,
    const std::function< double(const double &) > & aInterpolator,
    const std::size_t & aRbins,
    const double & aMinScanR,
    const double & aMaxScanR,
    const std::size_t & aTbins,
    const double & aMinScanT,
    const double & aMaxScanT,
    const double & aPB,
    const double & aAlpha )
```

Constructor which take the parameters directly.

Parameters

<i>aSigmaBins</i>	The number of sigma bins
<i>aSigmaMin</i>	The lowest sigma bin
<i>aSigmaMax</i>	The highest sigma bin
<i>aInterpolator</i>	Function-object to generate the probability of any given sigma
<i>aRbins</i>	The number of R bins to scan over
<i>aMinScanR</i>	The lowest value of R to scan
<i>aMaxScanR</i>	The largest value of R to scan
<i>aTbins</i>	The number of T bins to scan over
<i>aMinScanT</i>	The lowest value of T to scan
<i>aMaxScanT</i>	The largest value of T to scan
<i>aPB</i>	The P_b parameter
<i>aAlpha</i>	The alpha parameter

Definition at line 55 of file Configuration.cpp.

References SetAlpha(), SetPb(), SetRBins(), SetSigmaParameters(), and SetTBins().

4.14.2.3 ScanConfiguration() [3/5]

```
ScanConfiguration::ScanConfiguration (
    const std::size_t & aSigmaBins,
    const double & aSigmaMin,
    const double & aSigmaMax,
    const std::map< double, double > & aInterpolator,
    const std::size_t & aRbins,
    const double & aMinScanR,
    const double & aMaxScanR,
    const std::size_t & aTbins,
    const double & aMinScanT,
    const double & aMaxScanT,
    const double & aPB,
    const double & aAlpha )
```

Constructor which take the parameters directly.

Parameters

<i>aSigmaBins</i>	The number of sigma bins
<i>aSigmaMin</i>	The lowest sigma bin
<i>aSigmaMax</i>	The highest sigma bin
<i>aInterpolator</i>	A set of points from which to create an interpolator
<i>aRbins</i>	The number of R bins to scan over
<i>aMinScanR</i>	The lowest value of R to scan
<i>aMaxScanR</i>	The largest value of R to scan
<i>aTbins</i>	The number of T bins to scan over
<i>aMinScanT</i>	The lowest value of T to scan
<i>aMaxScanT</i>	The largest value of T to scan
<i>aPB</i>	The P_b parameter
<i>aAlpha</i>	The alpha parameter

Definition at line 69 of file Configuration.cpp.

References `GSLInterpolator::Eval()`, `SetAlpha()`, `SetPb()`, `SetRBins()`, `SetSigmaParameters()`, and `SetTBins()`.

4.14.2.4 ScanConfiguration() [4/5]

```
ScanConfiguration::ScanConfiguration (
    const ScanConfiguration & aOther ) [delete]
```

Deleted copy constructor.

Parameters

<i>aOther</i>	Anonymous argument
---------------	--------------------

4.14.2.5 ScanConfiguration() [5/5]

```
ScanConfiguration::ScanConfiguration (
    ScanConfiguration && aOther ) [default]
```

Default move constructor.

Parameters

<i>aOther</i>	Anonymous argument
---------------	--------------------

4.14.3 Member Function Documentation

4.14.3.1 alpha()

```
const double& ScanConfiguration::alpha ( ) const [inline]
```

Getter for the alpha parameter.

Returns

The alpha parameter

Definition at line 232 of file Configuration.hpp.

References mAlpha.

Referenced by Rolproxy::UpdateLogScore().

4.14.3.2 FromVector()

```
void ScanConfiguration::FromVector (
    const std::vector< std::string > & aArgs ) [private]
```

Parse the parameters when passed in as commandline arguments.

Parameters

<i>aArgs</i>	The commandline arguments
--------------	---------------------------

Definition at line 179 of file Configuration.cpp.

References GSLInterpolator::Eval(), SetAlpha(), SetPb(), SetRBins(), SetSigmaParameters(), SetTBins(), and Str↔ToDist().

Referenced by ScanConfiguration().

4.14.3.3 log_probability_sigma() [1/2]

```
const std::vector< double >& ScanConfiguration::log_probability_sigma ( ) const [inline]
```

Getter for the log of the probabilities of a given sigma.

Returns

The log of the probabilities of given sigma

Definition at line 170 of file Configuration.hpp.

References mLogProbabilitySigma.

Referenced by Cluster::UpdateLogScore().

4.14.3.4 log_probability_sigma() [2/2]

```
const double& ScanConfiguration::log_probability_sigma (
    const std::size_t & i ) const [inline]
```

Getter for the log-probability of the i'th value of sigma.

Parameters

<i>i</i>	The index of the value of sigma to get the log-probability for
----------	--

Returns

The log-probability of sigma_i

Definition at line 199 of file Configuration.hpp.

References mLogProbabilitySigma.

4.14.3.5 logAlpha()

```
const double& ScanConfiguration::logAlpha ( ) const [inline]
```

Getter for the logarithm of the alpha parameter.

Returns

The logarithm of the alpha parameter

Definition at line 238 of file Configuration.hpp.

References mLogAlpha.

Referenced by Rolproxy::UpdateLogScore().

4.14.3.6 logGammaAlpha()

```
const double& ScanConfiguration::logGammaAlpha ( ) const [inline]
```

Getter for the logarithm of the gamma function of alpha parameter.

Returns

The logarithm of the gamma function of alpha parameter

Definition at line 244 of file Configuration.hpp.

References mLogGammaAlpha.

Referenced by Rolproxy::UpdateLogScore().

4.14.3.7 logPb()

```
const double& ScanConfiguration::logPb ( ) const [inline]
```

Logarithm of the P_b parameter.

Returns

Logarithm of the P_b parameter

Definition at line 219 of file Configuration.hpp.

References mLogPb.

Referenced by Rolproxy::UpdateLogScore().

4.14.3.8 logPbDagger()

```
const double& ScanConfiguration::logPbDagger ( ) const [inline]
```

Logarithm of the (1 - P_b) parameter.

Returns

Logarithm of the (1 - P_b) parameter

Definition at line 225 of file Configuration.hpp.

References mLogPbDagger.

Referenced by Rolproxy::UpdateLogScore().

4.14.3.9 operator=() [1/2]

```
ScanConfiguration& ScanConfiguration::operator= (
    const ScanConfiguration & aOther ) [delete]
```

Deleted assignment operator.

Returns

Reference to this, for chaining calls

Parameters

<i>aOther</i>	Anonymous argument
---------------	--------------------

4.14.3.10 operator=() [2/2]

```
ScanConfiguration& ScanConfiguration::operator= (
    ScanConfiguration && aOther ) [default]
```

Default move-assignment constructor.

Returns

Reference to this, for chaining calls

Parameters

<i>aOther</i>	Anonymous argument
---------------	--------------------

4.14.3.11 probability_sigma() [1/2]

```
const std::vector< double >& ScanConfiguration::probability_sigma ( ) const [inline]
```

Getter for the probabilities of a given sigma.

Returns

The probabilities of given sigma

Definition at line 164 of file Configuration.hpp.

References mProbabilitySigma.

4.14.3.12 probability_sigma() [2/2]

```
const double& ScanConfiguration::probability_sigma (
    const std::size_t & i ) const [inline]
```

Getter for the probability of the i'th value of sigma.

Parameters

<i>i</i>	The index of the value of sigma to get the probability for
----------	--

Returns

The probability of sigma_i

Definition at line 192 of file Configuration.hpp.

References mProbabilitySigma.

4.14.3.13 Rbounds()

```
const tBounds& ScanConfiguration::Rbounds ( ) const [inline]
```

Getter for the bounds of R to scan.

Returns

The lbounds of R to scan

Definition at line 206 of file Configuration.hpp.

References mRbounds.

Referenced by Rol::ScanRT().

4.14.3.14 SetAlpha()

```
void ScanConfiguration::SetAlpha (
    const double & aAlpha )
```

Setter for the alpha parameter.

Parameters

<i>aAlpha</i>	The alpha parameter
---------------	---------------------

Definition at line 141 of file Configuration.cpp.

References mAlpha, mLogAlpha, and mLogGammaAlpha.

Referenced by FromVector(), and ScanConfiguration().

4.14.3.15 SetPb()

```
void ScanConfiguration::SetPb (
    const double & aPB )
```

Setter for the P_b parameter.

Parameters

<i>aPB</i>	The P_b parameter
------------	-------------------

Definition at line 134 of file Configuration.cpp.

References mLogPb, and mLogPbDagger.

Referenced by FromVector(), and ScanConfiguration().

4.14.3.16 SetRBins()

```
void ScanConfiguration::SetRBins (
    const std::size_t & aRbins,
    const double & aMinScanR,
    const double & aMaxScanR )
```

Setter for the R bins for the RT scan.

Parameters

<i>aRbins</i>	The number of R bins to scan over
<i>aMinScanR</i>	The lowest value of R to scan
<i>aMaxScanR</i>	The largest value of R to scan

Definition at line 114 of file Configuration.cpp.

References ScanConfiguration::tBounds::bins, ScanConfiguration::tBounds::max, ScanConfiguration::tBounds::min, mRbounds, and ScanConfiguration::tBounds::spacing.

Referenced by FromVector(), and ScanConfiguration().

4.14.3.17 SetSigmaParameters()

```
void ScanConfiguration::SetSigmaParameters (
    const std::size_t & aSigmaBins,
    const double & aSigmaMin,
    const double & aSigmaMax,
    const std::function< double(const double &) > & aInterpolator )
```

Setter for the sigma-bins to be integrated over.

Parameters

<i>aSigmaBins</i>	The number of sigma bins
<i>aSigmaMin</i>	The lowest sigma bin
<i>aSigmaMax</i>	The highest sigma bin
<i>aInterpolator</i>	Function-object to generate the probability of any given sigma

Definition at line 86 of file Configuration.cpp.

References mLogProbabilitySigma, mProbabilitySigma, mSigmabins, mSigmabins2, mSigmacount, mSigmaspacing, and range().

Referenced by FromVector(), and ScanConfiguration().

4.14.3.18 SetTBins()

```
void ScanConfiguration::SetTBins (
    const std::size_t & aTbins,
    const double & aMinScanT,
    const double & aMaxScanT )
```

Parameters

<i>aTbins</i>	The number of T bins to scan over
<i>aMinScanT</i>	The lowest value of T to scan
<i>aMaxScanT</i>	The largest value of T to scan

Definition at line 124 of file Configuration.cpp.

References ScanConfiguration::tBounds::bins, ScanConfiguration::tBounds::max, ScanConfiguration::tBounds::min, mTbounds, and ScanConfiguration::tBounds::spacing.

Referenced by FromVector(), and ScanConfiguration().

4.14.3.19 sigmabins() [1/2]

```
const std::vector< double >& ScanConfiguration::sigmabins ( ) const [inline]
```

Getter for the values of sigma.

Returns

The values of sigma

Definition at line 152 of file Configuration.hpp.

References mSigmabins.

Referenced by Cluster::UpdateLogScore(), and Rolproxy::UpdateLogScore().

4.14.3.20 sigmabins() [2/2]

```
const double& ScanConfiguration::sigmabins (
    const std::size_t & i ) const [inline]
```

Getter for the i'th value of sigma.

Parameters

<i>i</i>	The index of the value of sigma to get
----------	--

Returns

The value of sigma_i

Definition at line 178 of file Configuration.hpp.

References mSigmabins.

4.14.3.21 sigmabins2() [1/2]

```
const std::vector< double >& ScanConfiguration::sigmabins2 ( ) const [inline]
```

Getter for the values of sigma squared.

Returns

The values of sigma squared

Definition at line 158 of file Configuration.hpp.

References mSigmabins2.

Referenced by Rol::ScanRT(), and Rolproxy::ValidateLogScore().

4.14.3.22 sigmabins2() [2/2]

```
const double& ScanConfiguration::sigmabins2 (
    const std::size_t & i ) const [inline]
```

Getter for the i'th value of sigma squared.

Parameters

<i>i</i>	The index of the value of sigma squared to get
----------	--

Returns

The value of sigma_i squared

Definition at line 185 of file Configuration.hpp.

References mSigmabins2.

4.14.3.23 sigmacount()

```
const std::size_t& ScanConfiguration::sigmacount ( ) const [inline]
```

Getter for the sigma count.

Returns

The sigma count

Definition at line 138 of file Configuration.hpp.

References mSigmacount.

Referenced by Rolproxy::ValidateLogScore().

4.14.3.24 sigmaspacing()

```
const double& ScanConfiguration::sigmaspacing ( ) const [inline]
```

Getter for the sigma spacing.

Returns

The sigma spacing

Definition at line 145 of file Configuration.hpp.

References mSigmaspacing.

4.14.3.25 Tbounds()

```
const tBounds& ScanConfiguration::Tbounds ( ) const [inline]
```

Getter for the bounds of T to scan.

Returns

The lbounds of T to scan

Definition at line 212 of file Configuration.hpp.

References mTbounds.

Referenced by Rol::ScanRT().

The documentation for this class was generated from the following files:

- include/BayesianClustering/Configuration.hpp
- src/BayesianClustering/Configuration.cpp

4.15 ScanEntry Struct Reference

A struct for storing a result of an individual scan configuration.

```
#include <API.hpp>
```

Public Member Functions

- bool [operator<](#) (const [ScanEntry](#) &aOther)
Comparison operator for sorting.
- bool [operator==](#) (const [ScanEntry](#) &aOther)
Equality operator required by boost python.

Public Attributes

- double `r`
The R parameter
- double `t`
The T parameter.
- double `score`
The score.

4.15.1 Detailed Description

A struct for storing a result of an individual scan configuration.

Definition at line 16 of file API.hpp.

4.15.2 Member Function Documentation

4.15.2.1 `operator<()`

```
bool ScanEntry::operator< (
    const ScanEntry & aOther ) [inline]
```

Comparison operator for sorting.

Returns

Whether we are smaller than the other

Parameters

<i>aOther</i>	Another <code>ScanEntry</code> to compare against
---------------	---

Definition at line 24 of file API.hpp.

References `r`, and `t`.

4.15.2.2 `operator==()`

```
bool ScanEntry::operator== (
    const ScanEntry & aOther ) [inline]
```

Equality operator required by boost python.

Returns

Whether we are equal to the other

Parameters

<i>aOther</i>	Another ScanEntry to compare against
---------------	--

Definition at line 33 of file API.hpp.

References [r](#), [score](#), and [t](#).

The documentation for this struct was generated from the following file:

- [include/BayesianClustering/API.hpp](#)

4.16 ScanConfiguration::tBounds Struct Reference

A struct to store the bounds of a scan in either R or T.

```
#include <Configuration.hpp>
```

Public Attributes

- double [min](#)
The lowest value of R to scan.
- double [max](#)
The largest value of R to scan.
- double [spacing](#)
The spacing of value of R to scan.
- std::size_t [bins](#)
The number of R values to scan.

4.16.1 Detailed Description

A struct to store the bounds of a scan in either R or T.

Definition at line 17 of file Configuration.hpp.

The documentation for this struct was generated from the following file:

- [include/BayesianClustering/Configuration.hpp](#)


Chapter 5

File Documentation


5.1 include/BayesianClustering/API.hpp File Reference

```
#include <string>
#include <vector>
#include <functional>
```

Include dependency graph for API.hpp:



This graph shows which files directly or indirectly include this file:



Classes

- struct [ScanEntry](#)
A struct for storing a result of an individual scan configuration.
- struct [ClusterWrapper](#)
A struct for storing extracted parameters from a cluster.

Typedefs

- typedef std::function< void([Rolproxy](#) &, const double &, const double &) > [tFullScanCallback](#)
Typedef the full scan callback for clarity.
- typedef std::function< void(const std::string &, const std::vector< [ScanEntry](#) > &) > [tSimpleScanCallback](#)
Typedef the simplified scan callback for clarity.
- typedef std::function< void([Rolproxy](#) &) > [tFullClusterCallback](#)
Typedef the full clustering callback for clarity.
- typedef std::function< void(const std::string &, const std::vector< [ClusterWrapper](#) > &) > [tSimpleClusterCallback](#)
Typedef the simplified clustering callback for clarity.

Functions

- void [AutoRoi_Scan_FullCallback](#) (const std::string &alnFile, const [ScanConfiguration](#) &aScanConfig, const [tFullScanCallback](#) &aCallback)
Automatically extract [Rol](#), run scan and apply a full call-back.
- void [AutoRoi_Scan_SimpleCallback](#) (const std::string &alnFile, const [ScanConfiguration](#) &aScanConfig, const [tSimpleScanCallback](#) &aCallback)
Automatically extract [Rol](#), run scan and apply a simple call-back.
- void [AutoRoi_Scan_ToJson](#) (const std::string &alnFile, const [ScanConfiguration](#) &aScanConfig, const std::string &aOutputPattern)
Automatically extract [Rol](#), run scan and dump to JSON file.
- void [AutoRoi_Cluster_FullCallback](#) (const std::string &alnFile, const double &aR, const double &aT, const [tFullClusterCallback](#) &aCallback)
Automatically extract [Rol](#), clusterize and apply a full call-back.
- void [AutoRoi_Cluster_SimpleCallback](#) (const std::string &alnFile, const double &aR, const double &aT, const [tSimpleClusterCallback](#) &aCallback)
Automatically extract [Rol](#), clusterize and apply a full call-back.
- void [AutoRoi_Cluster_ToJson](#) (const std::string &alnFile, const double &aR, const double &aT, const std::string &aOutputPattern)
Automatically specify [Rol](#), clusterize and apply a full call-back.
- void [ManualRoi_Scan_FullCallback](#) (const std::string &alnFile, const [ManualRol](#) &aManualRol, const [ScanConfiguration](#) &aScanConfig, const [tFullScanCallback](#) &aCallback)
Manually specify [Rol](#), run scan and apply a full call-back.
- void [ManualRoi_Scan_SimpleCallback](#) (const std::string &alnFile, const [ManualRol](#) &aManualRol, const [ScanConfiguration](#) &aScanConfig, const [tSimpleScanCallback](#) &aCallback)
Manually specify [Rol](#), run scan and apply a simple call-back.
- void [ManualRoi_Scan_ToJson](#) (const std::string &alnFile, const [ManualRol](#) &aManualRol, const [ScanConfiguration](#) &aScanConfig, const std::string &aOutputPattern)
Manually specify [Rol](#), run scan and dump to JSON file.
- void [ManualRoi_Cluster_FullCallback](#) (const std::string &alnFile, const [ManualRol](#) &aManualRol, const double &aR, const double &aT, const [tFullClusterCallback](#) &aCallback)
Manually specify [Rol](#), clusterize and apply a full call-back.

- void [ManualRoi_Cluster_SimpleCallback](#) (const std::string &alnFile, const [ManualRoi](#) &aManualRoi, const double &aR, const double &aT, const [tSimpleClusterCallback](#) &aCallback)
Manually specify [Roi](#), clusterize and apply a full call-back.
- void [ManualRoi_Cluster_ToJson](#) (const std::string &alnFile, const [ManualRoi](#) &aManualRoi, const double &aR, const double &aT, const std::string &aOutputPattern)
Manually specify [Roi](#), clusterize and apply a full call-back.
- void [ImageJRoi_Scan_FullCallback](#) (const std::string &alnFile, const std::string &alimageJfile, const double &aScale, const [ScanConfiguration](#) &aScanConfig, const [tFullScanCallback](#) &aCallback)
Extract [Roi](#) using an image-map, run scan and apply a full call-back.
- void [ImageJRoi_Scan_SimpleCallback](#) (const std::string &alnFile, const std::string &alimageJfile, const double &aScale, const [ScanConfiguration](#) &aScanConfig, const [tSimpleScanCallback](#) &aCallback)
Extract [Roi](#) using an image-map, run scan and apply a simple call-back.
- void [ImageJRoi_Scan_ToJson](#) (const std::string &alnFile, const std::string &alimageJfile, const double &aScale, const [ScanConfiguration](#) &aScanConfig, const std::string &aOutputPattern)
Extract [Roi](#) using an image-map, run scan and dump to JSON file.
- void [ImageJRoi_Cluster_FullCallback](#) (const std::string &alnFile, const std::string &alimageJfile, const double &aScale, const double &aR, const double &aT, const [tFullClusterCallback](#) &aCallback)
Extract [Roi](#) using an image-map, clusterize and apply a full call-back.
- void [ImageJRoi_Cluster_SimpleCallback](#) (const std::string &alnFile, const std::string &alimageJfile, const double &aScale, const double &aR, const double &aT, const [tSimpleClusterCallback](#) &aCallback)
Extract [Roi](#) using an image-map, clusterize and apply a full call-back.
- void [ImageJRoi_Cluster_ToJson](#) (const std::string &alnFile, const std::string &alimageJfile, const double &aScale, const double &aR, const double &aT, const std::string &aOutputPattern)
Extract [Roi](#) using an image-map, clusterize and apply a full call-back.

5.1.1 Function Documentation

5.1.1.1 AutoRoi_Cluster_FullCallback()

```
void AutoRoi_Cluster_FullCallback (
    const std::string & aInFile,
    const double & aR,
    const double & aT,
    const tFullClusterCallback & aCallback )
```

Automatically extract [Roi](#), clusterize and apply a full call-back.

Parameters

<i>aInFile</i>	The name of the localization file
<i>aR</i>	The R value of the clusterizer
<i>aT</i>	The T value of the clusterizer
<i>aCallback</i>	The callback to be applied

Definition at line 161 of file API.cpp.

References [Roi::Clusterize\(\)](#), and [LocalizationFile::ExtractRols\(\)](#).

Referenced by [AutoRoi_Cluster_SimpleCallback\(\)](#).

5.1.1.2 AutoRoi_Cluster_SimpleCallback()

```
void AutoRoi_Cluster_SimpleCallback (
    const std::string & aInFile,
    const double & aR,
    const double & aT,
    const tSimpleClusterCallback & aCallback )
```

Automatically extract [Roi](#), clusterize and apply a full call-back.

Parameters

<i>aInFile</i>	The name of the localization file
<i>aR</i>	The R value of the clusterizer
<i>aT</i>	The T value of the clusterizer
<i>aCallback</i>	The callback to be applied

Definition at line 167 of file API.cpp.

References [_FullClusterToSimpleCluster_\(\)](#), and [AutoRoi_Cluster_FullCallback\(\)](#).

Referenced by [AutoRoi_Cluster_ToJson\(\)](#).

5.1.1.3 AutoRoi_Cluster_ToJson()

```
void AutoRoi_Cluster_ToJson (
    const std::string & aInFile,
    const double & aR,
    const double & aT,
    const std::string & aOutputPattern )
```

Automatically specify [Roi](#), clusterize and apply a full call-back.

Parameters

<i>aInFile</i>	The name of the localization file
<i>aR</i>	The R value of the clusterizer
<i>aT</i>	The T value of the clusterizer
<i>aOutputPattern</i>	A formattable-string specifying the name of the output JSON files. Substitutable fields are {input} (giving the stem of the input file name) and {roi} (giving the Roi id).

Definition at line 173 of file API.cpp.

References [_ClusterCallback_Json_\(\)](#), and [AutoRoi_Cluster_SimpleCallback\(\)](#).

Referenced by [BOOST_PYTHON_MODULE\(\)](#), and [main\(\)](#).

5.1.1.4 AutoRoi_Scan_FullCallback()

```
void AutoRoi_Scan_FullCallback (
    const std::string & aInFile,
    const ScanConfiguration & aScanConfig,
    const tFullScanCallback & aCallback )
```

Automatically extract [Roi](#), run scan and apply a full call-back.

Parameters

<i>aInFile</i>	The name of the localization file
<i>aScanConfig</i>	The configuration for the scan
<i>aCallback</i>	The full callback to be applied

Definition at line 141 of file API.cpp.

References [LocalizationFile::ExtractRols\(\)](#), and [Roi::ScanRT\(\)](#).

5.1.1.5 AutoRoi_Scan_SimpleCallback()

```
void AutoRoi_Scan_SimpleCallback (
    const std::string & aInFile,
    const ScanConfiguration & aScanConfig,
    const tSimpleScanCallback & aCallback )
```

Automatically extract [Roi](#), run scan and apply a simple call-back.

Parameters

<i>aInFile</i>	The name of the localization file
<i>aScanConfig</i>	The configuration for the scan
<i>aCallback</i>	The simple callback to be applied

Definition at line 147 of file API.cpp.

References [_FullScanToSimpleScan_\(\)](#), and [LocalizationFile::ExtractRols\(\)](#).

Referenced by [AutoRoi_Scan_ToJson\(\)](#).

5.1.1.6 AutoRoi_Scan_ToJson()

```
void AutoRoi_Scan_ToJson (
    const std::string & aInFile,
    const ScanConfiguration & aScanConfig,
    const std::string & aOutputPattern )
```

Automatically extract [Roi](#), run scan and dump to JSON file.

Parameters

<i>aInFile</i>	The name of the localization file
<i>aScanConfig</i>	The configuration for the scan
<i>aOutputPattern</i>	A formattable-string specifying the name of the output JSON files. Substitutable fields are {input} (giving the stem of the input file name) and {roi} (giving the Roi id).

Definition at line 153 of file API.cpp.

References `_ScanCallback_Json_()`, and `AutoRoi_Scan_SimpleCallback()`.

Referenced by `BOOST_PYTHON_MODULE()`, and `main()`.

5.1.1.7 ImageJRoi_Cluster_FullCallback()

```
void ImageJRoi_Cluster_FullCallback (
    const std::string & aInFile,
    const std::string & aImageJfile,
    const double & aScale,
    const double & aR,
    const double & aT,
    const tFullClusterCallback & aCallback )
```

Extract [Roi](#) using an image-map, clusterize and apply a full call-back.

Parameters

<i>aInFile</i>	The name of the localization file
<i>aImageJfile</i>	The name of an ImageJ Roi file file
<i>aScale</i>	The size of the LSB in the ImageJ file
<i>aR</i>	The R value of the clusterizer
<i>aT</i>	The T value of the clusterizer
<i>aCallback</i>	The callback to be applied

Definition at line 241 of file API.cpp.

References `Roi::Clusterize()`, and `LocalizationFile::ExtractRols()`.

Referenced by `ImageJRoi_Cluster_SimpleCallback()`.

5.1.1.8 ImageJRoi_Cluster_SimpleCallback()

```
void ImageJRoi_Cluster_SimpleCallback (
    const std::string & aInFile,
    const std::string & aImageJfile,
    const double & aScale,
```

```
const double & aR,  
const double & aT,  
const tSimpleClusterCallback & aCallback )
```

Extract [Rol](#) using an image-map, clusterize and apply a full call-back.

Parameters

<i>aInFile</i>	The name of the localization file
<i>aImageJfile</i>	The name of an ImageJ Roi file file
<i>aScale</i>	The size of the LSB in the ImageJ file
<i>aR</i>	The R value of the clusterizer
<i>aT</i>	The T value of the clusterizer
<i>aCallback</i>	The callback to be applied

Definition at line 247 of file API.cpp.

References [_FullClusterToSimpleCluster_\(\)](#), and [ImageJRoi_Cluster_FullCallback\(\)](#).

Referenced by [ImageJRoi_Cluster_ToJson\(\)](#).

5.1.1.9 ImageJRoi_Cluster_ToJson()

```
void ImageJRoi_Cluster_ToJson (
    const std::string & aInFile,
    const std::string & aImageJfile,
    const double & aScale,
    const double & aR,
    const double & aT,
    const std::string & aOutputPattern )
```

Extract [Roi](#) using an image-map, clusterize and apply a full call-back.

Parameters

<i>aInFile</i>	The name of the localization file
<i>aImageJfile</i>	The name of an ImageJ Roi file file
<i>aScale</i>	The size of the LSB in the ImageJ file
<i>aR</i>	The R value of the clusterizer
<i>aT</i>	The T value of the clusterizer
<i>aOutputPattern</i>	A formattable-string specifying the name of the output JSON files. Substitutable fields are {input} (giving the stem of the input file name) and {roi} (giving the Roi id).

Definition at line 253 of file API.cpp.

References [_ClusterCallback_Json_\(\)](#), and [ImageJRoi_Cluster_SimpleCallback\(\)](#).

Referenced by [BOOST_PYTHON_MODULE\(\)](#).

5.1.1.10 ImageJRoi_Scan_FullCallback()

```
void ImageJRoi_Scan_FullCallback (
    const std::string & aInFile,
```



```

const std::string & aImageJfile,
const double & aScale,
const ScanConfiguration & aScanConfig,
const tFullScanCallback & aCallback )

```

Extract [Roi](#) using an image-map, run scan and apply a full call-back.

Parameters

<i>aInFile</i>	The name of the localization file
<i>aImageJfile</i>	The name of an ImageJ Roi file file
<i>aScale</i>	The size of the LSB in the ImageJ file
<i>aScanConfig</i>	The configuration for the scan
<i>aCallback</i>	The full callback to be applied

Definition at line 221 of file API.cpp.

References `LocalizationFile::ExtractRols()`, and `Roi::ScanRT()`.

5.1.1.11 ImageJRoi_Scan_SimpleCallback()

```

void ImageJRoi_Scan_SimpleCallback (
    const std::string & aInFile,
    const std::string & aImageJfile,
    const double & aScale,
    const ScanConfiguration & aScanConfig,
    const tSimpleScanCallback & aCallback )

```

Extract [Roi](#) using an image-map, run scan and apply a simple call-back.

Parameters

<i>aInFile</i>	The name of the localization file
<i>aImageJfile</i>	The name of an ImageJ Roi file file
<i>aScale</i>	The size of the LSB in the ImageJ file
<i>aScanConfig</i>	The configuration for the scan
<i>aCallback</i>	The simple callback to be applied

Definition at line 227 of file API.cpp.

References `_FullScanToSimpleScan_()`, and `LocalizationFile::ExtractRols()`.

Referenced by `ImageJRoi_Scan_ToJson()`.

5.1.1.12 ImageJRoi_Scan_ToJson()

```
void ImageJRoi_Scan_ToJson (
    const std::string & aInFile,
    const std::string & aImageJfile,
    const double & aScale,
    const ScanConfiguration & aScanConfig,
    const std::string & aOutputPattern )
```

Extract [Roi](#) using an image-map, run scan and dump to JSON file.

Parameters

<i>aInFile</i>	The name of the localization file
<i>aImageJfile</i>	The name of an ImageJ Roi file file
<i>aScale</i>	The size of the LSB in the ImageJ file
<i>aScanConfig</i>	The configuration for the scan
<i>aOutputPattern</i>	A formattable-string specifying the name of the output JSON files. Substitutable fields are {input} (giving the stem of the input file name) and {roi} (giving the Roi id).

Definition at line 233 of file API.cpp.

References [_ScanCallback_Json_\(\)](#), and [ImageJRoi_Scan_SimpleCallback\(\)](#).

Referenced by [BOOST_PYTHON_MODULE\(\)](#).

5.1.1.13 ManualRoi_Cluster_FullCallback()

```
void ManualRoi_Cluster_FullCallback (
    const std::string & aInFile,
    const ManualRoi & aManualRoi,
    const double & aR,
    const double & aT,
    const tFullClusterCallback & aCallback )
```

Manually specify [Roi](#), clusterize and apply a full call-back.

Parameters

<i>aInFile</i>	The name of the localization file
<i>aManualRoi</i>	The manually-specified Roi window
<i>aR</i>	The R value of the clusterizer
<i>aT</i>	The T value of the clusterizer
<i>aCallback</i>	The callback to be applied

Definition at line 201 of file API.cpp.

References [Roi::Clusterize\(\)](#), and [LocalizationFile::ExtractRols\(\)](#).

Referenced by [ManualRoi_Cluster_SimpleCallback\(\)](#).

5.1.1.14 ManualRoi_Cluster_SimpleCallback()

```
void ManualRoi_Cluster_SimpleCallback (
    const std::string & aInFile,
    const ManualRoi & aManualRoi,
    const double & aR,
    const double & aT,
    const tSimpleClusterCallback & aCallback )
```

Manually specify [Roi](#), clusterize and apply a full call-back.

Parameters

<i>aInFile</i>	The name of the localization file
<i>aManualRoi</i>	The manually-specified Roi window
<i>aR</i>	The R value of the clusterizer
<i>aT</i>	The T value of the clusterizer
<i>aCallback</i>	The callback to be applied

Definition at line 207 of file API.cpp.

References [_FullClusterToSimpleCluster_\(\)](#), and [ManualRoi_Cluster_FullCallback\(\)](#).

Referenced by [ManualRoi_Cluster_ToJson\(\)](#).

5.1.1.15 ManualRoi_Cluster_ToJson()

```
void ManualRoi_Cluster_ToJson (
    const std::string & aInFile,
    const ManualRoi & aManualRoi,
    const double & aR,
    const double & aT,
    const std::string & aOutputPattern )
```

Manually specify [Roi](#), clusterize and apply a full call-back.

Parameters

<i>aInFile</i>	The name of the localization file
<i>aManualRoi</i>	The manually-specified Roi window
<i>aR</i>	The R value of the clusterizer
<i>aT</i>	The T value of the clusterizer
<i>aOutputPattern</i>	A formattable-string specifying the name of the output JSON files. Substitutable fields are {input} (giving the stem of the input file name) and {roi} (giving the Roi id).

Definition at line 213 of file API.cpp.

References [_ClusterCallback_Json_\(\)](#), and [ManualRoi_Cluster_SimpleCallback\(\)](#).

Referenced by [BOOST_PYTHON_MODULE\(\)](#).

5.1.1.16 ManualRoi_Scan_FullCallback()

```
void ManualRoi_Scan_FullCallback (
    const std::string & aInFile,
    const ManualRoi & aManualRoi,
    const ScanConfiguration & aScanConfig,
    const tFullScanCallback & aCallback )
```

Manually specify [Roi](#), run scan and apply a full call-back.

Parameters

<i>aInFile</i>	The name of the localization file
<i>aManualRoi</i>	The manually-specified Roi window
<i>aScanConfig</i>	The configuration for the scan
<i>aCallback</i>	The full callback to be applied

Definition at line 181 of file API.cpp.

References LocalizationFile::ExtractRols(), and Roi::ScanRT().

5.1.1.17 ManualRoi_Scan_SimpleCallback()

```
void ManualRoi_Scan_SimpleCallback (
    const std::string & aInFile,
    const ManualRoi & aManualRoi,
    const ScanConfiguration & aScanConfig,
    const tSimpleScanCallback & aCallback )
```

Manually specify [Roi](#), run scan and apply a simple call-back.

Parameters

<i>aInFile</i>	The name of the localization file
<i>aManualRoi</i>	The manually-specified Roi window
<i>aScanConfig</i>	The configuration for the scan
<i>aCallback</i>	The simple callback to be applied

Definition at line 187 of file API.cpp.

References _FullScanToSimpleScan_(), and LocalizationFile::ExtractRols().

Referenced by ManualRoi_Scan_ToJson().

5.1.1.18 ManualRoi_Scan_ToJson()

```
void ManualRoi_Scan_ToJson (
    const std::string & aInFile,
    const ManualRoi & aManualRoi,
    const ScanConfiguration & aScanConfig,
    const std::string & aOutputPattern )
```

Manually specify [Roi](#), run scan and dump to JSON file.

Parameters

<i>aInFile</i>	The name of the localization file
<i>aManualRoi</i>	The manually-specified Roi window
<i>aScanConfig</i>	The configuration for the scan
<i>aOutputPattern</i>	A formattable-string specifying the name of the output JSON files. Substitutable fields are {input} (giving the stem of the input file name) and {roi} (giving the Roi id).


Definition at line 193 of file API.cpp.

References [_ScanCallback_Json_\(\)](#), and [ManualRoi_Scan_SimpleCallback\(\)](#).


Referenced by [BOOST_PYTHON_MODULE\(\)](#).

5.2 include/BayesianClustering/Cluster.hpp File Reference

```
#include <vector>
#include "BayesianClustering/Precision.hpp"
Include dependency graph for Cluster.hpp:
```



This graph shows which files directly or indirectly include this file:




Classes

- class [Cluster](#)
A class representing a cluster.
- struct [Cluster::Parameter](#)
A struct representing the cluster parameters.


5.3 include/BayesianClustering/Configuration.hpp File Reference

```
#include <map>
#include <vector>
#include <string>
#include <functional>
#include <stdexcept>
```

Include dependency graph for Configuration.hpp:



This graph shows which files directly or indirectly include this file:




Classes

- class [ScanConfiguration](#)
A class for storing the scan configuration parameters.
- struct [ScanConfiguration::tBounds](#)
A struct to store the bounds of a scan in either R or T.
- class [AuxConfiguration](#)
Class for storing the auxilliary configuration parameters.


5.4 include/BayesianClustering/Data.hpp File Reference

```
#include <math.h>
#include <vector>
#include "BayesianClustering/Precision.hpp"
#include "BayesianClustering/Configuration.hpp"
```

Include dependency graph for Data.hpp:



This graph shows which files directly or indirectly include this file:




Classes

- class [Data](#)


A class to store the raw data-points.

5.5 include/BayesianClustering/DataProxy.hpp File Reference

```
#include <cstdint>
#include "BayesianClustering/Precision.hpp"
#include "BayesianClustering/Cluster.hpp"
Include dependency graph for DataProxy.hpp:
```



This graph shows which files directly or indirectly include this file:



Classes


- class [DataProxy](#)

A light-weight proxy for the raw data-points.


5.6 include/BayesianClustering/ImageJ_Rol.hpp File Reference

```
#include <string>
#include <map>
#include <boost/geometry.hpp>
#include <boost/geometry/geometries/polygon.hpp>
```

Include dependency graph for ImageJ_Rol.hpp:



This graph shows which files directly or indirectly include this file:



Typedefs

- `typedef boost::geometry::model::point< uint16_t, 2, boost::geometry::cs::cartesian > roi_point`
Typedef a boost::geometry type representing an ImageJ Roi point for simplicity.
- `typedef boost::geometry::model::ring< roi_point > roi_polygon`
Typedef a boost::geometry type representing an ImageJ Roi polygon for simplicity.

Functions

- `roi_polygon DecodeBinaryRol (const uint8_t *const aData)`
Decode ImageJ binary [Rol](#) data to boost::geometry polygon Reverse engineered from <https://github.com/imagej/ImageJ/blob/master/ij/io/RoiDecoder.java>.
- `std::map< std::string, roi_polygon > OpenRoiZipfile (const std::string &aZipFileName)`
Decode ImageJ zipped binary [Rol](#) data to a map of named boost::geometry polygons.

5.6.1 Function Documentation

5.6.1.1 DecodeBinaryRol()

```
roi_polygon DecodeBinaryRoI (
    const uint8_t *const aData )
```

Decode ImageJ binary [Rol](#) data to boost::geometry polygon Reverse engineered from <https://github.com/imagej/ImageJ/blob/master/ij/io/RoiDecoder.java>.

Parameters

<i>aData</i>	A C-array containing the binary Rol data
--------------	--

Returns

A boost::geometry polygon containing the [Rol](#) information

Definition at line 14 of file ImageJ_Rol.cpp.

Referenced by OpenRoiZipfile().

5.6.1.2 OpenRoiZipfile()

```
std::map< std::string , roi_polygon > OpenRoiZipfile (
    const std::string & aZipFileName )
```

Decode ImageJ zipped binary [Rol](#) data to a map of named boost::geometry polygons.

Parameters

<i>aZipFileName</i>	The name of the zip-file to be opened
---------------------	---------------------------------------

Returns

A map of named boost::geometry polygons containing the [Rol](#) information

Definition at line 28 of file ImageJ_Rol.cpp.

References DecodeBinaryRol().


Referenced by LocalizationFile::ExtractRols(), and GetRols().

5.7 include/BayesianClustering/LocalizationFile.hpp File Reference


```
#include <vector>
#include <string>
```

```
#include <functional>
```

Include dependency graph for LocalizationFile.hpp:



This graph shows which files directly or indirectly include this file:




Classes

- struct [ManualRol](#)
A struct for storing the parameters of a manual [Rol](#).
- class [LocalizationFile](#)
A class to store the raw data-points.

5.8 include/BayesianClustering/Precision.hpp File Reference

This graph shows which files directly or indirectly include this file:




5.9 include/BayesianClustering/Rol.hpp File Reference

```


#include <vector>
#include <functional>
#include <string>
#include "BayesianClustering/Data.hpp"
#include "BayesianClustering/Configuration.hpp"

```

Include dependency graph for Rol.hpp:



This graph shows which files directly or indirectly include this file:



Classes


- class [Rol](#)

A class which holds the raw [Rol](#) data and global parameters.


5.10 include/BayesianClustering/Rolproxy.hpp File Reference

```
#include <vector>
#include <functional>
#include <cstdint>
#include "BayesianClustering/Cluster.hpp"
#include "BayesianClustering/DataProxy.hpp"
#include "BayesianClustering/Configuration.hpp"
```

Include dependency graph for Rolproxy.hpp:



This graph shows which files directly or indirectly include this file:



Classes


- class [Rolproxy](#)

A lightweight wrapper for the [Rol](#) to store clusters for a given scan.


5.11 include/Utilities/GSLInterpolator.hpp File Reference

```
#include <map>
#include <vector>
#include <string>
#include <cassert>
#include <iostream>
#include <functional>
#include "gsl/gsl_interp.h"
#include "gsl/gsl_spline.h"
#include "gsl/gsl_errno.h"
```

Include dependency graph for GSLInterpolator.hpp:



This graph shows which files directly or indirectly include this file:



Classes

- class [GSLInterpolator](#)


A utility wrapper around the GSL interpolator to give it a clean C++ interface.

5.12 include/Utilities/ListComprehension.hpp File Reference


```
#include <numeric>
#include <functional>
#include <algorithm>
```

```
#include <vector>
```

Include dependency graph for ListComprehension.hpp:



This graph shows which files directly or indirectly include this file:



Functions

- `template<typename tContainer , typename tExpr , typename T = typename std::remove_reference<tContainer>::type::value_type, typename U = decltype(std::declval<tExpr>().operator()(std::declval<T>()))>`
`std::enable_if< not std::is_same< U, void >::value, std::vector< U >::type operator| (tExpr &&aExpr, tContainer &&aContainer)`

Super nerd template magic emulating list comprehension for function with return type.

- `template<typename tContainer , typename tExpr , typename T = typename std::remove_reference<tContainer>::type::value_type, typename U = decltype(std::declval<tExpr>().operator()(std::declval<T>()))>`
`std::enable_if< std::is_same< U, void >::value, void >::type operator| (tExpr &&aExpr, tContainer &&aContainer)`

Super nerd template magic emulating list comprehension for function with void return type.

- `template<typename tContainer , typename tType , typename tContainerType = typename std::remove_reference<tContainer>::type::value_type>`
`std::vector< tType > operator| (tType tContainerType::*aPtr, tContainer &&aContainer)`

Return a container holding copies of a member-variable from each object in a container.

- `std::vector< std::size_t > range (const std::size_t &N)`

Emulate the python range function to generate a vector of ints.

5.12.1 Function Documentation

5.12.1.1 operator" |() [1/3]

```
template<typename tContainer , typename tExpr , typename T = typename std::remove_reference<t↵
Container>::type::value_type, typename U = decltype( std::declval<tExpr>().operator()( std↵
::declval<T>() ) )>
std::enable_if< not std::is_same<U, void>::value, std::vector< U > ::type operator| (
    tExpr && aExpr,
    tContainer && aContainer ) [inline]
```

Super nerd template magic emulating list comprehension for function with return type.

Template Parameters

<i>tContainer</i>	A container type
<i>tExpr</i>	A function-call type
<i>T</i>	Template magic to determine the type of the data in the container
<i>U</i>	Template magic to determine the return-type of the function, given the type of the data in the container

Parameters

<i>aExpr</i>	A function-call to be applied to each element of the container
<i>aContainer</i>	A container holding the arguments to be fed to the expression

Returns

A vector of the results of the vectorized operations

Definition at line 20 of file ListComprehension.hpp.

5.12.1.2 operator" |() [2/3]

```
template<typename tContainer , typename tExpr , typename T = typename std::remove_reference<t↵
Container>::type::value_type, typename U = decltype( std::declval<tExpr>().operator()( std↵
::declval<T>() ) )>
std::enable_if< std::is_same<U, void>::value, void > ::type operator| (
    tExpr && aExpr,
    tContainer && aContainer ) [inline]
```

Super nerd template magic emulating list comprehension for function with void return type.

Template Parameters

<i>tContainer</i>	A container type
<i>tExpr</i>	A function-call type
<i>T</i>	Template magic to determine the type of the data in the container
<i>U</i>	Template magic to determine the return-type of the function, given the type of the data in the container

Parameters

<i>aExpr</i>	A function-call to be applied to each element of the container
<i>aContainer</i>	A container holding the arguments to be fed to the expression

Returns

Specialization of the vectorization for functions returning void

Definition at line 39 of file ListComprehension.hpp.

5.12.1.3 operator" | () [3/3]

```
template<typename tContainer , typename tType , typename tContainerType = typename std::remove_←
_reference<tContainer>::type::value_type>
std::vector< tType > operator| (
    tType tContainerType::* aPtr,
    tContainer && aContainer ) [inline]
```

Return a container holding copies of a member-variable from each object in a container.

Template Parameters

<i>tType</i>	A container type
<i>tContainerType</i>	Template magic to determine the type of the data in the container

Parameters

<i>aPtr</i>	A pointer-to-member-variable to be applied to each element of the container
<i>aContainer</i>	A container holding the objects whose member variable is to be extracted

Returns

A vector of the results of the vectorized operations

Definition at line 51 of file ListComprehension.hpp.

5.12.1.4 range()

```
std::vector< std::size_t > range (
    const std::size_t & N ) [inline]
```

Emulate the python range function to generate a vector of ints.

Parameters

N	The number of elements
-----	------------------------

Returns

A vector of ints


Definition at line 70 of file ListComprehension.hpp.

Referenced by LocalizationFile::LocalizationFile(), Rol::Preprocess(), Rol::ScanRT(), and ScanConfiguration::SetSigmaParameters().

5.13 include/Utilities/MemoryMonitoring.hpp File Reference

```
#include <unistd.h>
#include <ios>
#include <fstream>
#include <string>
```

Include dependency graph for MemoryMonitoring.hpp:

**Functions**

- void [mem_usage](#) (double &vm_usage, double &resident_set)
Utility to get Virtual Memory and Resident Set usage.

5.13.1 Function Documentation

5.13.1.1 mem_usage()

```
void mem_usage (
    double & vm_usage,
    double & resident_set )
```

Utility to get Virtual Memory and Resident Set usage.

Parameters

<i>vm_usage</i>	Return the Virtual Memory usage
<i>resident_set</i>	Return the Resident Set usage


Definition at line 12 of file MemoryMonitoring.hpp.

5.14 include/Utilities/ProgressBar.hpp File Reference


```
#include <chrono>
```

```
#include <mutex>
```

Include dependency graph for ProgressBar.hpp:



This graph shows which files directly or indirectly include this file:



Classes


- class [ProgressBar](#)
A utility progress-bar.
- struct [ProgressTimer](#)
A utility code timer.

5.15 include/Utilities/Units.hpp File Reference


```
#include <map>
```

```
#include <string>
```

Include dependency graph for Units.hpp:



This graph shows which files directly or indirectly include this file:



Functions

- long double `operator""_nanometer` (long double aVal)
User-defined literals for nanometer quantities.
- long double `operator""_nanometer` (unsigned long long aVal)
User-defined literals for nanometer quantities.
- long double `operator""_micrometer` (long double aVal)
User-defined literals for micrometer quantities.
- long double `operator""_micrometer` (unsigned long long aVal)
User-defined literals for micrometer quantities.
- long double `StrToDist` (const std::string &aStr)
Convert a string representation to a distance.

Variables

- double `nanometer` = 1e-9
Define a constant for converting nanometers to meters.
- double `micrometer` = 1e-6

- Define a constant for converting micrometers to meters.*
 - double `millimeter` = 1e-3
- Define a constant for converting millimeters to meters.*
 - double `meter` = 1e-0
- Define a constant for converting meters to meters.*
 - const std::map< std::string, double > `UnitMap`
- A map for converting string representations of SI units to scaling factors.*

5.15.1 Function Documentation

5.15.1.1 `operator""_micrometer()` [1/2]

```
long double operator""_micrometer (
    long double aVal )
```

User-defined literals for micrometer quantities.

Parameters

<i>aVal</i>	The specified value
-------------	---------------------

Returns

The literal value

Definition at line 39 of file Units.hpp.

References `micrometer`.

5.15.1.2 `operator""_micrometer()` [2/2]

```
long double operator""_micrometer (
    unsigned long long aVal )
```

User-defined literals for micrometer quantities.

Parameters

<i>aVal</i>	The specified value
-------------	---------------------

Returns

The literal value

Definition at line 47 of file Units.hpp.

References micrometer.

5.15.1.3 `operator""_nanometer()` [1/2]

```
long double operator""_nanometer (
    long double aVal )
```

User-defined literals for nanometer quantities.

Parameters

<i>aVal</i>	The specified value
-------------	---------------------

Returns

The literal value

Definition at line 23 of file Units.hpp.

References nanometer.

5.15.1.4 `operator""_nanometer()` [2/2]

```
long double operator""_nanometer (
    unsigned long long aVal )
```

User-defined literals for nanometer quantities.

Parameters

<i>aVal</i>	The specified value
-------------	---------------------

Returns

The literal value

Definition at line 31 of file Units.hpp.

References nanometer.

5.15.1.5 StrToDist()

```
long double StrToDist (
    const std::string & aStr )
```

Convert a string representation to a distance.

Parameters

<i>aStr</i>	A string representation of a distance
-------------	---------------------------------------

Returns

The literal value

Definition at line 12 of file Units.cpp.


References UnitMap.

Referenced by ScanConfiguration::FromVector(), and AuxConfiguration::FromVector().


5.16 include/Utilities/Vectorize.hpp File Reference

```
#include <boost/asio/post.hpp>
#include <boost/asio/thread_pool.hpp>
#include <functional>
#include <cmath>
#include "ListComprehension.hpp"
```

Include dependency graph for Vectorize.hpp:



This graph shows which files directly or indirectly include this file:



Functions

- `template<typename tContainer , typename tExpr , typename tContainerType = typename std::remove_reference<tContainer>::type←
::value_type>
void operator|| (tExpr &&aExpr, tContainer &&aContainer)`
Syntactic sugar to allow you to interleave parallelize via operator.
- `template<typename tContainer , typename tExpr , typename tContainerType = typename std::remove_reference<tContainer>::type←
::value_type>
void operator&& (tExpr &&aExpr, tContainer &&aContainer)`
Syntactic sugar to allow you to block parallelize via operator.

Variables

- `std::size_t Nthreads`
Utility variable for the concurrency.

5.16.1 Function Documentation

5.16.1.1 `operator&&()`

```
template<typename tContainer , typename tExpr , typename tContainerType = typename std::remove←
_reference<tContainer>::type::value_type>
void operator&& (
    tExpr && aExpr,
    tContainer && aContainer ) [inline]
```

Syntactic sugar to allow you to block parallelize via operator.

Template Parameters

<i>tContainer</i>	A container type
<i>tExpr</i>	A function-call type
<i>tContainerType</i>	A SFINAE hack to ensure that the container is a container

Parameters

<i>aExpr</i>	A function-call to be applied to each element of the container
<i>aContainer</i>	A container holding the arguments to be distributed to the parallelized function calls

Definition at line 38 of file Vectorize.hpp.

References [Nthreads](#).

5.16.1.2 operator" | " |()

```
template<typename tContainer , typename tExpr , typename tContainerType = typename std::remove←
_reference<tContainer>::type::value_type>
void operator| (
    tExpr && aExpr,
    tContainer && aContainer ) [inline]
```

Syntactic sugar to allow you to interleave parallelize via operator.

Template Parameters

<i>tContainer</i>	A container type
<i>tExpr</i>	A function-call type
<i>tContainerType</i>	A SFINAE hack to ensure that the container is a container

Parameters

<i>aExpr</i>	A function-call to be applied to each element of the container
<i>aContainer</i>	A container holding the arguments to be distributed to the parallelized function calls

Definition at line 22 of file Vectorize.hpp.

References Nthreads.

5.16.2 Variable Documentation

5.16.2.1 Nthreads

```
std::size_t Nthreads [extern]
```

Utility variable for the concurrency.

Utility variable for the concurrency.


Definition at line 8 of file Vectorize.cpp.

Referenced by AuxConfiguration::FromVector(), LocalizationFile::LocalizationFile(), operator&&(), operator|(), and Rol::ScanRT().

5.17 src/BayesianClustering/API.cpp File Reference

```
#include "BayesianClustering/API.hpp"
#include "BayesianClustering/LocalizationFile.hpp"
#include "BayesianClustering/Configuration.hpp"
#include "BayesianClustering/RoI.hpp"
#include "BayesianClustering/RoIproxy.hpp"
#include <map>
#include <algorithm>
#include <mutex>
#include <boost/geometry.hpp>
#include <boost/geometry/geometries/polygon.hpp>
#include <boost/filesystem.hpp>
#include <fmt/format.h>
```

Include dependency graph for API.cpp:



Functions

- void [_ScanCallback_Json_](#) (const std::string &aRoild, const std::vector< [ScanEntry](#) > &aVector, const std::string &aInFile, const std::string &aOutputPattern)
A callback to dump a scan to a JSON file.
- void [_FullScanToSimpleScan_](#) (RoI &aRoI, const [ScanConfiguration](#) &aScanConfig, const [tSimpleScanCallback](#) &aCallback)
A callback to neatly package the scan results for easy consumption.
- void [_ClusterCallback_Json_](#) (const std::string &aRoild, const std::vector< [ClusterWrapper](#) > &aVector, const std::string &aInFile, const std::string &aOutputPattern)
A callback to dump a clustering run to a JSON file.
- void [_FullClusterToSimpleCluster_](#) (RoIproxy &aRoIproxy, const [tSimpleClusterCallback](#) &aCallback)
A callback to neatly package the scan results for easy consumption.
- void [AutoRoI_Scan_FullCallback](#) (const std::string &aInFile, const [ScanConfiguration](#) &aScanConfig, const [tFullScanCallback](#) &aCallback)
Automatically extract [RoI](#), run scan and apply a full call-back.
- void [AutoRoI_Scan_SimpleCallback](#) (const std::string &aInFile, const [ScanConfiguration](#) &aScanConfig, const [tSimpleScanCallback](#) &aCallback)
Automatically extract [RoI](#), run scan and apply a simple call-back.
- void [AutoRoI_Scan_ToJson](#) (const std::string &aInFile, const [ScanConfiguration](#) &aScanConfig, const std::string &aOutputPattern)
Automatically extract [RoI](#), run scan and dump to JSON file.
- void [AutoRoI_Cluster_FullCallback](#) (const std::string &aInFile, const double &aR, const double &aT, const [tFullClusterCallback](#) &aCallback)
Automatically extract [RoI](#), clusterize and apply a full call-back.
- void [AutoRoI_Cluster_SimpleCallback](#) (const std::string &aInFile, const double &aR, const double &aT, const [tSimpleClusterCallback](#) &aCallback)

- Automatically extract [Roi](#), clusterize and apply a full call-back.*
- void [AutoRoi_Cluster_ToJson](#) (const std::string &InFile, const double &aR, const double &aT, const std::string &aOutputPattern)
- Automatically specify [Roi](#), clusterize and apply a full call-back.*
- void [ManualRoi_Scan_FullCallback](#) (const std::string &InFile, const [ManualRoi](#) &aManualRoi, const [ScanConfiguration](#) &aScanConfig, const [tFullScanCallback](#) &aCallback)
- Manually specify [Roi](#), run scan and apply a full call-back.*
- void [ManualRoi_Scan_SimpleCallback](#) (const std::string &InFile, const [ManualRoi](#) &aManualRoi, const [ScanConfiguration](#) &aScanConfig, const [tSimpleScanCallback](#) &aCallback)
- Manually specify [Roi](#), run scan and apply a simple call-back.*
- void [ManualRoi_Scan_ToJson](#) (const std::string &InFile, const [ManualRoi](#) &aManualRoi, const [ScanConfiguration](#) &aScanConfig, const std::string &aOutputPattern)
- Manually specify [Roi](#), run scan and dump to JSON file.*
- void [ManualRoi_Cluster_FullCallback](#) (const std::string &InFile, const [ManualRoi](#) &aManualRoi, const double &aR, const double &aT, const [tFullClusterCallback](#) &aCallback)
- Manually specify [Roi](#), clusterize and apply a full call-back.*
- void [ManualRoi_Cluster_SimpleCallback](#) (const std::string &InFile, const [ManualRoi](#) &aManualRoi, const double &aR, const double &aT, const [tSimpleClusterCallback](#) &aCallback)
- Manually specify [Roi](#), clusterize and apply a full call-back.*
- void [ManualRoi_Cluster_ToJson](#) (const std::string &InFile, const [ManualRoi](#) &aManualRoi, const double &aR, const double &aT, const std::string &aOutputPattern)
- Manually specify [Roi](#), clusterize and apply a full call-back.*
- void [ImageJRoi_Scan_FullCallback](#) (const std::string &InFile, const std::string &almageJfile, const double &aScale, const [ScanConfiguration](#) &aScanConfig, const [tFullScanCallback](#) &aCallback)
- Extract [Roi](#) using an image-map, run scan and apply a full call-back.*
- void [ImageJRoi_Scan_SimpleCallback](#) (const std::string &InFile, const std::string &almageJfile, const double &aScale, const [ScanConfiguration](#) &aScanConfig, const [tSimpleScanCallback](#) &aCallback)
- Extract [Roi](#) using an image-map, run scan and apply a simple call-back.*
- void [ImageJRoi_Scan_ToJson](#) (const std::string &InFile, const std::string &almageJfile, const double &aScale, const [ScanConfiguration](#) &aScanConfig, const std::string &aOutputPattern)
- Extract [Roi](#) using an image-map, run scan and dump to JSON file.*
- void [ImageJRoi_Cluster_FullCallback](#) (const std::string &InFile, const std::string &almageJfile, const double &aScale, const double &aR, const double &aT, const [tFullClusterCallback](#) &aCallback)
- Extract [Roi](#) using an image-map, clusterize and apply a full call-back.*
- void [ImageJRoi_Cluster_SimpleCallback](#) (const std::string &InFile, const std::string &almageJfile, const double &aScale, const double &aR, const double &aT, const [tSimpleClusterCallback](#) &aCallback)
- Extract [Roi](#) using an image-map, clusterize and apply a full call-back.*
- void [ImageJRoi_Cluster_ToJson](#) (const std::string &InFile, const std::string &almageJfile, const double &aScale, const double &aR, const double &aT, const std::string &aOutputPattern)
- Extract [Roi](#) using an image-map, clusterize and apply a full call-back.*

5.17.1 Function Documentation

5.17.1.1 [_ClusterCallback_Json_\(\)](#)

```
void _ClusterCallback_Json_ (
    const std::string & aRoiId,
    const std::vector< ClusterWrapper > & aVector,
    const std::string & aInFile,
    const std::string & aOutputPattern )
```

A callback to dump a clustering run to a JSON file.

Parameters

<i>aRoId</i>	The RoI ID
<i>aVector</i>	A vector of cluster-wrappers
<i>aInFile</i>	The name of the localization file
<i>aOutputPattern</i>	The name of the output JSON file

Definition at line 89 of file API.cpp.

Referenced by `AutoRoi_Cluster_ToJson()`, `ImageJRoi_Cluster_ToJson()`, and `ManualRoi_Cluster_ToJson()`.

5.17.1.2 `_FullClusterToSimpleCluster_()`

```
void _FullClusterToSimpleCluster_ (
    RoIproxy & aRoIproxy,
    const tSimpleClusterCallback & aCallback )
```

A callback to neatly package the scan results for easy consumption.

Parameters

<i>aRoIproxy</i>	The region-proxy containing the clusters
<i>aCallback</i>	The simple callback to be applied

Definition at line 108 of file API.cpp.

References `Roi::id()`, `Roiproxy::mData`, and `Roiproxy::mRoi`.

Referenced by `AutoRoi_Cluster_SimpleCallback()`, `ImageJRoi_Cluster_SimpleCallback()`, and `ManualRoi_Cluster_SimpleCallback()`.

5.17.1.3 `_FullScanToSimpleScan_()`

```
void _FullScanToSimpleScan_ (
    RoI & aRoI,
    const ScanConfiguration & aScanConfig,
    const tSimpleScanCallback & aCallback )
```

A callback to neatly package the scan results for easy consumption.

Parameters

<i>aRoI</i>	The region of interest
<i>aScanConfig</i>	The configuration for the scan
<i>aCallback</i>	The simple callback to be applied

Definition at line 74 of file API.cpp.

References `Rol::id()`, and `Rol::ScanRT()`.

Referenced by `AutoRoi_Scan_SimpleCallback()`, `ImageJRoi_Scan_SimpleCallback()`, and `ManualRoi_Scan_SimpleCallback()`.

5.17.1.4 _ScanCallback_Json_()

```
void _ScanCallback_Json_ (
    const std::string & aRoiId,
    const std::vector< ScanEntry > & aVector,
    const std::string & aInFile,
    const std::string & aOutputPattern )
```

A callback to dump a scan to a JSON file.

Parameters

<i>aRoiId</i>	The Rol ID
<i>aVector</i>	A vector of scan results
<i>aInFile</i>	The name of the localization file
<i>aOutputPattern</i>	The name of the output JSON file

Definition at line 28 of file API.cpp.

Referenced by `AutoRoi_Scan_ToJson()`, `ImageJRoi_Scan_ToJson()`, and `ManualRoi_Scan_ToJson()`.

5.17.1.5 AutoRoi_Cluster_FullCallback()

```
void AutoRoi_Cluster_FullCallback (
    const std::string & aInFile,
    const double & aR,
    const double & aT,
    const tFullClusterCallback & aCallback )
```

Automatically extract [Rol](#), clusterize and apply a full call-back.

Parameters

<i>aInFile</i>	The name of the localization file
<i>aR</i>	The R value of the clusterizer
<i>aT</i>	The T value of the clusterizer
<i>aCallback</i>	The callback to be applied

Definition at line 161 of file API.cpp.

References `Rol::Clusterize()`, and `LocalizationFile::ExtractRols()`.

Referenced by `AutoRoi_Cluster_SimpleCallback()`.

5.17.1.6 `AutoRoi_Cluster_SimpleCallback()`

```
void AutoRoi_Cluster_SimpleCallback (
    const std::string & aInFile,
    const double & aR,
    const double & aT,
    const tSimpleClusterCallback & aCallback )
```

Automatically extract `Rol`, clusterize and apply a full call-back.

Parameters

<i>aInFile</i>	The name of the localization file
<i>aR</i>	The R value of the clusterizer
<i>aT</i>	The T value of the clusterizer
<i>aCallback</i>	The callback to be applied

Definition at line 167 of file `API.cpp`.

References `_FullClusterToSimpleCluster_()`, and `AutoRoi_Cluster_FullCallback()`.

Referenced by `AutoRoi_Cluster_ToJson()`.

5.17.1.7 `AutoRoi_Cluster_ToJson()`

```
void AutoRoi_Cluster_ToJson (
    const std::string & aInFile,
    const double & aR,
    const double & aT,
    const std::string & aOutputPattern )
```

Automatically specify `Rol`, clusterize and apply a full call-back.

Parameters

<i>aInFile</i>	The name of the localization file
<i>aR</i>	The R value of the clusterizer
<i>aT</i>	The T value of the clusterizer
<i>aOutputPattern</i>	A formattable-string specifying the name of the output JSON files. Substitutable fields are {input} (giving the stem of the input file name) and {roi} (giving the <code>Rol</code> id).

Definition at line 173 of file `API.cpp`.

References `_ClusterCallback_Json_()`, and `AutoRoi_Cluster_SimpleCallback()`.

Referenced by `BOOST_PYTHON_MODULE()`, and `main()`.

5.17.1.8 AutoRoi_Scan_FullCallback()

```
void AutoRoi_Scan_FullCallback (
    const std::string & aInFile,
    const ScanConfiguration & aScanConfig,
    const tFullScanCallback & aCallback )
```

Automatically extract [Roi](#), run scan and apply a full call-back.

Parameters

<i>aInFile</i>	The name of the localization file
<i>aScanConfig</i>	The configuration for the scan
<i>aCallback</i>	The full callback to be applied

Definition at line 141 of file `API.cpp`.

References `LocalizationFile::ExtractRols()`, and `Roi::ScanRT()`.

5.17.1.9 AutoRoi_Scan_SimpleCallback()

```
void AutoRoi_Scan_SimpleCallback (
    const std::string & aInFile,
    const ScanConfiguration & aScanConfig,
    const tSimpleScanCallback & aCallback )
```

Automatically extract [Roi](#), run scan and apply a simple call-back.

Parameters

<i>aInFile</i>	The name of the localization file
<i>aScanConfig</i>	The configuration for the scan
<i>aCallback</i>	The simple callback to be applied

Definition at line 147 of file `API.cpp`.

References `_FullScanToSimpleScan_()`, and `LocalizationFile::ExtractRols()`.

Referenced by `AutoRoi_Scan_ToJson()`.

5.17.1.10 AutoRoi_Scan_ToJson()

```
void AutoRoi_Scan_ToJson (
    const std::string & aInFile,
    const ScanConfiguration & aScanConfig,
    const std::string & aOutputPattern )
```

Automatically extract [Roi](#), run scan and dump to JSON file.

Parameters

<i>aInFile</i>	The name of the localization file
<i>aScanConfig</i>	The configuration for the scan
<i>aOutputPattern</i>	A formattable-string specifying the name of the output JSON files. Substitutable fields are {input} (giving the stem of the input file name) and {roi} (giving the Roi id).

Definition at line 153 of file API.cpp.

References [_ScanCallback_Json_\(\)](#), and [AutoRoi_Scan_SimpleCallback\(\)](#).

Referenced by [BOOST_PYTHON_MODULE\(\)](#), and [main\(\)](#).

5.17.1.11 ImageJRoi_Cluster_FullCallback()

```
void ImageJRoi_Cluster_FullCallback (
    const std::string & aInFile,
    const std::string & aImageJfile,
    const double & aScale,
    const double & aR,
    const double & aT,
    const tFullClusterCallback & aCallback )
```

Extract [Roi](#) using an image-map, clusterize and apply a full call-back.

Parameters

<i>aInFile</i>	The name of the localization file
<i>aImageJfile</i>	The name of an ImageJ Roi file file
<i>aScale</i>	The size of the LSB in the ImageJ file
<i>aR</i>	The R value of the clusterizer
<i>aT</i>	The T value of the clusterizer
<i>aCallback</i>	The callback to be applied

Definition at line 241 of file API.cpp.

References [Roi::Clusterize\(\)](#), and [LocalizationFile::ExtractRols\(\)](#).

Referenced by [ImageJRoi_Cluster_SimpleCallback\(\)](#).

5.17.1.12 ImageJRoi_Cluster_SimpleCallback()

```
void ImageJRoi_Cluster_SimpleCallback (
    const std::string & aInFile,
    const std::string & aImageJfile,
    const double & aScale,
    const double & aR,
    const double & aT,
    const tSimpleClusterCallback & aCallback )
```

Extract [Roi](#) using an image-map, clusterize and apply a full call-back.

Parameters

<i>aInFile</i>	The name of the localization file
<i>aImageJfile</i>	The name of an ImageJ Roi file file
<i>aScale</i>	The size of the LSB in the ImageJ file
<i>aR</i>	The R value of the clusterizer
<i>aT</i>	The T value of the clusterizer
<i>aCallback</i>	The callback to be applied

Definition at line 247 of file API.cpp.

References [_FullClusterToSimpleCluster_\(\)](#), and [ImageJRoi_Cluster_FullCallback\(\)](#).

Referenced by [ImageJRoi_Cluster_ToJson\(\)](#).

5.17.1.13 ImageJRoi_Cluster_ToJson()

```
void ImageJRoi_Cluster_ToJson (
    const std::string & aInFile,
    const std::string & aImageJfile,
    const double & aScale,
    const double & aR,
    const double & aT,
    const std::string & aOutputPattern )
```

Extract [Roi](#) using an image-map, clusterize and apply a full call-back.

Parameters

<i>aInFile</i>	The name of the localization file
<i>aImageJfile</i>	The name of an ImageJ Roi file file
<i>aScale</i>	The size of the LSB in the ImageJ file
<i>aR</i>	The R value of the clusterizer
<i>aT</i>	The T value of the clusterizer
<i>aOutputPattern</i>	A formattable-string specifying the name of the output JSON files. Substitutable fields are {input} (giving the stem of the input file name) and {roi} (giving the Roi id).

Definition at line 253 of file API.cpp.

References `_ClusterCallback_Json_()`, and `ImageJRoi_Cluster_SimpleCallback()`.

Referenced by `BOOST_PYTHON_MODULE()`.

5.17.1.14 ImageJRoi_Scan_FullCallback()

```
void ImageJRoi_Scan_FullCallback (
    const std::string & aInFile,
    const std::string & aImageJfile,
    const double & aScale,
    const ScanConfiguration & aScanConfig,
    const tFullScanCallback & aCallback )
```

Extract [Roi](#) using an image-map, run scan and apply a full call-back.

Parameters

<i>aInFile</i>	The name of the localization file
<i>aImageJfile</i>	The name of an ImageJ Roi file file
<i>aScale</i>	The size of the LSB in the ImageJ file
<i>aScanConfig</i>	The configuration for the scan
<i>aCallback</i>	The full callback to be applied

Definition at line 221 of file `API.cpp`.

References `LocalizationFile::ExtractRois()`, and `Roi::ScanRT()`.

5.17.1.15 ImageJRoi_Scan_SimpleCallback()

```
void ImageJRoi_Scan_SimpleCallback (
    const std::string & aInFile,
    const std::string & aImageJfile,
    const double & aScale,
    const ScanConfiguration & aScanConfig,
    const tSimpleScanCallback & aCallback )
```

Extract [Roi](#) using an image-map, run scan and apply a simple call-back.

Parameters

<i>aInFile</i>	The name of the localization file
<i>aImageJfile</i>	The name of an ImageJ Roi file file
<i>aScale</i>	The size of the LSB in the ImageJ file
<i>aScanConfig</i>	The configuration for the scan
<i>aCallback</i>	The simple callback to be applied

Definition at line 227 of file API.cpp.

References `_FullScanToSimpleScan_()`, and `LocalizationFile::ExtractRols()`.

Referenced by `ImageJRoi_Scan_ToJson()`.

5.17.1.16 ImageJRoi_Scan_ToJson()

```
void ImageJRoi_Scan_ToJson (
    const std::string & aInFile,
    const std::string & aImageJfile,
    const double & aScale,
    const ScanConfiguration & aScanConfig,
    const std::string & aOutputPattern )
```

Extract [Roi](#) using an image-map, run scan and dump to JSON file.

Parameters

<i>aInFile</i>	The name of the localization file
<i>aImageJfile</i>	The name of an ImageJ Roi file file
<i>aScale</i>	The size of the LSB in the ImageJ file
<i>aScanConfig</i>	The configuration for the scan
<i>aOutputPattern</i>	A formattable-string specifying the name of the output JSON files. Substitutable fields are {input} (giving the stem of the input file name) and {roi} (giving the Roi id).

Definition at line 233 of file API.cpp.

References `_ScanCallback_Json_()`, and `ImageJRoi_Scan_SimpleCallback()`.

Referenced by `BOOST_PYTHON_MODULE()`.

5.17.1.17 ManualRoi_Cluster_FullCallback()

```
void ManualRoi_Cluster_FullCallback (
    const std::string & aInFile,
    const ManualRoi & aManualRoi,
    const double & aR,
    const double & aT,
    const tFullClusterCallback & aCallback )
```

Manually specify [Roi](#), clusterize and apply a full call-back.

Parameters

<i>aInFile</i>	The name of the localization file
<i>aManualRoi</i>	The manually-specified Roi window
<i>aR</i>	The R value of the clusterizer
<i>aT</i>	The T value of the clusterizer

Definition at line 201 of file API.cpp.

References `Rol::Clusterize()`, and `LocalizationFile::ExtractRols()`.

Referenced by `ManualRoi_Cluster_SimpleCallback()`.

5.17.1.18 ManualRoi_Cluster_SimpleCallback()

```
void ManualRoi_Cluster_SimpleCallback (
    const std::string & aInFile,
    const ManualRoi & aManualRoi,
    const double & aR,
    const double & aT,
    const tSimpleClusterCallback & aCallback )
```

Manually specify [Rol](#), clusterize and apply a full call-back.

Parameters

<i>aInFile</i>	The name of the localization file
<i>aManualRoi</i>	The manually-specified Rol window
<i>aR</i>	The R value of the clusterizer
<i>aT</i>	The T value of the clusterizer
<i>aCallback</i>	The callback to be applied

Definition at line 207 of file API.cpp.

References `_FullClusterToSimpleCluster_()`, and `ManualRoi_Cluster_FullCallback()`.

Referenced by `ManualRoi_Cluster_ToJson()`.

5.17.1.19 ManualRoi_Cluster_ToJson()

```
void ManualRoi_Cluster_ToJson (
    const std::string & aInFile,
    const ManualRoi & aManualRoi,
    const double & aR,
    const double & aT,
    const std::string & aOutputPattern )
```

Manually specify [Rol](#), clusterize and apply a full call-back.

Parameters

<i>aInFile</i>	The name of the localization file
<i>aManualRoi</i>	The manually-specified Rol window
<i>aR</i>	The R value of the clusterizer
<i>aT</i>	The T value of the clusterizer
<i>aOutputPattern</i>	A formattable-string specifying the name of the output JSON files. Substitutable fields are {input} (giving the stem of the input file name) and {roi} (giving the Rol id).

Definition at line 213 of file API.cpp.

References `_ClusterCallback_Json_()`, and `ManualRoi_Cluster_SimpleCallback()`.

Referenced by `BOOST_PYTHON_MODULE()`.

5.17.1.20 ManualRoi_Scan_FullCallback()

```
void ManualRoi_Scan_FullCallback (
    const std::string & aInFile,
    const ManualRoi & aManualRoi,
    const ScanConfiguration & aScanConfig,
    const tFullScanCallback & aCallback )
```

Manually specify [Roi](#), run scan and apply a full call-back.

Parameters

<i>aInFile</i>	The name of the localization file
<i>aManualRoi</i>	The manually-specified Roi window
<i>aScanConfig</i>	The configuration for the scan
<i>aCallback</i>	The full callback to be applied

Definition at line 181 of file API.cpp.

References `LocalizationFile::ExtractRols()`, and `Roi::ScanRT()`.

5.17.1.21 ManualRoi_Scan_SimpleCallback()

```
void ManualRoi_Scan_SimpleCallback (
    const std::string & aInFile,
    const ManualRoi & aManualRoi,
    const ScanConfiguration & aScanConfig,
    const tSimpleScanCallback & aCallback )
```

Manually specify [Roi](#), run scan and apply a simple call-back.

Parameters

<i>aInFile</i>	The name of the localization file
<i>aManualRoi</i>	The manually-specified Roi window
<i>aScanConfig</i>	The configuration for the scan
<i>aCallback</i>	The simple callback to be applied

Definition at line 187 of file API.cpp.

References `_FullScanToSimpleScan_()`, and `LocalizationFile::ExtractRols()`.

Referenced by ManualRoi_Scan_ToJson().

5.17.1.22 ManualRoi_Scan_ToJson()

```
void ManualRoi_Scan_ToJson (
    const std::string & aInFile,
    const ManualRoi & aManualRoi,
    const ScanConfiguration & aScanConfig,
    const std::string & aOutputPattern )
```

Manually specify [Roi](#), run scan and dump to JSON file.

Parameters

<i>aInFile</i>	The name of the localization file
<i>aManualRoi</i>	The manually-specified Roi window
<i>aScanConfig</i>	The configuration for the scan
<i>aOutputPattern</i>	A formattable-string specifying the name of the output JSON files. Substitutable fields are {input} (giving the stem of the input file name) and {roi} (giving the Roi id).

Definition at line 193 of file API.cpp.


References [_ScanCallback_Json\(\)](#), and [ManualRoi_Scan_SimpleCallback\(\)](#).

Referenced by [BOOST_PYTHON_MODULE\(\)](#).

5.18 src/BayesianClustering/Cluster.cpp File Reference

```
#include "Utilities/GSLInterpolator.hpp"
#include <boost/math/special_functions/erf.hpp>
#include "BayesianClustering/Cluster.hpp"
#include "BayesianClustering/Data.hpp"
#include "BayesianClustering/Configuration.hpp"
```

Include dependency graph for Cluster.cpp:



Functions

- double [normal_cdf](#) (const double &x, const double &sigma=1, const double &x0=0)

Evaluate the Gaussian normal_cdf at a given position Copied from the CERN ROOT implementaion, swap ROOT↔
::Math::erfc and ROOT::Math::erf for the boost::math version.

5.18.1 Function Documentation

5.18.1.1 normal_cdf()

```
double normal_cdf (
    const double & x,
    const double & sigma = 1,
    const double & x0 = 0 ) [inline]
```

Evaluate the Gaussian normal_cdf at a given position Copied from the CERN ROOT implementaion, swap ROOT↔
::Math::erfc and ROOT::Math::erf for the boost::math version.

Parameters

x	The position to evaluate the normal_cdf at
σ	The standard-deviation of the Gaussian
x_0	The mean of the Gaussian

Returns

the value of the Gaussian normal_cdf at x

Definition at line 22 of file Cluster.cpp.

Referenced by Cluster::Parameter::alt_log_score(), and Cluster::Parameter::log_score().

5.19 src/BayesianClustering/Configuration.cpp File Reference

```
#include "Utilities/GSLInterpolator.hpp"
#include "Utilities/ListComprehension.hpp"
#include "Utilities/Vectorize.hpp"
#include "Utilities/Units.hpp"
#include "BayesianClustering/Configuration.hpp"
#include <iostream>
#include <fstream>
#include <streambuf>
#include <boost/math/special_functions/gamma.hpp>
#include "boost/algorithm/string.hpp"
#include "boost/program_options.hpp"
```


Include dependency graph for Configuration.cpp:



5.20 src/BayesianClustering/Data.cpp File Reference

```
#include <stdlib.h>
#include <algorithm>
#include "BayesianClustering/Data.hpp"
#include "BayesianClustering/Cluster.hpp"
#include "BayesianClustering/RoI.hpp"
#include "Utilities/ProgressBar.hpp"
```


Include dependency graph for Data.cpp:



5.21 src/BayesianClustering/DataProxy.cpp File Reference

```
#include "BayesianClustering/DataProxy.hpp"
#include "BayesianClustering/Data.hpp"
#include "BayesianClustering/Cluster.hpp"
#include "BayesianClustering/RoIproxy.hpp"
#include "BayesianClustering/RoI.hpp"
#include <iostream>
```

Include dependency graph for DataProxy.cpp:




Macros

- `#define RECURSION_LIMIT 75000`
The maximum depth for recursive clustering.

5.22 src/BayesianClustering/ImageJ_Rol.cpp File Reference

```
#include <iostream>
#include <stdlib.h>
#include <cstring>
#include <zip.h>
#include <stdexcept>
#include "BayesianClustering/ImageJ_RoI.hpp"
```

Include dependency graph for ImageJ_Rol.cpp:



Functions

- `roi_polygon DecodeBinaryRol` (const uint8_t *const aData)
Decode ImageJ binary Rol data to boost::geometry polygon Reverse engineered from <https://github.com/imagej/ImageJ/blob/master/ij/io/RoiDecoder.java>.
- `std::map< std::string, roi_polygon > OpenRoiZipfile` (const std::string &aZipFileName)
Decode ImageJ zipped binary Rol data to a map of named boost::geometry polygons.

5.22.1 Function Documentation

5.22.1.1 DecodeBinaryRol()

```
roi_polygon DecodeBinaryRoI (
    const uint8_t *const aData )
```

Decode ImageJ binary Rol data to boost::geometry polygon Reverse engineered from <https://github.com/imagej/ImageJ/blob/master/ij/io/RoiDecoder.java>.

Parameters

<i>aData</i>	A C-array containing the binary Roi data
--------------	--

Returns

A boost::geometry polygon containing the [Roi](#) information

Definition at line 14 of file ImageJ_Roi.cpp.

Referenced by OpenRoiZipfile().

5.22.1.2 OpenRoiZipfile()

```
std::map< std::string , roi\_polygon > OpenRoiZipfile (
    const std::string & aZipFileName )
```

Decode ImageJ zipped binary [Roi](#) data to a map of named boost::geometry polygons.

Parameters

<i>aZipFileName</i>	The name of the zip-file to be opened
---------------------	---------------------------------------

Returns

A map of named boost::geometry polygons containing the [Roi](#) information

Definition at line 28 of file ImageJ_Roi.cpp.


References DecodeBinaryRoi().

Referenced by LocalizationFile::ExtractRols(), and GetRols().

5.23 src/BayesianClustering/LocalizationFile.cpp File Reference

```
#include <iostream>
#include "BayesianClustering/LocalizationFile.hpp"
#include "BayesianClustering/Data.hpp"
#include "BayesianClustering/RoI.hpp"
#include "BayesianClustering/ImageJ_RoI.hpp"
#include "Utilities/ProgressBar.hpp"
#include "Utilities/Vectorize.hpp"
#include "Utilities/Units.hpp"
#include <boost/filesystem.hpp>
```

Include dependency graph for LocalizationFile.cpp:



- `typedef std::array< std::array< int, 512 >, 512 > tArray`
Typedef an array for histogramming a Localization File.

- void **__LoadCSV__** (const std::string &aFilename, std::vector< **Data** > &aData, const std::size_t &aOffset, int aCount)
Multithreading handler for loading a chunk of data from CSV file.
- void **__RecursiveSearch__** (**tArray** &aHist, const int &aRolid, const int &i, const int &j)
Recursively search histogram for continuously connected regions over threshold.

5.23.1.1 __LoadCSV__()


Multithreading handler for loading a chunk of data from CSV file.

<i>aFilename</i>	The name of the file to open
<i>aData</i>	A vector into which to fill data
<i>aOffset</i>	The offset into the file
<i>aCount</i>	The (approximate) number of bytes to be handled by this handler

References nanometer.


```
#include "BayesianClustering/RoI.hpp"
#include "Utilities/ProgressBar.hpp"
#include <iostream>
```


Include dependency graph for RoIproxy.cpp:



5.26 src/Cluster.cxx File Reference

```
#include "BayesianClustering/API.hpp"
#include "BayesianClustering/Configuration.hpp"
#include <map>
#include <vector>
#include <iostream>
```

Include dependency graph for Cluster.cxx:



Functions

- void [ReportClusters](#) (const std::vector< [ClusterWrapper](#) > &aClusters)
Callback to report clusters.
- int [main](#) (int argc, char **argv)
The main function.

5.26.1 Function Documentation

5.26.1.1 main()

```
int main (
    int argc,
    char ** argv )
```

The main function.

Parameters

<i>argc</i>	The number of commandline arguments
<i>argv</i>	The commandline arguments

Returns

The exit code

Definition at line 28 of file Cluster.cxx.

References `AutoRoi_Cluster_ToJson()`, `AuxConfiguration::ClusterR()`, `AuxConfiguration::ClusterT()`, `AuxConfiguration::inputFile()`, and `AuxConfiguration::outputFile()`.

5.26.1.2 ReportClusters()

```
void ReportClusters (
    const std::vector< ClusterWrapper > & aClusters )
```

Callback to report clusters.

Parameters

<i>aClusters</i>	A vector of clusters
------------------	----------------------

Definition at line 14 of file Cluster.cxx.


5.27 src/PythonBindings/PythonBindings.cpp File Reference

Self-contained sourcefile for producing python-bindings.

```
#include <iostream>
#include <boost/python.hpp>
```

```
#include <boost/python/suite/indexing/vector_indexing_suite.hpp>
#include <boost/preprocessor/stringize.hpp>
#include <boost/preprocessor/seq/for_each.hpp>
#include "Utilities/Units.hpp"
#include "BayesianClustering/API.hpp"
#include "BayesianClustering/LocalizationFile.hpp"
#include "BayesianClustering/Configuration.hpp"
#include "BayesianClustering/RoI.hpp"
#include "BayesianClustering/RoIproxy.hpp"
#include "BayesianClustering/Data.hpp"
#include "BayesianClustering/ImageJ_RoI.hpp"
```

Include dependency graph for PythonBindings.cpp:



Macros

- `#define ADAPT_CALLBACK_CONSTRUCTOR(SIGNATURE) template<> template<> SIGNATURE< >::function< const object& >(const object& aCallback) : function([&](auto&&... aArgs){ aCallback(aArgs...); }) {}`
Helper macro to define a constructor for a std::function of a given signature from a boost::python callback object Using explicit specialization of the class to the specified type and explicit specialization of the constructor to take a object (hence two template<>'s at the start), create a generic variadic lambda that captures the boost::python callback object and pass the lambda to a deferred constructor.
- `#define FN(X, DOC, ...) def(#X , &X , args(__VA_ARGS__) , DOC)`
Helper Macro to simplify defining functions.
- `#define ADAPTED_FN(X, DOC, ...) def(#X , +Adapted::X , args(__VA_ARGS__) , DOC)`
Helper Macro to simplify defining functions with python callbacks.
- `#define STRUCT_ARG(r, CLASS, ARG) .def_readwrite(BOOST_PP_STRINGIZE(ARG) , &CLASS::ARG)`
Helper Macro to deal with the boilerplate when dealing with structs.
- `#define EXPOSE_STRUCT(CLASS, DOC, ARGS) class_< CLASS >(#CLASS , DOC) BOOST_PP_SEQ_FOR_EACH(STRUCT_ARG , CLASS , ARGS)`
Helper Macro to deal with the boilerplate when dealing with structs.
- `#define EXPOSE_VECTOR(CLASS) class_< std::vector< CLASS > >(BOOST_PP_STRINGIZE(Vector##CLASS) , BOOST_PP_STRINGIZE(An STL vector of CLASS)).def(vector_indexing_suite< std::vector< CLASS > >());`
Helper Macro to deal with the boilerplate when dealing with vectors of objects.

Functions

- `ADAPT_CALLBACK_CONSTRUCTOR(tFullScanCallback)`
Define a std::function constructor for full scan callback.
- `ADAPT_CALLBACK_CONSTRUCTOR(tSimpleScanCallback)`
Define a std::function constructor for simple scan callback.
- `ADAPT_CALLBACK_CONSTRUCTOR(tFullClusterCallback)`
Define a std::function constructor for full clusterizer callback.

- [ADAPT_CALLBACK_CONSTRUCTOR](#) ([tSimpleClusterCallback](#))
Define a `std::function` constructor for simple clusterizer callback.
- `std::shared_ptr< ScanConfiguration > ScanConfigurationConstructor` (`const std::size_t &aSigmaBins, const double &aSigmaMin, const double &aSigmaMax, const object &aInterpolator, const std::size_t &aRbins, const double &aMinScanR, const double &aMaxScanR, const std::size_t &aTbins, const double &aMinScanT, const double &aMaxScanT, const double &aPB, const double &aAlpha`)
Factory function to construct a [ScanConfiguration](#) which take the parameters directly in python.
- `boost::python::tuple GetLocalizations` (`const std::string &aFile`)
Debugging tool to get the raw x-y coordinates.
- `boost::python::list GetRols` (`const std::string &aFile`)
Debugging tool to get the raw coordinates from an ImageJ [Rol](#) file
- `boost::python::tuple CheckRols` (`const std::string &aFile, const std::string &aRolFile, const double &aScale`)
Debugging tool to get the raw x-y coordinates and which [Rol](#) they are included in.
- [BOOST_PYTHON_MODULE](#) ([BayesianClustering](#))
Boost Python Wrapper providing bindings for our C++ functions.

Variables

- `auto Adapted::AutoRoi_Scan_SimpleCallback = []` (`const std::string& aInFile , const ScanConfiguration& aScanConfig , const object& aCallback`) { `::AutoRoi_Scan_SimpleCallback(aInFile , aScanConfig , aCallback`); }
- Lambda to automatically extract [Rol](#), run scan and apply a simple python callback.*
- `auto Adapted::AutoRoi_Cluster_SimpleCallback = []` (`const std::string& aInFile , const double& aR , const double& aT , const object& aCallback`) { `::AutoRoi_Cluster_SimpleCallback(aInFile , aR , aT , aCallback`); }
- Lambda to automatically extract [Rol](#), clusterize and apply a simple python callback.*
- `auto Adapted::ManualRoi_Scan_SimpleCallback = []` (`const std::string& aInFile , const ManualRol& aManualRol , const ScanConfiguration& aScanConfig , const object& aCallback`) { `::ManualRoi_Scan_SimpleCallback(aInFile , aManualRol , aScanConfig , aCallback`); }
- Lambda to manually specify [Rol](#), run scan and apply a simple python callback.*
- `auto Adapted::ManualRoi_Cluster_SimpleCallback = []` (`const std::string& aInFile , const ManualRol& aManualRol , const double& aR , const double& aT , const object& aCallback`) { `::ManualRoi_Cluster_SimpleCallback(aInFile , aManualRol , aR , aT , aCallback`); }
- Lambda to manually specify [Rol](#), clusterize and apply a simple python callback.*
- `auto Adapted::ImageJRoi_Scan_SimpleCallback = []` (`const std::string& aInFile , const std::string& aImageJ , const double& aScale , const ScanConfiguration& aScanConfig , const object& aCallback`) { `::ImageJRoi_Scan_SimpleCallback(aInFile , aImageJ , aScale , aScanConfig , aCallback`); }
- Lambda to extract [Rol](#) via an ImageJ [Rol](#) file, run scan and apply a simple python callback.*
- `auto Adapted::ImageJRoi_Cluster_SimpleCallback = []` (`const std::string& aInFile , const std::string& aImageJ , const double& aScale , const double& aR , const double& aT , const object& aCallback`) { `::ImageJRoi_Cluster_SimpleCallback(aInFile , aImageJ , aScale , aR , aT , aCallback`); }
- Lambda to extract [Rol](#) via an ImageJ [Rol](#) file, clusterize and apply a simple python callback.*

5.27.1 Detailed Description

Self-contained sourcefile for producing python-bindings.

5.27.2 Macro Definition Documentation

5.27.2.1 ADAPT_CALLBACK_CONSTRUCTOR

```
#define ADAPT_CALLBACK_CONSTRUCTOR(  
    SIGNATURE ) template<> template<> SIGNATURE::function< const object& >( const  
object& aCallback ) : function( [&]( auto&&... aArgs ){ aCallback( aArgs... ); } ) {}
```

Helper macro to define a constructor for a `std::function` of a given signature from a `boost::python` callback object. Using explicit specialization of the class to the specified type and explicit specialization of the constructor to take a object (hence two `template<>`'s at the start), create a generic variadic lambda that captures the `boost::python` callback object and pass the lambda to a deferred constructor.

Gnarly!

Parameters

<i>SIGNATURE</i>	The signature of the <code>std::function</code> we are creating a constructor for
------------------	---

Definition at line 40 of file `PythonBindings.cpp`.

5.27.2.2 ADAPTED_FN

```
#define ADAPTED_FN(  
    X,  
    DOC,  
    ... ) def( #X , +Adapted::X , args( __VA_ARGS__ ) , DOC )
```

Helper Macro to simplify defining functions with python callbacks.

Parameters

<i>X</i>	The function being defined
<i>DOC</i>	A string to be used as python documentation
...	List of strings giving argument names

Definition at line 189 of file `PythonBindings.cpp`.

5.27.2.3 EXPOSE_STRUCT

```
#define EXPOSE_STRUCT(  
    CLASS,  
    DOC,  
    ARGS ) class_< CLASS >( #CLASS , DOC ) BOOST_PP_SEQ_FOR_EACH( STRUCT_ARG , CLASS  
, ARGS )
```

Helper Macro to deal with the boilerplate when dealing with structs.

Parameters

<i>CLASS</i>	The Class name
<i>DOC</i>	A string to be used as python documentation
<i>ARGS</i>	One of the arguments

Definition at line 201 of file PythonBindings.cpp.

5.27.2.4 EXPOSE_VECTOR

```
#define EXPOSE_VECTOR(
    CLASS ) class_< std::vector< CLASS > >( BOOST_PP_STRINGIZE( Vector##CLASS ) ,
BOOST_PP_STRINGIZE( An STL vector of CLASS ) ).def( vector_indexing_suite< std::vector< CLASS
> >() );
```

Helper Macro to deal with the boilerplate when dealing with vectors of objects.

Parameters

<i>CLASS</i>	The Class name
--------------	----------------

Definition at line 205 of file PythonBindings.cpp.

5.27.2.5 FN

```
#define FN(
    X,
    DOC,
    ... ) def( #X , &X , args( __VA_ARGS__ ) , DOC )
```

Helper Macro to simplify defining functions.

Parameters

<i>X</i>	The function being defined
<i>DOC</i>	A string to be used as python documentation
...	List of strings giving argument names

Definition at line 183 of file PythonBindings.cpp.

5.27.2.6 STRUCT_ARG

```
#define STRUCT_ARG(
    r,
```

```

    CLASS,
    ARG ) .def_readwrite( BOOST_PP_STRINGIZE( ARG ) , &CLASS::ARG )

```

Helper Macro to deal with the boilerplate when dealing with structs.

Parameters

<i>r</i>	BOOST PP internal
<i>CLASS</i>	The Class name
<i>ARG</i>	One of the arguments

Definition at line 195 of file PythonBindings.cpp.

5.27.3 Function Documentation

5.27.3.1 CheckRols()

```

boost::python::tuple CheckRoIs (
    const std::string & aFile,
    const std::string & aRoIFile,
    const double & aScale )

```

Debugging tool to get the raw x-y coordinates and which [Rol](#) they are included in.

Parameters

<i>aFile</i>	The name of the localizations file
<i>aRoIFile</i>	The name of an ImageJ Rol file file
<i>aScale</i>	The size of the LSB in the ImageJ file

Returns

A python tuple of the raw localizations and a list of tuples containing the x-coordinates and the y-coordinates of the localizations in each [Rol](#) (both optimised for displaying in Matplotlib)

Definition at line 150 of file PythonBindings.cpp.

References [LocalizationFile::data\(\)](#), [Rol::data\(\)](#), and [LocalizationFile::ExtractRols\(\)](#).

Referenced by [BOOST_PYTHON_MODULE\(\)](#).

5.27.3.2 GetLocalizations()

```

boost::python::tuple GetLocalizations (
    const std::string & aFile )

```

Debugging tool to get the raw x-y coordinates.

Parameters

<i>aFile</i>	The name of the localizations file
--------------	------------------------------------

Returns

The x-coordinates and the y-coordinates of the raw points as a python tuple (optimised for displaying in MatPlotLib)

Definition at line 112 of file PythonBindings.cpp.

References LocalizationFile::data().

Referenced by BOOST_PYTHON_MODULE().

5.27.3.3 GetRols()

```
boost::python::list GetRoIs (
    const std::string & aFile )
```

Debugging tool to get the raw coordinates from an ImageJ [Rol](#) file

Parameters

<i>aFile</i>	The name of an ImageJ Rol file
--------------	--

Returns

A list of python tuples, each containing the x-coordinates and the y-coordinates of the polygon points (optimised for displaying in MatPlotLib)

Definition at line 127 of file PythonBindings.cpp.

References OpenRoiZipfile().

Referenced by BOOST_PYTHON_MODULE().

5.27.3.4 ScanConfigurationConstructor()

```
std::shared_ptr< ScanConfiguration > ScanConfigurationConstructor (
    const std::size_t & aSigmaBins,
    const double & aSigmaMin,
    const double & aSigmaMax,
    const object & aInterpolator,
    const std::size_t & aRbins,
```

```

const double & aMinScanR,
const double & aMaxScanR,
const std::size_t & aTbins,
const double & aMinScanT,
const double & aMaxScanT,
const double & aPB,
const double & aAlpha )

```

Factory function to construct a [ScanConfiguration](#) which take the parameters directly in python.

Parameters

<i>aSigmaBins</i>	The number of sigma bins
<i>aSigmaMin</i>	The lowest sigma bin
<i>aSigmaMax</i>	The highest sigma bin
<i>aInterpolator</i>	A python function call or python dictionary containing a set of points from which to create an interpolator
<i>aRbins</i>	The number of R bins to scan over
<i>aMinScanR</i>	The lowest value of R to scan
<i>aMaxScanR</i>	The largest value of R to scan
<i>aTbins</i>	The number of T bins to scan over
<i>aMinScanT</i>	The lowest value of T to scan
<i>aMaxScanT</i>	The largest value of T to scan
<i>aPB</i>	The P_b parameter
<i>aAlpha</i>	The alpha parameter

Returns

a shared pointer to the new [ScanConfiguration](#)

Definition at line 64 of file PythonBindings.cpp.

Referenced by BOOST_PYTHON_MODULE().


5.28 src/Scan.cxx File Reference

```

#include "BayesianClustering/API.hpp"
#include "BayesianClustering/Configuration.hpp"
#include <iostream>

```

Include dependency graph for Scan.cxx:



Functions

- `int main (int argc, char **argv)`
The main function.

5.28.1 Function Documentation

5.28.1.1 main()

```
int main (
    int argc,
    char ** argv )
```

The main function.

Parameters

<code>argc</code>	The number of commandline arguments
<code>argv</code>	The commandline arguments

Returns

The exit code


Definition at line 15 of file Scan.cxx.

References `AutoRoi_Scan_ToJson()`, `AuxConfiguration::configFile()`, `AuxConfiguration::inputFile()`, and `AuxConfiguration::outputFile()`.

5.29 src/Utilities/GSLInterpolator.cpp File Reference

```
#include "Utilities/GSLInterpolator.hpp"
```

Include dependency graph for GSLInterpolator.cpp:




5.30 src/Utilities/ProgressBar.cpp File Reference

```
#include <iostream>
```

```
#include <iomanip>
```

```
#include "Utilities/ProgressBar.hpp"
```

Include dependency graph for ProgressBar.cpp:




5.31 src/Utilities/Units.cpp File Reference

```
#include "Utilities/Units.hpp"
```

```
#include <sstream>
```

Include dependency graph for Units.cpp:



Functions

- long double [StrToDist](#) (const std::string &aStr)
Convert a string representation to a distance.

Variables

- const std::map< std::string, double > [UnitMap](#) { {"nm",nanometer}, {"um",micrometer}, {"mm",millimeter}, {"m",meter} }
A map for converting string representations of SI units to scaling factors.

5.31.1 Function Documentation

5.31.1.1 StrToDist()

```
long double StrToDist (
    const std::string & aStr )
```

Convert a string representation to a distance.

Parameters

<i>aStr</i>	A string representation of a distance
-------------	---------------------------------------

Returns

The literal value

Definition at line 12 of file Units.cpp.

References UnitMap.


Referenced by ScanConfiguration::FromVector(), and AuxConfiguration::FromVector().

5.32 src/Utilities/Vectorize.cpp File Reference

```
#include "Utilities/Vectorize.hpp"
```

```
#include <thread>
```

Include dependency graph for Vectorize.cpp:

**Variables**

- `std::size_t Nthreads = std::thread::hardware_concurrency()`
The number of threads used, initialized to the number of hardware threads.

5.32.1 Variable Documentation

5.32.1.1 Nthreads

```
std::size_t Nthreads = std::thread::hardware_concurrency()
```

The number of threads used, initialized to the number of hardware threads.

Utility variable for the concurrency.

Definition at line 8 of file Vectorize.cpp.

Referenced by AuxConfiguration::FromVector(), LocalizationFile::LocalizationFile(), operator&&(), operator||(), and Rol::ScanRT().

Index

- [_ClusterCallback_Json_](#)
 - [API.cpp, 113](#)
 - [_FullClusterToSimpleCluster_](#)
 - [API.cpp, 114](#)
 - [_FullScanToSimpleScan_](#)
 - [API.cpp, 114](#)
 - [_ScanCallback_Json_](#)
 - [API.cpp, 115](#)
 - [__LoadCSV__](#)
 - [LocalizationFile.cpp, 129](#)
 - [__RecursiveSearch__](#)
 - [LocalizationFile.cpp, 130](#)
- [ADAPT_CALLBACK_CONSTRUCTOR](#)
 - [PythonBindings.cpp, 134](#)
- [ADAPTED_FN](#)
 - [PythonBindings.cpp, 135](#)
- [alpha](#)
 - [ScanConfiguration, 67](#)
- [alt_log_score](#)
 - [Cluster::Parameter, 44](#)
- [API.cpp](#)
 - [_ClusterCallback_Json_, 113](#)
 - [_FullClusterToSimpleCluster_, 114](#)
 - [_FullScanToSimpleScan_, 114](#)
 - [_ScanCallback_Json_, 115](#)
 - [AutoRoi_Cluster_FullCallback, 115](#)
 - [AutoRoi_Cluster_SimpleCallback, 116](#)
 - [AutoRoi_Cluster_ToJson, 116](#)
 - [AutoRoi_Scan_FullCallback, 117](#)
 - [AutoRoi_Scan_SimpleCallback, 117](#)
 - [AutoRoi_Scan_ToJson, 117](#)
 - [ImageJRoi_Cluster_FullCallback, 118](#)
 - [ImageJRoi_Cluster_SimpleCallback, 118](#)
 - [ImageJRoi_Cluster_ToJson, 119](#)
 - [ImageJRoi_Scan_FullCallback, 120](#)
 - [ImageJRoi_Scan_SimpleCallback, 120](#)
 - [ImageJRoi_Scan_ToJson, 121](#)
 - [ManualRoi_Cluster_FullCallback, 121](#)
 - [ManualRoi_Cluster_SimpleCallback, 122](#)
 - [ManualRoi_Cluster_ToJson, 122](#)
 - [ManualRoi_Scan_FullCallback, 123](#)
 - [ManualRoi_Scan_SimpleCallback, 123](#)
 - [ManualRoi_Scan_ToJson, 124](#)
- [API.hpp](#)
 - [AutoRoi_Cluster_FullCallback, 81](#)
 - [AutoRoi_Cluster_SimpleCallback, 81](#)
 - [AutoRoi_Cluster_ToJson, 82](#)
 - [AutoRoi_Scan_FullCallback, 82](#)
 - [AutoRoi_Scan_SimpleCallback, 83](#)
- [AutoRoi_Scan_ToJson, 83](#)
- [ImageJRoi_Cluster_FullCallback, 84](#)
- [ImageJRoi_Cluster_SimpleCallback, 84](#)
- [ImageJRoi_Cluster_ToJson, 86](#)
- [ImageJRoi_Scan_FullCallback, 86](#)
- [ImageJRoi_Scan_SimpleCallback, 87](#)
- [ImageJRoi_Scan_ToJson, 87](#)
- [ManualRoi_Cluster_FullCallback, 88](#)
- [ManualRoi_Cluster_SimpleCallback, 88](#)
- [ManualRoi_Cluster_ToJson, 89](#)
- [ManualRoi_Scan_FullCallback, 89](#)
- [ManualRoi_Scan_SimpleCallback, 90](#)
- [ManualRoi_Scan_ToJson, 90](#)
- [AutoRoi_Cluster_FullCallback](#)
 - [API.cpp, 115](#)
 - [API.hpp, 81](#)
- [AutoRoi_Cluster_SimpleCallback](#)
 - [API.cpp, 116](#)
 - [API.hpp, 81](#)
- [AutoRoi_Cluster_ToJson](#)
 - [API.cpp, 116](#)
 - [API.hpp, 82](#)
- [AutoRoi_Scan_FullCallback](#)
 - [API.cpp, 117](#)
 - [API.hpp, 82](#)
- [AutoRoi_Scan_SimpleCallback](#)
 - [API.cpp, 117](#)
 - [API.hpp, 83](#)
- [AutoRoi_Scan_ToJson](#)
 - [API.cpp, 117](#)
 - [API.hpp, 83](#)
- [AuxConfiguration, 7](#)
 - [AuxConfiguration, 8, 9](#)
 - [ClusterR, 9](#)
 - [ClusterT, 9](#)
 - [configFile, 9](#)
 - [FromVector, 10](#)
 - [inputFile, 10](#)
 - [outputFile, 10](#)
 - [SetConfigFile, 11](#)
 - [SetInputFile, 11](#)
 - [SetOutputFile, 12](#)
 - [SetValidate, 12](#)
 - [validate, 12](#)
- [CalculateLocalizationScore](#)
 - [Data, 22](#)
- [CheckClusterization](#)
 - [Rolproxy, 58](#)
- [CheckRois](#)

- PythonBindings.cpp, 137
- Cluster, 13
 - Cluster, 14, 15
 - GetParent, 15
 - operator+=, 16
 - operator=, 16
 - UpdateLogScore, 17
- Cluster.cpp
 - normal_cdf, 125
- Cluster.cxx
 - main, 132
 - ReportClusters, 132
- Cluster::Parameter, 44
 - alt_log_score, 44
 - log_score, 45
 - operator+=, 45
- Clusterize
 - DataProxy, 28
 - Rol, 51
 - Rolproxy, 59
- ClusterR
 - AuxConfiguration, 9
- ClusterT
 - AuxConfiguration, 9
- ClusterWrapper, 17
 - operator<, 18
 - operator==, 18
- configFile
 - AuxConfiguration, 9
- Data, 19
 - CalculateLocalizationScore, 22
 - Data, 21
 - dPhi, 22
 - dR, 23
 - dR2, 23
 - operator<, 23
 - operator=, 24
 - Preprocess, 25
 - PreprocessLocalizationScores, 25
- data
 - LocalizationFile, 40
 - Rol, 52
- DataProxy, 26
 - Clusterize, 28
 - DataProxy, 27
 - GetCluster, 29
 - operator=, 29
- DecodeBinaryRol
 - ImageJ_Rol.cpp, 127
 - ImageJ_Rol.hpp, 95
- Deriv
 - GSLInterpolator, 34
- Deriv2
 - GSLInterpolator, 34
- dPhi
 - Data, 22
- dR
 - Data, 23
- dR2
 - Data, 23
- Eval
 - GSLInterpolator, 34
- Evaluate
 - GSLInterpolator, 35
- EXPOSE_STRUCT
 - PythonBindings.cpp, 135
- EXPOSE_VECTOR
 - PythonBindings.cpp, 136
- ExtractRols
 - LocalizationFile, 41, 42
- FN
 - PythonBindings.cpp, 136
- FromVector
 - AuxConfiguration, 10
 - ScanConfiguration, 67
- getArea
 - Rol, 52
- getCentreX
 - Rol, 52
- getCentreY
 - Rol, 52
- GetCluster
 - DataProxy, 29
- GetData
 - Rolproxy, 59
- GetLocalizations
 - PythonBindings.cpp, 137
- GetParent
 - Cluster, 15
- GetRols
 - PythonBindings.cpp, 138
- GSLInterpolator, 30
 - Deriv, 34
 - Deriv2, 34
 - Eval, 34
 - Evaluate, 35
 - GSLInterpolator, 31, 32
 - Integ, 35
 - operator=, 37
 - SetData, 38
- id
 - Rol, 53
- ImageJ_Rol.cpp
 - DecodeBinaryRol, 127
 - OpenRoiZipfile, 128
- ImageJ_Rol.hpp
 - DecodeBinaryRol, 95
 - OpenRoiZipfile, 96
- ImageJRoi_Cluster_FullCallback
 - API.cpp, 118
 - API.hpp, 84
- ImageJRoi_Cluster_SimpleCallback
 - API.cpp, 118

- API.hpp, 84
- ImageJRoi_Cluster_ToJson
 - API.cpp, 119
 - API.hpp, 86
- ImageJRoi_Scan_FullCallback
 - API.cpp, 120
 - API.hpp, 86
- ImageJRoi_Scan_SimpleCallback
 - API.cpp, 120
 - API.hpp, 87
- ImageJRoi_Scan_ToJson
 - API.cpp, 121
 - API.hpp, 87
- include/BayesianClustering/API.hpp, 79
- include/BayesianClustering/Cluster.hpp, 91
- include/BayesianClustering/Configuration.hpp, 92
- include/BayesianClustering/Data.hpp, 93
- include/BayesianClustering/DataProxy.hpp, 94
- include/BayesianClustering/ImageJ_Rol.hpp, 95
- include/BayesianClustering/LocalizationFile.hpp, 96
- include/BayesianClustering/Precision.hpp, 98
- include/BayesianClustering/Rol.hpp, 98
- include/BayesianClustering/Rolproxy.hpp, 99
- include/Utilities/GSLInterpolator.hpp, 100
- include/Utilities/ListComprehension.hpp, 100
- include/Utilities/MemoryMonitoring.hpp, 104
- include/Utilities/ProgressBar.hpp, 105
- include/Utilities/Units.hpp, 106
- include/Utilities/Vectorize.hpp, 109
- inputFile
 - AuxConfiguration, 10
- Integ
 - GSLInterpolator, 35
- ListComprehension.hpp
 - operator | , 101–103
 - range, 103
- LocalizationFile, 39
 - data, 40
 - ExtractRols, 41, 42
 - LocalizationFile, 39, 40
 - operator=, 42, 43
- LocalizationFile.cpp
 - __LoadCSV__, 129
 - __RecursiveSearch__, 130
- log_probability_sigma
 - ScanConfiguration, 68
- log_score
 - Cluster::Parameter, 45
- logAlpha
 - ScanConfiguration, 68
- logGammaAlpha
 - ScanConfiguration, 69
- logPb
 - ScanConfiguration, 69
- logPbDagger
 - ScanConfiguration, 69
- main
 - Cluster.cxx, 132
 - Scan.cxx, 140
- ManualRol, 43
- ManualRoi_Cluster_FullCallback
 - API.cpp, 121
 - API.hpp, 88
- ManualRoi_Cluster_SimpleCallback
 - API.cpp, 122
 - API.hpp, 88
- ManualRoi_Cluster_ToJson
 - API.cpp, 122
 - API.hpp, 89
- ManualRoi_Scan_FullCallback
 - API.cpp, 123
 - API.hpp, 89
- ManualRoi_Scan_SimpleCallback
 - API.cpp, 123
 - API.hpp, 90
- ManualRoi_Scan_ToJson
 - API.cpp, 124
 - API.hpp, 90
- mem_usage
 - MemoryMonitoring.hpp, 104
- MemoryMonitoring.hpp
 - mem_usage, 104
- normal_cdf
 - Cluster.cpp, 125
- Nthreads
 - Vectorize.cpp, 143
 - Vectorize.hpp, 111
- OpenRoiZipfile
 - ImageJ_Rol.cpp, 128
 - ImageJ_Rol.hpp, 96
- operator<
 - ClusterWrapper, 18
 - Data, 23
 - ScanEntry, 77
- operator++
 - ProgressBar, 47
- operator+=
 - Cluster, 16
 - Cluster::Parameter, 45
- operator=
 - Cluster, 16
 - Data, 24
 - DataProxy, 29
 - GSLInterpolator, 37
 - LocalizationFile, 42, 43
 - Rol, 53, 54
 - Rolproxy, 59, 60
 - ScanConfiguration, 70
- operator==
 - ClusterWrapper, 18
 - ScanEntry, 77
- operator&&
 - Vectorize.hpp, 110
- operator""_micrometer

- Units.hpp, 107
- operator""_nanometer
 - Units.hpp, 108
- operator |
 - ListComprehension.hpp, 101–103
- operator | |
 - Vectorize.hpp, 110
- outputFile
 - AuxConfiguration, 10
- Preprocess
 - Data, 25
 - Rol, 54
- PreprocessLocalizationScores
 - Data, 25
- probability_sigma
 - ScanConfiguration, 71
- ProgressBar, 46
 - operator++, 47
 - ProgressBar, 47
- ProgressTimer, 48
 - ProgressTimer, 48
- PythonBindings.cpp
 - ADAPT_CALLBACK_CONSTRUCTOR, 134
 - ADAPTED_FN, 135
 - CheckRols, 137
 - EXPOSE_STRUCT, 135
 - EXPOSE_VECTOR, 136
 - FN, 136
 - GetLocalizations, 137
 - GetRols, 138
 - ScanConfigurationConstructor, 138
 - STRUCT_ARG, 136
- range
 - ListComprehension.hpp, 103
- Rbounds
 - ScanConfiguration, 71
- ReportClusters
 - Cluster.cxx, 132
- Rol, 49
 - Clusterize, 51
 - data, 52
 - getArea, 52
 - getCentreX, 52
 - getCentreY, 52
 - id, 53
 - operator=, 53, 54
 - Preprocess, 54
 - Rol, 50, 51
 - ScanRT, 54
 - SetArea, 55
 - SetCentre, 55
- Rolproxy, 56
 - CheckClusterization, 58
 - Clusterize, 59
 - GetData, 59
 - operator=, 59, 60
 - Rolproxy, 57, 58
- ScanRT, 60
- UpdateLogScore, 61
- ValidateLogScore, 61
- Scan.cxx
 - main, 140
- ScanConfiguration, 62
 - alpha, 67
 - FromVector, 67
 - log_probability_sigma, 68
 - logAlpha, 68
 - logGammaAlpha, 69
 - logPb, 69
 - logPbDagger, 69
 - operator=, 70
 - probability_sigma, 71
 - Rbounds, 71
 - ScanConfiguration, 64–66
 - SetAlpha, 71
 - SetPb, 72
 - SetRBins, 72
 - SetSigmaParameters, 73
 - SetTBins, 73
 - sigmabins, 74
 - sigmabins2, 74, 75
 - sigmacount, 75
 - sigmaspacing, 75
 - Tbounds, 76
- ScanConfiguration::tBounds, 78
- ScanConfigurationConstructor
 - PythonBindings.cpp, 138
- ScanEntry, 76
 - operator<, 77
 - operator==, 77
- ScanRT
 - Rol, 54
 - Rolproxy, 60
- SetAlpha
 - ScanConfiguration, 71
- SetArea
 - Rol, 55
- SetCentre
 - Rol, 55
- SetConfigFile
 - AuxConfiguration, 11
- SetData
 - GSLInterpolator, 38
- SetInputFile
 - AuxConfiguration, 11
- SetOutputFile
 - AuxConfiguration, 12
- SetPb
 - ScanConfiguration, 72
- SetRBins
 - ScanConfiguration, 72
- SetSigmaParameters
 - ScanConfiguration, 73
- SetTBins
 - ScanConfiguration, 73

- SetValidate
 - AuxConfiguration, [12](#)
- sigmabins
 - ScanConfiguration, [74](#)
- sigmabins2
 - ScanConfiguration, [74](#), [75](#)
- sigmacount
 - ScanConfiguration, [75](#)
- sigmaspacing
 - ScanConfiguration, [75](#)
- src/BayesianClustering/API.cpp, [112](#)
- src/BayesianClustering/Cluster.cpp, [124](#)
- src/BayesianClustering/Configuration.cpp, [125](#)
- src/BayesianClustering/Data.cpp, [126](#)
- src/BayesianClustering/DataProxy.cpp, [126](#)
- src/BayesianClustering/ImageJ_Rol.cpp, [127](#)
- src/BayesianClustering/LocalizationFile.cpp, [128](#)
- src/BayesianClustering/Rol.cpp, [130](#)
- src/BayesianClustering/Rolproxy.cpp, [130](#)
- src/Cluster.cxx, [131](#)
- src/PythonBindings/PythonBindings.cpp, [132](#)
- src/Scan.cxx, [139](#)
- src/Utilities/GSLInterpolator.cpp, [141](#)
- src/Utilities/ProgressBar.cpp, [141](#)
- src/Utilities/Units.cpp, [141](#)
- src/Utilities/Vectorize.cpp, [143](#)
- StrToDist
 - Units.cpp, [142](#)
 - Units.hpp, [108](#)
- STRUCT_ARG
 - PythonBindings.cpp, [136](#)
- Tbounds
 - ScanConfiguration, [76](#)
- Units.cpp
 - StrToDist, [142](#)
- Units.hpp
 - operator""_micrometer, [107](#)
 - operator""_nanometer, [108](#)
 - StrToDist, [108](#)
- UpdateLogScore
 - Cluster, [17](#)
 - Rolproxy, [61](#)
- validate
 - AuxConfiguration, [12](#)
- ValidateLogScore
 - Rolproxy, [61](#)
- Vectorize.cpp
 - Nthreads, [143](#)
- Vectorize.hpp
 - Nthreads, [111](#)
 - operator&&, [110](#)
 - operator | |, [110](#)