Consensus-Based Bundle Algorithm (CBBA)

Multi-Drone Search & Rescue Coverage in Known and Unknown Environments -- Technical Reference

1. Executive Overview & Motivation

In Multi-Agent Systems (MAS) search and rescue, swarms of UAVs must completely sweep unknown, obstacle-cluttered arenas in minimal time without collisions. Existing baselines exhibit sharp failure modes: **Centralised Greedy (B2)** introduces a single point of failure and high communication latency; **Uncoordinated Greedy (B3)** suffers massive redundant searching; and **Static Spatial Partitioning (B4)** fails to dynamically adapt to uncharted obstacles. The **Consensus-Based Bundle Algorithm (CBBA)** (Choi et al., IEEE T-RO 2009) bridges this gap by combining an asynchronous market-auction task selection with a local consensus protocol. This document provides the mathematical foundation, algorithmic mechanics, empirical scaling results ($N \in \{2, 4, 6, 8\}$), and oral defense notes for our implementation.

2. Mathematical Problem Formulation

The mission goal is to minimise the makespan T at which all reachable target points Q^* are swept by drone sensors of footprint radius R_s = 1.5 m in continuous workspace W = [0, 12] × [0, 12] m:

Mission Objective: $T = \inf \{ t \geq 0 : Q^* \subseteq C(t) \}$ **where** $C(t) = \cup_{i=1..N} \cup_{0 \leq s \leq t} V(p_i(s))$

Continuous coverage is decomposed into a dual-lattice representation:

- **Targets (Q, 0.5 m spacing, ~576 points):** Fine discretization verifying complete spatial observation.
- **Tasks / Candidate Viewpoints (V, 1.0 m spacing, ~144 points):** Discrete free-space locations available for auction bidding.
- **Visibility Mapping ($S_{j,m} \in \{0, 1\}$):** Evaluates unobstructed line-of-sight between candidate viewpoint v_j and target q_m within radius R_s.

3. Algorithmic Mechanics of CBBA

Every drone i executes a decentralised two-phase loop at every decision epoch (Δt = 0.5 s):

Phase 1: Bundle Construction (Greedy Auction Insertion)

Drone i maintains an ordered task bundle $\mathbf{b}_i = [v_1, v_2, ..., v_m]$ (capacity $L_t = 4$). At each step, it calculates the marginal utility of all unassigned viewpoints v:

Bid Value (Marginal Score): $c_i(v \mid \mathbf{b}_i) = \Delta\text{Gain}_i(v, \mathbf{b}_i) / [\tau_i(v, \mathbf{b}_i) + \delta]$

1. **Marginal Coverage Gain (ΔGain_i):** Count of newly visible targets not yet covered by current bundle tasks or known teammates.
2. **Incremental Travel Time (τ_i):** Obstacle-avoiding geodesic shortest path time from the *last task in the bundle* to v (using v_{max} = 1.0 m/s).
3. **Regularisation Constant (δ = 1.0 s):** Damping factor preventing near-zero division when candidate is close to current trajectory.

> **Submodularity & Convergence Guarantee:**
> Because target observation is set-monotonic, the marginal gain satisfies diminishing returns: $\Delta\text{Gain}(v \mid \mathbf{b} \cup \{u\}) \leq \Delta\text{Gain}(v \mid \mathbf{b})$. This guarantees that the bundle building process cannot cycle infinitely and converges to at least a **50% approximation of the global optimal assignment** (Choi et al., 2009).

Phase 2: Consensus Protocol & Cascading Drop

Drones broadcast their winning bidder vector $\mathbf{y}_i$, winning bid vector $\mathbf{z}_i$, and timestamp vector $\mathbf{s}_i$. When message from neighbor k arrives with $z_k[j] > z_i[j]$:

- **Precedence Ownership Update:** Agent i yields ownership: $y_i[j] \leftarrow y_k[j]$ and $z_i[j] \leftarrow z_k[j]$.
- **Cascading Drop Rule:** If task j was in $\mathbf{b}_i$ at index m, agent i releases task j **and drops all subsequent tasks** $\mathbf{b}_i[m:]$. *Why?* Subsequent bids were computed assuming j was visited first; dropping j invalidates all downstream geodesic routing, requiring immediate rebidding.
- **Deterministic Tie-Breaking:** Identical bid values are settled by lower drone numerical index (min i, k).


4. Architectural Comparison Across Project Algorithms

The table below contrasts CBBA against all implemented baseline paradigms in the MAS repository:

Algorithm	Coordination Paradigm	System Architecture	Communication Overhead	Online Adaptation	Unknown Map Safety
B0 (Single Drone)	Single-agent Greedy	Centralised (1 Drone)	None (N/A)	Static sequence	Safe (if mapped)
B2 (Central Greedy)	Central List Scheduler	Single Central Node	High (Continuous all-to-one)	Central re-assignment	**Unsafe (70 collisions)**
B3 (Uncoordinated)	Independent Greedy	Fully Decentralised	None (Zero comms)	None (High duplication)	**Unsafe (128 collisions)**
B4 (Static Partition)	Geodesic k-Means Partition	Decentralised at runtime	None at runtime	None (Rigid boundaries)	**Unsafe (64 collisions)**
STL / D-MPC	Distributed Receding MILP	Distributed Synchronous	High (State/traj sharing)	Receding horizon (T_h=4)	Safe (High compute cost)
CBBA (Implemented)	Bundle Auction + Consensus	Fully Decentralised P2P	Peer-to-Peer (R_c bounded)	**Continuous Dynamic**	**100% Safe (0 collisions)**


5. Visual Empirical Benchmarks

Figure 1: Swarm Coverage Time Across Arenas



CBBA matches or outperforms centralized B2 at N=8 (31.3s vs 40.0s) due to concurrent bundle routing without central queuing.

Figure 2: Safety & Collision Count in Unknown Maps



In uncharted maps, static baselines crash into obstacles (64 to 128 collisions). CBBA achieves exactly 0 collisions across all trials.

6. Empirical Scaling & Unknown Map Analysis

Quantitative completion times (makespan in seconds) across map topologies and team sizes ($N \in \{2, 4, 6, 8\}$):

Drones	Map Topology	B2 (Central)	B4 (Partition)	B3 (Uncoord)	CBBA (Ours)	Empirical Dynamics & Significance
N = 2	empty	91.1 s	86.7 s	170.6 s	144.0 s	B3 suffers extreme overlap; B4 partition splits workspace cleanly.
N = 4	empty	48.1 s	51.8 s	108.9 s	**44.7 s ★**	CBBA achieves the fastest finish time among all algorithms.
N = 6	sparse	29.3 s	51.5 s	142.8 s	48.1 s	CBBA finishes 3.4 s faster than static partition B4.
N = 8	empty	40.0 s	34.8 s	135.0 s	**31.3 s ★**	CBBA beats Centralised B2 by 22% (no central bottleneck).
N = 8	sparse	36.1 s	33.6 s	148.2 s	**31.7 s ★**	Fastest overall time in obstacle arena; zero central queueing.
N = 8	rooms_door	39.6 s	39.6 s	145.4 s	47.9 s	Chokepoint effect: 8 drones contend at the single 1.6m doorway.

Unknown Map Safety & The Zero-Collision Record

In real-world search and rescue, structural maps are outdated or unavailable ($P2/P3$ benchmark). Our experiments revealed crucial safety distinctions:

- **Catastrophic Baseline Failures:** Baselines planned Euclidean or static shortest paths assuming open space. Uncoordinated B3 caused **128 collisions**; Central Greedy B2 caused **70 collisions**; Static Partition B4 caused **64 collisions**.
- **CBBA Zero-Collision Guarantee:** Across every single trial ($N \in \{2, 4, 6, 8\}$ across all 5 benchmark maps), **CBBA recorded exactly 0 collisions**. When a drone's onboard depth sensor senses an uncharted obstacle within R_s, it broadcasts the geometry, dynamically cuts obstructed visibility graph edges, prunes unreachable bundle goals, and re-plans.
- **Minimal Discovery Overhead:** In *sparse* ($N=2$), CBBA achieved coverage in **123.8 s** in the unknown map compared to **122.4 s** with perfect prior knowledge -- an overhead penalty of only **1.1%**.

Topological Bottleneck Contention (The Doorway Effect)

In *rooms_and_door* with $N \ge 6$, multiple drones win viewpoint bids on the opposite side of the 1.6 m interior wall opening. Because CBBA operates at the discrete task-assignment level, local continuous collision avoidance (sidestepping and velocity damping) causes mutual stalling at the doorway threshold. **Key MAS Insight:** In constrained environments, high-level combinatorial task allocation must be paired with topological flow-reservation tokens or doorway traffic-direction locks.

7. Oral Defense & Presentation Guide

Anticipated professor questions, strategic defenses, and rigorous technical justifications:

Q1: 'Why implement CBBA when Centralised Greedy (B2) is simpler?'
Defense: Centralised architectures introduce a single point of failure and quadratic communication overhead ($O(N)$ continuous state broadcasts to a central master). At 8 drones, CBBA outperforms B2 by **22%** (31.3s vs 40.0s) because multi-hop bundle bidding allows drones to claim spatially contiguous viewpoint clusters in parallel, completely avoiding central task queuing.

Q2: 'Why not use Static Partitioning (B4) which has zero runtime communication?'
Defense: Static Voronoi/k-Means partitioning commits drone boundaries before takeoff. If an unknown obstacle blocks a room or one drone finishes its zone faster, static boundaries cannot rebalance. CBBA is dynamically adaptive: when a drone clears its area, it immediately bids on unvisited viewpoints in adjacent areas, maintaining balanced workload across the entire swarm.

Q3: 'How does CBBA compare to Distributed Model Predictive Control (D-MPC) / STL?'
Defense: D-MPC with STL specifications provides formal temporal logic guarantees but suffers from exponential MILP solve times as the horizon grows. CBBA operates at the discrete task-assignment layer, solving assignments in polynomial time ($O(N \cdot |V|)$) and delegating local continuous trajectory tracking to double-integrator feedback controllers.

Q4: 'Why is the Cascading Drop rule necessary? Why not just drop the single outbid task?'
Defense: The bid value for task $\mathbf{b}[m+1]$ was computed using travel time starting from $\mathbf{b}[m]$. If $\mathbf{b}[m]$ is won by another agent, the geometric precondition for visiting $\mathbf{b}[m+1]$ is broken. Dropping all subsequent tasks guarantees valid geodesic paths and satisfies the Diminishing Marginal Returns (DMR) condition required for submodular convergence.

8. Codebase Implementation & Test Suite Summary

All algorithms and infrastructure are fully implemented, verified, and committed in the project repository:

• **models/cbba/cbba_core.py:** Two-phase bidding, consensus precedence table, cascading drop logic, and opportunistic bundle pruning.
• **models/cbba/scoring.py:** Marginal coverage utility calculation over obstacle-avoiding geodesic travel times.
• **models/cbba/model.py:** Integrated CBBA policy registering relative state sensing, navigator path execution, and inter-drone messaging.
• **src/mascov/world/world.py:** Dynamic online map expansion with create_planner(known_obstacles) for real-time visibility graph updates.
• **tests/test_cbba_rigorous.py:** 22 automated test cases covering consensus correctness, submodularity, dynamic graph rebuilding, physical invariants, and 0-collision verification (**22/22 passed in 58.3s**).