

# Sets-STL

Sets are a part of the C++ STL. Sets are containers that store unique elements following a specific order. The mainly used member functions of sets are:

- *Declaration:*

```
set<int>st; //Creates a set of integers.
```

- *Size:*

```
int length=s.size(); //Gives the size of the set.
```

- *Insert:*

```
s.insert(x); //Inserts an integer x into the set s.
```

- *Erasing an element:*

```
s.erase(val); //Erases an integer val from the set s.
```

- *Finding an element:*

```
set<int>::iterator itr=s.find(val); //Gives the iterator to the element val if it is found otherwise returns s.end() .  
Ex: set<int>::iterator itr=s.find(100); //If 100 is not present then it==s.end().
```

To know more about sets [click Here](#). Coming to the problem, you will be given  $Q$  queries. Each query is of one of the three types:

- 1  $x$ : Add an element  $x$  to the set.
- 2  $x$ : Delete an element  $x$  from the set. (If the number  $x$  is not present in the set then do nothing).
- 3  $x$ : If the number  $x$  is present in the set then print "Yes"(without quotes) else print "No"(without quotes).

## Input Format

The first line of the input contains  $Q$  where  $Q$  is the number of queries. The next  $Q$  lines contain 1 query each. Each query consists of two integers  $y$  and  $x$  where  $y$  is the type of the query and  $x$  is an integer.

## Constraints

- $1 \leq Q \leq 10^5$
- $1 \leq y \leq 3$
- $1 \leq x \leq 10^9$

## Output Format

For queries of type 3 print "Yes"(without quotes) if the number  $x$  is present in the set and if not present then print "No"(without quotes).  
Each query of type 3 should be printed in a new line.

### Sample Input

```
8
1 9
1 6
1 10
1 4
3 6
3 14
2 6
3 6
```

### Sample Output

```
Yes
No
No
```