

Mac Development Handoff Plan

Cross-platform workflow for Mac development and
Windows takeover

Repository: Celestial-Pramit/SkyLink-FlightOps
Handoff commit: f72c9c5 | Tag: mac-handoff-2026-08
Prepared: August 2026



Current Repository State

The Windows preparation is complete. Start at **Phase 2**. Do not repeat the old setup phases or create another Maven-wrapper commit.

BRANCH master	LATEST COMMIT f72c9c5
HANDOFF TAG mac-handoff-2026-08	APPLICATION MySQL, port 8088
TESTS H2 test profile included	WRAPPER mvnw executable for macOS

Security: The old password may still exist in Git history. Rotate the real MySQL password and use the new value through `DB_PASSWORD`. Never put it in a committed file.

Phase 1 | Windows Handoff

This phase is complete. For reference:

```
git status --short --branch
```

Phase 2 | Install Requirements on Mac

2.1 Apple command-line tools

```
xcode-select --install
```

If macOS says they are already installed, continue.

2.2 Homebrew

Install Homebrew from <https://brew.sh>, then run:

```
brew update
```

Phase 3 | Clone the Project on Mac

Do not copy the project manually from Windows.

```
mkdir -p ~/Projects
```

Phase 4 | Configure MySQL on Mac

4.1 Create database and user

```
mysql -u root -p
```

```
CREATE DATABASE skylink_db;
```

```
CREATE USER 'flightadmin'@'localhost'  
IDENTIFIED BY 'your-new-secure-password';
```

```
GRANT ALL PRIVILEGES ON skylink_db.* TO 'flightadmin'@'localhost';  
FLUSH PRIVILEGES;  
EXIT;
```

4.2 Configure credentials

```
export DB_USERNAME=flightadmin
```

Phase 5 | IntelliJ and First Build

Open the cloned project in IntelliJ and reload Maven. From the project root run:

```
./mvnw clean test
```

Tests use H2 and do not require MySQL. Expected result: **BUILD SUCCESS**.

```
./mvnw spring-boot:run
```

Open `http://localhost:8088`. Stop the server with `Ctrl+C`.

- ☐ Login and signup load.
- ☐ Dashboard, flights, aircraft, customers, bookings, reports, and Super Admin pages load.
- ☐ CSS and JavaScript load without 404 errors.
- ☐ Login, logout, role restrictions, and image upload work.
- ☐ Booking creation and cancellation work.

Phase 6 | Start OpenCode

```
cd ~/Projects/SkyLink-FlightOps
opencode
```

Use this audit prompt first:

You are working inside the SkyLink FlightOps repository.

Repository facts:

- Spring Boot 4, Java 17, Maven wrapper
- Thymeleaf, Spring Security, Spring Data JPA
- MySQL for development and H2 for tests
- Existing SkyLink Ops UI design

Before editing:

1. Inspect pom.xml, README.md, AGENT.md, .gitignore, application.yml, and src/test/resources/application-test.yml.
2. Check git status.
3. Confirm there are no hardcoded database credentials.
4. Check for OS-specific absolute paths and missing static resources.
5. Do not edit or commit anything yet.
6. Report portability or security problems with file names and line numbers.

Use the Maven wrapper for verification commands.

Phase 7 | Feature Development on Mac

```
git switch -c feature/your-feature-name
```

Use this OpenCode prompt:

Implement this feature in the existing SkyLink FlightOps project:

FEATURE:

[Describe the feature clearly]

Rules:

1. Inspect the existing implementation before editing.
2. Follow AGENT.md and preserve the SkyLink Ops UI design.
3. Keep controllers responsible only for HTTP handling.
4. Keep business logic in services.
5. Reuse existing DTO, interface, repository, fragment, CSS, and JavaScript patterns.
6. Do not introduce Windows-specific or macOS-specific paths.
7. Do not modify credentials or unrelated files.
8. Add or update tests where appropriate.
9. Run ./mvnw clean test after implementation.
10. Show git status and git diff before suggesting a commit.
11. Do not commit or push until I approve.

Phase 8 | Review and Push Mac Changes

8.1 Review

```
git status
```

Check Java compilation, Spring Boot startup, MySQL and H2 compatibility, Thymeleaf expressions, Spring Security authorization, missing static resources, form actions, null risks, validation, macOS/Windows paths, secrets, unintended files, responsive UI regressions, and missing tests.

Run `./mvnw clean test` and report findings by severity with file names and line numbers.

8.2 Commit

```
git add src/main/java src/main/resources src/test
```


Phase 9 | Take Over on Windows

Before leaving the Mac:

```
git status
```

Phase 10 | Final Cross-Platform Verification

Mac	Windows PowerShell
<code>./mvnw clean test</code>	<code>.\mvnw.cmd clean test</code>
<code>./mvnw spring-boot:run</code>	<code>.\mvnw.cmd spring-boot:run</code>

- ☐ Both computers use Java 17.
- ☐ Both computers use the same Git commit.
- ☐ MySQL database is named `skylink_db`.
- ☐ Application starts on port `8088`.
- ☐ H2 tests pass without MySQL.
- ☐ Login, roles, pages, CSS, JavaScript, and uploads work.
- ☐ No absolute OS-specific paths exist.
- ☐ No secrets are committed.
- ☐ Both worktrees are clean before switching computers.

Rules to Follow Every Time

1. Commit and push before switching computers.
2. Pull before starting work on the other computer.
3. Use Java 17 on both systems.
4. Use the Maven wrapper.
5. Keep database credentials outside Git.
6. Do not expect GitHub to transfer MySQL data or uploaded images.
7. Use feature branches instead of developing directly on `master`.
8. Run tests before every push.
9. Use OpenCode to inspect, edit, test, review, then commit.

This document describes the project handoff as of commit `f72c9c5`. If the repository advances, verify the current commit before using these instructions.

