# BigBird
# Breaking the Quadratic Barrier

Deep Dive into the BigBird Transformer Model

Mohammad Nassar

# The Problem: BERT's Quadratic Bottleneck

*Dense self-attention creates an N x N matrix, causing exponential memory growth.*


Standard Transformers use dense self-attention.

Every token attends to every other token.

Creates an N x N matrix → $O(N^2)$ complexity.

Example: Doubling sequence length quadruples memory usage.

Limitation: BERT is capped at 512 tokens.



# The Solution: Dense to Sparse Transition

*BigBird strategically reduces connections to achieve linear O(N) complexity.*


BigBird replaces dense attention with a sparse mechanism.

Local (Diagonal): Attends to nearby tokens (window).

Random (Scattered): Attends to a few random tokens.

Global (Columns): Key tokens attend to everything.

Result: Computation drops from $O(N^2)$ to linear O(N).



# The Architecture: The BigBird Matrix

*Combining three distinct attention patterns to capture both short and long-range context.*


Local: Captures short-range syntax (like a sentence).

Random: Connects distant but related tokens.

Global: Lets key tokens (like [CLS]) influence everything.

The Secret: Each token only attends to 6-7 other tokens.

This keeps computation strictly linear regardless of length.



# How It Works: Sparse Attention Flow

*A visual journey through BigBird's layers: Global, Local, and Random connections.*


Input Tokens: Text is split and passed through the model.

Local Windows: Each token attends to nearby tokens.

Global Tokens: Special tokens attend to all tokens.

Random Connections: A few tokens connect to distant ones.

The Big Picture: Less computation, more context.



# Complexity Showdown: BERT vs. Longformer vs. BigBird


*BigBird is the only model that maintains linear complexity with theoretical guarantees.*

BERT: O(N²) - Full dense attention. Best for < 512 tokens.

Longformer: O(N) - Sliding window + Global attention.

BigBird: O(N) - Local + Global + Random attention.

Winner: BigBird is the only model with theoretical guarantees (Turing complete) while maintaining linear complexity.



# BigBird vs. Chunking


*Why BigBird is smarter than simply cutting long text into pieces.*

Chunking: Split document into 512-token chunks. Loses context between chunks.

BigBird: Process entire text as one long sequence.

Advantage: Maintains full context, handles long sequences efficiently.

Verdict: One sequence. Smarter attention. Better global understanding.



# Where to Use BigBird: Applications

*Built for long, complex, and structured data across multiple domains.*


DNA Sequences: Analyzing long genetic sequences.

Long News Articles: Summarizing thousands of tokens.

Supply Chain Graphs: Modeling complex relationships.

Scientific Text Mining: Extracting formulas and co-references.

Long-Form QA: Answering questions from entire books.



# The Reality Check: Limitations & Performance


*Practical constraints when deploying BigBird in real-world scenarios.*

Hardware Constraints: On V100 (16GB), max_len=768, batch_size=4 hits the limit.

Fixed PE Limit: max_position_embeddings=4096.

Short-Input Inefficiency: Slower than BERT for < 1024 tokens.

Multi-GPU Complexity: Requires careful tuning of batch size and learning rate.



# Inside the Heatmap: Visualizing the Attention


*How to read the diagonal lines, green columns, and random dots.*

Diagonal Lines: Local Attention (window).

Green Columns: Global Attention (key tokens reaching all).

Random Dots: Random Attention (long-range connections).

Why It Matters: Captures both short- and long-range context.



# Conclusion & Key Takeaways

- ☐ BigBird combines Global, Local, and Random attention to achieve linear complexity, bridging the gap between expressive Transformers and computational reality.
- ☐ Use BigBird for sequences exceeding 1024 tokens. For sequences of 1024 tokens or fewer (especially 512–1024), standard BERT remains the more efficient choice.

**Key Takeaway: Use BigBird to process long documents efficiently without losing global context.**

# References

Zaheer, M., et al. (2020). Big Bird: Transformers for Longer Sequences. NeurIPS.

Hugging Face Transformers Documentation. BigBirdModel.

InnerWorkingsAI Channel YouTube ( BigBird Research Course).