A MAP WORKSPACE FOR BUILDERS

CentrED# Local

Celobra Edition 0.7.4

Guide and comparison
Blank maps, ready map tabs and safer everyday editing.

Start with an existing UO map or create a fresh blank map. Prepare your available facets in separate tabs, build in managed working copies and inspect the result through player preview or your existing game client.

New in 0.7.4	What it lets you do
Create blank MUL or UOP maps	Choose a facet, size, terrain and elevation using matching UO artwork. Existing map files are optional.
Prepare several maps	See pending, loading, ready and failed tabs. Keep editing a ready map while the others prepare.
Keep each tab's work	Switch back to its view, navigation and Undo/Redo during this editor session.
Recover before continuing	A failed rollback blocks saving and editing, including after restarting, until a verified checkpoint is restored.

One local editor executable

The editing engine runs inside the Windows x64 app. Ordinary local editing needs no server login, listening port or separate server process. Supply your own usable UO data.

Use this guide: create a blank map (p.2), open map tabs (p.3), edit and organise the view (p.4), save/recover (p.5), inspect as a player (p.6), compare releases (pp.7-8), and check credits/limits (p.9).

NEW MAP WIZARD

Create a new blank map

Open **Maps and working copies > Create blank map**. Choose a separate new working copy; the wizard does not overwrite your original UO map set.

01 **Choose matching artwork**
Browse to your UO client-data folder and choose **Load terrain choices**. An artwork-only folder can be used; no existing map is required.

02 **Name the map and select its facet**
Choose map0/Felucca, map1/Trammel, map2/Ilshenar, map3/Malas, map4/Tokuno or map5/Ter Mur. The facet determines the new terrain/statics/index filenames.

03 **Choose the size**
Use **Standard facet size**, **Classic map0 / map1** (6144 x 4096), **Small practice map** (512 x 512), or **Custom dimensions**. Dimensions are in tiles and must be multiples of 8.

04 **Set terrain, elevation and format**
Search **Fill terrain** by name or ID; advanced users can enter a decimal terrain ID. Choose a flat elevation from -128 to 127 and **Terrain file: MUL or UOP**. Terrain does not have a hue.

05 **Create and watch preparation**
Review the estimated file size, then choose **Create blank map and open tab**. Progress continues when the panel is hidden; Cancel preparation stops pending work safely.

What is created

The new terrain map is filled with the selected tile and elevation. Its matching statics are empty and its index uses valid empty markers. MUL/UOP describes the terrain container; statics and index remain MUL files.

Custom limits: 8 to 32760 tiles per side, multiples of 8; terrain ID 0 to 16383 and available in the loaded tiledata. The writer also enforces supported file-size limits. Large blank maps take time and disk space. A custom size may require matching settings in your test game client/server.

PREPARED MAP WORKSPACE

Open maps and move between tabs

01 **Choose your UO folder**
Open **Maps and working copies > Open UO maps**, browse to the folder and choose **Look for maps**. Keep **Prepare all maps automatically** enabled to queue the compatible facets.

02 **Keep track of preparation**
Tabs appear while work is queued. File copies, validation and minimap preparation run in the background, one map at a time. You can use a ready map while another prepares.

Tab state	Meaning / next action
Pending / Copying / Preparing	Waiting, creating the working copy, or validating it and building its minimap. Cancel from the preparation list if needed.
Ready	The map backend is prepared. Select the tab to activate its editor view.
Needs dimensions	A custom map needs its width and height. Use the individual/custom-map controls.
Failed / Cancelled	Read the displayed reason, fix the input and Retry. Other ready maps remain available. A completed working copy can remain in Saved maps.

What stays with a tab

Switching saves the outgoing map. During the same open-tab session, each map keeps its own Undo/Redo and view/navigation state. Prepared backends stay available, avoiding another full minimap build for each switch.

Restart and close limits. Saved tabs and saved views can be reopened, but backends prepare again. Undo/Redo is held in memory: closing the tab or restarting the app starts fresh history. Undo never applies changes from another map. Use checkpoints for longer-term recovery.

Equivalent MUL/UOP versions of the same facet use one prepared choice; existing preferences are considered, then MUL is preferred. Extended map0x/map1x variants retain their own tabs. Discovery requires matching statics and index files. Up to 32 tabs are supported; each ready backend uses memory and holds its managed map files open.

EVERYDAY EDITING

Build, inspect and organise your workspace

The action bar keeps **Save map, Undo, Redo, Checkpoint, Go to, Inspector, Layers, Player view, Workspace and Help** close to the map. These controls pause when an operation or recovery state makes editing unavailable.

Task	Useful controls
Navigate	Enter X/Y, use the minimap, return with Back/Forward and keep bookmarks for each map.
Choose artwork	Search by name, decimal ID or 0x hexadecimal ID. Graphic IDs match exactly. Collect artwork and colors into palettes.
Inspect a tile stack	Use Inspector for terrain and stacked objects, positions, heights, IDs and hues. Sample a graphic or hue into the relevant painting control.
Paint or adjust	Use terrain/object drawing, Delete, Move, Elevate and Hue with the selected tool settings. Undo/Redo names identify the operation.
Work over an area	Pick two opposite corners on the editor or minimap. Picking fills bounds only; review the preview before applying a large operation.
Reuse structures	Blueprints support previews, tags, anchors, transforms and placement filters. Interchange can use explicit ID/hue mapping.
Focus the view	Layers, height ranges and graphic/hue filters reduce clutter. XY boundaries hide terrain/objects outside the region and prevent their selection.
Keep the panel arrangement	Workspace layouts save docking and panel visibility. Display presets retain map display settings; neither replaces map checkpoints.

Check before a large edit

Save and keep a checkpoint before an experiment. Use the operation preview, progress and Cancel controls. Local bulk operations use checkpoint recovery; completed remote changes have different recovery limits.

Missing legacy artwork still retains its ID and position for inspection. Deleting or replacing an object whose old ID/hue cannot be reinserted uses checkpoint Undo locally; normal valid edits retain lightweight packet Undo. A stroke containing such legacy objects can appear as several history items.

WORKING-COPY RECOVERY

Save, keep checkpoints and recover safely

Action	What it protects / produces
Save map	Commits accepted edits to the managed working copy. It does not overwrite the original imported files.
Keep a checkpoint	Keeps a verified complete terrain + statics + index snapshot. Use a checkpoint before experimenting or clearing history.
Restore selected checkpoint	Verifies the checkpoint before restoration. In an ordinary restore, a before-restore copy is kept first. The project returns to the selected snapshot.
Export a map copy	Creates a separate map triplet with checksums and artwork-identity information for matching test data. This is the whole map.
Export map image	Creates a PNG/JPEG picture using the chosen view settings. It is a picture, not an installable UO map.

If an operation cannot recover automatically

01 **Stop and read the recovery message**
A failed rollback leaves the project in a recovery state. Save, editing, further operations and closing are blocked; Activity explains the problem and checkpoint.

02 **Use the saved map or a checkpoint**
In **Current map / recovery**, choose **Restore last saved map** if the operation checkpoint is damaged. Or select another verified checkpoint and choose **Restore selected checkpoint**. Partial edits are not saved first.

03 **Check the result before continuing**
Successful verified recovery clears the restriction and resets current Undo/Redo. Inspect the map before continuing. If verification fails, use another valid checkpoint or repair a separate copy.

The save restriction survives restarting

A persistent private recovery record also blocks automatic saves, backups and shutdown flushes. Reopening can recover the last committed files for viewing, but editing stays restricted until explicit verified restoration.

Keep independent backups. Checkpoints consume substantial disk space, and full-map copy/hash work can pause the editor. Recovery protects committed data; a crash can lose unsaved work. If working files and their pre-edit journal are both unreadable, opening may fail before the recovery panel is available.

TWO INSPECTION WORKFLOWS

See the build from a player's perspective

1. Walk inside the editor

- Open **Player view**, start at the view centre and move the preview character with WASD or the arrow keys while the map is focused.
- The camera follows a male or female character using animation from the supplied UO artwork. Missing animation data is reported.
- Surface and clearance checks are approximate. Ignore collision supports free inspection; Hide objects above player offers an approximate roof view.
- Escape or **Return to editing** restores the previous view. Preview movement does not paint, move or otherwise edit map tiles.

Use the real game to check gameplay

Doors, live server objects, scripts, equipment, shard movement rules and multiplayer need the intended game client/server. The editor preview is an approximate inspection mode.

2. Test with your existing game client

01 **Choose the original client**
Open **Real client testing**. Select your existing client executable and any supported launch arguments. Private launch preferences can be saved locally.

02 **Prepare a separate test map**
Export the current map to a new folder. Back up receiving files, then prepare matching disposable test client/server data yourself, retaining the original graphic IDs.

03 **Launch and inspect in game**
Choose **Launch selected client**. It opens separately and uses its own configured data and server. Log in to your test server and walk through the build.

There is no embedded full game client, automatic installation or live synchronization. Editor edits do not appear instantly in a client that is already running. Map-file export includes the whole map; view boundaries affect image export. The launcher uses your selected existing client; it does not install exported map files or configure accounts and world saves.

RELEASE COMPARISON

What 0.7.4 adds to Celobra 0.7.3

Area	Celobra 0.7.3	Celobra 0.7.4
Blank maps	Import existing supported maps into working copies.	Guided blank MUL/UOP creation from matching artwork, with terrain/elevation, size estimate and safe new output.
Map preparation	Open a selected working-copy map through its tab.	Queue all compatible facets, show each preparation state and continue loading when the panel is hidden.
Switching	Reopen backend/minimap when changing map sessions.	Retain prepared backends and activate a ready map without rebuilding its minimap each switch.
Undo and view	A reopened map session starts fresh Undo.	Each open tab retains in-memory Undo/Redo plus its own view/navigation. Restart/closed-tab history still starts fresh.
Recovery guard	UI blocks actions after failed bulk rollback; backend periodic/final saves were independent.	Backend-enforced, persistent recovery state blocks partial-save paths until explicit verified restore.
Legacy objects	Bulk snapshot Undo handles invalid original metadata; ordinary Delete/Replace used packet inverses.	Ordinary invalid-source Delete/Replace uses accepted checkpoint Undo; replacements are checked before deletion.
GUI text	Some runtime strings used native formatting calls.	Paths, names, status and diagnostic text render literally, including percent signs; missing metadata is handled in Debug.
Carried forward	Local single EXE; guided copies; editing tools, blueprints, navigation, player preview, real-client launch, boundaries and layouts.	Retained, with the new workspace and creation flow around the existing editor.

The 0.7.3 Celobra Edition 1 reissue added publisher/maintainer branding and About/Credits to the Local 0.7.3 feature baseline. Version 0.7.4 is a new feature release. Earlier original and Celobra downloads remain available; already downloaded executables are not changed remotely.

ORIGINAL 0.6.11.31 BASELINE

How it differs from the original CentrED#

The original C# editor by **kaczy93** already provided map rendering, painting, Undo/Redo, a minimap, bookmarks, filters, blueprints, picture export, MUL/UOP loading, dockable windows, shortcut remapping and GUI LocalServer hosting.

Area	Original 0.6.11.31	Local 0.7.4
Local setup	Connection/hosting workflow, including GUI LocalServer and a separate server option.	Guided local projects use the editing engine inside the editor executable, without a local login or listening port.
Files / facets	MUL and UOP support already existed.	Discover matching companions, create separate working copies, prepare map tabs and generate new blank maps.
Safety	Saving and basic Undo/Redo were original features.	Verified working copies/checkpoints, recoverable bulk edits, persistent failed-recovery save locks and legacy-static checkpoint Undo.
Usability	Existing editing panels, navigation, filters and shortcuts.	Action bar, clearer search/inspector, named history, area picking, per-map boundaries and saved workspace arrangements.
Building / export	Blueprint, terrain, bulk-edit and image-export foundations.	Additional previews/transforms/interchange, bounded picture export, full map-set export and progress/cancellation around local workflows.
Player inspection	Editor map rendering.	Animated approximate player preview plus a configured launch path for an existing real game client.
Shared editing	Networked editing is an original strength.	Retained separately; TLS is the default and legacy unprotected compatibility must be enabled explicitly.

UOP remains a valid map format

Supported UOP terrain can be imported and new compatible UOP terrain can be generated. A complete map still needs its matching statics and index. Unsupported compression variants, malformed ranges or incompatible dimensions receive errors; not every UOP archive is promised.

PUBLICATION AND VALIDATION

Credits, official downloads and practical limits

Published and maintained by Celobra

Based on CentrED# by kaczy93, original version 0.6.11.31 (commit 50d23f7a8d7f). Original copyright, MIT licence and third-party notices remain, including in About/Credits. Celobra identifies this edition's maintainer and publisher; it does not imply sole authorship of the original program.

Branding and authenticity. Use the official download page and published SHA-256 checksums to identify the intended packages. The binaries are unsigned. Visible Celobra branding cannot prevent copying or removal of the name. No code-signing certificate or registered trademark protection is claimed; permitted reuse under MIT remains unaffected.

Checks and remaining acceptance

Targeted recovery and legacy-object checks passed: 17 tests, with no failures or skips. The original Local 0.7.3 feature suite passed 399 tests. These are separate test runs. See the release notices for the full 0.7.4 suite and final package/interface checks; these figures do not claim a completed full 0.7.4 release suite.

- Supply your own matching UO data. No game maps, artwork, accounts, saves, credentials or private diagnostic logs are included in the public editor packages.
- Test startup/graphics on another Windows PC, large or dense custom maps and memory use with several large ready tabs. Prepared maps still require initial copying, validation and minimap work.
- Check the build in the intended real client and test server. Approximate preview, configuration checks and synthetic regressions do not replace gameplay or external multiplayer acceptance.
- Keep backups and manage checkpoint storage. Saved views and map files persist; Undo/Redo does not persist after a tab closes or the application restarts.

Official downloads and upstream references

UO Asset Library - CentrED# Local / Celobra Edition
Current and earlier downloads, source, checksums and guides.

Original CentrED# project by kaczy93
Original MIT licence
Pascal CentrED reference by janinko

This is a community development edition, not an official upstream release. Pascal CentrED informed usability ideas; no Pascal program source or artwork was copied. Detailed format limits and behaviour are included with the program's user guide and release notices.