MPC planning steps - held-out shape-shift targets

Seven shapes x 50 targets x 3 test seeds per method and planner; identical initial/goal pairs. Ours: round-5 states of three chains, read-only.

Planner	Method	Episodes	Success (%)	Steps, all episodes	Steps, successes only
GD	Frozen	1,050	42.48	20.02 +/- 0.37	6.52 +/- 0.10
GD	AdaJEPA	1,050	72.19	14.52 +/- 0.61	8.56 +/- 0.11
GD	**Ours**	**3,150**	**81.59**	**11.30 +/- 0.53**	**7.08 +/- 0.15**
CEM	Frozen	1,050	43.81	21.08 +/- 0.58	9.65 +/- 0.16
CEM	AdaJEPA	1,050	70.38	16.02 +/- 0.33	10.13 +/- 0.45
CEM	**Ours**	**3,150**	**76.86**	**14.01 +/- 0.28**	**9.19 +/- 0.02**

Episodes per method and planner: 7 shapes x 50 targets x 3 test seeds = 1,050 (Ours: 3,150, its three chains on the same 1,050 targets).
Steps are MPC replanning iterations. Mean +/- sample SD is across the three test-seed means; lower means fewer iterations.
All-episode means include failures, which each used the full 30-step budget. Success-only means use each method's successful subset.
Success-only subsets differ across methods; read both step columns with the success rate. Checkpoints differ between Ours and the baselines.
Source: final_eval_results.npz of every run (action_len = first successful replan), checked against per_iter_logs.json for the sequential runs.