

Computer Graphics

Transformations of Objects

Ch5 Sec 6

Drawing 3D Shapes in OpenGL

- GLUT provides several 3D objects: a sphere, a cone, a torus, the five Platonic solids, and the teapot.
- Each is available as a **wireframe** model (one appearing as a collection of wires connected end to end) and as a solid model with faces that can be shaded.
- All are drawn by default centered at the origin.
- To use the solid version, replace **Wire** by **Solid** in the functions.

Middle Tennessee State University

Drawing 3D Shapes in OpenGL (2)

- **cube:** `glutWireCube (GLdouble size);`
 - Each side is of length size.
- **sphere:** `glutWireSphere (GLdouble radius, GLint nSlices, GLint nStacks);`
 - `nSlices` is the number of “orange sections” and `nStacks` is the number of disks.
 - Alternately, `nSlices` boundaries are longitude lines and `nStacks` boundaries are latitude lines.

Middle Tennessee State University

Drawing 3D Shapes in OpenGL (3)

- **torus:** `glutWireTorus (GLdouble inRad, GLdouble outRad, GLint nSlices, GLint nStacks);`
- **teapot:** `glutWireTeapot (GLdouble size);`
 - Why teapots? A standard graphics challenge for a long time was both making a teapot look realistic and drawing it quickly.

Middle Tennessee State University

Drawing 3D Shapes in OpenGL (4)

- **tetrahedron:** `glutWireTetrahedron ();`
- **octahedron:** `glutWireOctahedron ();`
- **dodecahedron:** `glutWireDodecahedron ();`
- **icosahedron:** `glutWireIcosahedron ();`
- **cone:** `glutWireCone (GLdouble baseRad, GLdouble height, GLint nSlices, GLint nStacks);`

Middle Tennessee State University

Drawing 3D Shapes in OpenGL (5)

- **tapered cylinder:** `gluCylinder (GLUquadricObj * qobj, GLdouble baseRad, GLdouble topRad, GLdouble height, GLint nSlices, GLint nStacks);`
- The **tapered cylinder** is actually a *family* of shapes, distinguished by the value of `topRad`.
 - When `topRad` is 1, there is no taper; this is the classic **cylinder**.
 - When `topRad` is 0, the tapered cylinder is identical to the **cone**.

Middle Tennessee State University

Drawing 3D Shapes in OpenGL (6)

- To draw the tapered cylinder in OpenGL, you must
 1. define a new quadric object,
 2. set the drawing style (`GLU_LINE`: wireframe, `GLU_FILL`: solid), and
 3. draw the object:

```


GLUquadricObj * qobj = gluNewQuadric ();
// make a quadric object
gluQuadricDrawStyle (qobj, GLU_LINE);
// set style to wireframe
gluCylinder (qobj, baseRad, topRad, nSlices, nStacks);
// draw the cylinder

```

Middle Tennessee State University

Demo Example


- Quadric objects with display list
- glu objects arranged in 3D



Middle Tennessee State University

Demo Solid 3D Drawing in OpenGL

- A solid object scene is rendered with shading. The light produces highlights on the sphere, teapot, and jack.



Middle Tennessee State University

Solid 3D Drawing in OpenGL (2)

- The scene contains three objects resting on a table in the corner of a room.
- The three walls are made by flattening a cube into a thin sheet and moving it into position.
- The jack is composed of three stretched spheres oriented at right angles plus six small spheres at their ends.

Middle Tennessee State University

Solid 3D Drawing in OpenGL (3)

- The table consists of a table top and four legs.
- Each of the table's five pieces is a cube that has been scaled to the desired size and shape (next slide).
- The table is based on four parameters that characterize the size of its parts: topWidth, topThick, legLen, and legThick.

Middle Tennessee State University

Solid 3D Drawing in OpenGL (4)

- A routine `tableLeg()` draws each leg and is called four times within the routine `table()` to draw the legs in the four different locations.
- The different parameters used produce different modeling transformations within `tableLeg()`. As always, a `glPushMatrix()`, `glPopMatrix()` pair surrounds the modeling functions to isolate their effect.


Middle Tennessee State University

Code for the Solid Example

- The solid version of each shape, such as `glutSolidSphere()`, is used.
- To create shaded images, the position and properties of a light source and certain properties of the objects' surfaces must be specified, in order to describe how they reflect light (Ch. 8).
- We just present the various function calls here; using them as shown will generate shading.

Middle Tennessee State University


Jack on Table Example



Solid sphere centered at origin


Middle Tennessee State University

Jack on Table Example




Middle Tennessee State University

Jack on Table Example



Middle Tennessee State University

Jack on Table Example




Solid cube centered at origin

Draw Table Top

Middle Tennessee State University

Jack on Table Example



glPushMatrix()


glTranslated(0, 0.3, 0) // O' raised 0.3 from 0 along y
glScaled(0.6, 0.02, 0.6) // O' (0.4, 0.3, 0.4)
glutSolidCube(1.0)

Table Top

glPopMatrix()

Middle Tennessee State University

Jack on Table Example




Leg Thickness = 0.02
Leg Length = 0.3

Draw Table Leg

Middle Tennessee State University

Jack on Table Example




pushMatrix
glTranslated(0, 0.3, 0)
glScaled(0.6, 0.02, 0.6)
glutSolidCube(1.0)
popMatrix

Assemble The Table (draw table)


Middle Tennessee State University

Table Construction



Middle Tennessee State University

Jack on Table Example




```
pushMatrix
dist = 0.6 * 0.95 / 2 - 0.02 / 2.0 = 0.275
glTranslated(0.275, 0, 0.275)
DrawTableLeg(0.02, 3.0)
```

```
pushMatrix
glTranslated(0, len/2, 0)
glScaled(0.02, len, 0.02)
glutSolidCube(1.0)
popMatrix
```

Middle Tennessee State University

Jack on Table Example



Assembled Table

```
dist = 0.275
glTranslated(0, 0, -2*dist)
DrawTableLeg(0.02, 0.3)

glTranslated(-2*dist, 0, 2*dist)
DrawTableLeg(0.02, 0.3)

glTranslated(0, 0, -2*dist)
DrawTableLeg(0.02, 0.3)
```

Middle Tennessee State University

Scene Description Language (SDL)

- Previous scenes were described through specific OpenGL calls that transform and draw each object, as in the following code:

```
glTranslated(0.25, 0.42, 0.35);
glutSolidSphere(0.1, 15, 15);
// draw a sphere
```

- The objects were “hard-wired” into the program. This method is cumbersome and error-prone.

Middle Tennessee State University

SDL (2)

- We want the designer to be able to specify the objects in a scene using a simple language and place the description in a file.
- The drawing program becomes a general-purpose program:
 - It reads a scene file at run-time and draws whatever objects are encountered in the file.

Middle Tennessee State University

Example SDL Scene

```
! example.dat: simple scene: 1 light and 4 shapes
! beginning ! is a comment; extends to end of line
background 0 0 1      ! create a blue background
light 2 9 8 1 1 1     ! put a white light at (2, 9, 8)
diffuse .9 .1 .1      ! make following objects reddish
translate 3 5 -2 sphere ! put a sphere at 3 5 -2
translate -4 -6 8 cone ! put a cone in the scene
translate 1 1 1 cube   ! add a cube
diffuse 0 1 0          ! make following objects green
translate 40 5 2 scale .2 .2 .2 sphere ! tiny sphere
```

Middle Tennessee State University

The SDL Scene

- The scene has a bright blue background color (*red, green, blue*) = (0, 0, 1), a bright white (1, 1, 1) light situated at (2, 9, 8), and four objects: two spheres, a cone and a cube.
- The light field points to the list of light sources, and the obj field points to the object list.
- Each shape object has its own affine transformation M that describes how it is scaled, rotated, and positioned in the scene. It also contains various data fields that specify its material properties. Only the diffuse field is shown in the example.


Middle Tennessee State University

Using SDL

- The **Scene Description Language (SDL)**, provides a Scene class that supports the reading of an SDL file and the drawing of the objects described in the file.
- A global Scene object is created:
`Scene scn; // create a scene object`
- Read in a scene file using the read method of the class:
`scn.read("example.dat"); // read the scene file & build an object list`

Middle Tennessee State University

SDL Data Structure



Middle Tennessee State University

The SDL Scene (2)

- Once the light list and object list have been built, the application can render the scene:


```
scn.makeLightsOpenGL(),
scn.drawSceneOpenGL(); // render scene with OpenGL
```
- The first instruction passes a description of the light sources to OpenGL. The second uses the method `drawSceneOpenGL()` to draw each object in the object list.
- The code for this method is very simple:


```
void Scene :: drawSceneOpenGL()
{
    for(GeomObj* p = obj; p ; p = p->next)
        p->drawOpenGL(); // draw it
}
```

Middle Tennessee State University

The SDL Scene (3)

- The function moves a pointer through the object list, calling `drawOpenGL()` for each object in turn.
- Each different shape can draw itself; it has a method `drawOpenGL()` that calls the appropriate routine for that shape.
- Each first passes the object's material properties to OpenGL, then updates the modelview matrix with the object's specific affine transformation.
- The original modelview matrix is pushed and later restored to protect it from being affected after this object has been drawn.

Middle Tennessee State University

Examples of Objects which can Draw Themselves

```
void Sphere :: drawOpenGL()
{
    tellMaterialsGL(); //pass material data to OpenGL
    glPushMatrix();
    glMultMatrixf(transf.m); // load this object's matrix
    glutSolidSphere(1.0,10,12); // draw a sphere
    glPopMatrix();
}

void Cone :: drawOpenGL()
{
    tellMaterialsGL(); //pass material data to OpenGL
    glPushMatrix();
    glMultMatrixf(transf.m); // load this object's matrix
    glutSolidCone(1.0,1.0, 10,12); // draw a cone
    glPopMatrix();
}
```

Middle Tennessee State University


Drawing 3D Scenes in OpenGL

- We want to transform objects in order to orient and position them as desired in a 3D scene.
- OpenGL provides the necessary functions to build and use the required matrices.
- The matrix stacks maintained by OpenGL make it easy to set up a transformation for one object, and then return to a previous transformation, in preparation for transforming another object.

Middle Tennessee State University

The Viewing Process and the Graphics Pipeline


- The 2D drawing so far is a special case of 3D viewing, based on a simple parallel projection.
- The eye is looking along the z-axis at the world window, a rectangle in the xy-plane.



Middle Tennessee State University

The Viewing Process and the Graphics Pipeline (2)


- *Eye* is simply a point in 3D space.
- The “orientation” of the eye ensures that the view volume is in front of the eye.
- Objects closer than *near* or farther than *far* are too blurred to see.



Middle Tennessee State University

The Viewing Process and the Graphics Pipeline (3)

- The **view volume** of the camera is a rectangular parallelepiped (Orthographic Projection)
- Its side walls are fixed by the window edges; its other two walls are fixed by a **near plane** and a **far plane**.



Middle Tennessee State University

The Viewing Process and the Graphics Pipeline (4)

- The **view volume** of the camera using Perspective Projection (to be discussed later)
- Its side walls are fixed by the window edges; its other two walls are fixed by a **near plane** and a **far plane**.

Middle Tennessee State University

The Viewing Process and the Graphics Pipeline (5)

- Points inside the view volume are projected onto the window along lines parallel to the z-axis.
- We ignore their z-component, so that the 3D point (x_1, y_1, z_1) projects to $(x_1, y_1, 0)$.
- Points lying outside the view volume are clipped off.
- A separate **viewport transformation** maps the projected points from the window to the viewport on the display device.

Middle Tennessee State University

The Viewing Process and the Graphics Pipeline (6)





- In 3D, the only change we make is to allow the camera (eye) to have a more general position and orientation in the scene in order to produce better views of the scene.

Middle Tennessee State University

The Viewing Process and the Graphics Pipeline (7)


- The z axis points *toward* the eye. X and y point to the viewer's right and up, respectively.
- Everything outside the view volume is clipped.
- Everything inside it is projected along lines parallel to the axes onto the window plane (parallel projection).

Middle Tennessee State University



The Modelview Matrix (V)


- The camera moves from its position in the scene to its generic position (eye at the origin and the view volume aligned with the z-axis).
- The coordinates of the block's vertices are changed so that projecting them onto a plane (e.g., the near plane) displays the projected image properly.



Middle Tennessee State University

The Modelview Matrix (V)

- The matrix V changes the coordinates of the scene vertices into the **camera's coordinate system**, or into **eye coordinates**.
- To inform OpenGL that we wish it to operate on the modelview matrix we call `glMatrixMode(GL_MODELVIEW);`



Middle Tennessee State University

Setting Up the Scene

```
glMatrixMode (GL_MODELVIEW);
// set up the modelview matrix
glLoadIdentity ();
// initialize modelview matrix
// set up the view part of the matrix
// do any modeling transformations on the scene
```

Middle Tennessee State University

Setting Up the Camera (View Matrix)

```
glMatrixMode (GL_MODELVIEW);
// make the modelview matrix current
glLoadIdentity();
// start with identity matrix
// position and aim the camera
gluLookAt (eye.x, eye.y, eye.z, // eye position
look.x, look.y, look.z, // the "look at" point
0, 1, 0) // approximation to true up direction
// Now do the modeling transformations
```


Middle Tennessee State University

Setting Up the Camera (2)

- What `gluLookAt` does is create a camera coordinate system of three mutually orthogonal unit vectors: **u**, **v**, and **n**.
- n** = eye - look; **u** = **up** × **n**; **v** = **n** × **u**
- Normalize **n**, **u**, **v** (in the camera system) and
- let **e** = eye - O in the camera system, where O is the origin.

Middle Tennessee State University

The effect of gluLookAt



Middle Tennessee State University

Setting Up the Camera (3)

- Then `gluLookAt ()` sets up the view matrix

$$V = \begin{pmatrix} u_x & u_y & u_z & d_x \\ v_x & v_y & v_z & d_y \\ n_x & n_y & n_z & d_z \\ 0 & 0 & 0 & 1 \end{pmatrix}$$

where **d** = (-**e**·**u**, -**e**·**v**, -**e**·**n**)

- up** is usually (0, 1, 0) (along the y-axis), *look* is frequently the middle of the window, and *eye* frequently looks down on the scene.

Middle Tennessee State University

Practice Question

- Given: `gluLookAt (4, 4, 4, 0, 1, 0, 0, 1, 0);`
What is the View matrix **V**?

Steps:

1. Compute vectors **n**, **u**, **v**
2. Normalize **n**, **u**, **v**
3. Compute vector: **e** = eye - O
d = (-**e**·**u**, -**e**·**v**, -**e**·**n**)
4. Put the view matrix together

Middle Tennessee State University

Practice Question

$$\mathbf{n} = \text{eye} - \text{look} = (4, 3, 4)$$

$$\mathbf{u} = \mathbf{up} \times \mathbf{n} = \begin{vmatrix} \mathbf{i} & \mathbf{j} & \mathbf{k} \\ 0 & 1 & 0 \\ 4 & 3 & 4 \end{vmatrix} = (4, 0, -4)$$

$$\mathbf{v} = \mathbf{n} \times \mathbf{u} = (-12, 32, -12)$$

Normalize \mathbf{u} , \mathbf{v} , and \mathbf{n} .

$$\mathbf{n} = (0.6247, 0.4685, 0.6247)$$

$$\mathbf{u} = (0.70711, 0, -0.70711)$$

$$\mathbf{v} = (-0.3313, 0.8834, -0.3313)$$

$$dx = -\text{eye} \cdot \mathbf{u} = (-4, -4, -4) \cdot (0.70711, 0, -0.70711) = 0$$

$$dy = -\text{eye} \cdot \mathbf{v} = (-4, -4, -4) \cdot (-0.3313, 0.8834, -0.3313) = -0.88345$$

$$dz = -\text{eye} \cdot \mathbf{n} = (-4, -4, -4) \cdot (0.6247, 0.4685, 0.6247) = -6.872$$

So that,

$$V = \begin{pmatrix} .70711 & 0 & -.70711 & 0 \\ -.3313 & .88345 & -.3313 & -.88345 \\ .6247 & .4685 & .6247 & -6.872 \\ 0 & 0 & 0 & 1 \end{pmatrix}$$

Middle Tennessee State University

Setting Up the Camera


- We shall use a **jib camera**.
- The photographer rides at the top of the tripod.
- The camera moves through the scene bobbing up and down to get the desired shots.




Changing Camera Orientation

- We can think of the jib camera as behaving like an airplane.
 - It can pitch, roll, or yaw from its position.


a) pitch



b) roll



c) yaw



Middle Tennessee State University

Changing Camera Orientation (2)

- **Pitch** – the angle between the longitudinal axis and world horizontal.
- **Roll** – the angle between the transverse axis and the world.
- **Yaw** – motion of the longitudinal axis causing a change in the direction of the plane's flight.

Middle Tennessee State University

