

Chapter 3

Objectives

- Simple Shaders
 - Vertex shader
 - Fragment shaders
- Programming shaders with GLSL

Middle Tennessee State University

Vertex Shader Applications

- Moving vertices
 - Morphing
 - Wave motion
 - Fractals
- Lighting
 - More realistic models
 - Cartoon shaders

Middle Tennessee State University

Fragment Shader Applications

Per fragment lighting calculations




per vertex lighting

per fragment lighting

Middle Tennessee State University

Fragment Shader Applications


Texture mapping



smooth shading



environment mapping



bump mapping

Middle Tennessee State University

Writing Shaders

- First programmable shaders were programmed in an assembly-like manner
- OpenGL extensions added functions for vertex and fragment shaders
- Cg (C for graphics) C-like language for programming shaders
 - Works with both OpenGL and DirectX
 - Interface to OpenGL complex
- OpenGL Shading Language (GLSL)

Middle Tennessee State University

GLSL

- OpenGL Shading Language
- Part of OpenGL 2.0 and up
- High level C-like language
- New data types
 - Matrices
 - Vectors
 - Samplers
- As of OpenGL 3.1, application must provide shaders

Middle Tennessee State University

Simple Vertex Shader

```


attribute vec4 vPosition;
void main(void)
{
    gl_Position = vPosition;
}
    
```

Annotations:

- input from application (points to `vPosition`)
- must link to variable in application (points to `vPosition`)
- built in variable (points to `gl_Position`)

Middle Tennessee State University

Execution Model



Middle Tennessee State University


Simple Fragment Program

```

precision mediump float;
void main(void)
{
    gl_FragColor = vec4(1.0, 0.0, 0.0, 1.0);
}
    
```

Middle Tennessee State University

Execution Model



Middle Tennessee State University

Data Types

- C types: int, float, bool
- Vectors:
 - float vec2, vec3, vec4
 - Also int (ivec) and boolean (bvec)
- Matrices: mat2, mat3, mat4
 - Stored by columns
 - Standard referencing `m[row][column]`
- C++ style constructors
 - `vec3 a = vec3(1.0, 2.0, 3.0)`
 - `vec2 b = vec2(a)`

Middle Tennessee State University

No Pointers

- There are no pointers in GLSL
- We can use C structs which can be copied back from functions
- Because matrices and vectors are basic types they can be passed into and output from GLSL functions, e.g.
`mat3 func(mat3 a)`
- variables passed by copying

Middle Tennessee State University

Qualifiers

- GLSL has many of the same qualifiers such as **const** as C/C++
- Need others due to the nature of the execution model
- Variables can change
 - Once per primitive
 - Once per vertex
 - Once per fragment
 - At any time in the application
- Vertex attributes are interpolated by the rasterizer into fragment attributes

Middle Tennessee State University

Attribute Qualifier

- Attribute-qualified variables can change at most once per vertex
- There are a few built in variables such as `gl_Position` but most have been deprecated
- User defined (in application program)
 - **attribute float temperature**
 - **attribute vec3 velocity**
 - recent versions of GLSL use **in** and **out** qualifiers to get to and from shaders

Middle Tennessee State University

Uniform Qualified

- Variables that are constant for an entire primitive
- Can be changed in application and sent to shaders
- Cannot be changed in shader
- Used to pass information to shader such as the time or a bounding box of a primitive or transformation matrices

Middle Tennessee State University

Varying Qualified

- Variables that are passed from vertex shader to fragment shader
- Automatically interpolated by the rasterizer
- With WebGL, GLSL uses the varying qualifier in both shaders
`varying vec4 color;`
- More recent versions of WebGL use **out** in vertex shader and **in** in the fragment shader
`out vec4 color; //vertex shader`
`in vec4 color; // fragment shader`

Middle Tennessee State University

Our Naming Convention

- attributes passed to vertex shader have names beginning with v (`vPosition`, `vColor`) in both the application and the shader
 - Note that these are different entities with the same name
- Varying variables begin with f (`fColor`) in both shaders
 - must have same name
- Uniform variables are unadorned and can have the same name in application and shaders

Middle Tennessee State University

Example: Vertex Shader

```
attribute vec4 vPosition;
attribute vec4 vColor;
varying vec4 fColor;
void main()
{
    gl_Position = vPosition;
    fColor = vColor;
}
```

Middle Tennessee State University

Corresponding Fragment Shader

```
precision mediump float;

varying vec3 fColor;
void main()
{
    gl_FragColor = fColor;
}
```

Middle Tennessee State University

Sending Colors from Application

```
var cBuffer = gl.createBuffer();
gl.bindBuffer( gl.ARRAY_BUFFER, cBuffer );
gl.bufferData( gl.ARRAY_BUFFER, flatten(colors),
               gl.STATIC_DRAW );

var vColor = gl.getAttribLocation( program, "vColor" );
gl.vertexAttribPointer( vColor, 3, gl.FLOAT, false, 0, 0 );
gl.enableVertexAttribArray( vColor );
```

Middle Tennessee State University

Sending a Uniform Variable

```
// in application

vec4 color = vec4(1.0, 0.0, 0.0, 1.0);
colorLoc = gl.getUniformLocation( program, "color" );
gl.uniform4f( colorLoc, color);

// in fragment shader (similar in vertex shader)

uniform vec4 color;

void main()
{
    gl_FragColor = color;
}
```

Middle Tennessee State University

Operators and Functions

- Standard C functions
 - Trigonometric
 - Arithmetic
 - Normalize, reflect, length
- Overloading of vector and matrix types

```
mat4 a;
vec4 b, c, d;
c = b*a; // a column vector stored as a 1d array
d = a*b; // a row vector stored as a 1d array
```

Middle Tennessee State University


Swizzling and Selection

- Can refer to array elements by element using [] or selection (.) operator with
 - x, y, z, w
 - r, g, b, a
 - s, t, p, q
 - **a[2], a.b, a.z, a.p** are the same
- **Swizzling** operator lets us manipulate components

```
vec4 a, b;
a.yz = vec2(1.0, 2.0, 3.0, 4.0);
b = a.yxzw;
```

Middle Tennessee State University


WebGLPrimitives



Middle Tennessee State University

Polygon Issues

- WebGL will only display triangles
 - Simple: edges cannot cross
 - Convex: All points on line segment between two points in a polygon are also in the polygon
 - Flat: all vertices are in the same plane
- Application program must tessellate a polygon into triangles (triangulation)
- OpenGL 4.1 contains a tessellator but not WebGL



Middle Tennessee State University


Polygon Testing

- Conceptually simple to test for simplicity and convexity
- Time consuming
- Earlier versions assumed both and left testing to the application
- Present version only renders triangles
- Need algorithm to triangulate an arbitrary polygon

Middle Tennessee State University

Good and Bad Triangles

- Long thin triangles render badly




- Equilateral triangles render well
- Maximize minimum angle
- Delaunay triangulation for unstructured points

Middle Tennessee State University

Triangularization


- Convex polygon



- Start with abc, remove b, then acd,

Middle Tennessee State University


Non-convex (concave)



Middle Tennessee State University

Recursive Division

- Find leftmost vertex and split



Middle Tennessee State University


Attributes

- Attributes determine the appearance of objects
 - Color (points, lines, polygons)
 - Size and width (points, lines)
 - Stipple pattern (lines, polygons)
 - Polygon mode
 - Display as filled: solid color or stipple pattern
 - Display edges
 - Display vertices
- Only a few (`gl_PointSize`) are supported by WebGL functions

Middle Tennessee State University

RGB color


- Each color component is stored separately in the frame buffer
- Usually 8 bits per component in buffer
- Color values can range from 0.0 (none) to 1.0 (all) using floats or over the range from 0 to 255 using unsigned bytes



Middle Tennessee State University

Indexed Color


- Colors are indices into tables of RGB values
- Requires less memory
 - indices usually 8 bits
 - not as important now
 - Memory inexpensive
 - Need more colors for shading



Middle Tennessee State University

Smooth Color

- Default is *smooth* shading
 - Rasterizer interpolates vertex colors across visible polygons
- Alternative is *flat shading*
 - Color of first vertex determines fill color
 - Handle in shader



Middle Tennessee State University

Setting Colors

- Colors are ultimately set in the fragment shader but can be determined in either shader or in the application
- Application color: pass to vertex shader as a uniform variable or as a vertex attribute
- Vertex shader color: pass to fragment shader as a varying variable
- Fragment color: can alter via shader code

Middle Tennessee State University

Objectives

- Coupling shaders to applications
 - Reading
 - Compiling
 - Linking
- Vertex Attributes
- Setting up uniform variables
- Example applications

Middle Tennessee State University

Linking Shaders with Application

- Read shaders
- Compile shaders
- Create a program object
- Link everything together
- Link variables in application with variables in shaders
 - Vertex attributes
 - Uniform variables

Middle Tennessee State University

Program Object

- Container for shaders
 - Can contain multiple shaders
 - Other GLSL functions

```
var program = gl.createProgram();  
  
gl.attachShader( program, vertShdr );  
gl.attachShader( program, fragShdr );  
gl.linkProgram( program );
```

Middle Tennessee State University

Reading a Shader

- Shaders are added to the program object and compiled
- Usual method of passing a shader is as a null-terminated string using the function
- `gl.shaderSource(fragShdr, fragElem.text);`
- If shader is in HTML file, we can get it into application by `getElementById` method
- If the shader is in a file, we can write a reader to convert the file to a string

Middle Tennessee State University

Adding a Vertex Shader

```
var vertShdr;  
var vertElem =  
    document.getElementById( vertexShaderId );  
  
vertShdr = gl.createShader( gl.VERTEX_SHADER );  
  
gl.shaderSource( vertShdr, vertElem.text );  
gl.compileShader( vertShdr );  
  
// after program object created  
gl.attachShader( program, vertShdr );
```

Middle Tennessee State University

Shader Reader

- Following code may be a security issue with some browsers if you try to run it locally
 - Cross Origin Request

```
function getShader(gl, shaderName, type) {  
    var shader = gl.createShader(type);  
    shaderScript = loadFileAJAX(shaderName);  
    if (!shaderScript) {  
        alert("Could not find shader source" +  
            shaderName);  
    }  
}
```

Middle Tennessee State University

Precision Declaration

- In GLSL for WebGL we must specify desired precision in fragment shaders
 - artifact inherited from OpenGL ES
 - ES must run on very simple embedded devices that may not support 32-bit floating point
 - All implementations must support mediump
 - No default for float in fragment shader
- Can use preprocessor directives (`#ifdef`) to check if highp supported and, if not, default to mediump

Middle Tennessee State University

Pass Through Fragment Shader

```
#ifdef GL_FRAGMENT_SHADER_PRECISION_HIGH
precision highp float;
#else
precision mediump float;
#endif

varying vec4 fcolor;
void main(void)
{
    gl_FragColor = fcolor;
}
```

Middle Tennessee State University