


SMD POWER INDUCTORS











- Features
- 1 Excellent Power Density
- 2 Engineered to Provide High Efficiency

ELECTRICAL CHARACTERISTICS



Part NumSer	Inductance	Test	DC Resistance	Saturation (3)	Temperature (4)
	(uH)	Frequency	(Ω MAX)	Current	Current (4)
	(1)		(2)	(A)	(A)
SCEP125H-1R0	1.0	100KHZ	2.5m	20.0	20.0
SCEP125H-1R8	1.8	100KHZ	3.8m	15.3	13.0
SCEP125H-2R8	2.8	100KHZ	5.4m	12.3	12.2
SCEP125H-4R0	4.0	100KHZ	8.0m	10.3	11.8
SCEP125H-5R6	5.6	100KHZ	11.4m	8.80	9.80
SCEP125H-7R2	7.2	100KHZ	13.5m	7.80	8.80





- (1). Inductance tolerance ±20% tested at 0.25V, 0ADC and 25°C
- (2). DCR measured at 25°C.
- (3). The DC current at which the inductance decreases by 25% from its initial value.
- (4). The DC current that results in a 40°C temperature rise from 25°C ambient.

Click here for QUANTITY PER REEL & PACKING INFORMATION



Custom versions available upon request.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Bel:

SCEP125H-2R8 SCEP125H-5R6 SCEP125H-7R2 SCEP125H-4R0 SCEP125H-1R8 SCEP125H-1R0