

TMEngine

An Open Source Translation Memory Manager

Rodolfo M. Raya

rmraya@maxprograms.com

Maxprograms

<https://www.maxprograms.com>

Table of Contents

Overview	1
TMEngine	1
Java Library	2
REST API	3
REST Methods	3
Create Memory	3
List Memories	5
Open Memory	5
Close Memory	6
Import TMX File	7
Process Status	8
Export TMX File	9
Search Translations	10
Concordance Search	10
Rename Memory	10
Delete Memory	10
Stop Server	10

Overview

TMEngine

TMEngine is an open source [Translation Memory](#)™ manager written in Java.

TMEngine can be used either as an embedded library that manages translation memories in a Java application or as a standalone TM server via its REST API.

Java Library

REST API

REST Methods

The REST methods that TMEngine's server supports are:

- [Create Memory](#)
- [List Memories](#)
- [Open Memory](#)
- [Close Memory](#)
- [Import TMX File](#)
- [Process Status](#)
- [Export TMX File](#)
- [Search Translations](#)
- [Search Translations](#)
- [Rename Memory](#)
- [Delete Memory](#)
- [Stop Server](#)

Default TMEngine URL is 'http://localhost:8000/TMServer/'.

Note

It is possible to select a custom port for the server, passing the '-port' parameter to the script used for launching it.

All methods return a JSON object with a 'status' field. Applications must watch this field and verify that it is set to 'OK'.

In case of error, the JSON response includes a field named 'reason' that contains the error cause.

Create Memory

End Point: [TMEngine URL]/create

Default: http://localhost:8000/TMServer/create

Send a 'POST' request to the method end point with these parameters in a JSON body:

Field	Required	Content
id	No	ID of the memory to create. The value of ID must be unique. Default value is current server time represented as the number of milliseconds since January 1, 1970, 00:00:00 GMT

Field	Required	Content
name	Yes	A meaningful name to identify the memory
owner	No	Text string used to identify the owner of the memory. Default value is the user name of the user running the server.
type	No	Type of engine to use. Possible values are: 'MapDbEngine' (default) and 'SQLEngine'
serverName	No	Required for SQLEngine. Name or IP of the server running MySQL or MariaDB
port	No	Required for SQLEngine. Port in which MySQL or MariaDB listens for requests
userName	No	Required for SQLEngine. ID of of the MySQL or MariaDB user creating the database
password	No	Required for SQLEngine. Password of the MySQL or MariaDB user creating the database

Example:

```
{
  "name": "First Memory",
  "type": "MapDbEngine"
}
```

```
{
  "name": "MariaMemory",
  "type": "SQLEngine",
  "serverName": "localhost",
  "port": 3306,
  "userName": "root",
  "password": "secret123!"
}
```

The server responds with a JSON object containing two fields.

On success, field 'status' is set to 'OK' and field 'id' contains the ID assigned to the new memory.

Example:

```
{
  "status": "OK",
  "id": "1234567890987"
}
```

On error, field 'status' is set to 'failed' and field 'reason' contains the error cause.

Example:

```
{
  "status": "failed",
  "reason": "Duplicated id"
}
```

List Memories

End Point: [TMEngine URL]/list

Default: <http://localhost:8000/TMServer/list>

Send a 'GET' request to the method end point.

The server responds with a JSON object containing two fields. On success, field 'status' is set to 'OK' and field 'memories' contains an array with memory details.

```
{
  "memories": [
    {
      "owner": "manager",
      "isOpen": false,
      "name": "Fluenta Localization",
      "id": "fluenta",
      "type": "MapDbEngine",
      "creationDate": "2019-09-10 21:54:13 UYT"
    },
    {
      "owner": "manager",
      "isOpen": false,
      "name": "First Memory",
      "id": "1568163112478",
      "type": "MapDbEngine",
      "creationDate": "2019-09-10 21:51:52 UYT"
    }
  ],
  "status": "OK"
}
```

On error, field 'status' is set to 'failed' and field 'reason' contains the error cause.

Example:

```
{
  "status": "failed",
  "reason": "Error reading memories"
}
```

Open Memory

End Point: [TMEngine URL]/create

Default: <http://localhost:8000/TMServer/open>

Send a 'POST' request to the method end point with this parameters in a JSON body:

Field	Required	Content
id	Yes	ID of the memory to open

Example:

```
{
  "id": "1568163112478"
}
```

The server responds with a JSON object. On success, field 'status' is set to 'OK'.

```
{
  "status": "OK"
}
```

On error, field 'status' is set to 'failed' and field 'reason' contains the error cause.

Example:

```
{
  "status": "failed",
  "reason": "Unknown memory type"
}
```

Close Memory

End Point: [TMEngine URL]/create

Default: <http://localhost:8000/TMServer/close>

Send a 'POST' request to the method end point with this parameters in a JSON body:

Field	Required	Content
id	Yes	ID of the memory to close

Example:

```
{
  "id": "1568163112478"
}
```

The server responds with a JSON object. On success, field 'status' is set to 'OK'.

```
{
  "status": "OK"
}
```

On error, field 'status' is set to 'failed' and field 'reason' contains the error cause.

Example:

```
{
  "status": "failed",
  "reason": "Unknown memory"
}
```


Import TMX File

End Point: [TMEngine URL]/import

Default: <http://localhost:8000/TMServer/import>

Send a 'POST' request to the method end point with these parameters in a JSON body:

Field	Required	Content
id	Yes	ID of the memory to populate with TMX data
file	Yes	Path to the TMX file being imported
subject	No	Name or identifier of the subject associated with the TMX file
client	No	Name or identifier of the client associated with the TMX file
project	No	Name or identifier of the project associated with the TMX file

Example:

```
{
  "id": "1568163112478",
  "file": "/Volumes/Data/segments.tmx",
  "project": "Main TM"
}
```

The server responds with a JSON object containing two fields.

On success, field 'status' is set to 'OK' and field 'process' contains the ID of the background import process that was initiated.

```
{
  "process": "1568222345643",
  "status": "OK"
}
```

On error, field 'status' is set to 'failed' and field 'reason' contains the error cause.

```
{
  "status": "failed",
  "reason": "Unknown memory type"
}
```

After starting the import process, monitor its status using the [Process Status](#) method. On successful completion, the result will contain the number of segments imported.

Example:

```
{
  "result": "Completed",
  "data": {
    "imported": "57678"
  }
}
```

```
},
"status": "OK"
}
```

Process Status

End Point: [TMEngine URL]/create

Default: <http://localhost:8000/TMServer/status>

Send a POST request to the method end point with this parameters in a JSON body:

Field	Required	Content
process	Yes	ID of the background process to check

Example:

```
{
  "process": "1568223016762"
}
```

The server responds with a JSON object containing two or three fields.

On successful status check, field 'status' is set to 'OK' and field 'result' contains current status.

Example:

Field 'result' may have these values:

- **Pending:** processing is still going on.

```
{
  "result": "Pending",
  "status": "OK"
}
```

- **Completed:** processing has finished. If the process produces any data, it is placed in the 'data' field.

```
{
  "result": "Completed",
  "data": {
    "imported": "57678"
  },
  "status": "OK"
}
```

- **Failed:** processing failed. Failure reason is provided in 'reason' field.

```
{
  "result": "Failed",
  "reason": "/Volumes/Data/something.tmx (No such file or directory)",
  "status": "failed"
}
```

If process status cannot be checked, the server omits the 'result' field and provides a failure reason.

```
{
```

```
"reason": "Missing 'process' parameter",
"status": "failed"
}
```

Export TMX File

End Point: [TMEngine URL]/create

Default: <http://localhost:8000/TMServer/export>

Send a 'POST' request to the method end point with these parameters in a JSON body:

Field	Required	Content
id	Yes	ID of the memory to populate with TMX data
file	Yes	Path to the TMX file being created
langs	No	JSON array containing the list of languages to export
srcLang	No	Language to set as source language. The wildcard '*all*' is used by default
properties	No	JSON object with string properties to set in the exported file

Example:

```
{
  "id": "1568163112478",
  "file": "/Volumes/Data/segments.tmx",
  "langs": [
    "en-US",
    "ja",
    "fr-FR",
    "it"
  ],
  "srcLang": "en-US",
  "properties": {
    "project": "Milky Way",
    "subject": "Astronomy Device"
  }
}
```

The server responds with a JSON object containing two fields.

On success, field 'status' is set to 'OK' and field 'process' contains the ID of the background export process that was initiated.

```
{
  "process": "1568222345643",
  "status": "OK"
}
```

On error, field 'status' is set to 'failed' and field 'reason' contains the error cause.

```
{
  "status": "failed",
  "reason": "Unknown memory type"
}
```

After starting the export process, monitor its status using the [Process Status](#) method.

Search Translations

End Point: [TMEngine URL]/create

Default: <http://localhost:8000/TMServer/search>

Concordance Search

End Point: [TMEngine URL]/create

Default: <http://localhost:8000/TMServer/concordance>

Rename Memory

End Point: [TMEngine URL]/create

Default: <http://localhost:8000/TMServer/rename>

Delete Memory

End Point: [TMEngine URL]/create

Default: <http://localhost:8000/TMServer/delete>

Stop Server

End Point: [TMEngine URL]/create

Default: <http://localhost:8000/TMServer/stop>

Send a 'GET' request to the method end point.

The server responds with a JSON object. On success, field 'status' is set to 'OK'.

Example:

```
{
  "status": "OK"
}
```

On error, field 'status' is set to 'failed' and field 'reason' contains the error cause.

Example:

```
{
  "status": "failed",
  "reason": "Error connecting to database"
}
```