

II. Working with data in R (presentation)

18 May, 2022

Tidyverse package

The tidyverse is a collection of R packages which, among other things, facilitate data handling and data transformation in R. See <https://www.tidyverse.org/> for details.

We must install and load the R package **tidyverse** before we have access to the functions.

- Install package: One option is to go via the *Packages* tab of the lower right panel: *Packages* → *Install* → write **tidyverse** in the field called *Packages*. This only has to be done once. Otherwise use the `install.packages` function as shown here:

```
install.packages("tidyverse", repos = "https://mirrors.dotsrc.org/cran/")
```

- Load package: Use the `library` command. This has to be done in every R-session where you use the package.

```
library(tidyverse)
```

Import data

Data from Excel files can be imported via the *Import Dataset* facility. You may get the message that the package **readxl** should be installed. If so, then install it as explained for **tidyverse** above.

- In the *Environment* tab in the upper right panel, find *Import Dataset* and choose *From Excel* in the dropdown menu.
- A new window opens. Browse for the relevant Excel file; then a preview of the dataset is shown. Check that it looks OK, and click *Import*.
- Three things happened: Three lines of code were generated (and executed) in the Console, a new dataset now appears in the Environment window, and the dataset is shown in the top left window. Check again that it looks OK.
- Copy the first two lines of code into your R script (or into an R chunk in your Markdown document), but delete the line starting with **View** and write instead the name of the dataset, here **downloads**. Then the first 10 lines of the data set are printed.

```
library(readxl)
downloads <- read_excel("downloads.xlsx")
downloads
```

```
## # A tibble: 147,035 x 6
##   machineName userID size time date month
##   <chr>      <dbl> <dbl> <dbl> <dtm> <chr>
## 1 cs18      146579 2464 0.493 1995-04-24 00:00:00 1995-04
## 2 cs18      995988 7745 0.326 1995-04-24 00:00:00 1995-04
## 3 cs18      317649 6727 0.314 1995-04-24 00:00:00 1995-04
## 4 cs18      748501 13049 0.583 1995-04-24 00:00:00 1995-04
## 5 cs18      955815 356 0.259 1995-04-24 00:00:00 1995-04
```

```
## 6 cs18      444174      0 0      1995-04-24 00:00:00 1995-04
## 7 cs18      446911      0 0      1995-04-24 00:00:00 1995-04
## 8 cs18      449552      0 0      1995-04-24 00:00:00 1995-04
## 9 cs18      456142      0 0      1995-04-24 00:00:00 1995-04
## 10 cs18     458942      0 0      1995-04-24 00:00:00 1995-04
## # ... with 147,025 more rows
```

R has stored the data in a so-called *tibble*, a type of data frame. Rows are referred to as *observations* or *data lines*, columns as *variables*. The data rows appear in the order as in the Excel file.

A slight digression: If data are saved in a csv file (comma separated values), possibly generated via an Excel sheet, then data can be read with the `read_csv` function. For example, if the data file is called `mydata.csv` and values are separated with commas, then the command

```
mydata <- read.csv("mydata.csv", sep=",")
```

creates a data frame in R with the data. The dataframe is *not* a tibble and some of the commands below would not work for such a data frame. However, you can easily cast dataframes into tibbles, see `presentation1.Rmd`.

About the data

The dataset is from Boston University and is about www data transfers from November 1994 to May 1995, see <http://ita.ee.lbl.gov/html/contrib/BU-Web-Client.html>.

- It has 147,035 data lines and 6 variables
 - *size* is the download size in bytes, and *time* is the download time in seconds.
-

Filtering data (selecting rows): `filter`

The `filter` function is used to make sub-datasets where only certain data lines (rows) are maintained. It's described with *logical expressions* which lines should be kept in the dataset.

Say that we only want observations with download time larger than 1000 seconds; there happens to be eight such observations:

```
downloads %>%
  filter(time > 1000)
```

```
## # A tibble: 8 x 6
##   machineName userID      size time date      month
##   <chr>      <dbl>    <dbl> <dbl> <dtm>    <chr>
## 1 cs18      502807  4055821 1275. 1994-12-02 00:00:00 1994-12
## 2 cs18      16653   2573336 1335. 1994-11-22 00:00:00 1994-11
## 3 cs18      957883   2743516 1151. 1994-11-22 00:00:00 1994-11
## 4 cs18      47910   4720220 1749. 1994-11-22 00:00:00 1994-11
## 5 tweetie   223655    245003 1214. 1995-04-13 00:00:00 1995-04
## 6 kermit    576790  14518894 1380. 1995-04-20 00:00:00 1995-04
## 7 kermit    139654   1079731 1129. 1995-02-23 00:00:00 1995-02
## 8 pluto     337530   8674562 1878. 1995-03-13 00:00:00 1995-03
```

Or say that only want observations with strictly positive download size:

```
downloads3 <- downloads %>%
  filter(size > 0)
```

Notice that this result is assigned to **downloads3**. It has 36,708 data lines. The original data called **downloads** still exists with 147,035 data lines.

Filtering requires *logical predicates*. These are expressions in terms of columns, which evaluate to either TRUE or FALSE for each row. Logical expressions can be combined with logical operations.

- Comparisons: ==, !=, <, >, <=, >=, %in%, is.na
- Logical operations: ! (not), | (or), & (and). A comma can be used instead of &

Here comes two sub-datasets:

```
# Rows from kermit, and with size greater than 200000 bytes are kept.
downloads3 %>% filter(machineName == "kermit", size > 200000)
```

```
## # A tibble: 98 x 6
##   machineName userID      size    time date      month
##   <chr>      <dbl>    <dbl>    <dbl> <dtm>      <chr>
## 1 kermit    157161  498325  0.629 1995-04-13 00:00:00 1995-04
## 2 kermit    734988  271058  17.3   1995-04-22 00:00:00 1995-04
## 3 kermit    388066  435923  29.2   1995-04-22 00:00:00 1995-04
## 4 kermit     34030  642771  4.80   1995-04-12 00:00:00 1995-04
## 5 kermit    327021  724757  4.98   1995-04-12 00:00:00 1995-04
## 6 kermit     38016  561762  9.75   1995-04-05 00:00:00 1995-04
## 7 kermit    277395  404209  11.3   1995-04-05 00:00:00 1995-04
## 8 kermit    576790 14518894 1380.   1995-04-20 00:00:00 1995-04
## 9 kermit     17623  489473  21.2   1995-04-20 00:00:00 1995-04
## 10 kermit   198041  355963  15.3   1995-04-20 00:00:00 1995-04
## # ... with 88 more rows
```

```
# Rows NOT from kermit, and with size greater than 200000 bytes are kept.
downloads3 %>% filter(machineName != "kermit" & size > 200000)
```

```
## # A tibble: 220 x 6
##   machineName userID      size    time date      month
##   <chr>      <dbl>    <dbl>    <dbl> <dtm>      <chr>
## 1 cs18      204764 2691689  0.834 1995-04-26 00:00:00 1995-04
## 2 cs18      397405  215045  1.10   1994-12-15 00:00:00 1994-12
## 3 cs18      809091  226586  3.92   1994-12-15 00:00:00 1994-12
## 4 cs18      779032 1080472 156.    1994-12-11 00:00:00 1994-12
## 5 cs18      688294  748705  93.1   1994-12-11 00:00:00 1994-12
## 6 cs18      447740 6360764 863.    1994-12-11 00:00:00 1994-12
## 7 cs18      708452  204918  7.07   1994-12-18 00:00:00 1994-12
## 8 cs18      598668  204918  12.7   1994-12-18 00:00:00 1994-12
## 9 cs18      288167  204918  4.98   1994-12-18 00:00:00 1994-12
## 10 cs18     974956  203714  6.13   1994-12-16 00:00:00 1994-12
## # ... with 210 more rows
```

A helpful function to know which machine names are valid can be:

```
# get unique machineName values in downloads3
distinct(downloads3, machineName)
```

```
## # A tibble: 5 x 1
##   machineName
##   <chr>
## 1 cs18
## 2 piglet
## 3 kermit
```

```
## 4 tweetie
## 5 pluto
```

And if you are looking for multiple values for a given variable:

```
downloads3 %>% filter(machineName %in% c("kermit","pluto"), size > 2000000)
```

```
## # A tibble: 8 x 6
##   machineName userID      size  time date      month
##   <chr>      <dbl>    <dbl> <dbl> <dtm>    <chr>
## 1 kermit      576790 14518894 1380. 1995-04-20 00:00:00 1995-04
## 2 kermit      756949  4418124  439. 1995-04-20 00:00:00 1995-04
## 3 kermit      287308  6935603   88.2 1995-04-24 00:00:00 1995-04
## 4 kermit      928227  9523767  171. 1995-02-08 00:00:00 1995-02
## 5 kermit      128147  2743816  216. 1995-02-23 00:00:00 1995-02
## 6 pluto       867173  4670973  230. 1995-03-14 00:00:00 1995-03
## 7 kermit      456524  2836135  127. 1995-03-31 00:00:00 1995-03
## 8 pluto       337530  8674562 1878. 1995-03-13 00:00:00 1995-03
```

Selecting columns: `select`

Sometimes, datasets have many columns of variables of which only some are relevant for the analysis. Columns can be selected or skipped with the `select` function.

```
# Only include the three mentioned variable names
downloads4 <- downloads3 %>%
  select(machineName, size, time)
downloads4
```

```
## # A tibble: 36,708 x 3
##   machineName size time
##   <chr>      <dbl> <dbl>
## 1 cs18        2464 0.493
## 2 cs18        7745 0.326
## 3 cs18        6727 0.314
## 4 cs18       13049 0.583
## 5 cs18         356 0.259
## 6 cs18       15063 0.336
## 7 cs18        2548 0.285
## 8 cs18        1932 0.286
## 9 cs18        7294 0.397
## 10 cs18       4470 3.41
## # ... with 36,698 more rows
```

Notice that we have made a new dataframe, **downloads4** with only three variables.

Transformations of data

Transformations of existing variables in the data set can be computed and included in the data set with the `mutate` function.

We first compute two new variables, download speed (**speed**) and the logarithm of the download size (**logSize**):

```
downloads4 <- downloads4 %>%
  mutate(speed = size / time, logSize = log10(size))
downloads4
```

```
## # A tibble: 36,708 x 5
##   machineName size time speed logSize
##   <chr>      <dbl> <dbl> <dbl> <dbl>
## 1 cs18      2464 0.493 4998. 3.39
## 2 cs18      7745 0.326 23786. 3.89
## 3 cs18      6727 0.314 21444. 3.83
## 4 cs18     13049 0.583 22400. 4.12
## 5 cs18       356 0.259 1373. 2.55
## 6 cs18     15063 0.336 44897. 4.18
## 7 cs18      2548 0.285 8945. 3.41
## 8 cs18      1932 0.286 6763. 3.29
## 9 cs18      7294 0.397 18368. 3.86
## 10 cs18     4470 3.41 1311. 3.65
## # ... with 36,698 more rows
```

We then make a new categorial variable, **slow**, which is “Yes” is speed < 150 and “No” otherwise

```
downloads4 <- downloads4 %>%
  mutate(slow = ifelse(speed < 150, "Yes", "No"))
downloads4
```

```
## # A tibble: 36,708 x 6
##   machineName size time speed logSize slow
##   <chr>      <dbl> <dbl> <dbl> <dbl> <chr>
## 1 cs18      2464 0.493 4998. 3.39 No
## 2 cs18      7745 0.326 23786. 3.89 No
## 3 cs18      6727 0.314 21444. 3.83 No
## 4 cs18     13049 0.583 22400. 4.12 No
## 5 cs18       356 0.259 1373. 2.55 No
## 6 cs18     15063 0.336 44897. 4.18 No
## 7 cs18      2548 0.285 8945. 3.41 No
## 8 cs18      1932 0.286 6763. 3.29 No
## 9 cs18      7294 0.397 18368. 3.86 No
## 10 cs18     4470 3.41 1311. 3.65 No
## # ... with 36,698 more rows
```

Counting, tabulation of categorical variables: count

The count function is useful for counting data datalines, possibly according to certain criteria or for the different levels of categorical values.

```
# Total number of observations in the current dataset
downloads4 %>% count()
```

```
## # A tibble: 1 x 1
##       n
##   <int>
## 1 36708
```

```
# Number of observations from each machine
downloads4 %>% count(machineName)
```

```
## # A tibble: 5 x 2
##   machineName      n
##   <chr>          <int>
## 1 cs18           3814
## 2 kermit         9094
## 3 piglet        11200
## 4 pluto          5253
## 5 tweetie        7347

# Number of observations which have/have not size larger than 5000
downloads4 %>% count(size>5000)

## # A tibble: 2 x 2
##   `size > 5000`      n
##   <lgl>          <int>
## 1 FALSE         25865
## 2 TRUE          10843
```

Sorting data: arrange

The `arrange` function can be used to sort the data according to one or more columns.

Let's sort the data according to download size (ascending order). The first lines of the sorted data set is printed on-screen, but the dataset `downloads4` has *not* been changed.

```
downloads4 %>% arrange(size)

## # A tibble: 36,708 x 6
##   machineName size time speed logSize slow
##   <chr>      <dbl> <dbl> <dbl> <dbl> <chr>
## 1 cs18         3  3.73 0.804  0.477 Yes
## 2 piglet        3  1.53 1.96   0.477 Yes
## 3 piglet        3  1.53 1.96   0.477 Yes
## 4 tweetie       3  1.11 2.71   0.477 Yes
## 5 kermit        3  1.12 2.69   0.477 Yes
## 6 pluto         3  8.60 0.349  0.477 Yes
## 7 pluto         3  9.87 0.304  0.477 Yes
## 8 pluto         3  3.78 0.793  0.477 Yes
## 9 pluto         3  4.68 0.641  0.477 Yes
## 10 pluto        3  4.93 0.608  0.477 Yes
## # ... with 36,698 more rows
```

Two different examples:

```
# According to download size in descending order
downloads4 %>% arrange(desc(size))
```

```
## # A tibble: 36,708 x 6
##   machineName size time speed logSize slow
##   <chr>      <dbl> <dbl> <dbl> <dbl> <chr>
## 1 kermit    14518894 1380. 10522.  7.16 No
## 2 piglet    14158123 123. 115169.  7.15 No
## 3 kermit     9523767 171. 55562.  6.98 No
## 4 piglet     9384067 80.0 117309.  6.97 No
## 5 pluto     8674562 1878.  4619.  6.94 No
## 6 kermit     6935603 88.2 78655.  6.84 No
```

```
## 7 cs18          6360764 863.    7374.    6.80 No
## 8 piglet        5143062 597.    8611.    6.71 No
## 9 piglet        4812334 215.    22345.   6.68 No
## 10 cs18         4720220 1749.   2700.    6.67 No
## # ... with 36,698 more rows

# After machine name and then according to download size in descending order
downloads4 %>% arrange(machineName, desc(size))

## # A tibble: 36,708 x 6
##   machineName    size    time    speed logSize slow
##   <chr>         <dbl>   <dbl>   <dbl>  <dbl> <chr>
## 1 cs18         6360764 863.    7374.    6.80 No
## 2 cs18         4720220 1749.   2700.    6.67 No
## 3 cs18         4055821 1275.    3180.    6.61 No
## 4 cs18         3047343  20.9   146038.   6.48 No
## 5 cs18         2952381  318.    9289.    6.47 No
## 6 cs18         2743516 1151.    2383.    6.44 No
## 7 cs18         2691689   0.834 3228695.   6.43 No
## 8 cs18         2613025  18.5   140959.   6.42 No
## 9 cs18         2573336 1335.    1928.    6.41 No
## 10 cs18        1931453  186.    10388.    6.29 No
## # ... with 36,698 more rows
```

Grouping: group_by

We can group the dataset by one or more categorical variables with `group_by`. The dataset is not changed as such, but - as we will see - grouping can be useful for computation of summary statistics and graphics.

Here we group after machine name (first) *and* the slow variable (second). The only way we can see it at this point is in the second line in the output (`# Groups:`):

```
# Group according to machine
downloads4 %>% group_by(machineName)

## # A tibble: 36,708 x 6
## # Groups:   machineName [5]
##   machineName    size    time    speed logSize slow
##   <chr>         <dbl> <dbl>   <dbl>  <dbl> <chr>
## 1 cs18         2464 0.493  4998.    3.39 No
## 2 cs18         7745 0.326 23786.    3.89 No
## 3 cs18         6727 0.314 21444.    3.83 No
## 4 cs18        13049 0.583 22400.    4.12 No
## 5 cs18          356 0.259  1373.    2.55 No
## 6 cs18        15063 0.336 44897.    4.18 No
## 7 cs18         2548 0.285  8945.    3.41 No
## 8 cs18         1932 0.286  6763.    3.29 No
## 9 cs18         7294 0.397 18368.    3.86 No
## 10 cs18         4470 3.41   1311.    3.65 No
## # ... with 36,698 more rows

# Group according to machine and slow
downloads4 %>% group_by(machineName, slow)
```

```
## # A tibble: 36,708 x 6
```

```
## # Groups:   machineName, slow [10]
##   machineName size  time  speed logSize slow
##   <chr>      <dbl> <dbl> <dbl>   <dbl> <chr>
## 1 cs18      2464 0.493  4998.    3.39 No
## 2 cs18      7745 0.326 23786.    3.89 No
## 3 cs18      6727 0.314 21444.    3.83 No
## 4 cs18     13049 0.583 22400.    4.12 No
## 5 cs18       356 0.259  1373.    2.55 No
## 6 cs18     15063 0.336 44897.    4.18 No
## 7 cs18      2548 0.285  8945.    3.41 No
## 8 cs18      1932 0.286  6763.    3.29 No
## 9 cs18      7294 0.397 18368.    3.86 No
## 10 cs18     4470 3.41  1311.    3.65 No
## # ... with 36,698 more rows
```

Summary statistics, revisited: `summarize`

Recall how we could compute summary statistics for a single variable in a dataset, e.g.

```
mean(downloads4$size)
```

```
## [1] 16638.36
```

```
max(downloads4$size)
```

```
## [1] 14518894
```

With `summarize` we can compute summary statistics for a variable for each level of a grouping variable or for each combination of several grouping variables.

First, a bunch of summaries for the size variable for each machine name, where we give explicit names for the new variables:

```
downloads4 %>%
  group_by(machineName) %>%
  summarise(avg = mean(size),
            med = median(size),
            stdev = sd(size),
            total = sum(size),
            n = n())

## # A tibble: 5 x 6
##   machineName avg   med  stdev   total    n
##   <chr>      <dbl> <dbl>   <dbl>   <dbl> <int>
## 1 cs18      26375. 1990. 208915. 100593281 3814
## 2 kermit    19247. 2466  213985. 175032552 9094
## 3 piglet    14121. 2146. 188340. 158149841 11200
## 4 pluto     13822. 2069  144425.  72605544 5253
## 5 tweetie   14207. 2197   94318. 104379794 7347
```

Second, the same thing but for each combination of machine name and the slow variable:

```
downloads4 %>%
  group_by(machineName, slow) %>%
  summarize(avg = mean(size),
            med = median(size),
            stdev = sd(size),
```



```
total = sum(size),
n = n())
```

```
## # A tibble: 10 x 7
## # Groups:   machineName [5]
##   machineName slow    avg    med    stdev    total    n
##   <chr>      <chr> <dbl> <dbl> <dbl>    <dbl> <int>
## 1 cs18      No    27445. 2092. 213140. 100503042 3662
## 2 cs18      Yes     594. 368.   614.    90239    152
## 3 kermit    No    20030. 2598 218529. 174602282 8717
## 4 kermit    Yes    1141. 541   3049.   430270    377
## 5 piglet    No    14687. 2264 192365. 157650747 10734
## 6 piglet    Yes    1071. 416.   1934.   499094    466
## 7 pluto     No    14564. 2164 148551. 72280790 4963
## 8 pluto     Yes    1120. 413   2108.   324754    290
## 9 tweetie   No    14894. 2373 96694. 104001733 6983
## 10 tweetie  Yes    1039. 471   2603.   378061    364
```

The datasets with summaries can be saved as datasets themselves, for example to be used as the basis for certain graphs.

The pipe operator: %>%

Two or more function calls can be evaluated sequentially using the so-called pipe operator, %>%. Nesting of function calls becomes more readable, and intermediate assignments are avoided.

Let's try it to do a bunch of things in one go, starting with the original dataset:

```
downloads %>%
  filter(size>0) %>% # Subset of data
  group_by(machineName) %>% # Grouping
  summarize(avg = mean(size)) %>% # Compute mean
  arrange(avg) # Sort after mean
```

```
## # A tibble: 5 x 2
##   machineName    avg
##   <chr>      <dbl>
## 1 pluto     13822.
## 2 piglet    14121.
## 3 tweetie   14207.
## 4 kermit    19247.
## 5 cs18     26375.
```

More functions: relocate, rename, pull & join

Below are three useful functions for column manipulation, relocate, rename and pull:

```
# relocate (move one or more columns):
downloads %>% relocate(time, .before = size)
```

```
## # A tibble: 147,035 x 6
##   machineName userID time size date          month
##   <chr>      <dbl> <dbl> <dbl> <dtm>      <chr>
## 1 cs18      146579 0.493 2464 1995-04-24 00:00:00 1995-04
```

```
## 2 cs18          995988 0.326 7745 1995-04-24 00:00:00 1995-04
## 3 cs18          317649 0.314 6727 1995-04-24 00:00:00 1995-04
## 4 cs18          748501 0.583 13049 1995-04-24 00:00:00 1995-04
## 5 cs18          955815 0.259 356 1995-04-24 00:00:00 1995-04
## 6 cs18          444174 0      0 1995-04-24 00:00:00 1995-04
## 7 cs18          446911 0      0 1995-04-24 00:00:00 1995-04
## 8 cs18          449552 0      0 1995-04-24 00:00:00 1995-04
## 9 cs18          456142 0      0 1995-04-24 00:00:00 1995-04
## 10 cs18         458942 0      0 1995-04-24 00:00:00 1995-04
## # ... with 147,025 more rows

# rename (rename one column):
downloads %>% rename(year.month=month)

## # A tibble: 147,035 x 6
##   machineName userID size time date year.month
##   <chr>      <dbl> <dbl> <dbl> <dtm>      <chr>
## 1 cs18      146579 2464 0.493 1995-04-24 00:00:00 1995-04
## 2 cs18      995988 7745 0.326 1995-04-24 00:00:00 1995-04
## 3 cs18      317649 6727 0.314 1995-04-24 00:00:00 1995-04
## 4 cs18      748501 13049 0.583 1995-04-24 00:00:00 1995-04
## 5 cs18      955815 356 0.259 1995-04-24 00:00:00 1995-04
## 6 cs18      444174 0 0 1995-04-24 00:00:00 1995-04
## 7 cs18      446911 0 0 1995-04-24 00:00:00 1995-04
## 8 cs18      449552 0 0 1995-04-24 00:00:00 1995-04
## 9 cs18      456142 0 0 1995-04-24 00:00:00 1995-04
## 10 cs18     458942 0 0 1995-04-24 00:00:00 1995-04
## # ... with 147,025 more rows

# pull out one column, equivalent to using $:
downloads %>% pull(machineName) %>% head()

## [1] "cs18" "cs18" "cs18" "cs18" "cs18" "cs18"
```

Below is an example of how to use the family of `_join` function included in tidyverse. They are useful for combining two (or more) datasets, even if the sets only contain partial/subset of information.

```
# Join tibbles with subsets of information together:

# machineName and power rank
downloads5 <- tibble(machineName=c("cs18","piglet","tweetie","kermit", "pluto"),
                     powerRank=c(2,4,1,3,5))

# machineName and location of machine
downloads6 <- tibble(machineName=c("cs18","tweetie","kermit","skeeter"),
                     location=c("China", "USA", "Germany", "Japan"))

# all machineNames from tibble on the left are kept
left_join(downloads5, downloads6)

## # A tibble: 5 x 3
##   machineName powerRank location
##   <chr>      <dbl> <chr>
## 1 cs18          2 China
## 2 piglet        4 <NA>
```

```
## 3 tweetie          1 USA
## 4 kermit           3 Germany
## 5 pluto            5 <NA>

# all machineNames from tibble on the right are kept
right_join(downloads5, downloads6)

## # A tibble: 4 x 3
##   machineName powerRank location
##   <chr>         <dbl> <chr>
## 1 cs18          2 China
## 2 tweetie       1 USA
## 3 kermit        3 Germany
## 4 skeeter       NA Japan

# only machineNames in both left and right tibble are kept
inner_join(downloads5, downloads6)

## # A tibble: 3 x 3
##   machineName powerRank location
##   <chr>         <dbl> <chr>
## 1 cs18          2 China
## 2 tweetie       1 USA
## 3 kermit        3 Germany

# all machineNames, from both tibbles are kept
full_join(downloads5, downloads6)

## # A tibble: 6 x 3
##   machineName powerRank location
##   <chr>         <dbl> <chr>
## 1 cs18          2 China
## 2 piglet        4 <NA>
## 3 tweetie       1 USA
## 4 kermit        3 Germany
## 5 pluto         5 <NA>
## 6 skeeter       NA Japan
```