

Leads API - Documentation

This document provides a comprehensive guide to the **Leads API**. It details all the available endpoints for managing leads, their required parameters, expected request payloads, and API responses.

Base URL

All endpoints are relative to the base URL of your application. Assuming you are running this locally, the base URL is: `http://localhost:8080`

1. Initiate Lead

Initiates a new lead, setting its initial status to `INITIATED`.

- **URL:** `/leads/v1/initiate`
- **Method:** `POST`
- **Content-Type:** `application/json`

Request Body

```
{
  "leadId": "1778842379.6",
  "location": "Unknown",
  "phoneNumber": "+919108778105",
  "callStatus": "MISSED",
  "leadSource": "Asterisk-MissedCall-Campaign",
  "calledNumber": "h",
  "callerNumber": "+919108778105",
  "callStartTime": "2026-05-15T10:53:09Z",
  "callDurationSeconds": 0
}
```

Response

```
{
  "message": "successfully created",
  "params": {
    "resmsgid": null,
    "msgid": null,
    "err": null,
    "status": null,
    "errmsg": null
  },
  "responseCode": "OK",
  "result": {
```

```
    "status": "INITIATED",
    "location": "Unknown",
    "phoneNumber": "+919108778105",
    "callStatus": "MISSED",
    "leadSource": "Asterisk-MissedCall-Campaign",
    "calledNumber": "h",
    "callerNumber": "+919108778105",
    "callStartTime": "2026-05-15T10:53:09Z",
    "callDurationSeconds": 0,
    "leadsId": "leads-78712975710321793652107454978476"
  }
}
```

2. Qualify Lead

Updates an existing lead's status to indicate whether they are qualified or disqualified.

[!IMPORTANT] The previous status of the lead **must** be **INITIATED**. The new **status** can only be **QUALIFIED** or **DISQUALIFIED**.

- **URL:** `/leads/v1/qualify`
- **Method:** `PUT`
- **Content-Type:** `application/json`

Request Body

```
{
  "leads_id": "leads-78712975710321793652107454978476",
  "status": "QUALIFIED"
}
```

Response

```
{
  "message": "successfully updated",
  "params": {
    "resmsgid": null,
    "msgid": null,
    "err": null,
    "status": null,
    "errmsg": null
  },
  "responseCode": "OK",
  "result": {
    "status": "QUALIFIED",
    "location": "Unknown",
    "phoneNumber": "+919108778105",
  }
}
```

```
    "callStatus": "MISSED",
    "leadSource": "Asterisk-MissedCall-Campaign",
    "calledNumber": "h",
    "callerNumber": "+919108778105",
    "callStartTime": "2026-05-15T10:53:09Z",
    "callDurationSeconds": 0,
    "leadsId": "leads-78712975710321793652107454978476"
  }
}
```

3. Process Lead

Updates an existing lead's status to indicate that it has been processed.

[!IMPORTANT] The previous status of the lead **must** be **QUALIFIED**. The new **status** can only be **PROCESSED** or **REJECTED**.

- **URL:** `/leads/v1/process`
- **Method:** `PUT`
- **Content-Type:** `application/json`

Request Body

```
{
  "leads_id": "leads-78712975710321793652107454978476",
  "status": "PROCESSED"
}
```

Response

```
{
  "message": "successfully updated",
  "params": {
    "resmsgid": null,
    "msgid": null,
    "err": null,
    "status": null,
    "errmsg": null
  },
  "responseCode": "OK",
  "result": {
    "status": "PROCESSED",
    "location": "Unknown",
    "phoneNumber": "+919108778105",
    "callStatus": "MISSED",
    "leadSource": "Asterisk-MissedCall-Campaign",
    "calledNumber": "h",

```

```
    "callerNumber": "+919108778105",
    "callStartTime": "2026-05-15T10:53:09Z",
    "callDurationSeconds": 0,
    "leadsId": "leads-78712975710321793652107454978476"
  }
}
```

4. Read Lead

Retrieves the details of a specific lead using its unique ID.

- **URL:** `/leads/v1/read/{id}`
- **Method:** `GET`

Path Parameters

- `id` (String): The unique identifier of the lead (e.g., `leads-78712975710321793652107454978476`).

Example Request

`GET http://localhost:8080/leads/v1/read/leads-78712975710321793652107454978476`

Response

```
{
  "message": "successfully read",
  "params": {
    "resmsgid": null,
    "msgid": null,
    "err": null,
    "status": null,
    "errmsg": null
  },
  "responseCode": null,
  "result": {
    "result": {
      "status": "INITIATED",
      "location": "Unknown",
      "phoneNumber": "+919108778105",
      "callStatus": "MISSED",
      "leadSource": "Asterisk-MissedCall-Campaign",
      "calledNumber": "h",
      "callerNumber": "+919108778105",
      "callStartTime": "2026-05-15T10:53:09Z",
      "callDurationSeconds": 0
    }
  }
}
```

5. Search Leads

Searches for leads based on specific criteria (like pagination, filtering, etc.).

- **URL:** `/leads/v1/search`
- **Method:** `POST`
- **Content-Type:** `application/json`

Request Body

A JSON object containing the `SearchCriteria`.

Example 1: Basic Search to retrieve leads

```
{
  "pageNumber": 0,
  "pageSize": 10
}
```

Example 2: Search with Date Range Filter

```
{
  "pageNumber": 0,
  "pageSize": 10,
  "query": {
    "range": {
      "callStartTime": {
        "gte": "2026-05-15T00:00:00Z",
        "lte": "2026-05-15T23:59:59Z"
      }
    }
  }
}
```

Example 3: Search with Facets

```
{
  "pageNumber": 0,
  "pageSize": 0,
  "facets": [
    "status"
  ]
}
```