

Package ‘MESHr’

December 10, 2018

Type Package

Title pre- and post processing for MESH

Version 0.1.8

Date 2018-12-10

Author Al Pietroniro, Environment Canada

Maintainer Kevin Shook <kevin.shook@usask.ca>

Description This package contains functions for pre- and post- processing data for the MESH model.

Depends R (>= 3.1)

Imports

grid, ggplot2, stringr, knitr, reshape2, hydroGOF, raster, rts, readr, stats, hydroTSM, sp, methods

License GPL-3

LazyData true

URL <https://github.com/CentreForHydrology/MESHr>

RoxygenNote 6.1.0

NeedsCompilation no

VignetteBuilder knitr

R topics documented:

MESHr-package	2
basinLapseRates	3
basinPrecipEvapRunoffPlot	4
basinRunoffPlot	4
basinSnowPlot	5
basinSnowRainPondedPlot	6
basinSoilWaterIcePlot	7
basinSoilWaterPlot	8
basinStoragePlot	9
basinStorageVariablesPlot	9
basinWaterBalancePlot	11
distribPrecip	12

doubleHydrograph	13
findRecord	15
gridPrecip	16
gridTemp	17
hydroStats	19
MESH_streamflows	21
parseNums	21
parseText	22
PBIAS	23
plotDataCompleteness	23
read_AEP_csv	24
read_MESH_OutputTimeseries_csv	26
read_r2c_raster	27
read_r2c_shed	28
read_tb0	29
simpleHydrograph	30
var_present	32
win.eol	33
write_r2c_shed	33
write_tb0	34
Index	37

MESHr-package	<i>Functions for MESH pre- and post- processing</i>
---------------	---

Description

The intent of this package is to contain functions do do common tasks for MESH modelling, such as reading output, plotting, and assessing model quality. The first functions will use .csv files - support for netCDF will be added.

References

To cite **MESHr** in publications, use the command `citation("MESHr")` to get the current version of the citation.

basinLapseRates	<i>Calculates basin-wide lapse rates</i>
-----------------	--

Description

This function calculates basin-wide historical lapse rates, by month and hour of day. The intent is to produce a file of rates that can be used for interpolation, when there are insufficient values to determine lapse rates from measured air temperatures. The lapse rates are determined as the slope of a linear regression of delta air temperature vs delta elevation for each time step. The delta air temperature is the difference in air temperature between each station's value and that of the lowest elevation station. The delta elevation is the difference between each station's elevation and that of the lowest-elevation station. Therefore the lapse rate is in K/m.

Usage

```
basinLapseRates(temps = NULL, elevs = NULL)
```

Arguments

temps	Required. A time series data frame of air temperatures in Celsius or K, as returned by <code>read_tb0</code> . The first column must be <code>datetime</code> , which is a POSIXct value. Each station's elevation will be in a separate column.
elevs	Required. A data frame of station elevations. Note that the first column must contain the station names (which must be the same as in the air temperatures), and the second column must contain the elevation (in m).

Value

If successful, returns a data frame with 24 rows (one for each hour), and 12 columns (one for each month), containing the lapse rates.

Author(s)

Kevin Shook

See Also

[gridTemp read_tb0](#)

Examples

```
## Not run:  
lapse_rates <- basinLapseRates(temperatures, elevations)  
## End(Not run)
```

```
basinPrecipEvapRunoffPlot
```

Plots basin precipitation evaporation and runoff

Description

Plots basin precipitation evaporation and runoff

Usage

```
basinPrecipEvapRunoffPlot(basinWaterBalance)
```

Arguments

basinWaterBalance

Required. Data frame to be plotted. As read in by `read_MESH_OutputTimeseries_csv`.

Value

Returns a **ggplot2** line plot of the variable values (mm).

Author(s)

Kevin Shook

See Also

[read_MESH_OutputTimeseries_csv](#) [basinStoragePlot](#) [basinSoilWaterIcePlot](#)

Examples

```
## Not run:
waterBalance <- read_MESH_OutputTimeseries_csv("Basin_average_water_balance.csv")
p <- basinPrecipEvapRunoffPlot(waterBalance)
## End(Not run)
```

```
basinRunoffPlot
```

Plots basin runoff components

Description

Plots basin runoff components

Usage

```
basinRunoffPlot(basinWaterBalance, cumul = FALSE)
```

Arguments

`basinWaterBalance` Required. Data frame to be plotted. As read in by `read_MESH_OutputTimeseries_csv`.

`cumul` Optional. If FALSE, then interval values are plotted. If TRUE (the default) then cumulative values are plotted. Note that the cumulative values are determined by summing the interval values *not* by plotting the MESH cumulative variables.

Value

Returns a **ggplot2** line plot of the variable values (mm).

Author(s)

Kevin Shook

See Also

[read_MESH_OutputTimeseries_csv](#) [basinStoragePlot](#) [basinSoilWaterIcePlot](#)

Examples

```
## Not run:
waterBalance <- read_MESH_OutputTimeseries_csv("Basin_average_water_balance.csv")
p <- basinRunoffPlot(waterBalance)
## End(Not run)
```

basinSnowPlot	<i>Plots basin snow water equivalent</i>
---------------	--

Description

Plots basin snow water equivalent

Usage

```
basinSnowPlot(basinWaterBalance)
```

Arguments

`basinWaterBalance` Required. Data frame to be plotted. As read in by `read_MESH_OutputTimeseries_csv`.

Value

Returns a **ggplot2** stacked line plot of the basin SWE (mm).

Author(s)

Kevin Shook

See Also

[read_MESH_OutputTimeseries_csv](#) [basinStoragePlot](#)

Examples

```
## Not run:  
waterBalance <- read_MESH_OutputTimeseries_csv("Basin_average_water_balance.csv")  
p <- basinSnowPlot(waterBalance)  
## End(Not run)
```

basinSnowRainPondedPlot

Plots basin snow and rain in the canopy and ponded water

Description

Plots basin snow and rain in the canopy and ponded water

Usage

```
basinSnowRainPondedPlot(basinWaterBalance)
```

Arguments

basinWaterBalance

Required. Data frame to be plotted. As read in by `read_MESH_OutputTimeseries_csv`.

Value

Returns a **ggplot2** line plot of the basin variables (mm).

Author(s)

Kevin Shook

See Also

[read_MESH_OutputTimeseries_csv](#) [basinStoragePlot](#)

Examples

```
## Not run:  
waterBalance <- read_MESH_OutputTimeseries_csv("Basin_average_water_balance.csv")  
p <- basinSnowRainPondedPlot(waterBalance)  
## End(Not run)
```

basinSoilWaterIcePlot *Plots basin soil water and ice*

Description

Plots basin soil water and ice

Usage

```
basinSoilWaterIcePlot(basinWaterBalance, layers = c(1, 2))
```

Arguments

basinWaterBalance Required. Data frame to be plotted. As read in by `read_MESH_OutputTimeseries_csv`.

layers Optional. A vector of the layers to be plotted. By default layers 1 and 2 are used.

Value

Returns a **ggplot2** line plot of the variable values (mm) faceted by Layer number. The name of the variable is layer, so you can change change the facetting.

Author(s)

Kevin Shook

See Also

[read_MESH_OutputTimeseries_csv](#) [basinStoragePlot](#)

Examples

```
## Not run:  
waterBalance <- read_MESH_OutputTimeseries_csv("Basin_average_water_balance.csv")  
p <- basinSoilWaterIcePlot(waterBalance)  
## End(Not run)
```

basinSoilWaterPlot	<i>Plots basin soil liquid water</i>
--------------------	--------------------------------------

Description

Plots basin soil liquid water

Usage

```
basinSoilWaterPlot(basinWaterBalance, layers = c(1, 2, 3, 4, 5, 6))
```

Arguments

basinWaterBalance	Required. Data frame to be plotted. As read in by <code>read_MESH_OutputTimeseries_csv</code> .
layers	Optional. A vector of the layers to be plotted. By default layers 1 though 6 are used.

Value

Returns a **ggplot2** line plot of the variable values (mm).

Author(s)

Kevin Shook

See Also

[read_MESH_OutputTimeseries_csv](#) [basinStoragePlot](#) [basinSoilWaterIcePlot](#)

Examples

```
## Not run:  
waterBalance <- read_MESH_OutputTimeseries_csv("Basin_average_water_balance.csv")  
p <- basinSoilWaterPlot(waterBalance)  
## End(Not run)
```

basinStoragePlot	<i>Plots total basin storage</i>
------------------	----------------------------------

Description

Plots total basin storage

Usage

```
basinStoragePlot(basinWaterBalance)
```

Arguments

basinWaterBalance
Required. Data frame to be plotted. As read in by read_MESH_OutputTimeseries_csv.

Value

Returns a **ggplot2** line plot of the value of STG (mm).

Author(s)

Kevin Shook

See Also

[read_MESH_OutputTimeseries_csv](#) [basinStorageVariablesPlot](#) [basinSoilWaterIcePlot](#)

Examples

```
## Not run:  
waterBalance <- read_MESH_OutputTimeseries_csv("Basin_average_water_balance.csv")  
p <- basinStoragePlot(waterBalance)  
## End(Not run)
```

basinStorageVariablesPlot	<i>Plots basin water balance storage components</i>
---------------------------	---

Description

Creates a **ggplot2** stacked area plot of specified water balance storage components. The variables plotted may include:

variable definition

SNCAN Snow component of precipitation intercepted by the canopy

RCAN Rain component of precipitation intercepted by the canopy mm or kg m⁻² of water AVG

SNO Snow water equivalent (SWE) of the snow mass

ZPND Depth of water ponded at the surface

LQWS Water equivalent of the volumetric liquid water content of the soil

FZWS Water equivalent of the volumetric frozen water content of the soil

ALWS Water equivalent of the volumetric liquid and frozen water contents of the soil, sum of LQWS and FZWS

Usage

```
basinStorageVariablesPlot(basinWaterBalance, varNames = "",
  layers = c(1, 2, 3, 4, 5, 6))
```

Arguments

basinWaterBalance	Required. Data frame to be plotted. As read in by read_MESH_OutputTimeseries_csv.
varNames	Optional. A vector of the names of the variables to be plotted. If not specified, all of the variables listed above will be plotted.
layers	Optional. A vector of the layers to be plotted. By default layers 1 through 6 are used.

Value

Returns a **ggplot2** stacked area time plot of the variable values (mm).

Author(s)

Kevin Shook

See Also

[read_MESH_OutputTimeseries_csv](#)

Examples

```
## Not run:
waterBalance <- read_MESH_OutputTimeseries_csv("Basin_average_water_balance.csv")
p <- basinStorageVariablesPlot(waterBalance)
# the plot can have a restricted date range
startDate <- as.Date("2005-10-01", format = "%Y-%m-%d")
```

```

endDate <- as.Date("2006-09-30", format = "%Y-%m-%d")
library(ggplot2)
p <- p + xlim(startDate, endDate)
p
# you can also change the colours used, either by
# using a defined scale, or by manually specifying them
# This example uses the colours in the package viridis
# which scales from dark to light by reversing the direction
library(viridis)
p <- p + scale_fill_viridis(discrete = TRUE, direction = -1)
p

## End(Not run)

```

basinWaterBalancePlot *Plots basin precipitation cumulative water balance.*

Description

As with the basinRunoffPlot, the cumulative values of precipitation, evaporation and runoff (and optionally, delta storage) are computed by the function, rather than by using the MESH variables. This allows the plot to be used on a sub-set of the basin output data.

Usage

```
basinWaterBalancePlot(basinWaterBalance, accumulate_delta_storage = TRUE)
```

Arguments

basinWaterBalance
 Required. Data frame to be plotted. As read in by read_MESH_OutputTimeseries_csv.
 Note that because the value of DTSG (delta storage) can be negative, you need to set a threshold value much smaller than zero when you read in the values.

accumulate_delta_storage
 Optional. If TRUE (the default), the delta storage is accumulated from the beginning of the data set. If FALSE, the delta storage values in the file are *not* accumulated as they are assumed to be cumulative values.

Value

Returns a **ggplot2** line plot of the variable values (mm).

Author(s)

Kevin Shook

See Also

[read_MESH_OutputTimeseries_csv](#) [basinStoragePlot](#) [basinSoilWaterIcePlot](#)

Examples

```
## Not run:
waterBalance <- read_MESH_OutputTimeseries_csv("Basin_average_water_balance.csv",
missingValueThreshold = -1e6)
p <- basinWaterBalancePlot(waterBalance)
## End(Not run)
```

distribPrecip	<i>Distributes precipitation in time</i>
---------------	--

Description

MESH requires all forcing data to have the same time interval, which prevents the use of precipitation data reported at lower frequencies than the model time step. This function distributes low-frequency precipitation (e.g. daily) according to a set of high frequency precipitation (e.g. hourly). The high-frequency values are summed to have the same time intervals as the low-frequency data. The ratios of low/high frequency precipitations are determined for each time step, and these ratios are multiplied by the high-frequency data. Where the high-frequency total precipitation is zero, the low-frequency data is spread evenly over the high-frequency interval.

Usage

```
distribPrecip(LFprecip = NULL, HFprecip = NULL,
  zero_missing_HF = TRUE, period_threshold = 48)
```

Arguments

LFprecip	Required. A data frame of low temporal frequency (e.g. daily) precipitation. The first column must be a POSIXct date/time called <code>datetime</code> . The second column must be the precipitation.
HFprecip	Required. A data frame of high temporal frequency (e.g. hourly) precipitation. The first column must be a POSIXct date/time called <code>datetime</code> . The second column must be the precipitation.
zero_missing_HF	Optional. If TRUE (the default) missing high-frequency precipitation values are replaced with zeros.
period_threshold	Length of maximum infilled period in hours. Sequences of missing low-frequency values exceeding this length will be set to <code>NA_real_</code> , and the next low-frequency value will be assigned to the next high frequency interval. This is usually required when a gauge is not reported for a seasonal period.

Value

Returns a data frame of the adjusted high-frequency precipitation, with the variables `datetime` and `distributedP`. Note that the last date/time in the returned data corresponds to the final value in the low-frequency data.

Author(s)

Kevin Shook

See Also[read_tb0](#)**Examples**

```
## Not run: distributed <- distribPrecip(myPrecip[, c(1, 5)],
adjacentP)

## End(Not run)
```

doubleHydrograph

*Creates hydrograph from 2 MESH output files***Description**

Creates a **ggplot** hydrograph from MESH output. This function *only* uses values from two MESH data frames (as read in using readOutputTimeseriesCSV). It is assumed that the observed data are the same in both cases - only the simulations differ. Because this function returns a **ggplot** object, you can change its format in any way you like. The plots produced may be faceted using the commands facet_wrap or facet_grid.

Usage

```
doubleHydrograph(MESHvals1, stationNames1 = "", MESHname1 = "MESH1",
  MESHvals2, stationNames2 = "", MESHname2 = "MESH2",
  byStation = TRUE, byYear = FALSE, meas = TRUE, sim = TRUE,
  calStart = "", calEnd = "", alpha = 1)
```

Arguments

MESHvals1	Required. A data frame of output from a MESH run, as produced by read_MESH_OutputTimeseries_csv
stationNames1	Optional. A vector of strings holding station names. If specified, the station names will be used in the plots. Otherwise the MESH station numbers will be used.
MESHname1	Optional. A string giving the name of the first MESH output. Default is "MESH1".
MESHvals2	Required. A data frame of output from a MESH run, as produced by read_MESH_OutputTimeseries_csv
stationNames2	Optional. A vector of strings holding station names.
MESHname2	Optional. A string giving the name of the second MESH output. Default is "MESH2".
byStation	Optional. If TRUE (the default) then the plots will be coloured according to the station names. You may want to set this to FALSE if you are facetting by station name.

byYear	Optional. If TRUE then the plots will be able to be faceted by year. Note that this means that the dates are all plotted using the year 2000, so you will see strange results if you set this to TRUE and don't facet by year. Default is FALSE
meas	Optional. Should the measured values be plotted? Default is TRUE. If FALSE, they will be omitted.
sim	Optional. Should the simulated values be plotted? Default is TRUE. If FALSE, they will be omitted.
calStart	Optional. The start date of the calibration period. Must be a string in the format 'yyyy-mm-dd'. If specified, values on and after this date will be designated as the Calibration period. The remaining values will be designated as the Validation period.
calEnd	Optional. The start date of the calibration period. Must be a string in the format 'yyyy-mm-dd'. If specified, values on and after this date will be designated as the Calibration period. The remaining values will be designated as the Validation period.
alpha	Optional. Sets the alpha channel (transparency) of the plots. The default value is 1, i.e. opaque. Setting alpha to less than 1 makes the plots transparent, which can be useful to see overlapping hydrographs.

Value

If successful, returns a **ggplot2** object. If unsuccessful, returns FALSE. The object can be faceted by the name of the station (the variable is called station). If the option `byYear = TRUE`, then the object can be faceted by the variable YEAR.

Note

Specifying the calibration start and/or end dates will allow the resulting plot to be faceted by the variable period.

Author(s)

Kevin Shook

See Also

[simpleHydrograph read_MESH_OutputTimeseries_csv hydroStats](#)

Examples

```
## Not run:
p <- doubleHydrograph(MESHvals1 = capa, MESHname1 = "CaPa precip",
  MESHvals2 = kevin, MESHname2 = "Station precip", byStation = TRUE,
  alpha = 0.6)
p
# facet by station
p2 <- p + facet_wrap(~station, scales = "free_y", strip.position = "right")
p2
# add scale colour
```

```
colours <- c("red", "blue", "black")
p3 <- p2 + + scale_colour_manual(values = colours)
# restrict plot to a range of dates
p3
startDate <- as.Date("2005-04-01")
endDate <- as.Date("2005-10-01")
p4 <- p3 + scale_x_date(limits = c(startDate, endDate))
p4

## End(Not run)
```

findRecord	<i>Finds record in r2c data specified by string</i>
------------	---

Description

Finds record in r2c data specified by string

Usage

```
findRecord(recordLines, string, ignore.case = TRUE)
```

Arguments

recordLines	Required. Vector of lines from r2c file.
string	Required. Record name to search for.
ignore.case	Optional. If TRUE (the default), then case is ignored.

Value

Returns trimmed record.

Author(s)

Kevin Shook

gridPrecip

*Grids station precipitation***Description**

Grids station interval precipitation values, so that they can be used as MESH inputs. The gridding method is performed by the **hydroTSM** function `hydrokrige`, using the IDW (inverse distance weighting) algorithm.

Usage

```
gridPrecip(precip = NULL, shed_raster = NULL, IDW_file = NULL,
           quiet = TRUE, progress_bar = TRUE)
```

Arguments

<code>precip</code>	Required. A list containing 3 elements: 1. the header meta data, 2. the column meta data, and 3. the precipitation values (in mm). These values are returned automatically by the MESHr command <code>read_tb0</code> . Note that the precipitation values are in mm.
<code>shed_raster</code>	Required. A RasterBrick object describing the MESH basin. This can be created using the MESHr command <code>read_r2c_shed</code> with the parameter <code>as_rasters = TRUE</code> .
<code>IDW_file</code>	Required. Name of the output file which holds gridded precipitation for all time steps.
<code>quiet</code>	Optional. If TRUE (the default), messages are suppressed. If FALSE, the time interval and messages from each gridding are listed.
<code>progress_bar</code>	Optional. If TRUE (the default), a progress bar is displayed showing the completed fraction of the <code>precip</code> .

Value

If unsuccessful, returns FALSE. If successful, returns TRUE and the gridded precipitation values are written to the `IDW_file`. Note that each interval's precipitation is written as it is gridded. This saves on memory, and will save at least some of the values in case there is a crash, but is slower. The gridded precipitation is in mm/s.

Author(s)

Kevin Shook

See Also

[gridTemp](#) [read_r2c_shed](#) [read_tb0](#)

Examples

```
## Not run:
hourly_precip_file <- "Red_Deer_all_hourly_precip_new.tb0"
precip <- read_tb0(hourly_precip_file, values_only = FALSE, timezone = "Etc/GMT+7", NValue = -0.1)
shedfile <- "RedDeer_MESH_drainage_database.r2c"
shed_raster <- read_r2c_shed(shedfile, as_rasters = TRUE, values_only = TRUE)
IDW_file <- "RedDeerPrecip.idw"
gridPrecip(precip, shed_raster, IDW_file)

## End(Not run)
```

gridTemp

Grids station temperatures

Description

Grids station interval temperature values, so that they can be used as MESH inputs. The gridding method is performed by the **hydroTSM** function `hydrokrige`, using the IDW (inverse distance weighting) algorithm. The gridding uses a basin-scale lapse rate, which is determined by fitting a linear model to the difference between each site's temperature and that of the lowest site, and the difference in elevation relative to the lowest site. The procedure is the same as used in the function `basinLapseRates`. In effect, all site temperatures are converted to have the same elevation before gridding. After gridding, each temperature is raised to its specified elevation using the same lapse rate. Where there are only 1 or 2 stations with available air temperatures, the hourly x monthly lapse rates returned by `basinLapseRates` are used.

Usage

```
gridTemp(temp = NULL, shed_raster = NULL, site_elev = NULL,
         lapse_rates = NULL, IDW_file = NULL, tmin = 223.15,
         tmax = 313.15, quiet = TRUE, progress_bar = TRUE)
```

Arguments

temp	Required. A list containing 3 elements: 1. the header meta data, 2. the column meta data, and 3. the air temperature values (in C). These values are returned automatically by the MESHr command <code>read_tb0</code> .
shed_raster	Required. A RasterBrick object describing the MESH basin. This can be created using the MESHr command <code>read_r2c_shed</code> with the parameter <code>as_rasters = TRUE</code> .
site_elev	Required. A data frame of station elevations. Note that the first column must contain the station names (which must be the same as in the air temperatures), and the second column must contain the elevation (in m).
lapse_rates	Optional. If there are 2 or fewer air temperatures in any interval, then the lapse rate cannot be calculated. In this case, if the historical <code>lapse_rates</code> are specified, then they will be used. If they are not specified, then this function will terminate with an error message. So, if you are confident that your dataset always has at least 3 stations with non- missing values of air temperatures, then

you can omit this parameter. Note that the historical lapse rates must be a data frame of 12 columns (monthly) and 24 rows (hourly) values as returned by the function `basinLapseRates`.

<code>IDW_file</code>	Required. Output file which holds gridded air temperatures for all time steps.
<code>tmin</code>	Required. The minimum permitted air temperature of the gridded (and lapsed) air temperatures. All values exceeding <code>tmin</code> will be set to this value. The default is 223.15 K, or -50 C.
<code>tmax</code>	Required. The maximum permitted air temperature of the gridded (and lapsed) air temperatures. All values exceeding <code>tmax</code> will be set to this value. The default is 313.15 K, or 40 C.
<code>quiet</code>	Optional. If TRUE (the default) messages are suppressed. If FALSE, the time interval and messages from each gridding are listed.
<code>progress_bar</code>	Optional. If TRUE (the default), a progress bar is displayed showing the completed fraction of the temp.

Value

If unsuccessful, returns FALSE. If successful, returns TRUE and the gridded temperatures values are written to the `IDW_file`. Note that each interval's temperatures are written as they are gridded. This saves on memory, but can be quite slow. Note that the air temperatures in the file are in K.

Author(s)

Kevin Shook

See Also

[gridPrecip](#) [basinLapseRates](#) [read_r2c_shed](#) [read_tb0](#)

Examples

```
## Not run:
hourly_temp_file <- "Red_Deer_all_hourly_temp_new.tb0"
temp <- read_tb0(hourly_temp_file, values_only = FALSE, timezone = "Etc/GMT+7", NValue = -0.1)
shedfile <- "RedDeer_MESH_drainage_database.r2c"
shed_raster <- read_r2c_shed(shedfile, as_rasters = TRUE, values_only = TRUE)
elev_file <- "site_elevations.csv"
site_elev <- read.csv(elev_file, header = TRUE, stringsAsFactors = FALSE)
lapse_rates_file <- "RedDeerLapseRates.csv"
lapse_rates <- read.csv(lapse_rates_file, header = TRUE, stringsAsFactors = FALSE, row.names = 1)
IDW_file <- "RedDeerTemp.idw"
gridPrecip(temp = temp, shed_raster = shed_raster, site_elev = site_elev,
lapse_rates = lapse_rates)
## End(Not run)
```

hydroStats	<i>Calculates Goodness of Fit statistics for MESH output</i>
------------	--

Description

This function is a wrapper for the function `gof` in the package **hydroGOF**. It computes several Goodness of Fit statistics for each station. The output of this function may be used on its own, or to annotate a hydrograph.

Usage

```
hydroStats(MESHvals, stationNames = "", calStart = "", calEnd = "",
  removeMissing = TRUE, doSpearman = FALSE, doPBFDC = FALSE,
  digits = 2, j = 1, norm = "sd", s = c(1, 1, 1),
  method = c("2009", "2012"), lQ.thr = 0.7, hQ.thr = 0.2)
```

Arguments

MESHvals	Required. A data frame of output from a MESH run, as produced by <code>readOutputTimeseriesCSV</code> .
stationNames	Optional. A vector of strings holding station names. If specified, the station names will be used in the returned data frame, otherwise the MESH station numbers will be used.
calStart	Optional. The start date of the calibration period. Must be a string in the format 'yyyy-mm-dd'. If specified, values on and after this date will be designated as the Calibration period. The remaining values will be designated as the Validation period.
calEnd	Optional. The start date of the calibration period. Must be a string in the format 'yyyy-mm-dd'. If specified, values on and after this date will be designated as the Calibration period. The remaining values will be designated as the Validation period.
removeMissing	Required. Should rows with missing values be removed before statistics are calculted? Default is TRUE
doSpearman	Optional. Should Spearman correlation be computed? Default is FALSE.
doPBFDC	Optional. Should percent bias of slope of the midsegment of the FDC be computed? Default is FALSE.
digits	Optional. The number of decimal places for rounding goodness of fit statistics. If 0 the default, then it is not set. Default value is 2. Note that percentages like NRMSE and PBIAS will only use a maximum of one decimal place.
j	Optional. Argument passed to the <code>mNSE</code> function in hydroGOF .
norm	Optional. Argument passed to the <code>nrmse</code> function in hydroGOF .
s	Optional. Argument passed to the <code>KGE</code> function in hydroGOF .
method	Optional. Argument passed to the <code>KGE</code> function in hydroGOF .
lQ.thr	Optional. Argument passed to the <code>pbiassfdc</code> function in hydroGOF .
hQ.thr	Optional. Argument passed to the <code>pbiassfdc</code> function in hydroGOF .

Value

Returns a data frame with the following variables: #'

station station name or number

me Mean Error

mae Mean Absolute Error

mse Mean Squared Error

rmse Root Mean Square Error

normse Normalized Root Mean Square Error ($-100\% \leq \text{nrms} \leq 100\%$)

PBIAS Percent Bias

pbiasfdc PBIAS in the slope of the midsegment of the Flow Duration Curve, if selected

RSR Ratio of RMSE to the Standard Deviation of the Observations, $\text{RSR} = \text{rms} / \text{sd}(\text{obs})$. ($0 \leq \text{RSR} \leq +\text{Inf}$)

rSD Ratio of Standard Deviations, $\text{rSD} = \text{sd}(\text{sim}) / \text{sd}(\text{obs})$

NSE Nash-Sutcliffe Efficiency ($-\text{Inf} \leq \text{NSE} \leq 1$)

mNSE Modified Nash-Sutcliffe Efficiency

rNSE Relative Nash-Sutcliffe Efficiency

d Index of Agreement ($0 \leq d \leq 1$)

d1 Modified Index of Agreement

rd Relative Index of Agreement

cp Persistence Index ($0 \leq \text{PI} \leq 1$)

r Pearson Correlation coefficient ($-1 \leq r \leq 1$)

r.Spearman Spearman Correlation coefficient ($-1 \leq \text{r.Spearman} \leq 1$), if selected

R2 Coefficient of Determination ($0 \leq \text{R2} \leq 1$).

Gives the proportion of the variance of one variable that is predictable from the other variable

br2 R2 multiplied by the coefficient of the regression line between sim and obs
($0 \leq \text{br2} \leq 1$)

KGE Kling-Gupta efficiency between sim and obs
($0 \leq \text{KGE} \leq 1$)

VE Volumetric efficiency between sim and obs
($-\text{Inf} \leq \text{VE} \leq 1$)

If the calibration period is specified, then statistics will be computed separately for the Calibration and Validation periods. The period names and dates will be specified in additional columns.

Author(s)

Kevin Shook

See Also

[simpleHydrograph](#) [gof](#)

Examples

```
stats <- hydroStats(MESH_streamflows)
stats$NSE
periodStats <- hydroStats(MESH_streamflows, calEnd = "2010-01-01")
periodStats[,1:7]
```

MESH_streamflows	<i>MESH streamflow data</i>
------------------	-----------------------------

Description

A data frame containing MESH outputs for the Simonette river, as read in using the function `read_MESH_OutputTimeSeries_csv`.

Usage

```
MESH_streamflows
```

Format

A data frame with 4381 rows and 5 variables (including the datetime):

DATE date and time as an R date object

QOMEAS1 measured flows at station 1

QOSIM1 simulated flows at station 1

QOMEAS2 measured flows at station 2

QOSIM2 simulated flows at station 2

Source

This data was obtained by running MESH.

parseNums	<i>Parses a string containing numbers</i>
-----------	---

Description

Parses a string containing numbers

Usage

```
parseNums(numString)
```

Arguments

numString Required. A character string containing numbers separated by any number of spaces.

Value

Returns a numeric vector.

Author(s)

Kevin Shook

Examples

```
parseNums(' 1 2 3 4 5 ')
```

parseText	<i>Parses a string containing several sub-strings</i>
-----------	---

Description

Parses a string containing several sub-strings

Usage

```
parseText(textString)
```

Arguments

textString Required. A character string containing strings separated by any number of spaces.

Value

Returns a character vector.

Author(s)

Kevin Shook

Examples

```
parseText(' red green blue black')
```

PBIAS	<i>Compute bias as a percentage</i>
-------	-------------------------------------

Description

Compute bias as a percentage

Usage

```
PBIAS(obs, sim)
```

Arguments

obs	Observed values as a numeric vector.
sim	Simulated values values as a numeric vector.

Value

If successful returns the percentage of bias as an integer. If unsuccessful, returns the value FALSE.

Author(s)

Muluneh A. Mekonnen

Examples

```
obs <- runif(100)
sim <- runif(100)
PBIAS(obs, sim)
```

plotDataCompleteness	<i>Time plots of variable completeness</i>
----------------------	--

Description

Time plots of variable completeness

Usage

```
plotDataCompleteness(MESHdata)
```

Arguments

MESHdata	Required. A data frame of MESH time series, as returned by read_tb0
----------	---

Value

Returns a **ggplot2** wrapped faceted plot of data completeness (as a line) for each station. Missing periods are indicated by gaps in the line. The plot is faceted by the variable `station` - so you can change the facetting.

Author(s)

Kevin Shook

See Also

[read_tb0](#)

Examples

```
## Not run:
qvals <- read_tb0("MESH_input_streamflow.tb0", NAvalue = -0.01, values_only = TRUE)
p <- plotDataCompleteness(qvals)
# change facetting
# the y-axis is unimportant, so the plots can be squished vertically
library(ggplot2)
p <- p + facet_wrap(~station, ncol = 2)
## End(Not run)
```

read_AEP_csv

Reads csv file produced by Alberta Environment and Parks

Description

Reads csv file produced by Alberta Environment and Parks

Usage

```
read_AEP_csv(AEPfile = "", timezone = "", values_only = TRUE)
```

Arguments

AEPfile	Required. Name of AEP file to be read in.
timezone	Optional. The name of the timezone of the data as a character string. If the timezone is not specified, your default value (i.e. your time zone) will be used. This should be the timezone of your data, but omitting daylight savings time. Note that the timezone code is specific to your OS. To avoid problems, you should use a timezone without daylight savings time. Under Windows or OSX, you can use 'etc/GMT+6' or 'etc/GMT+7' for Central Standard and Mountain Standard time. Under Linux you should use 'Etc/GMT+6' or 'Etc/GMT+7'.
values_only	optional. If TRUE (the default), only the time series values will be returned. If FALSE, the meta data will also be returned.

Value

Returns the time series data as a data frame, with the POSIXct variable `datetime` as the time stamp. Note that the time series interval may be irregular. If `values_only = TRUE`, then the returned value will be a list consisting of the time series data frame and the header meta data as a list, with the variables `values` and `header_meta`, respectively. The meta data are:

variable type

station_site character

station_name character

station_number character

parameter_name character

parameter_type character

parameter_type_name character

time_series_name character

time_series_unit character

longitude numeric

latitude numeric

Author(s)

Kevin Shook

See Also

[read_MESH_OutputTimeseries_csv](#)

Examples

```
## Not run:
precip <- read_AEP_csv("05CA805 Skoki Lodge - PC - C.Merged - All.csv",
  values_only = FALSE)
# show values
head(precip$values)
# show latitude
precip$header_meta$latitude
## End(Not run)
```

```
read_MESH_OutputTimeseries_csv
```

Reads MESH output .csv file containing timeseries

Description

Reads a file containing any output from a MASH model into a standard R data frame. The names of the variables will be trimmed to remove leading and trailing spaces, and the time variables are combined into a single R date or datetime.

Usage

```
read_MESH_OutputTimeseries_csv(outputFile, timezone = "",
  missingValueThreshold = -0.1)
```

Arguments

outputFile	Required. Name of MESH output file. Must be a .csv file.
timezone	Not required for daily time series. Required for sub-daily time series. The name of the timezone of the data as a character string. This should be the timezone of your data, but omitting daylight savings time. Note that the timezone code is specific to your OS. To avoid problems, you should use a timezone without daylight savings time. You can use 'etc/GMT+6' or 'etc/GMT+7' for Central Standard and Mountain Standard time, respectively. DO NOT use 'America/Regina' as the time zone, as it includes historical changes between standard and daylight savings time.
missingValueThreshold	Optional. Any value smaller than this value will be set to NA_real_ when the file is imported. The default value is -0.1 to prevent zero values from being affected.

Value

If successful, returns a data frame. The first columns will be called 'DATE' for daily values, and will contain a standard R date. For sub-daily timeseries the first column will be called 'DATETIME' and will contain a standard POSIXct date/time. If unsuccessful, returns the value FALSE.

Author(s)

Kevin Shook

See Also

[simpleHydrograph](#)

Examples

```
## Not run:
timezone <- 'etc/GMT+6'
outfile <- "Basin_average_water_balance_ts.csv"
output <- read_MESH_OutputTimeseries_csv(outfile, timezone)
## End(Not run)
```

read_r2c_raster	<i>Reads r2c file to raster brick</i>
-----------------	---------------------------------------

Description

This function reads a file containing a time series of 2D values, which is output from a MESH model. It is not intended to read in a file describing a drainage basin. For that purpose, you should be using the function `read_r2c_shed`. This function returns either a **raster** brick or an **rts** rts object, which is a timeseries raster. Each Frame in the original file becomes a separate layer. The name of each layer in the **raster** brick is set to the time stamp of each Frame. Because the layer names are standard R variables, they must obey the rules for variable names, including beginning with a character, and not containing spaces. These rule will change the layer names if you are not careful.

Usage

```
read_r2c_raster(r2cFile, NValue = NULL, as_rts = FALSE,
  timezone = "", layerNameFormat = NULL)
```

Arguments

<code>r2cFile</code>	Required. Name of r2c file containing time series.
<code>NValue</code>	Optional. If specified, values smaller than NValue will be set to NA_real_
<code>as_rts</code>	Optional. If TRUE, the returned value will be a rts object, which allows the creation of 1-D time series, and for temporal aggregation. If FALSE (the default) a standard raster brick object is returned, which is better for simple plotting of the layers.
<code>timezone</code>	Optional. If the <code>r2cFile</code> contains date values for each Frame, then the Frame times are returned as R dates. If there are hours and seconds, then they will be converted to POSIXct datetime values. In this case, you may want to specify the timezone of the data. If the timezone is not specified, your default value will be used.
<code>layerNameFormat</code>	Optional. Sets the layer names when returning the raster brick to avoid conflicting with the R variable rules.

Value

Returns either a **raster** brick or an **rts** rts object.

Author(s)

Kevin Shook

See Also

[rts read_r2c_shed](#)

Examples

```
## Not run:
temps <- read_r2c_raster("TA_M.r2c", NAvalue = 0, as_rts = FALSE, layerNameFormat = "%b_%Y")
# convert air temps from K to C
temps <- temps - 273.15
plot(temps)
# create an animation and save it as a file
library(animation)
saveGIF(animate(temps, n = 1))
## End(Not run)
```

read_r2c_shed	<i>Reads r2c file of a MESH watershed</i>
---------------	---

Description

This function reads in a file containing the layers which define a MESH watershed. To read in a file of timeseries, use the function `r2c2raster`.

Usage

```
read_r2c_shed(r2cFile = "", values_only = TRUE, as_rasters = TRUE)
```

Arguments

r2cFile	Required. Name of r2c file.
values_only	Optional. If TRUE (the default), then only the values are returned, either as a raster brick (useful for plotting) or as a 3D array (useful for analysis). If FALSE, then a <i>list</i> will be returned, containing the 1) the data, 2) the metadata (the variable names, types and units) are returned for each layer, and 3) the r2c file header lines.
as_rasters	Optional. If TRUE, the layers will be returned as as raster brick. If FALSE, they will be returned as an array.

Value

Returns eiher an array or a raster brick of values, and optionally, the meta data and file header.

Author(s)

Kevin Shook

See Also[read_r2c_raster](#)**Examples**

```
## Not run:
# read in basin as a raster brick
basin <- r2c2basin("MESH_drainage_database.r2c")
# read in as an array
basin_array <- r2c2basin("MESH_drainage_database.r2c", as_rasters = FALSE)
# get meta data as well
basin_array <- r2c2basin("MESH_drainage_database.r2c", values_only = FALSE,
as_rasters = FALSE)

## End(Not run)
```

read_tb0

*Reads a MESH tb0 file***Description**

Reads in a tb0 file. The time series values, if present, will be stored in a data frame. Optionally, the meta data will be stored as lists. The meta data are of 2 types, the header values, which refer to the entire file and column values, which pertain to individual columns.

Usage

```
read_tb0(tb0File = "", values_only = TRUE, timezone = "",
NAvalue = NULL)
```

Arguments

tb0File	Required. The name of the file to be read.
values_only	Optional. If TRUE (the default), only the time series values will be returned. If FALSE, the meta data will also be returned. Note that if the value is set to TRUE, and there are no time series values in the file, as for a reservoir file, then an error will result.
timezone	Optional. The data time series have POSIXct datetime values. You may want to specify the timezone of the data. If the timezone is not specified, your default value (i.e. your time zone) will be used.
NAvalue	Optional. If specified, values smaller than NAvalue will be set to NA_real_

Value

Returns time series as a data frame. If meta data are specified, they are returned as a list of header data and a data frame of column meta data. In this case all three sets of data are combined in a single

Author(s)

Kevin Shook

See Also

[read_r2c_raster](#) [read_MESH_OutputTimeseries_csv](#)

Examples

```
## Not run:
qvals <- read_tb0("MESH_input_streamflow.tb0", NAvalue = -0.01, values_only = TRUE)

## End(Not run)
```

simpleHydrograph	<i>Creates hydrograph from MESH output</i>
------------------	--

Description

Creates a **ggplot** hydrograph from MESH output. This function *only* uses values from a single MESH data frame (as read in using readOutputTimeseriesCSV), so does not work with outside sources, such as WSC files. Because this function returns a **ggplot** object, you can change its format in any way you like. The plots produced may be faceted using the commands facet_wrap or facet_grid.

Usage

```
simpleHydrograph(MESHvals, stationNames = "", byStation = TRUE,
  byYear = FALSE, meas = TRUE, sim = TRUE, calStart = "",
  calEnd = "", alpha = 1)
```

Arguments

MESHvals	Required. A data frame of output from a MESH run, as produced by read_MESH_OutputTimeseries_csv
stationNames	Optional. A vector of strings holding station names. If specified, the station names will be used in the plots. Otherwise the MESH station numbers will be used.
byStation	Optional. If TRUE (the default) then the plots will be coloured according to the station names. You may want to set this to FALSE if you are facetting by station name.

byYear	Optional. If TRUE then the plots will be able to be faceted by year. Note that this means that the dates are all plotted using the year 2000, so you will see strange results if you set this to TRUE and don't facet by year. Default is FALSE
meas	Optional. Should the measured values be plotted? Default is TRUE. If FALSE, they will be omitted.
sim	Optional. Should the simulated values be plotted? Default is TRUE. If FALSE, they will be omitted.
calStart	Optional. The start date of the calibration period. Must be a string in the format 'yyyy-mm-dd'. If specified, values on and after this date will be designated as the Calibration period. The remaining values will be designated as the Validation period.
calEnd	Optional. The end date of the calibration period. Must be a string in the format 'yyyy-mm-dd'. If specified, values on and after this date will be designated as the Calibration period. The remaining values will be designated as the Validation period.
alpha	Optional. Sets the alpha channel (transparency) of the plots. The default value is 1, i.e. opaque. Setting alpha to less than 1 makes the plots transparent, which can be useful to see overlapping hydrographs.

Value

If successful, returns a **ggplot2** object. If unsuccessful, returns FALSE. The object can be faceted by the name of the station (the variable is called station). If the option `byYear = TRUE`, then the object can be faceted by the variable YEAR.

Note

Specifying the calibration start and/or end dates will allow the resulting plot to be faceted by the variable period.

Author(s)

Kevin Shook

See Also

[read_MESH_OutputTimeseries_csv](#) [hydroStats](#)

Examples

```
# plot hydrograph of all data on single graph
p1 <- simpleHydrograph(MESH_streamflows)
p1
# add station names, and replot
stations <- c("Station1", "Station2")
p2 <- simpleHydrograph(MESH_streamflows, stationNames = stations)
p2
# remove colouring by station, and facet, changing the axis label format
p3 <- simpleHydrograph(MESH_streamflows, stationNames = stations, byStation = FALSE)
```

```

# load in all of ggplot2 to modify plots
library(ggplot2)
p3 <- p3 + facet_wrap(~station, nrow = 2) + scale_x_date(date_labels = "%Y")
p3
# plot by year, then facet
p4 <- simpleHydrograph(MESH_streamflows, stationNames = stations, byYear = TRUE)
p4 <- p4 + facet_wrap(~YEAR, scales = "free_y")
p4
# remove colouring for stations, and facet by station and year
p5 <- simpleHydrograph(MESH_streamflows, stationNames = stations, byStation = FALSE, byYear = TRUE)
p5 <- p5 + facet_grid(YEAR~station, scales = "free_y")
# change colours
plotcols <- c("red", "blue")
p5 <- p5 + scale_colour_manual(values = plotcols)
p5

```

var_present	<i>Find if variable is present in a data frame</i>
-------------	--

Description

Find if variable is present in a data frame

Usage

```
var_present(dataframe, variable)
```

Arguments

dataframe	Required. Dataframe to be checked
variable	Required. Variable name as a character string.

Value

Returns TRUE or FALSE

Examples

```
## Not run: var_present(values, "datetime")
```

`win.eol`*Gets the Windows end of line characters*

Description

Finds the end of line (eol) characters required for writing Windows files, such as CRHM obs files. No parameters are required. This is an internal **CRHM** function and should *never* need to be called directly.

Usage

```
win.eol()
```

Value

Returns the Windows end of line characters (cr and lf).

Note

This function is used to make the creation of Windows-specific files work on all platforms. CRHM requires its obs and project files to use the Windows end of line characters, which are expressed differently on UNIX-based operating systems such as Linux and OSX.

Author(s)

Kevin Shook

Examples

```
windowsEndOfLine <- win.eol()
```

`write_r2c_shed`*Write MESH watershed data to r2c file*

Description

Write MESH watershed data to r2c file

Usage

```
write_r2c_shed(basin, header, r2cFile = "")
```

Arguments

basin	Required. The values defining the basin parameters, as read in by read_r2c_shed. Can either be an array or a raster brick.
header	Required. The header lines from the basin r2c file, as read in by read_r2c_shed
r2cFile	Required. The file to be written.

Value

If successful, returns TRUE. If unsuccessful, returns FALSE

Author(s)

Kevin Shook

See Also

[read_r2c_shed](#)

Examples

```
## Not run:
# read in basin
shed <- read_r2c_shed("MESH_drainage_database.r2c", values_only = FALSE,
as_rasters = FALSE)
# write as another file
write_r2c_shed(shed$basin, shed$header_lines, "new_basin.r2c")

## End(Not run)
```

write_tb0	<i>Writes a MESH tb0 file</i>
-----------	-------------------------------

Description

Writes a MESH tb0 file

Usage

```
write_tb0(values = NULL, column_meta = NULL, header = NULL,
NAvalue = -1, tb0File = "")
```

Arguments

values	Optional. A data frame of the values to be written, if the file is to be a time series. Note that the first column must be called <code>datetime</code> and must be a POSIXct date/time.
column_meta	Required. A data frame containing the following columns #' columnUnits required columnType required columnName required columnLocationX required columnLocationY required DA optional coeff1 optional coeff2 optional coeff3 optional coeff4 optional coeff5 optional
header	Required. A list containing the following variables filetype optional, default is <code>tb0 ASCII EnSim 1.0</code> datatype optional, default is <code>Time Series</code> application optional, default is <code>EnSimHydrologic</code> version optional, default is <code>default is 2.1.23</code> written_by optional, default is <code>default is MESHr</code> creation_date optional, default is <code>current date/time</code> source_file optional, default is <code>nothing</code> name required projection required, character string ellipsoid required, character string start_time required if values are not specified delta_t required if values are not specified attributeunits optional, default is <code>nothing</code> unitconversion optional, default is <code>nothing</code>
NAvalue	Optional. Value to be used for <code>NA_real_</code> values in the <code>.tb0</code> file. The default value is <code>-1</code> , which is not suitable for air temperatures.
tb0File	Required. Name of file to be written.

Value

If successful, returns `TRUE`. If unsuccessful, returns `FALSE`

Author(s)

Kevin Shook

See Also[read_tb0](#)**Examples**

```
## Not run: write_tb0(values, column_meta_data, header, "MESH_values.ts0")
```

Index

*Topic **datasets**

MESH_streamflows, 21

basinLapseRates, 3, 18

basinPrecipEvapRunoffPlot, 4

basinRunoffPlot, 4

basinSnowPlot, 5

basinSnowRainPondedPlot, 6

basinSoilWaterIcePlot, 4, 5, 7, 8, 9, 11

basinSoilWaterPlot, 8

basinStoragePlot, 4–8, 9, 11

basinStorageVariablesPlot, 9, 9

basinWaterBalancePlot, 11

distribPrecip, 12

doubleHydrograph, 13

findRecord, 15

gof, 20

gridPrecip, 16, 18

gridTemp, 3, 16, 17

hydroStats, 14, 19, 31

MESH_streamflows, 21

MESHR-package, 2

parseNums, 21

parseText, 22

PBIAS, 23

plotDataCompleteness, 23

read_AEP_csv, 24

read_MESH_OutputTimeseries_csv, 4–11, 14, 25, 26, 30, 31

read_r2c_raster, 27, 29, 30

read_r2c_shed, 16, 18, 28, 28, 34

read_tb0, 3, 13, 16, 18, 24, 29, 36

rts, 28

simpleHydrograph, 14, 20, 26, 30

var_present, 32

win.eol, 33

write_r2c_shed, 33

write_tb0, 34