



## Ladder safety

*The Work at Height Regulations came into force in 2005.* These regulations apply to work at height where there is a risk of fall liable to cause personal injury. This applies to both internal and external work at height, and includes below ground level and low height.

All ladders should be checked daily and prior to use for any damage, faults or wear and tear. In addition they should be inspected at defined intervals as part of a risk assessment programme. Use these inserts to manage the identification, safety, maintenance of ladders and help conform to the Work at Height Regulations 2005.

The AssetTag holder should be permanently fixed to the ladder in a suitable safe place. Perform an inspection of the ladder (a checklist is printed on the reverse) and record the result on the tag. If the ladder fails the inspection remove insert and inform a supervisor.

Inserts are designed for use with the AssetTag holder, insert and tag details below. The AssetTag holder clearly states 'Do not use this equipment' when the tag is removed.



The AssetTag multi-purpose tag holder is great for many purposes including fitting onto industrial ladders (with our ladder tag). Different inserts greatly expand the possible applications.

With no insert in place, 'Do not use this equipment Information tag is missing', along with 'Ref: No.'

### Tag Specifications

Height: 210mm  
Width: 55mm  
Depth: 6mm  
Material: Nylon 6

### Insert Specifications

Height: 181mm  
Width: 50mm  
Depth: 0.5mm  
Material: Polypropylene