Scan 1 IPs 3/6/2026 7:41 PM (UTC)

ID: bbf5e7aa-5596-4771-b161-8972b6142745

Status Completed Type TOP 1,000 common ports

Remember to close unused ports, verify and 'harden' the services that are exposed and reduce vulnerabilities by keeping your software up to date.

Open Ports Detected

Vulnerabilities Detected

Show all CVEs

1	11	13 CVEs	78 CVSS
Hosts	Open Ports	Vulnerabilities	Vulnerability Score

192.250.229.187

11 Open Ports | 13 CVEs | 78 CVSS

Port	Protocol	Product	Version	Banner	ISP	CVEs	CVSS	Sources
21	tcp	Pure-FTPd		220---------- Welcome to ..	WHG Hosting Services Ltd	0	0	
22	tcp	OpenSSH	8.0	SSH-2.0-OpenSSH_8.0	WHG Hosting Services Ltd	13	78	
25	tcp	Exim smtpd	4.99.1	220-s4217.fra1.stableserv..	WHG Hosting Services Ltd	0	0	
80	tcp	LiteSpeed httpd		openresty/1.27.1.1	WHG Hosting Services Ltd	0	0	
110	tcp	Dovecot pop3d		+OK Dovecot ready.	WHG Hosting Services Ltd	0	0	
143	tcp	Dovecot imapd		* OK [CAPABILITY IMAP4rev..	WHG Hosting Services Ltd	0	0	
443	tcp	LiteSpeed httpd		openresty/1.27.1.1	WHG Hosting Services Ltd	0	0	
465	tcp	Exim smtpd	4.99.1	220-s4217.fra1.stableserv..	WHG Hosting Services Ltd	0	0	
587	tcp	Exim smtpd	4.99.1	220-s4217.fra1.stableserv..	WHG Hosting Services Ltd	0	0	
993	tcp	Dovecot imapd		* OK [CAPABILITY IMAP4rev..	WHG Hosting Services Ltd	0	0	
995	tcp	Dovecot pop3d		+OK Dovecot ready.	WHG Hosting Services Ltd	0	0	

Web Application Security (OWASP) Results

22Total Alerts
0High Risk
4Medium Risk
12Low Risk
6Info

Alert	Risk Level	URI	Count	Solution	
Content Security Policy (CSP) Header Not Set	Medium	Medium (High)	https://takepossw.cyberarenalivetech.it/robots.txt	2	Ensure that your web server, application server, load balancer, etc. is configured to set the Content-Security-Policy header, to achieve optimal browser support: "Content-Security-Policy" for Chrome 25+, Firefox 23+ and Safari 7+, "X-Content-Security-Policy" for Firefox 4.0+ and Internet Explorer 10+, and "X-WebKit-CSP" for Chrome 14+ and Safari 6+.
Content Security Policy (CSP) Header Not Set	Medium	Medium (High)	https://takepossw.cyberarenalivetech.it/sitemap.xml	2	Ensure that your web server, application server, load balancer, etc. is configured to set the Content-Security-Policy header, to achieve optimal browser support: "Content-Security-Policy" for Chrome 25+, Firefox 23+ and Safari 7+, "X-Content-Security-Policy" for Firefox 4.0+ and Internet Explorer 10+, and "X-WebKit-CSP" for Chrome 14+ and Safari 6+.
Sub Resource Integrity Attribute Missing	Medium	Medium (High)	https://takepossw.cyberarenalivetech.it/	2	Provide a valid integrity attribute to the tag.
Sub Resource Integrity Attribute Missing	Medium	Medium (High)	https://takepossw.cyberarenalivetech.it/index.php?page=login	2	Provide a valid integrity attribute to the tag.

Alert	Risk Level	URI	Count	Solution	
Absence of Anti-CSRF Tokens	Low	Low (Medium)	https://takepossw.cyberarenalivetech.it/	2	Phase: Architecture and Design Use a vetted library or framework that does not allow this weakness to occur or provides constructs that make this weakness easier to avoid. For example, use anti-CSRF packages such as the OWASP CSRFGuard. Phase: Implementation Ensure that your application is free of cross-site scripting issues, because most CSRF defenses can be bypassed using attacker-controlled script. Phase: Architecture and Design Generate a unique nonce for each form, place the nonce into the form, and verify the nonce upon receipt of the form. Be sure that the nonce is not predictable (CWE-330). Note that this can be bypassed using XSS. Identify especially dangerous operations. When the user performs a dangerous operation, send a separate confirmation request to ensure that the user intended to perform that operation. Note that this can be bypassed using XSS. Use the ESAPI Session Management control. This control includes a component for CSRF. Do not use the GET method for any request that triggers a state change. Phase: Implementation Check the HTTP Referer header to see if the request originated from an expected page. This could break legitimate functionality, because users or proxies may have disabled sending the Referer for privacy reasons.

Alert	Risk Level	URI	Count	Solution	
Absence of Anti-CSRF Tokens	Low	Low (Medium)	https://takepossw.cyberarenalivetech.it/index.php?page=login	2	Phase: Architecture and Design Use a vetted library or framework that does not allow this weakness to occur or provides constructs that make this weakness easier to avoid. For example, use anti-CSRF packages such as the OWASP CSRFGuard. Phase: Implementation Ensure that your application is free of cross-site scripting issues, because most CSRF defenses can be bypassed using attacker-controlled script. Phase: Architecture and Design Generate a unique nonce for each form, place the nonce into the form, and verify the nonce upon receipt of the form. Be sure that the nonce is not predictable (CWE-330). Note that this can be bypassed using XSS. Identify especially dangerous operations. When the user performs a dangerous operation, send a separate confirmation request to ensure that the user intended to perform that operation. Note that this can be bypassed using XSS. Use the ESAPI Session Management control. This control includes a component for CSRF. Do not use the GET method for any request that triggers a state change. Phase: Implementation Check the HTTP Referer header to see if the request originated from an expected page. This could break legitimate functionality, because users or proxies may have disabled sending the Referer for privacy reasons.
Cookie No HttpOnly Flag	Low	Low (Medium)	https://takepossw.cyberarenalivetech.it/	1	Ensure that the HttpOnly flag is set for all cookies.
Cookie Without SameSite Attribute	Low	Low (Medium)	https://takepossw.cyberarenalivetech.it/	1	Ensure that the SameSite attribute is set to either 'lax' or ideally 'strict' for all cookies.

Alert	Risk Level	URI	Count	Solution	
Permissions Policy Header Not Set	Low	Low (Medium)	https://takepossw.cyberarenalivetech.it/robots.txt	2	Ensure that your web server, application server, load balancer, etc. is configured to set the Permissions-Policy header.
Permissions Policy Header Not Set	Low	Low (Medium)	https://takepossw.cyberarenalivetech.it/sitemap.xml	2	Ensure that your web server, application server, load balancer, etc. is configured to set the Permissions-Policy header.
Insufficient Site Isolation Against Spectre Vulnerability	Low	Low (Medium)	https://takepossw.cyberarenalivetech.it/	6	Ensure that the application/web server sets the Cross-Origin-Resource-Policy header appropriately, and that it sets the Cross-Origin-Resource-Policy header to 'same-origin' for all web pages. 'same-site' is considered as less secured and should be avoided. If resources must be shared, set the header to 'cross-origin'. If possible, ensure that the end user uses a standards-compliant and modern web browser that supports the Cross-Origin-Resource-Policy header (https://caniuse.com/mdn-http_headers_cross-origin-resource-policy).
Insufficient Site Isolation Against Spectre Vulnerability	Low	Low (Medium)	https://takepossw.cyberarenalivetech.it/index.php?page=login	6	Ensure that the application/web server sets the Cross-Origin-Resource-Policy header appropriately, and that it sets the Cross-Origin-Resource-Policy header to 'same-origin' for all web pages. 'same-site' is considered as less secured and should be avoided. If resources must be shared, set the header to 'cross-origin'. If possible, ensure that the end user uses a standards-compliant and modern web browser that supports the Cross-Origin-Resource-Policy header (https://caniuse.com/mdn-http_headers_cross-origin-resource-policy).
CSP: Notices	Low	Low (Medium)	https://takepossw.cyberarenalivetech.it/	2	Ensure that your web server, application server, load balancer, etc. is properly configured to set the Content-Security-Policy header.

Alert	Risk Level	URI	Count	Solution	
CSP: Notices	Low	Low (Medium)	https://takepossw.cyberarenalivetech.it/index.php?page=login	2	Ensure that your web server, application server, load balancer, etc. is properly configured to set the Content-Security-Policy header.
Strict-Transport-Security Header Not Set	Low	Low (High)	https://takepossw.cyberarenalivetech.it/robots.txt	2	Ensure that your web server, application server, load balancer, etc. is configured to enforce Strict-Transport-Security.
Strict-Transport-Security Header Not Set	Low	Low (High)	https://takepossw.cyberarenalivetech.it/sitemap.xml	2	Ensure that your web server, application server, load balancer, etc. is configured to enforce Strict-Transport-Security.
User Controllable HTML Element Attribute (Potential XSS)	Informational	Informational (Low)	https://takepossw.cyberarenalivetech.it/index.php?page=login	1	Validate all input and sanitize output it before writing to any HTML attributes.
Session Management Response Identified	Informational	Informational (Medium)	https://takepossw.cyberarenalivetech.it/	2	This is an informational alert rather than a vulnerability and so there is nothing to fix.
Storable and Cacheable Content	Informational	Informational (Medium)	https://takepossw.cyberarenalivetech.it/	3	Validate that the response does not contain sensitive, personal or user-specific information. If it does, consider the use of the following HTTP response headers, to limit, or prevent the content being stored and retrieved from the cache by another user: Cache-Control: no-cache, no-store, must-revalidate, private Pragma: no-cache Expires: 0 This configuration directs both HTTP 1.0 and HTTP 1.1 compliant caching servers to not store the response, and to not retrieve the response (without validation) from the cache, in response to a similar request.

Alert	Risk Level	URI	Count	Solution	
Storable and Cacheable Content	Informational	Informational (Medium)	https://takepossw.cyberarenalivetech.it/index.php?page=login	3	Validate that the response does not contain sensitive, personal or user-specific information. If it does, consider the use of the following HTTP response headers, to limit, or prevent the content being stored and retrieved from the cache by another user: Cache-Control: no-cache, no-store, must-revalidate, private Pragma: no-cache Expires: 0 This configuration directs both HTTP 1.0 and HTTP 1.1 compliant caching servers to not store the response, and to not retrieve the response (without validation) from the cache, in response to a similar request.
Storable and Cacheable Content	Informational	Informational (Medium)	https://takepossw.cyberarenalivetech.it/sitemap.xml	3	Validate that the response does not contain sensitive, personal or user-specific information. If it does, consider the use of the following HTTP response headers, to limit, or prevent the content being stored and retrieved from the cache by another user: Cache-Control: no-cache, no-store, must-revalidate, private Pragma: no-cache Expires: 0 This configuration directs both HTTP 1.0 and HTTP 1.1 compliant caching servers to not store the response, and to not retrieve the response (without validation) from the cache, in response to a similar request.
Authentication Request Identified	Informational	Informational (High)	https://takepossw.cyberarenalivetech.it/index.php?page=login	1	This is an informational alert rather than a vulnerability and so there is nothing to fix.

Reminder to run a 65k scan

Only the top 1000 ports were tested, **run a full 65k scan** to test all possible ports..

More Information

Cve vulnerabilities found - what to do next

Help & Support

If you have any questions, or need some help understanding these results, please contact us directly. We'd like to hear from you and are happy to help.

Install the **Network Scanner** mobile app, from the Google Play Store.

Google Play

RoboShadow

Cyber Security, Demystified.

RoboShadow, 64 Great Eastern St, London, EC2A 3QR, UK
www.roboshadow.com | hello@roboshadow.com | +44 203 588 2584