

Paredit Cheatsheet

Basic Insertion Commands

```
(
  paredit-open-round
  (a b | c d)
  (a b (| ) c d)

  (foo "bar | baz" quux)
  (foo "bar (| baz" quux)

)
paredit-close-round
(a b | c )
(a b c)|

; Hello,| world!
; Hello,)| world!

M-) paredit-close-round-and-newline
(defun f (x| ))
(defun f (x)
| )

; (Foo.|
; (Foo.)|

[
paredit-open-square
(a b | c d)
(a b [| ]c d)

(foo "bar | baz" quux)
(foo "bar [baz" quux)

]
paredit-close-square
(define-key keymap [frob|
] 'frobnicate)
(define-key keymap [frob]|
'frobnicate)

; [Bar.|
; [Bar.]|

"
paredit-doublequote
(frob grovel | full lexical)
(frob grovel "|" | full lexical)

(foo "bar | baz" quux)
(foo "bar [| baz" quux)

M-" paredit-meta-doublequote
(foo "bar | baz" quux)
(foo "bar baz"
| quux)

(foo | (bar #\x "baz \\quux") zot)
(foo "|" (bar #\x bãz \\\quux)"
zot)

\
paredit-backslash
(string #| )
; Escaping character... (x)
(string #\x| )

"foo| bar"
; Escaping character... (")
"foo\"| bar"
```

```
M-; paredit-comment-dwim
(foo | bar)    ; baz
(foo bar)      ; | baz

(frob grovel)|
(frob grovel) ; |

| (defun hello-world ...)
;; |
(defun hello-world ...)
```

C-j paredit-newline

```
(let ((n (frobbotz))) | (display (+
n 1)
port))
(let ((n (frobbotz)))
| (display (+ n 1)
port))
```

Deleting and Killing

```
C-d    paredit-forward-delete
(quu | x "zot")
(quu | "zot")

(quux | "zot")
(quux " | zot")
(quux " | ot")

(foo ( | ) bar)
(foo | bar)

| (foo bar)
(| foo bar)
```

```
DEL    paredit-backward-delete
("zot" q | uux)
("zot" | uux)

("zot" | quux)
("zot | " quux)
("zo | " quux)

(foo ( | ) bar)
(foo | bar)

(foo bar) |
(foo bar | )
```

```
C-k  paredit-kill
(foo bar) | ; Useless comment!
(foo bar) |
(| foo bar) ; Useful comment!
(| ) ; Useful comment!
| (foo bar) ; Useless line!
|

(foo " | bar baz"
quux)
(foo " | "
quux)
```

```
M-D    paredit-forward-kill-word
      | (foo bar) ; baz
      | | bar) ; baz
      | | ) ; baz
      | ) ; |
      | ) ; |

      ;; | Frobnicate
      (defun frobnicate ...)
      ;; |
      (defun frobnicate ...)
      ;; |
      (| frobnicate ...)

M-DEL  paredit-backward-kill-word
      (foo bar) ; baz
      (quux) |
      (foo bar) ; baz
      (| )
      (foo bar) ; |
      ()
      (foo | ) ;
      ()
      (| ) ;
      ()
```

Movement and Navigation

```
C-M-f  paredit-forward
(foo | (bar baz) quux)
(foo (bar baz)| quux)

(foo (bar) | )
(foo (bar)) |
```

```
C-M-b  paredit-backward
(foo (bar baz)| quux)
(foo | (bar baz) quux)

(| (foo) bar)
| ((foo) bar)
```

C-M-u paredit-backward-up
C-M-d paredit-forward-down
C-M-p paredit-backward-down
C-M-n paredit-forward-up

Depth Changing

```
M- (   paredit-wrap-round
      (foo | bar baz)
      (foo (| bar) baz)

M-S   paredit-splice-sexp
      (foo (bar| baz) quux)
      (foo bar| baz quux)

M-↑   paredit-splice-sexp-killing-backward
      (foo (let ((x 5)) | (sqrt n)) bar)
      (foo (sqrt n) bar)
```

```

M-↓  paredit-splice-sexp-killing-forward
      (a (b c | d e) f)
      (a b c f)

M-r  paredit-raise-sexp
      (dynamic-wind in (lambda () | body)
out)
      (dynamic-wind in | body out)
      | body

```

Barfage and Slurpage

```
C→  paredit-forward-slurp-sexp
      (foo (bar | baz) quux zot)
      (foo (bar | baz quux) zot)

      (a b ((c | d)) e f)
      (a b ((c | d) e) f)
```

```
C ← paredit-forward-barf-sexp
      (foo (bar | baz quux) zot)
      (foo (bar | baz) quux zot)
```

```
C-M ← paredit-backward-slrp-sexp
      (foo bar (baz | quux) zot)
      (foo (bar baz | quux) zot)
      (a b ((c | d)) e f)
      (a (b (c | d)) e f)
```

```
C-M→  paredit-backward-barf-sexp
      (foo (bar baz | quux) zot)
      (foo bar (baz | quux) zot)
```

Miscellaneous

```
M-S  paredit-split-sexp
      (hello| world)
      (hello)| (world)

      "Hello, | world!"
      "Hello, " | "world!"
```

```
M-J  paredit-join-sexps
      (hello) | (world)
      (hello | world)

      "Hello, " | "world!"
      "Hello,  | world!"

      hello-
      | world
      hello- | world
```

```
C-c C-M-l  paredit-recentre-on-sexp
M-g        paredit-reindent-defun
```