Employing Metaprogramming: A Macro-Driven Strategy to Overcome Compiler-Imposed Limitations on Specialization

Davide Cerato
Id. Number: 984481

BSc in Computer Science

Advisor: Prof. Walter Cazzola
Co-Advisor: Mr. Federico Cristiano Bruzzone





UNIVERSITÀ DEGLI STUDI DI MILANO
Computer Science Department
ADAPT-Lab

Academic Year 2024–2025

COMPUTER SCIENCE DEPARTMENT • ADAPT-LAB

Contents

1 Introduction **1**

2 Running Example **3**

3 Background **5**

3.1 The Rust Programming Language. 5

3.2 Dispatch Techniques 7

3.3 Metaprogramming 9

4 A deep dive into MyTool **11**

5 Experimentation **13**

6 Related Work **15**

7 Future Work **17**

8 Conclusions **19**

1 Introduction

Premise A core challenge in high-performance systems programming is achieving zero-cost abstraction through generic programming and polymorphism while allowing type-specific performance optimizations, aka *specialization*. This challenge is particularly acute in Rust, a modern systems programming language designed for safety, concurrency and performance. Its trait system enable polymorphism and generic programming without incurring runtime overhead, as the compiler typically performs monomorphization, ensuring high performance across the board. However, for maximum efficiency, there are instances where a generic function could benefit significantly from a custom, highly optimized implementation when dealing with specific types / conditions. The ability to provide such a conditional, type-specific implementation for a trait method is known as Trait Specialization.

State of the Art The concept of specialization is a common aspiration in advanced type systems. Many programming languages have explored various mechanisms to achieve this, with varying degrees of success and complexity. Without native support for specialization, the common practice usually relies on various complex workarounds which often result in cumbersome code, poor compiler diagnostics or insufficient optimization compared to true specialization. In 2015, the Rust community introduced an experimental feature called *trait specialization* [34], which soon received widespread interest, but up to now is still confined to the *Nightly* channel, after its stabilization attempts stalled due to various design and implementation challenges.

Limitations A general obstacle for adopting powerful, cutting-edge language features is the tension between innovation and stability, often manifested in experimental versus production-ready compiler versions. This is true for specialization as well, which forces library authors and application developers to make an undesirable trade-off: either forgo the performance and elegance improvements offered by specialization to maintain stability or commit to volatile and constantly changing unstable versions. The primary and most critical limitation facing the Rust ecosystem is indeed the Nightly-Stable divide regarding specialization (the difference between these channels is explained in Section 3.1). While the feature offers significant potential for optimization and cleaner trait designs, its unstable status prevents its adoption in commercial, production-ready or long-term supported codebases.

Problem Statement While the concept of specialization is a crucial tool for optimizing generic code in any performance-oriented language, its practical application is often gated by compiler maturity and stability concerns. Given the performance focus of the Rust programming language and the significant utility of trait specialization, the central problem is the lack of a robust, idiomatic and performance-preserving mechanism for implementing trait specialization in stable Rust. The instability of the official feature creates a gap between what is theoretically possible for optimization and what is practically available to the vast majority of the community, putting a performance ceiling on stable Rust code.

Proposal To address the general limitations of specialization features in current stable ecosystems, this thesis proposes an innovative approach to the matter by moving the monomorphization and specialization logics to an earlier stage in the compilation process. To prove the effectiveness of this approach, we introduce a metaprogramming-based technique to simulate the behavior of specialization. By utilizing the metaprogramming capabilities of the language, we can analyze the input and generate the necessary boilerplate and type-checking logic at compile time, effectively allowing a user to define specialized implementations in stable code. This approach (which can be applied to most languages with metaprogramming support) avoids runtime overhead entirely and circumvents the restrictions imposed by unstable compiler features.

Contributions This work provides the following key contributions. A Novel Stable Specialization Technique: the design and implementation of a new, purely metaprogramming-based approach for achieving specialization. Implementation of Reusable Tools: the creation of a Rust procedural macro library that provides an alternative to nightly specialization and an analysis tool that evaluates real-world public Rust codebases to identify common patterns where this stable specialization mechanism could yield substantial benefits.

Structure The remainder of this thesis is structured as follows. Chapter 2 (Running Example) shows an example of the tool in action, illustrating its usage and benefits through a concrete scenario. Chapter 3 (Background) provides foundational knowledge on Rust, dispatch techniques and metaprogramming. Chapter 4 (A deep dive into MyTool) details the design principles and the implementation architecture of the specialization macro tool, focusing on the compile-time token manipulation strategy. Chapter 5 (Experimentation) presents the methodology and results collected with the analysis tool, including benchmarks and ecosystem analysis. Chapter 6 (Related Work) reviews existing solutions, nightly specialization and other techniques used to address the matter in Rust and related languages. Chapter 7 (Future Work) outlines potential extensions to the metaprogramming technique and further research avenues. Finally, Chapter 8 (Conclusions) summarizes the findings, reiterates the primary contributions and concludes the thesis.

2
Running Example

The simplest form of specialization using the tool is the following. We'll show the example in Rust, but the approach is general and can be applied to other languages with similar features.

The default implementation does not need any change compared to standard code. The specialized implementation instead, is annotated with the attribute macro `#[when(...)]`, that lets us specify the conditions under which that implementation should be used. In this case, we want to specialize the implementation of `MyTrait` for the type `i32`, so we write `#[when(T = i32)]`. This will create a specialized version of the `trait` and of the `impl`, through a process we'll be calling *monomorphic specialization*.

After doing this, we also need to instruct the method calls to use the correct version of the method. This is done by using the `spec!` macro, which takes as first argument the method call and as second argument the type to specialize for. As better explained in Chapter 4, this is required because in the macro expansion phase the compiler doesn't give us enough information to automatically determine the types of the variables.

The complete code is shown in Listing 1, where you can see the macros in action. As you can probably understand, this approach preserves the soundness of the type system, since after the monomorphization process (see Listing 2) we have two completely separate versions of the trait and its implementation, that the compiler can easily distinguish and type check independently.

```
1  trait MyTrait { fn my_method(&self); }
3  impl<T> MyTrait for T {
4      fn my_method(&self) {
5          println!("Generic implementation");
6      }
7  }
9  #[when(T = i32)]
10 impl<T> MyTrait for T {
11     fn my_method(&self) {
12         println!("Specialized for i32");
13     }
14 }
16 fn main() {
17     spec! { 10.my_method(); i32 };   // prints "Specialized for i32"
18     spec! { 10.5.my_method(); f64 }; // prints "Generic implementation"
19 }
```

Listing 1. *Example of the tool usage.*

```rust
trait MyTrait { fn my_method(&self); }

trait MyTrait_i32 { fn my_method(&self); }

impl<T> MyTrait for T {
    fn my_method(&self) {
        println!("Generic implementation");
    }
}

impl MyTrait_i32 for i32 {
    fn my_method(&self) {
        println!("Specialized for i32");
    }
}

fn main() {
    <i32 as MyTrait_i32>::my_method(&10); // prints "Specialized for i32"
    <f64 as MyTrait>::my_method(&10.5);   // prints "Generic implementation"
}
```

Listing 2. *Example of the code after our macros' expansion.*

In addition to using the two macros, we need to instruct the compiler to allow us to define and use the macros correctly independently from the order of their definition. In Rust this is done with *build scripts*, as shown in Listing 3.

```rust
fn main() {
    spec_trait_order::handle_order();
}
```

Listing 3. *Example of the minimal content of the* `build.rs` *file.*

With this simple example, we have shown how to use the tool to define a specialized implementation of a trait method for a specific type. In the next chapters, we will explore more complex scenarios, including multiple specializations, constraints on generic parameters and how the tool handles these cases internally.

3 Background

3.1 The Rust Programming Language.

Rust is a system programming language that focuses on safety, speed and concurrency. It ensures memory safety without garbage collection, meaning pure Rust programs are free from null pointer dereferences and data races.

Ownership and Borrowing Rust's ownership system—integrated into its type system—is inspired by *linear logic* [17, 18] and *linear types* [44, 33], enforcing that each piece of memory (a value) has a single *owner* (the variable binding) at any time [11, 4]. When the owner goes out of scope, the memory is automatically deallocated, enabling user-defined destructors and supporting the *resource acquisition is initialization* (RAII) pattern [40]. Ownership can be transferred (*moved*) or temporarily shared (*borrowed*) through references. Rust supports two types of borrows: multiple *immutable* borrows or a single *mutable* borrow, but never both at the same time. These constraints, enforced by the compiler through *borrow checking*, guarantee memory safety and prevent dangling pointers by ensuring that reference lifetimes never outlive their owners. To support low-level operations, Rust provides `unsafe` blocks, where the compiler's safety guarantees are suspended and the burden of avoiding undefined behavior falls on the programmer. Outside of these blocks, Rust enforces strict safety, making undefined behavior impossible in safe code.

Structs, Traits and Impls Structs (`struct`) and enums (`enum`) are the primary composite data types in Rust, enabling the creation of complex data structures with named fields and variant types, respectively.

```
struct MyStruct {
    field1: i32,
    field2: String,
}
```

Listing 4. *Example of a Rust struct.*

```
enum MyEnum {
    Variant1,
    Variant2(i32),
}
```

Listing 5. *Example of a Rust enum.*

Rust's trait system is a central mechanism for expressing polymorphism and shared behavior across types [24, 29]. Traits (`trait`) define a set of method signatures that types can implement, enabling abstraction over operations without committing to a concrete type. Implementation blocks (`impl`) associate specific types with traits, providing

concrete method definitions that satisfy the trait's contract. Rust also supports *inherent implementations*, where methods are defined directly on a type without requiring a trait, allowing type-specific functionality and constructor-like associated functions.

```rust
trait MyTrait { fn do_something(&self) }
impl MyTrait for i32 {
    fn do_something(&self) {}
}
```

Listing 6. *Example of a Rust trait impl.*

```rust
struct MyStruct;
impl MyStruct {
    fn do_something(&self) {}
}
```

Listing 7. *Example of a Rust inherent impl.*

By combining *traits*, *trait bounds* and *impl blocks*, Rust achieves ad hoc polymorphism [5, 44] and generic programming [32, 2] while preserving static guarantees and enabling the compiler to resolve method calls efficiently at compile time. Trait-based design is tightly integrated with Rust's ownership and borrowing model, ensuring that polymorphic abstractions do not compromise memory safety.

Software Variability Rust supports software variability through its attribute system, particularly the `cfg` attribute, which allows conditional compilation based on specified configuration predicates A feature in Rust is defined by all *terms* annotated with the same *config name* in a `cfg` *outer attribute*. The inclusion of a feature in a product depends on the evaluation of a *configuration predicate* at compile time, e.g. `#[cfg(any(unix, windows))]`. *Cargo*, Rust's package manager, lets developers declare features using *config names* in the `Cargo.toml` file, combining them with logical operators into *configuration predicates*. Feature dependencies, i.e., *cross-tree constraints* of *feature models* [22, 38, 23], can also be specified in the same file.

Release Channels Rust is distributed through three release channels: *stable*, *beta* and *nightly*. These channels differ in maturity guarantees and access to experimental language features [37]. The *stable* channel prioritizes reliability and backwards compatibility: only fully tested features are enabled, ensuring that libraries and applications compiled on stable continue to work across future releases. The *beta* channel serves as a staging ground for upcoming stable releases, allowing developers to test new features before they reach stable. In contrast, the *nightly* channel is updated daily and exposes experimental compiler internals, unstable language constructs and opt-in features (guarded by `#![feature(...)]` attributes). These features include advanced compiler hooks, low-level intrinsics and incomplete language extensions such as *specialization* and are available exclusively on nightly because their behavior is still under active design and soundness evaluation. Although nightly enables powerful experimentation, it provides no stability guarantees: features may change, be redesigned or removed without deprecation. For this reason, production-grade Rust codebases overwhelmingly target the stable channel, limiting developers from relying on certain expressive but unstable mechanisms.

3.2 Dispatch Techniques

Modern programming languages employ a variety of dispatch strategies at run-time or compile-time to determine which function or method is executed. These strategies fundamentally influence a language's expressiveness, performance guarantees and capacity for static reasoning [5, 31]. Rust integrates several dispatch paradigms to reconcile expressive abstraction with predictable performance, adhering to the principle of *zero-cost abstraction* [39, 41]. Most decisions are resolved statically, enabling the compiler to generate optimized machine code without runtime overhead [1, 13]. At the same time, Rust offers controlled forms of dynamic dispatch where late binding is essential, such as trait objects [29]. Beyond these core mechanisms, techniques like inlining heuristics [7], function cloning [14] and trait-based overloading [42] enable the compiler to further optimize code based on contextual information [9, 46]. Together, Rust's dispatch mechanisms provide a flexible yet robust model that preserves safety and performance.

Monomorphization Monomorphization [19] is the process by which the compiler generates concrete, type-specific versions of generic functions, methods and data structures. When a generic function is instantiated with a particular type parameter, the compiler produces a specialized version of the function in the final binary. This approach mirrors C++ template instantiation [43], enabling aggressive optimizations such as inlining, constant propagation and dead-code elimination [1, 46, 13].

```cpp
template <typename T>
T add(T a, T b) {
    return a + b;
}
int main() {
    // 1. Instantiation with int
    int x = add<int>(5, 3);
    // 2. Instantiation with double
    double y = add<double>(5.5, 3.2);
    return 0;
}
```

```cpp
int add_int(int a, int b) {
    return a + b;
}
double add_double(double a, double b) {
    return a + b;
}
int main() {
    int x = add_int(5, 3);
    double y = add_double(5.5, 3.2);
    return 0;
}
```

Listing 8. *Monomorphization process in C++: on the left, a generic function `add<T>` is defined and instantiated with two different types (`int` and `double`); on the right, the compiler generates two specialized versions of the function (`add_int` and `add_double`) and uses them accordingly.*

Because all type information is known at compile time, monomorphized functions avoid virtual dispatch overhead and allow the compiler to reason precisely about memory layout [27]. The primary trade-off is *code bloat*: large applications with many generic instantiations may experience increased binary size. Nevertheless, Rust's monomorphization strategy is central to its performance model, making generic abstractions effectively as fast as handwritten, type-specific code.

Overloading Overloading allows multiple functions or methods to share the same name but differ in parameter types or counts. Rust does not support traditional function overloading by parameter types as seen in languages like C++ or Java. Instead, it employs a unified mechanism based on *trait resolution* and *associated functions* [24]. Overloading emerges indirectly: different types may provide different implementations of the same trait methods and users may introduce trait bounds to guide method selection. This form of ad hoc polymorphism resembles *type classes* in Haskell [45, 20], where method resolution is determined by the combination of the type and the trait. Rust enforces coherence to guarantee that the compiler can unambiguously select an implementation at compile time [10, 16], preventing conflicts caused by independently defined overlapping instances. In addition, traits can define associated functions that behave similarly to static methods, allowing for API designs that mimic overloading while remaining type-safe and deterministic. This approach ensures predictable dispatch behavior, maintains clarity in method resolution and avoids the complexities of multi-parameter or ambiguous overload sets common in other languages [21].

Specialization Specialization is an advanced dispatch mechanism that allows more specific trait implementations to refine or override default behavior. In Rust, specialization aims to resolve long-standing expressiveness gaps in the trait system by enabling prioritized selection among overlapping implementations. This is particularly useful when a general-purpose implementation exists (often expressed as a *default* method in a trait) but certain types require optimized or semantically distinct behavior [28]. The feature builds on Rust's *coherence* and *orphan rules*[36], ensuring that overlapping implementations maintain type-safety and global consistency [10]. Although as of today specialization remains unstable and experimental (through the `#![feature(specialization)]` or `#![feature(min_specialization)]` flags [34, 35]), it provides a foundation for advanced library design patterns, such as optimized container types, numerical traits and fallback-based APIs [28]. The mechanism is conceptually related to multi-methods and ad hoc polymorphism in other languages [8, 6], but Rust restricts its form to preserve determinism and avoid ambiguity in resolution that have yet to be fully addressed.

```cpp
template <typename T>
void myMethod(T value) {
    cout << "Generic implementation" << endl;
}

template <>
void myMethod<int>(int value) {
    cout << "Specialized for int" << endl;
}

int main() {
    myMethod(10);       // prints "Specialized for int"
    myMethod(10.5);     // prints "Generic implementation"
    return 0;
}
```

Listing 9. *Specialization in C++. The code is the equivalent of that in Listing 1.*

```rust
#![feature(specialization)]
trait MyTrait { fn my_method(&self); }

impl<T> MyTrait for T {
    fn my_method(&self) {
        println!("Generic implementation");
    }
}

impl MyTrait for i32 {
    fn my_method(&self) {
        println!("Specialized for i32");
    }
}

fn main() {
    10.my_method();     // prints "Specialized for i32"
    10.5.my_method();   // prints "Generic implementation"
}
```

Listing 10. *Specialization in Rust (unstable). The code is the equivalent of that in Listing 9.*

3.3 Metaprogramming

Metaprogramming refers to the practice of writing code that generates or manipulates other code, enabling abstraction, automation and domain-specific optimizations. Historically rooted in Lisp's symbolic macro systems [30] and later expanded through compile-time techniques such as C++ templates [43], metaprogramming has evolved into a fundamental paradigm in modern language design. Its goals are multifaceted: reducing boilerplate, enforcing structural invariants, encoding repetitive patterns and enabling compile-time specialization or reasoning that would otherwise be impossible or inefficient at run-time. Across programming ecosystems, metaprogramming serves both practical and expressive purposes, ranging from code generation and DSL construction to advanced type-level computation. Rust approaches metaprogramming through a powerful and expressive macro system designed to maintain the language's guarantees of safety, determinism and predictable compilation. Rust distinguishes between two primary categories: *declarative macros* and *procedural macros*.

Declarative Macros Declarative macros (defined using `macro_rules!`) operate using pattern matching over token streams, allowing developers to define custom syntactic constructs that expand into valid Rust code. While reminiscent of Lisp macros in spirit, Rust's declarative macros enforce *hygiene* [25, 26, 12]: macro-generated identifiers cannot inadvertently capture variables or introduce unintended bindings. This prevents entire classes of errors common in textual or non-hygienic macro systems.

Procedural Macros Procedural macros provide direct access to the compiler's abstract syntax tree (AST [1, 3]) through the `proc_macro` API. These macros behave as compiler plugins that transform annotated code items at compile time. Three major forms exist:

function-like procedural macros, *attribute macros* and *derive macros*. The latter are widely used to automatically implement traits such as `Clone`, `Debug` or `Serialize`, significantly reducing repetitive boilerplate and enabling library authors to design ergonomic declarative APIs. Attribute macros allow developers to attach custom semantics or transformations to items, facilitating the creation of embedded domain-specific languages (DSLs) and compile-time validation tools; the `#[when(...)]` attribute macro introduced in this thesis is an example of such usage. Function-like procedural macros (e.g. the `spec!` macro) enable arbitrary code generation based on input token streams, allowing for complex compile-time computations and code synthesis. Because procedural macros operate on structured syntax trees instead of raw text, they can enforce well-formedness and preserve strong static guarantees during expansion.

Integration with the Compilation Pipeline Rust's macro system integrates deeply with the compiler's type checking and optimization phases. Unlike languages where macros expand at a separate preprocessing stage (e.g. the C preprocessor [15]), Rust expands macros as part of the front-end compilation pipeline, ensuring that hygiene, scoping and type resolution remain consistent. This design enables robust static analyses to occur alongside macro expansion and avoids undesired ambiguities or semantic inconsistencies. The combination of hygienic rewriting, AST-level transformations and compile-time type awareness makes Rust's metaprogramming capabilities both expressive and safe, empowering developers to construct efficient abstractions without compromising reliability.

4
A deep dive into MyTool

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

Nulla malesuada porttitor diam. Donec felis erat, congue non, volutpat at, tincidunt tristique, libero. Vivamus viverra fermentum felis. Donec nonummy pellentesque ante. Phasellus adipiscing semper elit. Proin fermentum massa ac quam. Sed diam turpis, molestie vitae, placerat a, molestie nec, leo. Maecenas lacinia. Nam ipsum ligula, eleifend at, accumsan nec, suscipit a, ipsum. Morbi blandit ligula feugiat magna. Nunc eleifend consequat lorem. Sed lacinia nulla vitae enim. Pellentesque tincidunt purus vel magna. Integer non enim. Praesent euismod nunc eu purus. Donec bibendum quam in tellus. Nullam cursus pulvinar lectus. Donec et mi. Nam vulputate metus eu enim. Vestibulum pellentesque felis eu massa.

Quisque ullamcorper placerat ipsum. Cras nibh. Morbi vel justo vitae lacus tincidunt ultrices. Lorem ipsum dolor sit amet, consectetuer adipiscing elit. In hac habitasse platea dictumst. Integer tempus convallis augue. Etiam facilisis. Nunc elementum fermentum wisi. Aenean placerat. Ut imperdiet, enim sed gravida sollicitudin, felis odio placerat quam, ac pulvinar elit purus eget enim. Nunc vitae tortor. Proin tempus nibh sit amet nisl. Vivamus quis tortor vitae risus porta vehicula.

5
Experimentation

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

Nulla malesuada porttitor diam. Donec felis erat, congue non, volutpat at, tincidunt tristique, libero. Vivamus viverra fermentum felis. Donec nonummy pellentesque ante. Phasellus adipiscing semper elit. Proin fermentum massa ac quam. Sed diam turpis, molestie vitae, placerat a, molestie nec, leo. Maecenas lacinia. Nam ipsum ligula, eleifend at, accumsan nec, suscipit a, ipsum. Morbi blandit ligula feugiat magna. Nunc eleifend consequat lorem. Sed lacinia nulla vitae enim. Pellentesque tincidunt purus vel magna. Integer non enim. Praesent euismod nunc eu purus. Donec bibendum quam in tellus. Nullam cursus pulvinar lectus. Donec et mi. Nam vulputate metus eu enim. Vestibulum pellentesque felis eu massa.

Quisque ullamcorper placerat ipsum. Cras nibh. Morbi vel justo vitae lacus tincidunt ultrices. Lorem ipsum dolor sit amet, consectetuer adipiscing elit. In hac habitasse platea dictumst. Integer tempus convallis augue. Etiam facilisis. Nunc elementum fermentum wisi. Aenean placerat. Ut imperdiet, enim sed gravida sollicitudin, felis odio placerat quam, ac pulvinar elit purus eget enim. Nunc vitae tortor. Proin tempus nibh sit amet nisl. Vivamus quis tortor vitae risus porta vehicula.

6
Related Work

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

Nulla malesuada porttitor diam. Donec felis erat, congue non, volutpat at, tincidunt tristique, libero. Vivamus viverra fermentum felis. Donec nonummy pellentesque ante. Phasellus adipiscing semper elit. Proin fermentum massa ac quam. Sed diam turpis, molestie vitae, placerat a, molestie nec, leo. Maecenas lacinia. Nam ipsum ligula, eleifend at, accumsan nec, suscipit a, ipsum. Morbi blandit ligula feugiat magna. Nunc eleifend consequat lorem. Sed lacinia nulla vitae enim. Pellentesque tincidunt purus vel magna. Integer non enim. Praesent euismod nunc eu purus. Donec bibendum quam in tellus. Nullam cursus pulvinar lectus. Donec et mi. Nam vulputate metus eu enim. Vestibulum pellentesque felis eu massa.

Quisque ullamcorper placerat ipsum. Cras nibh. Morbi vel justo vitae lacus tincidunt ultrices. Lorem ipsum dolor sit amet, consectetuer adipiscing elit. In hac habitasse platea dictumst. Integer tempus convallis augue. Etiam facilisis. Nunc elementum fermentum wisi. Aenean placerat. Ut imperdiet, enim sed gravida sollicitudin, felis odio placerat quam, ac pulvinar elit purus eget enim. Nunc vitae tortor. Proin tempus nibh sit amet nisl. Vivamus quis tortor vitae risus porta vehicula.

7
Future Work

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

Nulla malesuada porttitor diam. Donec felis erat, congue non, volutpat at, tincidunt tristique, libero. Vivamus viverra fermentum felis. Donec nonummy pellentesque ante. Phasellus adipiscing semper elit. Proin fermentum massa ac quam. Sed diam turpis, molestie vitae, placerat a, molestie nec, leo. Maecenas lacinia. Nam ipsum ligula, eleifend at, accumsan nec, suscipit a, ipsum. Morbi blandit ligula feugiat magna. Nunc eleifend consequat lorem. Sed lacinia nulla vitae enim. Pellentesque tincidunt purus vel magna. Integer non enim. Praesent euismod nunc eu purus. Donec bibendum quam in tellus. Nullam cursus pulvinar lectus. Donec et mi. Nam vulputate metus eu enim. Vestibulum pellentesque felis eu massa.

Quisque ullamcorper placerat ipsum. Cras nibh. Morbi vel justo vitae lacus tincidunt ultrices. Lorem ipsum dolor sit amet, consectetuer adipiscing elit. In hac habitasse platea dictumst. Integer tempus convallis augue. Etiam facilisis. Nunc elementum fermentum wisi. Aenean placerat. Ut imperdiet, enim sed gravida sollicitudin, felis odio placerat quam, ac pulvinar elit purus eget enim. Nunc vitae tortor. Proin tempus nibh sit amet nisl. Vivamus quis tortor vitae risus porta vehicula.

8 Conclusions

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

Nulla malesuada porttitor diam. Donec felis erat, congue non, volutpat at, tincidunt tristique, libero. Vivamus viverra fermentum felis. Donec nonummy pellentesque ante. Phasellus adipiscing semper elit. Proin fermentum massa ac quam. Sed diam turpis, molestie vitae, placerat a, molestie nec, leo. Maecenas lacinia. Nam ipsum ligula, eleifend at, accumsan nec, suscipit a, ipsum. Morbi blandit ligula feugiat magna. Nunc eleifend consequat lorem. Sed lacinia nulla vitae enim. Pellentesque tincidunt purus vel magna. Integer non enim. Praesent euismod nunc eu purus. Donec bibendum quam in tellus. Nullam cursus pulvinar lectus. Donec et mi. Nam vulputate metus eu enim. Vestibulum pellentesque felis eu massa.

Quisque ullamcorper placerat ipsum. Cras nibh. Morbi vel justo vitae lacus tincidunt ultrices. Lorem ipsum dolor sit amet, consectetuer adipiscing elit. In hac habitasse platea dictumst. Integer tempus convallis augue. Etiam facilisis. Nunc elementum fermentum wisi. Aenean placerat. Ut imperdiet, enim sed gravida sollicitudin, felis odio placerat quam, ac pulvinar elit purus eget enim. Nunc vitae tortor. Proin tempus nibh sit amet nisl. Vivamus quis tortor vitae risus porta vehicula.

Bibliography

[1] Alfred V. Aho, Monica S. Lam, Ravi Sethi, and Jeffrey D. Ullman. *Compilers: Principles, Techniques, and Tools*. Pearson/Addison-Wesley, 2nd edition, 2006.

[2] Roland Backhouse, Patrik Jansson, Johan Jeuring, and Lambert Meertens. Generic programming. In S. Doaitse Swierstra, José N. Oliveira, and Pedro R. Henriques, editors, *Advanced Functional Programming*, Berlin, Heidelberg, 1999. Springer Berlin Heidelberg.

[3] I.D. Baxter, A. Yahin, L. Moura, M. Sant'Anna, and L. Bier. Clone detection using abstract syntax trees. In *Proceedings. International Conference on Software Maintenance (Cat. No. 98CB36272)*, pages 368–377, 1998.

[4] Chandrasekhar Boyapati, Robert Lee, and Martin Rinard. Ownership Types for Safe Programming: Preventing Data Races And Deadlocks. In Satoshi Matsuoka, editor, *Proceedings of the 17th Annual ACM Conference on Object-Oriented Programming, Systems, Languages, and Applications (OOPSLA'02)*, pages 211–230, Seattle, WA, USA, November 2002. ACM Press.

[5] Luca Cardelli and Peter Wegner. On understanding types, data abstraction, and polymorphism. In *ACM Computing Surveys*, volume 17, 1985.

[6] Giuseppe Castagna. Covariance and contravariance: Conflict without a cause. *ACM Transactions on Programming Languages and Systems (TOPLAS)*, 17(4), 1995.

[7] J. Cavazos and M.F.P. O'Boyle. Automatic tuning of inlining heuristics. In *SC '05: Proceedings of the 2005 ACM/IEEE Conference on Supercomputing*, pages 14–14, 2005.

[8] Craig Chambers, David Ungar, and Elgin Lee. An efficient implementation of self, a dynamically-typed object-oriented language based on prototypes. In *OOPSLA '92*, 1992.

[9] B. F. Chang and L. K. John. Exploring the limits of inlining. In *Proceedings of the ACM SIGPLAN Conference on Programming Language Design and Implementation (PLDI)*, 1997.

[10] Adam Chlipala. Certified programming with dependent types. In *Lecture Notes*, 2011. MIT Course Notes, early chapters discuss type class coherence and overlapping instance safety.

[11] David G Clarke, John M Potter, and James Noble. Ownership types for flexible alias protection. In Craig Chambers, editor, *Proceedings of 13th International Conference on Object-Oriented Programming Systems, Languages and Applications (OOPSLA'98)*, pages 48–64, Vancouver, BC, CAnada, October 1998. ACM.

[12] William D. Clinger and Mitchell Wand. Hygienic macro technology. *Proceedings of the ACM on Programming Languages*, 4, 2020.

[13] Ron Cytron, Jeanne Ferrante, Barry K. Rosen, Mark N. Wegman, and F. Kenneth Zadeck. Efficiently computing static single assignment form and the control dependence graph. *ACM Transactions on Programming Languages and Systems (TOPLAS)*, 13(4), 1991.

[14] Dibyendu Das. Function inlining versus function cloning. *SIGPLAN Not.*, 38(6), June 2003.

[15] Christian J. Dietrich. Cppsig: Extracting type information for c-preprocessor macro expansions. *Proceedings of the 11th Workshop on Programming Languages and Operating Systems*, 2021.

[16] Jacques Garrigue. Programming with polymorphic variants. In *Proceedings of the International Conference on Functional Programming (ICFP)*, 1998.

[17] Jean-Yves Girard. Linear Logic. *Theoretical Computer Science*, 50(1):1–101, 1987.

[18] Jean-Yves Girard, Yves Lafont, and Laurent Regnier. *Advances in Linear Logic*. Cambridge University Press, July 1995.

[19] Robert Griesemer, Raymond Hu, Wen Kokke, Julien Lange, Ian Lance Taylor, Bernardo Toninho, Philip Wadler, and Nobuko Yoshida. Featherweight go. *Proceedings of the ACM on Programming Languages*, 4:1 – 29, 2020.

[20] Cordelia Hall, Kevin Hammond, Simon L. Peyton Jones, and Philip Wadler. Type classes in haskell. *ACM Transactions on Programming Languages and Systems (TOPLAS)*, 18(2), 1996.

[21] Simon Peyton Jones, Mark Jones, and Erik Meijer. Type classes: An exploration of the design space. In *Proceedings of the ACM SIGPLAN Haskell Workshop*, 2000.

[22] Kyo C. Kang, Sholom G. Cohen, James A. Hess, William E. Novak, and A. Spencer Peterson. Feature-Oriented Domain Analysis (FODA) Feasibility Study. Technical Report CMU/SEI-90-TR-21, Carnegie Mellon University, Pittsburgh, Pennsylvania, USA, November 1990.

[23] ahmet serkan karataş, halit oğuztüzün, and ali doğru. global constraints on feature models. In david cohen, editor, *proceedings of the 16th international conference on principles and practice of constraint programming (cp'10)*, lncs 6308, pages 537–551, st. andrews, scotland, September 2010. springer.

[24] Steve Klabnik and Carol Nichols. The rust programming language. `https://doc.rust-lang.org/book/`, 2019.

[25] Eugene Kohlbecker, Daniel P. Friedman, Matthias Felleisen, and Bruce Duba. Hygienic macro expansion. In *Proceedings of the ACM SIGPLAN Symposium on Interpreters and Interpretive Techniques*. ACM, 1992.

[26] Eugene E. Kohlbecker, Daniel P. Friedman, Matthias Felleisen, and Bruce F. Duba. Hygienic macro expansion. In *LFP '86*, 1986.

[27] Chris Lattner and Vikram Adve. Llvm: A compilation framework for lifelong program analysis and transformation. In *Proceedings of the International Symposium on Code Generation and Optimization (CGO)*. IEEE, 2004.

[28] Nicholas D. Matsakis. Rfc 1210: Specialization. `https://github.com/rust-lang/rfcs/pull/1210`, 2015.

[29] Nicholas D. Matsakis and Felix S. Klock II. The rust language. In *Proceedings of the ACM SIGAda Annual Conference on High Integrity Language Technology (HILT)*, 2014.

[30] John McCarthy. Recursive functions of symbolic expressions and their computation by machine, part i. *Communications of the ACM*, 3(4), 1960.

[31] Robin Milner. A theory of type polymorphism in programming. *Journal of Computer and System Sciences*, 17(3), 1978.

[32] David R. Musser and Alexander A. Stepanov. Generic programming. In P. Gianni, editor, *Symbolic and Algebraic Computation*, Berlin, Heidelberg, 1989. Springer Berlin Heidelberg.

[33] Martin Odersky. Observers for Linear Types. In Bernd Krieg-Brückner, editor, *Proceedings of the 4th European Symposium on Programming (ESOP'92)*, LNCS 582, pages 390–407, Rennes, France, February 1992. Springer.

[34] Rust Project Developers. Specialization rfc. `https://rust-lang.github.io/rfcs/1210-impl-specialization.html`, 2015.

[35] Rust Project Developers. Maximally minimal specialization: always applicable impls. `https://smallcultfollowing.com/babysteps/blog/2018/02/09/maximally-minimal-specialization-always-applicable-impls/`, 2018.

[36] Rust Project Developers. The orphan rules. `https://doc.rust-lang.org/reference/items/implementations.html#orphan-rules`, 2024. Accessed: 2025-01-01.

[37] Rust Project Developers. Rust release channels. `https://doc.rust-lang.org/book/appendix-07-nightly-rust.html`, 2024. Accessed: 2025-01-01.

[38] Christoph Seidl, Tim Winkelmann, and Ina Schaefer. A Software Product Line of Feature Modeling Notations and Cross-Tree Constraint Languages. In Andreas

Oberweis and Ralf H. Reussner, editors, *Proceedings of the 13th Edition of Modellierung (Modellierung'16)*, LNI P-254, pages 157–172, Karlsruhe, Germany, March 2016. Springer.

[39] Guy L. Steele. Making asynchronous parallelism safe for the world. In *Proceedings of the 17th ACM SIGPLAN-SIGACT Symposium on Principles of Programming Languages*, POPL '90, New York, NY, USA, 1989. Association for Computing Machinery.

[40] Bjarne Stroustrup. *The Design and Evolution of C++*. Addison-Wesley, first edition, March 1994.

[41] Bjarne Stroustrup. *The C++ Programming Language*. Addison-Wesley, 3rd edition edition, 2005.

[42] Peter J. Stuckey and Martin Sulzmann. A theory of overloading. *ACM Trans. Program. Lang. Syst.*, 27(6), November 2005.

[43] David Vandevoorde and Nicolai M. Josuttis. *C++ Templates: The Complete Guide*. Addison-Wesley, 2002.

[44] Philip Wadler. Linear Types Can Change the World! In Manfred Broy and Cliff B. Jones, editors, *Proceedings of the 2nd Working Conference on Programming Concepts and Methods (IFIP'90)*, pages 561–582, Sea of Galilee, Israel, April 1990. North-Holland.

[45] Philip Wadler and Stephen Blott. How to make ad-hoc polymorphism less ad-hoc. In *Proceedings of the 16th ACM SIGPLAN-SIGACT Symposium on Principles of Programming Languages (POPL)*. ACM, 1989.

[46] Mark N. Wegman and F. Kenneth Zadeck. Constant propagation with conditional branches. In *POPL '85*. ACM, 1985.