

Introduction to SpaDES

Alex M. Chubaty

Natural Resources Canada, Pacific Forestry Centre
email: achubaty@nrcan.gc.ca

Eliot McIntire

Natural Resources Canada, Pacific Forestry Centre
email: emcintir@nrcan.gc.ca

July 25, 2014

Contents

1	Spatial Discrete Event Simulation (SpaDES)	2
2	SpaDES modules	3
3	Working with maps	4
4	Simulating “agents”	6
4.1	Spatial agents	6
4.1.1	Point agents	6
5	A simple fire model	7
6	A simple individual based model (IBM)	10

1 Spatial Discrete Event Simulation (SpaDES)

Requirements This package makes heavy use of the `raster` and `sp` packages, so familiarity with these packages and their classes and methods is recommended.

```
> ## for now only while testing, etc.
> OS <- tolower(Sys.info()["sysname"])
> hostname <- gsub(Sys.info()["nodename"], pattern=".-VIC-", replace="")
> if (OS=="windows") {
+   if(any(pmatch(c("A105200", "A105192"), hostname, nomatch=FALSE))) {
+     path <- "c:/Eliot/GitHub"
+   } else {
+     path <- "~/GitHub"
+   }
+ } else {
+   path <- "~/Documents/GitHub"
+ }
> #devtools::dev_mode(TRUE)
> devtools::load_all(file.path(path, "SpaDES")) # for development/testing
```

```
Note: no visible binding for global variable 'to'
Note: no visible global function definition for 'J'
Note: no visible binding for global variable 'to'
Note: no visible binding for global variable 'to'
Note: no visible binding for global variable 'to'
```

```
>
> ##
> #library(SpaDES)
```

2 SpaDES modules

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetur id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

Nulla malesuada porttitor diam. Donec felis erat, congue non, volutpat at, tincidunt tristique, libero. Vivamus viverra fermentum felis. Donec nonummy pellentesque ante. Phasellus adipiscing semper elit. Proin fermentum massa ac quam. Sed diam turpis, molestie vitae, placerat a, molestie nec, leo. Maecenas lacinia. Nam ipsum ligula, eleifend at, accumsan nec, suscipit a, ipsum. Morbi blandit ligula feugiat magna. Nunc eleifend consequat lorem. Sed lacinia nulla vitae enim. Pellentesque tincidunt purus vel magna. Integer non enim. Praesent euismod nunc eu purus. Donec bibendum quam in tellus. Nullam cursus pulvinar lectus. Donec et mi. Nam vulputate metus eu enim. Vestibulum pellentesque felis eu massa.

Quisque ullamcorper placerat ipsum. Cras nibh. Morbi vel justo vitae lacus tincidunt ultrices. Lorem ipsum dolor sit amet, consectetur adipiscing elit. In hac habitasse platea dictumst. Integer tempus convallis augue. Etiam facilisis. Nunc elementum fermentum wisi. Aenean placerat. Ut imperdiet, enim sed gravida sollicitudin, felis odio placerat quam, ac pulvinar elit purus eget enim. Nunc vitae tortor. Proin tempus nibh sit amet nisl. Vivamus quis tortor vitae risus porta vehicula.

Fusce mauris. Vestibulum luctus nibh at lectus. Sed bibendum, nulla a faucibus semper, leo velit ultricies tellus, ac venenatis arcu wisi vel nisl. Vestibulum diam. Aliquam pellentesque, augue quis sagittis posuere, turpis lacus congue quam, in hendrerit risus eros eget felis. Maecenas eget erat in sapien mattis porttitor. Vestibulum porttitor. Nulla facilisi. Sed a turpis eu lacus commodo facilisis. Morbi fringilla, wisi in dignissim interdum, justo lectus sagittis dui, et vehicula libero dui cursus dui. Mauris tempor ligula sed lacus. Duis cursus enim ut augue. Cras ac magna. Cras nulla. Nulla egestas. Curabitur a leo. Quisque egestas wisi eget nunc. Nam feugiat lacus vel est. Curabitur consectetur.

Suspendisse vel felis. Ut lorem lorem, interdum eu, tincidunt sit amet, laoreet vitae, arcu. Aenean faucibus pede eu ante. Praesent enim elit, rutrum at, molestie non, nonummy vel, nisl. Ut lectus eros, malesuada sit amet, fermentum eu, sodales cursus, magna. Donec eu purus. Quisque vehicula, urna sed ultricies auctor, pede lorem egestas dui, et convallis elit erat sed nulla. Donec luctus. Curabitur et nunc. Aliquam dolor odio, commodo pretium, ultricies non, pharetra in, velit. Integer arcu est, nonummy in, fermentum faucibus, egestas vel, odio.


Sed commodo posuere pede. Mauris ut est. Ut quis purus. Sed ac odio. Sed vehicula hendrerit sem. Duis non odio. Morbi ut dui. Sed accumsan risus eget odio. In hac habitasse platea dictumst. Pellentesque non elit. Fusce sed justo eu urna porta tincidunt. Mauris felis odio, sollicitudin sed, volutpat a, ornare ac, erat. Morbi quis dolor. Donec pellentesque, erat ac sagittis semper, nunc dui lobortis purus, quis congue purus metus ultricies tellus. Proin et quam. Class aptent taciti sociosqu ad litora torquent per conubia nostra, per inceptos hymenaeos. Praesent sapien turpis, fermentum vel, eleifend faucibus, vehicula eu, lacus.

3 Working with maps

A raster map Sample map of habitat quality.

```
> # Give dimensions of dummy raster
> nx = 1.3e2
> ny = 1e2
> template = raster(nrows=ny, ncols=nx, xmn=-nx/2, xmx=nx/2, ymn=-ny/2, ymx=ny/2)
> # Make dummy maps for testing of models
> DEM = round(GaussMap(template, scale = 300, var = 0.03, speedup=1), 1)*1000
> Age = round(GaussMap(template, scale = 10, var = 0.1, speedup=1), 1)*20
> Forest_Cover = round(GaussMap(template, scale = 50, var = 1, speedup=1), 2)*10
> Pct_Pine = round(GaussMap(template, scale = 50, var = 1, speedup=1), 1)
> # Scale them as needed
> Age = Age/maxValue(Age)*100
> Pct_Pine = Pct_Pine/maxValue(Pct_Pine)*100
> # Make layers that are derived from other layers
> HabitatQuality = (DEM+10 + (Forest_Cover+5)*10)/100
> HabitatQuality = HabitatQuality/maxValue(HabitatQuality)
> # Stack them into a single stack for plotting
> habitat = stack(list(DEM, Age, Forest_Cover, HabitatQuality, Pct_Pine))
> names(habitat) = c("DEM", "Age", "Forest_Cover", "HabitatQuality", "Pct_Pine")
> library(RColorBrewer)
> cols = list(
+   transparent.red=c("#00000000", paste(brewer.pal(8, "Greys"), "66", sep="")[8:1]),
+   grey = brewer.pal(9, "Greys"),
+   spectral = brewer.pal(8, "Spectral"),
+   terrain = rev(terrain.colors(100)),
+   heat = heat.colors(10),
+   topo = topo.colors(10)
+ )
> dev(4);simPlot(habitat, col = cols[c(2:5, 3)])
```

Fires



4 Simulating “agents”

4.1 Spatial agents

4.1.1 Point agents

Agents represented by a single set of coordinates indicating their current position.

Use a `SpatialPointsDataFrame` with additional columns as needed.

Non-mobile point agents e.g., plants

Mobile point agents e.g., animals use a `SpatialPointsDataFrame`, with additional columns for agents’ previous `n` positions, and any other columns such as age, sex, group membership, etc.

```
> N <- 1e1 # number of agents
> # caribou data vectors
> IDs <- c("Alice", "Bob", "Clark", "Daisy", "Eric",
+         "Franz", "Gabby", "Hayley", "Igor", "Jane")
> sex <- c("female", "male", "male", "female", "male",
+         "male", "female", "female", "male", "female")
> age <- round(rnorm(N, mean=8, sd=3))
> prevX <- runif(N, xmin(habitat)+(ncol(habitat)*0.2), xmax(habitat)-(ncol(habitat)*0.2)) # previous X
> prevY <- runif(N, ymin(habitat)+(nrow(habitat)*0.2), ymax(habitat)-(nrow(habitat)*0.2)) # previous Y
> # create the caribou agent object
> caribou <- SpatialPointsDataFrame(coords=cbind(x=rnorm(N, prevX, ncol(habitat)/20),
+         y=rnorm(N, prevY, ncol(habitat)/20)),
+         data=data.frame(prevX, prevY, sex, age))
> row.names(caribou) <- IDs # alternatively, add IDs as column in data.frame above
> heading(SpatialPoints(cbind(x=prevX,y=prevY)),caribou)
```

	Alice	Bob	Clark	Daisy	Eric	Franz	Gabby	Hayley
	144.55398	182.42939	48.59348	57.57656	279.25616	171.04977	253.22975	247.84398
	Igor	Jane						
	350.33210	149.47044						

```
> coordinates(caribou)
```


	x	y
Alice	-30.230719	-16.677306
Bob	-10.755234	-16.146952
Clark	9.657445	13.495304
Daisy	11.463725	13.919743
Eric	-12.790430	-1.629268
Franz	23.505723	-18.996257
Gabby	-13.174640	-19.172969
Hayley	22.606989	18.325854
Igor	14.912511	24.787351
Jane	-24.689211	6.129674

```
> ## conventional plotting method - agents don't plot properly when it is a raster stack
> #plot(habitat)
> #plot(caribou, add=TRUE)
```

```

>
> # convenient plotting using simPlot
> simPlot(habitat,col = cols[c(2:5,3)])
> simPlot(caribou,on.which.to.plot=c(2,3,5),pch=19,size=unit(0.1,"inches"))
> drawArrows(from = SpatialPoints(cbind(x=prevX,y=prevY)),
+           to = caribou,
+           on.which.to.plot = "DEM")

```



5 A simple fire model

Burn some of the forest Using the spread function, we can simulate fires, and subsequent changes to the various map layers. Here, spreadProb can be a single probability or a raster map where each pixel has a probability. In the example below, each cell's probability is taken from the Percent Pine map layer.

```

> nFires <- 10 # number of agents
> habitat[["Fires"]] <- spread(habitat[[1]],loci=as.integer(sample(1:ncell(habitat),nFires)),
+                             spreadProb = .225,#habitat[["Pct_Pin"]]/(maxValue(habitat[["Pct_Pin"]]))*0.2,
+                             persistance=0,
+                             mapFireID=T,
+                             mask = NULL,
+                             maxSize = 1e8,


```

```

+                               directions = 8,
+                               iterations=1e6,
+                               plot.it=F,
+                               mapID=T)
> simPlot(habitat[["Fires"]])

> # Show the burning more strongly over abundant pine
> simPlot(habitat[["Pct_Pin"]],col=cols[[3]])
> simPlot(habitat[["Fires"]],add=T,delete.previous=F,col=cols[[1]])

```



We can see that the fires tend to be in the Pines because we made it that way, using an arbitrary weighting with pine abundance

```

> # Show the burning more strongly over abundant pine
> fire<-reclassify(habitat[["Fires"]],rcl= cbind(0:1,c(0,ncell(habitat)),0:1))
> pine<-reclassify(habitat[["Pct_Pin"]],rcl= cbind(0:9*10,1:10*10,0:9))
> PineByFire<-crosstab(fire,pine,long=T)
> colnames(PineByFire)<-c("fire","pine","freq")
> PineByFire$pine <- as.numeric(as.character(PineByFire$pine))
> summary(glm(freq ~ fire*pine, data=PineByFire,family="poisson"))

```



```
Call:
glm(formula = freq ~ fire * pine, family = "poisson", data = PineByFire)
```

Deviance Residuals:

	Min	1Q	Median	3Q	Max
	-46.909	-24.265	-6.621	17.245	34.913

Coefficients:

	Estimate	Std. Error	z value	Pr(> z)
(Intercept)	7.172729	0.017146	418.324	< 2e-16 ***
fire1	-1.379572	0.038371	-35.953	< 2e-16 ***
pine	-0.057311	0.003474	-16.495	< 2e-16 ***
fire1:pine	0.043177	0.008114	5.321	1.03e-07 ***

Signif. codes: 0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1

(Dispersion parameter for poisson family taken to be 1)


Null deviance: 14966 on 18 degrees of freedom
Residual deviance: 10937 on 15 degrees of freedom
AIC: 11082

Number of Fisher Scoring iterations: 5

Sure enough, there are more fires as the abundance of pine goes up, as seen by the positive interaction term (the negative fire1 term means that there are more pixels without fires than with fires).

Impact some of the forest

```
> habitat[["Age"]][habitat[["Fires"]]>0] <- 0
> habitat[["Forest_Cover"]][habitat[["Fires"]]>0] <- 0
> habitat[["HabitatQuality"]][habitat[["Fires"]]>0] <- 0.1
> habitat[["Pct_Pin"]][habitat[["Fires"]]>0] <- 0
> simPlot(habitat,col = cols[c(2:5,3,1)])
```



6 A simple individual based model (IBM)

Move some agents Using a simple habitat dependent correlated random walk, simulate the movement of caribou across a heterogeneous landscape. Because we had just had fires, and we assume that fires have a detrimental effect on animal movement, we can see the long steps taken in the new, low quality, post-burn sections of the landscape.

```
> simPlot(habitat[["HabitatQuality"]],col = cols[[3]])
> for (i in 1:10) {
+
+   #crop any caribou that went off maps
+   caribou <- crop(caribou,habitat)
+   drawArrows(from =
+               SpatialPoints(cbind(x=caribou$prevX,y=caribou$prevY)),
+               to = caribou,length=0.04,
+               on.which.to.plot = 1)
+
+   # find out what pixels the individuals are on now
+   ex = habitat[["HabitatQuality"]][caribou]
+
+   #step length is a function of current cell's habitat quality
```

```

+   sl = 0.25/ex
+
+   ln = rlnorm(length(ex), sl, 0.02) # log normal step length
+   sd = 30 # could be specified globally in params
+
+   caribou <- crw(caribou, stepLength=ln, stddev=sd, lonlat=FALSE)
+
+ }

```

