REDBIRD FLIGHT SIMULATIONS

QUALIFICATION AND APPROVAL GUIDE (QAG)

MX2 ADVANCED AVIATION TRAINING DEVICES
AMENDED QUALIFICATION AND APPROVAL GUIDE
VERSION 2.0B



Advanced Aviation Training Device(s)

2301 East St. Elmo Rd., Suite 100
Austin, Texas 78744
(512) 301-0718 Phone
(512) 301-0770 Fax
info@redbirdflight.com

FAA APPROVED QAG
Signature and Date

May 9, 2018

SHAWN M HAYES
Digitally signed by SHAWN M HAYES
Date: 2018.08.01 15:55:21 -04'00'

Shawn Hayes
Manager, Airmen Training and Certification Branch

Table of Contents

LOG OF REVISIONS 4
SECTION 1: COMPLIANCE STATEMENT 5
SECTION 2: AVIATION TRAINING DEVICE (ATD) DESCRIPTION AND PICTURES 6
Configuration Components 7
Instructor's Station 7
Aircraft Instrument Configurations 7
Modular Controls 8
SECTION 3: TRAINING DEVICE COMPONENT LIST 11
Statements of Compatibility of Software and Hardware 13
SECTION 4: AVIATION TRAINING DEVICE (ATD) DESIGN CRITERIA LIST 14
Basic ATD Requirements List [Appendix 2 items] 14
Advanced ATD Requirements List [Appendix 3 items] 17
SECTION 5: AIRCRAFT CONFIGURATIONS 19
List of Previously Approved Configurations (QAG V1.0) 19
Beechcraft BE36-S1 19
Beechcraft BE36-G1 20
Beechcraft BE55-S1 21
Beechcraft BE58-S1 22
Beechcraft BE58-S2 23
Beechcraft BE58-G1 24
Beechcraft BE76-S1 25
Cessna C172-S1 26
Cessna C172-S2 27
Cessna C172-G1 28
Cessna C172-G2 29
Cessna C182-S1 30
Cessna C182-S2 31
Cessna C182-G1 32
Cessna C182-G2 33
Cessna C206-S1 34
Cessna C206-S2 35
Cessna C206-G1 36
Cessna C206-G2 37
Cirrus SR20-G1 38
Cirrus SR20-G2 39
Cirrus SR22-G1 40
Cirrus SR22-G2 41
Diamond DA20-S1 42
Diamond DA40-G1 43
Diamond DA42-G1 44
Liberty LXL2-S1 45
Liberty LXL2-S2 46
Piper Warrior PA28-60-S1 47
Piper Warrior PA28-60-S2 48

Piper Warrior PA28-60-G1 49
Piper Archer PA28-80-S1 50
Piper Archer PA28-80-S2 51
Piper Arrow PA28-2R-S1 52
Piper Arrow PA28-2R-S2 53
Piper Arrow PA28-2R-G1 54
Piper Seneca PA34-S1 55
Piper Seneca PA34-G1 56
Piper Seminole PA44-S1 57
Piper Seminole PA44-G1 58
Socata TB10-S1 59
Tecnam P2006-G1 60
Additional configurations included in this version (QAG V2.0B) 61
Cessna C206T-S1 61
Diamond DA40-G2 62
Diamond DA42L-G2 63
Mooney M20-G1 64
Piper Archer PA28-80-G1 65
Piper Arrow PA28-2R-G2 66
Piper Seminole PA44T-S1 67
Performance Table 68
SECTION 6: VISUAL SYSTEM WITH IFR, VFR, DAY, AND NIGHT CAPABILITY 70
SECTION 7: ATD FUNCTIONS & MANEUVERS CHECKLISTS 72

LOG OF REVISIONS

Description of Changes	Version	Edited By
Original	1.0	CG
Added Log of Revisions	2.0	WJ
Updated Section 1 Device Overview	2.0	WJ
Removed List of Applicable Configurations from Section 1	2.0	WJ
Replaced Section 2 with Overall Aviation Training Device and Description and Pictures	2.0	WJ
Moved Figures subsections from Section 4 to Section 2	2.0	WJ
Replaced Section 3 with Training Device Components Lists	2.0	WJ
Added Win10, Navigator to Table 1 in Section 3	2.0	WJ
Moved Statements of Compatibility to Section 3	2.0	WJ
Replaced Section 4 with ATD Design Criteria	2.0	WJ
Moved Statement of Compliance to Section 4	2.0	WJ
Updated Display Requirements (1) and (2)	2.0	WJ
Added Performance tables to Section 4	2.0	WJ
Added Section 5 Aircraft Configurations	2.0	WJ
Moved Previously Approved Configurations to Section 5	2.0	WJ
Edited redundant information from aircraft configuration	2.0	WJ
Added PA28-80-G1 configuration for approval	2.0	WJ
Added DA40-G2 configuration for approval	2.0	WJ
Added DA42-G2 configuration for approval	2.0	WJ
Added PA28-2R-G2 configuration for approval	2.0	WJ
Added C206T-S1 configuration for approval	2.0	WJ
Added M20-G1 configuration for approval	2.0	WJ
Added PA44T-S1 configuration for approval	2.0	WJ
Added Section 6 Visual System details	2.0	WJ
Added Section 7 ATD Functions and Maneuvers Checklist	2.0	WJ
Renamed Section 1 Compliance Statement	2.0A	WJ
Added Figures 4.7, 4.8, 5.5, 6.1 and 6.2 to Section 2	2.0A	WJ
Added Optional CAPS to Table 1 in Section 3	2.0A	WJ
Added Control Loading (Single) yokes to Table 1 in Section 3	2.0A	WJ
Added Control Loading (Single) rudder pedals to Table 1 in Section 3	2.0A	WJ
Updated misc. images in Section 2	2.0A	WJ
Updated images in Section 5	2.0A	WJ
Moved Figure 5.4 to Section 5	2.0A	WJ
Added W&B, component list to Section 5 aircraft configurations	2.0A	WJ
Consolidated Groups 1 – 5 in Section 5 into Configuration Components	2.0A	WJ
Updated Performance Table	2.0A	WJ
Updated panel images in Section 5	2.0B	WJ

SECTION 1: COMPLIANCE STATEMENT

This Qualification and Approval Guide (QAG) includes a detailed description of all components, functions, and capabilities for a variety of the Redbird models. This includes any optional aircraft configurations with quality color pictures and diagrams. The required information as described in the current advisory circular, AC 61-136A / FAA Approval of Aviation Training Devices (ATD) and Their Use for Training and Experience, required for FAA approval, is contained within this document. This includes listing all the required qualifying items, functions, and capabilities. This QAG is used to clearly describe and verify the functionality of this aviation training device platform confirming its suitability for airman training and experience. A valid FAA Letter of Authorization (LOA) specifying the ATD allowances must also accompany the training device when utilized for airman training or experience requirements as specified in 14 CFR §61 or 141.

This ATD must continue to maintain its performance and function without degradation. The operator of this device is expected to maintain its condition and functionally when used for airmen training or experience requirements. Only the configurations approved for this model, as described within this QAG, can be utilized when satisfying FAA experience or training requirements. Any additions, changes, or revisions to the model or to the available configurations described within this document must be approved in writing by The General Aviation and Commercial Division, AFS-800.

Any questions concerning FAA approval of ATDs should be directed to the General Aviation and Commercial Division, AFS-800.

SECTION 2: AVIATION TRAINING DEVICE (ATD) DESCRIPTION AND PICTURES

The Redbird models are based on the dimensions and layout of a several production aircraft. These models closely represent the overall functionality, performance, avionics, and instrumentation. The platform consists of a cockpit section, instructor's control station, visual display system and an audio system. It incorporates a combination of hardware and software components that is assembled and checked by Redbird Flight Simulations. All hardware elements are permanently installed and designed so the cockpit has the appearance and feel of an actual aircraft. From the pilot's seated position, there are no computer hardware elements such as keyboards, pointing devices, etc. for his or her use.

Redbird provides realistic and true-to-scale cockpit design, avionics, and reliable hardware/software performance. This platform also provides an effective training environment for student and certificated pilots. This includes the capability of practicing scenario based flight training events, simulated equipment failure and emergency procedures, pilot evaluations, instrument procedures/ experience, and facilitating increased pilot proficiency overall.

The Redbird MX2 is a versatile, expandable and affordable device that has been designed to be representative of popular single and twin-engine piston aircraft. They offer the user the ability to change the cockpit controls and aircraft models to represent a wide range of popular training aircraft. The line is equipped with the following notable features:

- 3-axis electric motion platform providing pitch, roll and yaw motions
- Wrap-around exterior visuals provided by 5 LCD screens
- Single pilot controls with optional 2-axis control-loaded yoke and interconnected rudder pedals
- Realistic switches, buttons, knobs, circuit breakers and other cockpit controls that are designed to represent the family of aircraft.
- An interchangeable instrument panel, throttles, and yokes to allow a quick-change configuration options to the end user.
- Closed Circuit intercom system, allowing for communication between the pilot, co-pilot and instructors using standard aviation headsets
- A portable instructors station, allowing the instructor to operate from inside or outside the simulator

Configuration Components

Instructor's Station

The Redbird Instructor Station interface is operated through any PC and/or web browser enabled device. The Instructor Station software is available as an installed program on the PC and web-browser based application. PC based Instructor Station can be on either a desktop computer or laptop/mobile PC.



Figure 5.2: Instructors PC/Tablet or Mobile Device

Aircraft Instrument Configurations

The Redbird MX2 simulator is capable of supporting multiple aircraft configurations utilizing both traditional analog instruments as well as glass panels.



Figure 5.12: Traditional 6-pack Instrument Panel Configuration (Example)



Figure 5.13: Glass Panel Instrument Configuration (Example)

Modular Controls

The modular design of the Redbird MX2 simulator allow for quick configuration changes between single and multi-engine aircraft configurations.



Figure 2.1: Center Yoke



Figure 2.2: Side Yoke



Figure 2.3: Center Stick



Figure 3.1: Single Engine Vernier Throttle Quadrant



Figure 3.2: Single Engine Complex Vernier Throttle Quadrant




Figure 3.3: Single Engine "Boat Style" Throttle Quadrant




Figure 3.4: Single Engine Complex "Boat Style" Throttle Quadrant




Figure 3.5: Twin Engine Throttle Quadrant – Type 1



Figure 3.6: Twin Engine Throttle Quadrant – Type 2




Figure 3.7: Twin Engine Throttle Quadrant – Type 3




Figure 3.8: Twin Engine Throttle Quadrant – Type 4



Figure 6.1: Optional CAPS for Cirrus Configurations



Figure 6.2: Optional CAPS for Cirrus Configurations



Figure 4.1: Left Side of Lower Switch Panel Type 3



Figure 4.3: Manual Trim Wheel Switch Panel Type 3



Figure 4.2: Right Side of Lower Switch Panel Type 3



Figure 4.7: Switch Panel 1 Starter Switch*



Figure 4.8: Switch Panel 1 Starter Switch*



Figure 5.1: Training Session Buttons*



Figure 5.5: Training Session Buttons*




Figure 5.3: Rudder Pedals – Single

*May vary by serial number



Figure 5.6: Example Assembled Cockpit Configuration



Figure 5.7: External Shroud and Motion Platform Type 2

SECTION 3: TRAINING DEVICE COMPONENT LIST

Qty	Type	Manufacturer	Name	Description/Function	Configuration
1	Software	Microsoft	Windows XP, 7, or 10	Operating system. (depending on serial number)	All
1	Software	Microsoft	ESP or FSX	Simulation engine. (depending on serial number)	All
1	Software	Lockheed Martin	Prepar3D	Simulation engine. (depending on serial number)	All
1	Software	Redbird Flight Simulations	RB Sim	Simulation control and component integration.	All
1	Software	Redbird Flight Simulations	MX2 Control	Motion system control and component integration.	All
1	Software	Redbird Flight Simulations	Instructors Station	Environmental, location and failure controls with map, track and glideslope display.	All
1	Software	Redbird Flight Simulations	Navigator	Simulation control and component integration. Environmental, location and failure controls with map, track and glideslope display.	All
1	Software	Redbird Flight Simulations	Parrot and Cygnus	Optional software providing ATC and location services	All
1	Software	Mindstar Aviation	Redbird 1000	Virtual flight instruments, GPS, radios, gauges, indicators, alerts, misc. instruments and logic controls for simulated systems.	See Configuration
1	Software	Mindstar Aviation	Redbird 430/ 530	Virtual GPS and radios	See Configuration
1	Software	Mindstar Aviation	Redbird KLN94	Virtual GPS	See Configuration
1	Software	Mindstar Aviation	Redbird EFD1000	Virtual EFD	See Configuration
1	Software	Mindstar Aviation	Redbird Entegra	Virtual flight instruments, radios, gauges, indicators, alerts, misc. instruments and logic controls for simulated systems.	See Configuration
1	Software	Mindstar Aviation	Redbird Autopilot	Virtual Autopilot (Redbird 140, 55, or 700)	See Configuration
1	Software	Mindstar Aviation	Redbird Radios	Virtual Radios (KX155, SL40)	See Configuration
1	Software	Mindstar Aviation	Miscellaneous Gauges	Virtual Miscellaneous Gauges	See Configuration
1	Software	Flight 1	Compass	Virtual Compass	All
1	Software	Redbird Flight Simulations	Analog Gauges	Virtual Airspeed, Attitude, Altimeter, Turn and Bank, Heading, HSI, VSI, RMI, CDI, and ADF Gauges , Radios	See Configuration
1	Software	Redbird Flight Simulations	Miscellaneous Gauges	Virtual Miscellaneous Gauges	All
1	Hardware	Redbird Flight Simulations	Simulation Computer	Host computer for flight simulation engine, simulation control software, airplane systems and instruments.	All
1	Hardware	Redbird Flight Simulations	Motion Control Computer	Host computer for MX2 Control.	All
1	Hardware	Industry Standard	Instructors Station Computer or Wireless Mobile Device	Host computer for Instructors Station.	All
1	Hardware	Redbird Flight Simulations	Motion Platform: Type 2	Gimbaled, steel motion platform with movement in pitch, roll and yaw. Includes all motors, sensors and safety controls.	All
1	Hardware	Redbird Flight Simulations	Cockpit Enclosure	Cockpit enclosure to exclude distractions.	All
5	Hardware	22" LCD Industry Standard Monitor	Visual Display	Flat Panel displays for exterior views.	All

2	Hardware	19" LCD Industry Standard Monitor	LCD	Flat Panel displays for virtual instruments.	All
1	Hardware	Redbird Flight Simulations	Yoke, Side Yoke, Center Stick	Pitch and roll controller with switches and buttons for airplane systems operation. As required for each configuration.	All – Varies by configuration
1	Hardware	Redbird Flight Simulations	Yoke, Side Yoke, Center Stick (Single) – Control Loading	Optional Control loading pilot yoke with pitch and roll controller and switches and buttons for airplane systems operation. As required for each configuration.	All – Varies by configuration
1	Hardware	Redbird Flight Simulations	Throttle Quadrant	As required for each configuration.	All- See Configuration
1	Hardware	Redbird Flight Simulations	Rudder Pedals - Single	Rudder control pedals with toe brakes.	All – Varies by configuration
1	Hardware	Redbird Flight Simulations	Rudder Pedals (Single) – Control Loading	Optional Control loading pilot rudder control pedals with toe brakes.	All – Varies by configuration
1	Hardware	Redbird Flight Simulations	Switch Panel: Type 3	Lower switch panel with airplane configuration and systems controls.	All
1	Hardware	Redbird Flight Simulations	Instrument Controls Overlay	Flight instruments, radios, airplane configuration and systems controls as required for each configuration.	All- See Configuration
1	Hardware	Redbird Flight Simulations	CAPS	Optional CAPS	All – See Configuration

Table 1: Training Device Component List (Above)

Statements of Compatibility of Software and Hardware

AC 61-136A, Appendix 1, 5.b.:

The device and all configurations included in this Qualification and Approval Guide (QAG) meet the requirements for the Compatibility of Software and Hardware.

Microsoft Windows (Operating System)

“This is to certify that Microsoft Corporation, the owner and developer of the Windows operating system, has evaluated that their operating system works with industry standard PC’s and USB flight control devices. Redbird Flight Simulations, Inc., utilizes industry standard USB flight control devices for all pilot input. All input control devices meet the USB 2.0 industry standard specified interfaces. Redbird Flight Simulations, Inc., the component integrator, has determined that the transport delay time is less than 300 milliseconds, and that all analog and digital input signals meet the performance criteria established for the software.”

Lockheed Martin Prepar3D (Simulation Engine)

This is to certify that Lockheed Martin, the owner and developer of the Prepar3D Simulator Engine, has evaluated that their software application works with industry standard PC’s and USB flight control devices. Redbird Flight Simulations, Inc., utilizes industry standard USB flight control devices for all pilot input. All input control devices meet the USB 2.0 industry standard specified interfaces. Redbird Flight Simulations, Inc., the component integrator, has determined that the transport delay time is less than 300 milliseconds, and that all analog and digital input signals meet the performance criteria established for the software

Mindstar Aviation Redbird Virtual Instrument Suite

This is to certify that Mindstar Aviation, the owner and developer of the Redbird Virtual Instrument Suite, including the Redbird 1000, Redbird 430/530, Redbird KLN94, Redbird 140 Autopilot, Redbird 55 Autopilot, Redbird Radios, Redbird Entegra and Redbird Perspective and Redbird Flight Simulations, the hardware manufacturer and component integrator, have demonstrated that the Redbird Virtual Instrument Suite software package is fully compatible with the Redbird Flight Simulations MX2. Mindstar Aviation and Redbird Flight Simulations can assure that the communications/transport data delay is not greater than 300 milliseconds and all analog and digital input signals meet the performance criteria established for the software performance by Redbird Flight Simulations**.**

The device and all configurations included in this Qualification and Approval Guide (QAG) meet the requirements for the Compatibility of Software and Hardware.

Flight 1 Compass

"This is to certify that Flight 1, the owner and developer of the Compass and Redbird Flight Simulations, the hardware manufacturer and component integrator, have demonstrated that the Compass software is fully compatible with the Redbird Flight Simulations MX2. Redbird Flight Simulations can assure that the communications/transport data delay is not greater than 300 milliseconds and all analog and digital input signals meet the performance criteria established for the software performance by Redbird Flight Simulations."

SECTION 4: AVIATION TRAINING DEVICE (ATD) DESIGN CRITERIA LIST

The following section provides the detailed "word for word" listing and design criteria of each of the required items, functions, and capabilities (listed in AC 61-136A, for BATD requirements Appendix 2 and the additional AATD items of Appendix 3) and operational performance value/scale (as applicable) for each of the functions described for the Redbird MX2.

Basic ATD Requirements List [Appendix 2 items]

All configurations for this model, as noted, meet AC 61-136A, Appendix 2 requirements

a. The Redbird MX2 meets the following Control Input requirements:

(1) Physical flight and aircraft control systems are designed such that they are recognizable as to their function and how they are manipulated solely from their appearance. No keyboard, mouse, or gaming joystick is used to control the aircraft.
(2) Virtual controls are limited to setting the aircraft configuration, location, weather conditions, and pausing action.
(3) No keyboard or mouse is used to set or position any of the below listed features of this device. The required and additional equipment is operated in the same manner in which it would be operated in the aircraft represented (as applicable). This includes the landing gear, wing flaps, cowl flaps, carburetor heat, and mixture, propeller, and throttle controls.
(4) The physical arrangement, appearance, and operation of controls, instruments, and switches (as applicable) closely represents the model of aircraft including: Master/battery, magnetos, alternators/generators, auxiliary power units, fuel boost/prime pumps, avionics master, pitot heat, rotation beacon/strobe, navigation, taxi, and landing lights.
(5) Only the software evaluated and approved by the FAA is installed on this computer system.

b. The Redbird MX2 meets the following Control Requirements:

(1) Airplane
  (a) Self-centering control yoke or control stick that allows continuous adjustment of pitch and bank
  (b) Self-centering rudder pedals rudder pedals that allow continuous adjustment of yaw and corresponding reaction in heading and roll.
  (c) Throttle or Power controls/levers as applicable that allows for continuous movement from idle to full power, with corresponding changes in pitch and yaw.
  (d) Mixture/condition, propeller, and throttle/power control(s) as applicable to the model aircraft represented
  (e) Controls for the following items applicable to the aircraft represented:
    - Wing flaps,
    - Pitch trim,
    - Communication and navigation radios,
    - Clock or timer,
    - Gear handle (if applicable),
    - Transponder,
    - Altimeter,
    - Carburetor heat (if applicable), and
    - Cowl flaps (if applicable).

c. The Redbird MX2 meets the following Control Input requirements:

(1) Time from control input to recognizable system response must be without delay (i.e., not appear to lag in any way). “Redbird Flight Simulations, Inc.” verifies that the “Redbird MX2” meets this requirement.
(2) The control inputs are tested by the computer and software at each session startup and displayed as a confirmation message or a “warning message” that the transport delay time or any design parameter is out of original tolerances. It is not possible to continue the training session unless the problem is resolved and all components are functioning properly. This test considers the items listed in the display requirements.

d. The Redbird MX2 meets the following Display Requirements:

(1) **Instruments and indicators** replicated and properly located as appropriate to the aircraft model represented:

Flight instruments in a standard configuration, represented as traditional “round dial” flight instruments, or as an electronic primary flight instrument display (PFD) and multi-function display (MFD) with reversionary and back-up flight instruments.

- A sensitive **altimeter** with incremental markings each 20 feet or less, operable throughout the normal operating range of the aircraft or family of aircraft represented.
- A **magnetic direction indicator**.
- A **heading indicator** with incremental markings each 5 degrees or less, displayed on a 360 degree circle. Arc segments of less than 360 degrees may be selectively displayed if desired or required, as applicable to the aircraft or family of aircraft represented.
- An **airspeed indicator** with incremental markings as shown on the aircraft or family of aircraft represented; airspeed markings of less than 40 knots need not be displayed.
- A **vertical speed indicator** with incremental markings each 100 feet per minute (fpm) for both climb and descent, for the first 1,000 fpm of climb and descent, and at each 500 fpm climb and descent for the remainder of a minimum ± 2,000 fpm total display, or as applicable to the aircraft or family of aircraft being represented.
- A **gyroscopic rate-of-turn indicator** or equivalent with appropriate markings for a rate of 3 degrees per second turn for left and right turns. If a turn and bank indicator is used, the 3 degrees per second rate index must be inside of the maximum deflection of the indicator.
- A **slip and skid indicator** with coordination information displayed in the conventional skid ball format where a coordinated flight condition is indicated with the ball in the center position. A bar or split image triangle indication may be used if the aircraft is equipped with an electronic PFD.
- An **attitude indicator** with incremental markings each 5 degrees of pitch or less, from 20 degree pitch up to 40 degree pitch down or as applicable to the aircraft or family of aircraft represented. Bank angles must be identified at “wings level” and at 10, 20, 30, and 60 degrees of bank (with an optional additional identification at 45 degrees) in left and right banks.
- **Engine instruments** as applicable to the aircraft or family of aircraft being represented, providing markings for normal ranges and minimum and maximum limits.
- A **suction gauge** or instrument pressure gauge, if applicable, with a display appropriate to the model of aircraft represented.
- A **flap setting indicator** that displays the current flap setting. Setting indications should be typical of that found in an actual aircraft.
- A **pitch trim indicator** with a display that shows zero trim and appropriate indices of airplane nose down and airplane nose up trim, as would be found in an aircraft.
- **Communication radio(s)** with display(s) of the radio frequency in use.
- A **clock** with incremental markings for each minute and second, or a timer with a display of minutes and seconds,

- A **transponder** that displays the current transponder setting.
- A **fuel quantity indicator(s)** that displays the fuel remaining, either in analog or digital format, as appropriate for the aircraft or family of aircraft represented.

Navigation Equipment: Replicates both precision and non-precision instrument navigation, including approach procedures (with an aural identification feature if normally available), and a marker beacon receiver. Examples: an ILS receiver, non-directional radio beacon (NDB), Global Positioning System (GPS), Localizer (LOC) or Very high frequency Omnidirectional Range (VOR). Graduated markings as indicated below are present on each course deviation indicator as applicable.

Required markings include:

- One-half dot or less for **course/glide slope deviation indicator** (i.e., VOR, LOC, or ILS),
- 5 degrees or less for bearing deviation for automatic direction finder (ADF) and radio magnetic indicator (RMI), as applicable.
- If equipped with a PFD and/or MFD, the flight and navigation information and guidance must replicate the avionics manufactures same scales and navigation information presentation provided in the aircraft equipment.

(2) All instrument displays listed above must be visible during all flight operations. The update rate of all displays must provide an image of the instrument that:
   (a) Does not appear to be out of focus or illegible
   (b) Does not appear to "jump" or "step" to a distracting degree during operation.
   (c) Does not appear with distracting jagged lines or edges.
   (d) Does not appear to lag relative to the action and use of the flight controls.

(3) Control inputs are reflected by the flight instruments in real time and without a perceived delay in action. Display updates or actions show all changes (within the total range of the replicated instrument) that are equal to or greater than the following:

   (a) Airspeed indicator: change of 5 knots.
   (b) Attitude indicator: change of 2 degrees in pitch and bank.
   (c) Altimeter: change of 10 feet.
   (d) Turn and bank: change of ¼ standard rate turn.
   (e) Heading indicator: change of 2 degrees.
   (f) Vertical speed indicator (VSI): change of 100 fpm.
   (g) Tachometer: change of 25 rpm or 2 percent of turbine speed.
   (h) VOR/ILS: change of 1 degree for VOR or ¼ of 1 degree for ILS.
   (i) ADF: change of 2 degrees.
   (j) GPS: change as appropriate for the model of GPS based navigator represented.
   (k) Clock or timer: change of 1 second.

(4) **Flight Displays reflect proper dynamic behavior**. Examples: VSI reading of 500 fpm reflects a corresponding movement in altimeter. Throttle movement reflects an appropriate change in pitch, rpm indication, or the power indicator. Pitch changes reflect an appropriate change in airspeed and altitude.

e. The Redbird MX2 meets the following Flight Dynamics Requirements:

(1) All flight dynamics are comparable to the way the represented airplane performs and handles.
(2) All simulated aircraft performance parameters (such as maximum speed, cruise speed, stall speed, maximum climb rate and hovering/sideward/forward/rearward flight) are comparable to the airplane

represented. A performance table is included in the QAG for each aircraft configuration for sea level and 5,000 feet.

(3) Vertical lift component changes as a function of bank/load factor, comparable to the aircraft represented.

(4) Changes in flap setting and gear position are accompanied by changes in flight dynamics comparable and reasonably equivalent to the aircraft represented

(5) The presence and intensity of wind and turbulence must be reflected in the handling and performance qualities of the simulated aircraft and should be comparable to the way the aircraft or family of aircraft represented performs and handles.

f. The Redbird MX2 meets the following Instructional Management Requirements:

(1) The instructor can pause the system at any point during the training session for the purpose of administering instruction regarding the training task at hand.

(2) If a training session begins with the "aircraft in the air" and ready for the performance of a particular procedural task, the instructor can manipulate the following system parameters independently of the simulation:

- Aircraft geographic location,
- Aircraft heading,
- Aircraft airspeed,
- Aircraft altitude, and
- Wind direction, speed, and turbulence.

(3) The system is capable of recording both a horizontal and vertical track of aircraft movement for the entire training session for later playback and review.

(4) The instructor can disable any of the instruments prior to or during a training session and simulate failure of any of the instruments without stopping the flight simulation to affect the failure.

(5) The ATD has an available navigational database that is local to the training facility. All navigational data must be based on procedures as published per 14 CFR part 97.

Advanced ATD Requirements List [Appendix 3 items]

All configurations, as noted in AC 61-136A, Appendix 3 meet these additional AATD design criteria items listed.

a. The Redbird MX2 meets the following additional AATD CRITERIA:

(1) A realistic shrouded (enclosed) or unshrouded (open) cockpit design and instrument panel arrangement representing a specific model aircraft cockpit.

(2) **Cockpit knobs, system controls, switches, and/or switch panels in realistic sizes and design** appropriate to each intended functions, in the proper position and distance from the pilot's seated position, and representative of the category and class of aircraft being represented.

(3) Primary flight and navigation instruments appropriately sized and properly arranged that exhibit neither stepping nor excessive transport delay.

(4) Digital Avionics Panel

(5) **Global Positioning System (GPS)** navigator with moving map display.

(6) **Two-axis autopilot**, and, as appropriate, a flight director (FD). This is not required for an ATD representing a helicopter.

(7) **Pitch trim** (manual or electric pitch trim) permitting indicator movement either electrically or analog in an acceptable trim ratio.
(8) An independent **visual system**, panel, or screen that provides realistic cues in both day and night visual flight rules (VFR) and instrument flight rules (IFR) meteorological conditions to enhance a pilot's visual orientation in the vicinity of an airport including:
- Adjustable visibility parameters; and
- Adjustable ceiling parameters.

(9) A **pilot seat** appropriate to the aircraft configuration.
(10) **Rudder pedals** secured to the cockpit floor structure, or that can be physically secured to the floor beneath the device in proper relation to cockpit orientation.
(11) Push-to-talk switch on the control yoke.
(12) A **separate instructor station** to permit effective interaction without interrupting the flight in overseeing the pilot's horizontal and vertical flight profiles in real time and space. This must include the ability to:
(a) Oversee tracks along airways, holding entries and patterns, and Localizer (LOC) and glideslope (GS) alignment/deviation (or other approaches with a horizontal and vertical track).
(b) Function as air traffic control (ATC) in providing vectors, etc., change in weather conditions, ceilings, visibilities, wind speed and direction, light/moderate/severe turbulence, and icing conditions.
(c) Invoke failures in navigation and instruments, radio receivers, landing gear and flaps, engine power (partial and total), and other aircraft systems (pitot, electric, static, etc.) by using either a keyboard or mouse.
(13) Capable of simulating all of the emergency procedures for which a checklist is prescribed in the aircraft pilot's operating handbook (POH) or flight manual.

b. The Redbird MX2 meets the following additional encouraged AATD CRITERIA:

(2) Motion capability with simulated bank, yaw, and pitch ques
(3) Loss of performance and aerodynamic changes from ice accretion
(4) Realistic aircraft engine sound appropriate to the aircraft configuration, power settings, and speed.
A magnetic compass with incremental markings each 5 degrees, that displays the proper lead or lag during turns, and displays incremental markings typical of that shown in the aircraft.

SECTION 5: AIRCRAFT CONFIGURATIONS

List of Previously Approved Configurations (QAG V1.0):

Beechcraft BE36-S1



MTOW	FWD/AFT CG Limit
3600 lbs	81 in / 87.7 in

- **Yoke – Center (See Figure 2.1)**
- **Throttle – Single Engine Complex Lever (T-P-M) (See Figure 3.4)**
- **Traditional analog gauges & 430/530 GPS with KAP140 Autopilot**

Beechcraft BE36-G1



MTOW	FWD/AFT CG Limit
3600 lbs	81 in / 87.7 in

- **Yoke – Center (See Figure 2.1)**
- **Throttle – Single Engine Complex Lever (T-P-M) (See Figure 3.4)**
- **Glass Cockpit G1000 PFD/MFD & GFC700 Autopilot**

Beechcraft BE55-S1



MTOW	FWD/AFT CG Limit
5000 lbs	80 in / 86 in

- **Yoke – Center (See Figure 2.1)**
- **Throttle – Twin Engine Complex Lever (PP-TT-MM) (See Figure 3.6)**
- **Traditional analog gauges & 430/530 GPS with KAP140 Autopilot**

Beechcraft BE58-S1



MTOW	FWD/AFT CG Limit
5500 lbs	78 in / 86 in

- **Yoke – Center (See Figure 2.1)**
- **Throttle – Twin Engine Complex Lever (PP-TT-MM) (See Figure 3.6)**
- **Traditional analog gauges & 430/530 GPS with KAP140 Autopilot**

Beechcraft BE58-S2



MTOW	FWD/AFT CG Limit
5500 lbs	78 in / 86 in

- **Yoke – Center (See Figure 2.1)**
- **Throttle – Twin Engine Complex Lever (TT-PP-MM) (See Figure 3.5)**
- **Traditional analog gauges & 430/530 GPS with KAP140 Autopilot**

Beechcraft BE58-G1



MTOW	FWD/AFT CG Limit
5500 lbs	78 in / 86 in

- **Yoke – Center (See Figure 2.1)**
- **Throttle – Twin Engine Complex Lever (TT-PP-MM) (See Figure 3.5)**
- **Glass Cockpit G1000 PFD/MFD & GFC700 Autopilot**

Beechcraft BE76-S1



MTOW	FWD/AFT CG Limit
3900 lbs	110.6 in / 117.5 in

- **Yoke – Center (See Figure 2.1)**
- **Throttle – Twin Engine Complex Lever (TT-PP-MM) (See Figure 3.5)**
- **Traditional analog gauges & 430/530 GPS with KAP140 Autopilot**

Cessna C172-S1



MTOW	FWD/AFT CG Limit
2550 lbs	41 in / 47.3 in

- **Yoke – Center (See Figure 2.1)**
- **Throttle – Single Engine Vernier (T-M) (See Figure 3.1)**
- **Traditional analog gauges & 430/530 GPS with KAP140 Autopilot**

Cessna C172-S2



MTOW	FWD/AFT CG Limit
2550 lbs	41 in / 47.3 in

- **Yoke – Center (See Figure 2.1)**
- **Throttle – Single Engine Vernier (T-M) (See Figure 3.1)**
- **Traditional analog gauges & KLN94 GPS with KAP140 Autopilot**

Cessna C172-G1



MTOW	FWD/AFT CG Limit
2550 lbs	41 in / 47.3 in

- **Yoke – Center (See Figure 2.1)**
- **Throttle – Single Engine Vernier (T-M) (See Figure 3.1)**
- **Glass Cockpit G1000 PFD/MFD & KAP140 Autopilot**

Cessna C172-G2



MTOW	FWD/AFT CG Limit
2550 lbs	41 in / 47.3 in

- **Yoke – Center (See Figure 2.1)**
- **Throttle – Single Engine Vernier (T-M) (See Figure 3.1)**
- **Glass Cockpit G1000 PFD/MFD & GFC700 Autopilot**

Cessna C182-S1



MTOW	FWD/AFT CG Limit
3100 lbs	40.9 in / 46 in

- **Yoke – Center (See Figure 2.1)**
- **Throttle – Single Engine Complex Vernier (T-P-M) (See Figure 3.2)**
- **Traditional analog gauges & 430/530 GPS with KAP140 Autopilot**

Cessna C182-S2



MTOW	FWD/AFT CG Limit
3100 lbs	40.9 in / 46 in

- **Yoke – Center (See Figure 2.1)**
- **Throttle – Single Engine Complex Vernier (T-P-M) (See Figure 3.2)**
- **Traditional analog gauges & KLN94 GPS with KAP140 Autopilot**

Cessna C182-G1



MTOW	FWD/AFT CG Limit
3100 lbs	40.9 in / 46 in

- **Yoke – Center (See Figure 2.1)**
- **Throttle – Single Engine Complex Vernier (T-P-M) (See Figure 3.2)**
- **Glass Cockpit G1000 PFD/MFD & KAP140 Autopilot**

Cessna C182-G2



MTOW	FWD/AFT CG Limit
3100 lbs	40.9 in / 46 in

- **Yoke – Center (See Figure 2.1)**
- **Throttle – Single Engine Complex Vernier (T-P-M) (See Figure 3.2)**
- **Glass Cockpit G1000 PFD/MFD & GFC700 Autopilot**

Cessna C206-S1



MTOW	FWD/AFT CG Limit
3600 lbs	42.5 in / 49.7 in

- **Yoke – Center (See Figure 2.1)**
- **Throttle – Single Engine Complex Vernier (T-P-M) (See Figure 3.2)**
- **Traditional analog gauges & 430/530 GPS with KAP140 Autopilot**

Cessna C206-S2



MTOW	FWD/AFT CG Limit
3600 lbs	42.5 in / 49.7 in

- **Yoke – Center (See Figure 2.1)**
- **Throttle – Single Engine Complex Vernier (T-P-M) (See Figure 3.2)**
- **Traditional analog gauges & KLN94 GPS with KAP140 Autopilot**

Cessna C206-G1



MTOW	FWD/AFT CG Limit
3600 lbs	42.5 in / 49.7 in

- **Yoke – Center (See Figure 2.1)**
- **Throttle – Single Engine Complex Vernier (T-P-M) (See Figure 3.2)**
- **Glass Cockpit G1000 PFD/MFD & KAP140 Autopilot**

Cessna C206-G2



MTOW	FWD/AFT CG Limit
3600 lbs	42.5 in / 49.7 in

- **Yoke – Center (See Figure 2.1)**
- **Throttle – Single Engine Complex Vernier (T-P-M) (See Figure 3.2)**
- **Glass Cockpit G1000 PFD/MFD & GFC700 Autopilot**

Cirrus SR20-G1



MTOW	FWD/AFT CG Limit
3000 lbs	144.1 in / 148 in.

- **Yoke – Left (See Figure 2.2)**
- **Throttle – Single Engine Lever (T-M) (See Figure 3.3)**
- **Glass Cockpit Entegra PFD/MFD & Dual 430 GPS with STEC55 Autopilot**

Cirrus SR20-G2



MTOW	FWD/AFT CG Limit
3000 lbs	144.1 in / 148 in.

- **Yoke – Left (See Figure 2.2)**
- **Throttle – Single Engine Lever (T-M) (See Figure 3.3)**
- **Glass Cockpit Perspective PFD/MFD & FMS Keypad with Perspective Autopilot**

Cirrus SR22-G1



MTOW	FWD/AFT CG Limit
3400 lbs	142.3 in / 148.1 in

- **Yoke – Left (See Figure 2.2)**
- **Throttle – Single Engine Lever (T-M) (See Figure 3.3)**
- **Glass Cockpit Entegra PFD/MFD & Dual 430 GPS with STEC55 Autopilot**

Cirrus SR22-G2



MTOW	FWD/AFT CG Limit
3400 lbs	142.3 in / 148.1 in

- **Yoke – Left (See Figure 2.2)**
- **Throttle – Single Engine Lever (T-M) (See Figure 3.3)**
- **Glass Cockpit Perspective PFD/MFD & FMS Keypad with Perspective Autopilot**

Diamond DA20-S1



MTOW	FWD/AFT CG Limit
1609 lbs	9.84 in / 15.4 in

- **Yoke – Stick (See Figure 2.3)**
- **Throttle – Single Engine Lever (T-M) (See Figure 3.3)**
- **Traditional analog gauges & 430 GPS with STEC55 Autopilot**

Diamond DA40-G1



MTOW	FWD/AFT CG Limit
2535 lbs	96.9 in / 102.0 in

- **Yoke – Stick (See Figure 2.3)**
- **Throttle – Single Engine Complex Lever (T-P-M) (See Figure 3.4)**
- **Glass Cockpit G1000 PFD/MFD & GFC700 Autopilot**

Diamond DA42-G1



MTOW	FWD/AFT CG Limit
3935 lbs	95.47 in / 96.5 in

- **Yoke – Stick (See Figure 2.3)**
- **Throttle – Twin Engine Lever (TT-MM) (See Figure 3.7)**
- **Glass Cockpit G1000 PFD/MFD & GFC700 Autopilot**

Liberty LXL2-S1



MTOW	FWD/AFT CG Limit
1653 lbs	82.2 in / 86.8 in

- **Yoke – Stick (See Figure 2.3)**
- **Throttle – Single Engine Lever (T-M) (See Figure 3.3)**
- **Traditional analog gauges & 430/530 GPS with STEC55 Autopilot**

Liberty LXL2-S2



MTOW	FWD/AFT CG Limit
1653 lbs	82.2 in / 86.8 in

- **Yoke – Stick (See Figure 2.3)**
- **Throttle – Single Engine Lever (T-M) (See Figure 3.3)**
- **Traditional analog gauges & 430 GPS, EFD1000, SL40 & STEC55 Autopilot**

Piper Warrior PA28-60-S1



MTOW	FWD/AFT CG Limit
2440 lbs	88.3 in / 93.0 in

- **Yoke – Center (See Figure 2.1)**
- **Throttle – Single Engine Lever (T-M) (See Figure 3.3)**
- **Traditional analog gauges & Dual 430 GPS with STEC55 Autopilot**

Piper Warrior PA28-60-S2



MTOW	FWD/AFT CG Limit
2440 lbs	88.3 in / 93.0 in

- **Yoke – Center (See Figure 2.1)**
- **Throttle – Single Engine Lever (T-M) (See Figure 3.3)**
- **Traditional analog gauges & 430/530 GPS with KAP140 Autopilot**

Piper Warrior PA28-60-G1



MTOW	FWD/AFT CG Limit
2440 lbs	88.3 in / 93.0 in

- **Yoke – Center (See Figure 2.1)**
- **Throttle – Single Engine Lever (T-M) (See Figure 3.3)**
- **Glass Cockpit Entegra PFD/MFD & Dual 430 GPS with STEC55 Autopilot**

Piper Archer PA28-80-S1



MTOW	FWD/AFT CG Limit
2550 lbs	88.6 in / 93.0 in

- **Yoke – Center (See Figure 2.1)**
- **Throttle – Single Engine Lever (T-M) (See Figure 3.3)**
- **Traditional analog gauges & Dual 430 GPS with STEC55 Autopilot**

Piper Archer PA28-80-S2



MTOW	FWD/AFT CG Limit
2550 lbs	88.6 in / 93.0 in

- **Yoke – Center (See Figure 2.1)**
- **Throttle – Single Engine Lever (T-M) (See Figure 3.3)**
- **Traditional analog gauges & 430/530 GPS with KAP140 Autopilot**

Piper Arrow PA28-2R-S1



MTOW	FWD/AFT CG Limit
2750 lbs	88.9 in / 91.5 in

- **Yoke – Center (See Figure 2.1)**
- **Throttle – Single Engine Complex Lever (T-P-M) (See Figure 3.4)**
- **Traditional analog gauges & Dual 430 GPS with STEC55 Autopilot**

Piper Arrow PA28-2R-S2



MTOW	FWD/AFT CG Limit
2750 lbs	88.9 in / 91.5 in

- **Yoke – Center (See Figure 2.1)**
- **Throttle – Single Engine Complex Lever (T-P-M) (See Figure 3.4)**
- **Traditional analog gauges & 430/530 GPS with KAP140 Autopilot**

Piper Arrow PA28-2R-G1



MTOW	FWD/AFT CG Limit
2750 lbs	88.9 in / 91.5 in

- **Yoke – Center (See Figure 2.1)**
- **Throttle – Single Engine Complex Lever (T-P-M) (See Figure 3.4)**
- **Glass Cockpit Entegra PFD/MFD & Dual 430 GPS with STEC55 Autopilot**

Piper Seneca PA34-S1



MTOW	FWD/AFT CG Limit
4750 lbs	90.6 in / 94.6 in

- **Yoke – Center (See Figure 2.1)**
- **Throttle – Twin Engine Complex Lever (TT-PP-MM) (See Figure 3.5)**
- **Traditional analog gauges & 430/530 GPS with KAP140 Autopilot**

Piper Seneca PA34-G1



MTOW	FWD/AFT CG Limit
4750 lbs	90.6 in / 94.6 in

- **Yoke – Center (See Figure 2.1)**
- **Throttle – Twin Engine Complex Lever (TT-PP-MM) (See Figure 3.5)**
- **Glass Cockpit G1000 PFD/MFD & GFC700 Autopilot**

Piper Seminole PA44-S1



MTOW	FWD/AFT CG Limit
3800 lbs	89 in / 93 in

- **Yoke – Center (See Figure 2.1)**
- **Throttle – Twin Engine Complex Lever (TT-PP-MM) (See Figure 3.5)**
- **Traditional analog gauges & 430/530 GPS with KAP140 Autopilot**

Piper Seminole PA44-G1



MTOW	FWD/AFT CG Limit
3800 lbs	89 in / 93 in

- **Yoke – Center (See Figure 2.1)**
- **Throttle – Twin Engine Complex Lever (TT-PP-MM) (See Figure 3.5)**
- **Glass Cockpit G1000 PFD/MFD & GFC700 Autopilot**

Socata TB10-S1



MTOW	FWD/AFT CG Limit
2535 lbs	42.6 in / 47.4 in

- **Yoke – Center (See Figure 2.1)**
- **Throttle – Single Engine Complex Vernier (T-P-M) (See Figure 3.2)**
- **Traditional analog gauges & 430/530 GPS with KAP140 Autopilot**

Tecnam P2006-G1



MTOW	FWD/AFT CG Limit
2601 lbs	8.7 in / 16.3 in

- **Yoke – Stick (See Figure 2.3)**
- **Throttle – Twin Engine Lever (TT-CC-PP) (See Figure 3.8)**
- **Glass Cockpit G1000 PFD/MFD & STEC55 Autopilot**

Additional configurations included in this version (QAG V2.0B)

Cessna C206T-S1



MTOW	FWD/AFT CG Limit
3600 lbs	42.5 in / 49.7 in

- **Yoke – Center (See Figure 2.1)**
- **Throttle – Single Engine Complex Lever (T-P-M) (See Figure 3.4)**
- **Traditional analog gauges & 430/530 GPS with KAP140 Autopilot**

Diamond DA40-G2



MTOW	FWD/AFT CG Limit
2535 lbs	96.9 in / 102.0 in

- **Yoke – Stick (See Figure 2.3)**
- **Throttle – Single Engine Complex Lever (T-P-M) (See Figure 3.4)**
- **Glass Cockpit G1000 PFD/MFD & KAP140 Autopilot**

Diamond DA42L-G2



MTOW	FWD/AFT CG Limit
3935 lbs	95.47 in / 96.5 in

- **Yoke – Stick (See Figure 2.3)**
- **Throttle – Twin Engine Lever (TT-PP-MM) (See Figure 3.5)**
- **Glass Cockpit G1000 PFD/MFD & KAP140 Autopilot**

Mooney M20-G1



MTOW	FWD/AFT CG Limit
3668 lbs	46 in / 51 in

- **Yoke – Stick (See Figure 2.3)**
- **Throttle – Single Engine Complex Lever (T-P-M) (See Figure 3.4)**
- **Glass Cockpit G1000 PFD/MFD & GFC700 Autopilot**

Piper Archer PA28-80-G1



MTOW	FWD/AFT CG Limit
2550 lbs	88.6 in / 93.0 in

- **Yoke – Center (See Figure 2.1)**
- **Throttle – Single Engine Complex Lever (T-P-M) (See Figure 3.4)**
- **Glass Cockpit G1000 PFD/MFD & GFC700 Autopilot**

Piper Arrow PA28-2R-G2



MTOW	FWD/AFT CG Limit
2750 lbs	88.9 in / 91.5 in

- **Yoke – Center (See Figure 2.1)**
- **Throttle – Single Engine Complex Lever (T-P-M) (See Figure 3.4)**
- **Glass Cockpit G1000 PFD/MFD & GFC700 Autopilot**

Piper Seminole PA44T-S1



MTOW	FWD/AFT CG Limit
3925 lbs	89.7 in / 93 in

- **Yoke – Center (See Figure 2.1)**
- **Throttle – Twin Engine Complex Lever (TT-PP-MM) (See Figure 3.5)**
- **Traditional analog gauges & 430/530 GPS with KAP140 Autopilot**

Performance Table

Aircraft Model	V_{SO}	V_{S1}	V_X	V_Y	V_A	V_{NE}	V_{MCA}	KTAS @ Cruise / 75% power setting	Rate of Climb (fpm) @ (V_Y) / Full Power	Single Engine Rate of Climb (V_{YSE})
Beechcraft (A36) Bonanza	53 KIAS	62 KIAS	78 KIAS	96 KIAS	140 KIAS	204 KIAS	N/A	160 KTAS	1030 fpm	N/A
							5000' -->	166 KTAS	740 fpm	N/A
Cessna 172 Skyhawk	40 KIAS	48 KIAS	56 KIAS	74 KIAS	105 KIAS	163 KIAS	N/A	116 KTAS	730 fpm	N/A
							5000' -->	119 KTAS	550 fpm	N/A
Cessna 182 Skylane	35 KIAS	40 KIAS	58 KIAS	80 KIAS	110 KIAS	175 KIAS	N/A	129 KTAS	925 fpm	N/A
							5000' -->	135 KTAS	705 fpm	N/A
Cessna 206 Stationair	34 KIAS	41 KIAS	65 KIAS	84 KIAS	120 KIAS	183 KIAS	N/A	141 KTAS	920 fpm	N/A
							5000' -->	145 KTAS	640 fpm	N/A
Cessna 206 Stationair TC	39 KIAS	50 KIAS	74 KIAS	87 KIAS	125 KIAS	182 KIAS	N/A	139 KTAS	1050 fpm	N/A
							5000' -->	144 KTAS	955 fpm	N/A
Cirrus SR20	56 KIAS	65 KIAS	75 KIAS	85 KIAS	131 KIAS	200 KIAS	N/A	147 KTAS	828 fpm	N/A
							5000' -->	151 KTAS	566 fpm	N/A
Cirrus SR22	59 KIAS	70 KIAS	78 KIAS	91 KIAS	133 KIAS	201 KIAS	N/A	170 KTAS	1304 fpm	N/A
							5000' -->	175 KTAS	1015 fpm	N/A
Diamond DA20	37 KIAS	41 KIAS	57 KIAS	65 KIAS	104 KIAS	161 KIAS	N/A	98 KTAS	675 fpm	N/A
							5000' -->	108 KTAS	440 fpm	N/A
Diamond DA40	49 KIAS	52 KIAS	66 KIAS	66 KIAS	108 KIAS	178 KIAS	N/A	128 KTAS	1100 fpm	N/A
							5000' -->	136 KTAS	720 fpm	N/A
Liberty XL2	41 KIAS	51 KIAS	70 KIAS	80 KIAS	100 KIAS	157 KIAS	N/A	N/A	682 fpm	N/A
							5000' -->	N/A	438 fpm	N/A
Mooney M20	61 KIAS	67 KIAS	84 KIAS	104 KIAS	127 KIAS	194 KIAS	N/A	182 KTAS	1375 fpm	N/A
							5000' -->	197 KTAS	1275 fpm	N/A
Piper PA-28-161 Warrior III	44 KIAS	50 KIAS	53 KIAS	79 KIAS	111 KIAS	160 KIAS	N/A	106 KTAS	644 fpm	N/A
							5000' -->	114 KTAS	396 fpm	N/A
Piper PA-28-181 Archer III	45 KIAS	50 KIAS	60 KIAS	76 KIAS	113 KIAS	154 KIAS	N/A	121 KTAS	680 fpm	N/A
							5000' -->	125 KTAS	480 fpm	N/A
Piper PA-28R-201 Arrow	55 KIAS	60 KIAS	60 KIAS	90 KIAS	118 KIAS	183 KIAS	N/A	131 KTAS	840 fpm	N/A
							5000' -->	135 KTAS	580 fpm	N/A
Socata TB10	53 KIAS	60 KIAS	65 KIAS	78 KIAS	122 KIAS	165 KIAS	N/A	119 KTAS	787 fpm	N/A
							5000' -->	124 KTAS	525 fpm	N/A
Beechcraft (BE55) Baron	73 KIAS	79 KIAS	91 KIAS	107 KIAS	157 KIAS	224 KIAS	78 KIAS	168 KTAS	1725 fpm	400 fpm @ 100 KIAS
							5000' -->	180 KTAS	1250 fpm	125 fpm @ 100 KIAS
Beechcraft (BE58) Baron	74 KIAS	84 KIAS	92 KIAS	105 KIAS	156 KIAS	223 KIAS	84 KIAS	188 KTAS	1725 fpm	395 fpm @ 101 KIAS
							5000' -->	203 KTAS	1325 fpm	150 fpm @ 101 KIAS
Beechcraft (BE76) Duchess	60 KIAS	70 KIAS	71 KIAS	85 KIAS	132 KIAS	194 KIAS	65 KIAS	148 KTAS	1250 fpm	230 fpm @ 85 KIAS
							5000' -->	160 KTAS	900 fpm	90 fpm @ 85 KIAS

Diamond DA42 L360	57 KIAS	64 KIAS	90 KIAS	90 KIAS	126 KIAS	194 KIAS	65 KIAS	153 KTAS	1119 fpm	185 fpm @ 85 KIAS
							5000' -->	160 KTAS	1045 fpm	106 fpm @ 85 KIAS
Diamond DA42 NG	62 KIAS	69 KIAS	85 KIAS	90 KIAS	122 KIAS	188 KIAS	76 KIAS	147 KTAS	1065 fpm	175 fpm @ 85 KIAS
							5000' -->	152 KTAS	996 fpm	122 fpm @ 85 KIAS
Piper PA-34 Seneca V	61 KIAS	67 KIAS	76 KIAS	88 KIAS	139 KIAS	204 KIAS	66 KIAS	157 KTAS	1470 fpm	255 fpm @ 88 KIAS
							5000' -->	171 KTAS	1380 fpm	220 fpm @ 88 KIAS
Piper PA-44 Seminole	55 KIAS	57 KIAS	70 KIAS	88 KIAS	135 KIAS	202 KIAS	56 KIAS	152 KTAS	1350 fpm	225 fpm @ 88 KIAS
							5000' -->	159 KTAS	925 fpm	0 fpm @ 88 KIAS
Piper PA-44T Seminole	56 KIAS	60 KIAS	84 KIAS	88 KIAS	137 KIAS	202 KIAS	57 KIAS	151 KTAS	1275 fpm	180 fpm @ 88 KIAS
							5000' -->	159 KTAS	1175 fpm	150 fpm @ 88 KIAS
Tecnam P2006	53 KIAS	66 KIAS	80 KIAS	80 KIAS	118 KIAS	167 KIAS	62 KIAS	142 KTAS	1150 fpm	230 fpm @ 80 KIAS
							5000' -->	139 KTAS	840 fpm	60 fpm @ 80 KIAS

SECTION 6: VISUAL SYSTEM WITH IFR, VFR, DAY, AND NIGHT CAPABILITY

Redbird MX2 Visual System
The visual system is capable of providing a field-of-view of a minimum of 200 degrees horizontally and 24 degrees vertically, for the pilot, including adjustable cloud base and visibility in night, dusk and day scenes.

- The Redbird MX2 provides a means of recording the visual response time for the visual system that is installed.
- The Redbird MX2 visual system is free of optical discontinuities and artifacts that create non-realistic cues.
- The visual system is directly displayed on five (5) LCD monitors inside the cockpit enclosure, situated in an arc around the Pilot. Each monitor is 28 cm tall, and 47 cm wide. Based upon the designated Pilot Eye Point, these monitors provide a horizontal FOV of over 220 (5 monitors) degrees and a vertical FOV of 24 degrees.

Daylight: The visual system provides full color presentations and sufficient surfaces with appropriate textural cues to conduct a visual approach, landing and airport movement. Surface shading effects are consistent with the simulated sun position.

Twilight: The visual system provides full color presentations of reduced ambient intensity, sufficient surfaces with appropriate textural cues that include self-illuminated objects such as road networks, ramp lighting and airport signage, to conduct a visual approach, landing and airport movement. Scenes include a definable horizon and typical terrain characteristics such as fields, roads and bodies of water and surfaces illuminated by representative ownship lighting.

Night: The visual system provides the same as above except the portrayal of reduced ambient intensity; therefore, there is no ground cues that are not self-illuminating or illuminated by ownship lights.

Designated Eye Point: The designated Pilot Eye Point is located 67 cm from the center of the forward most external view monitor, 50 cm from the left most external view monitor and 105 cm from the floor of the simulator enclosure. This point is roughly centered over the pilot's seat when it is adjusted to the middle position, at a height consistent with the height of the pilot's head.




Figure 1: Designated Eye Point Diagram



Figure 5.4: Visual Displays

SECTION 7: ATD FUNCTIONS & MANEUVERS CHECKLISTS

AVIATION TRAINING DEVICE CHECKLIST

Functions and Maneuvers	Satisfactory? Yes/No
a. Preparation for Flight	
(1) Preflight	Yes
b. Pre-Takeoff	
(1) Engine start	Yes
(2) Brake operation	Yes
c. Takeoff	
(1) **AIRPLANE Takeoff**	
(i) Power plant checks	Yes
(ii) Acceleration characteristics	Yes
(iii) Nose wheel and rudder steering	Yes
(iv) Effect of crosswind	Yes
(v) Instrument	Yes
(vi) Landing gear, wing flap operation	Yes
(2) **HELICOPTER Takeoff**	
(i) Power plant checks	N/A
(ii) From Hover	N/A
(iii) From Ground	N/A
(iv) Vertical	N/A
(v) Running	N/A
d. In-flight Operation	
(1) **AIRPLANE In-flight Operation**	
(i) Climb	Yes
(a) Normal	Yes
(b) One engine inoperative procedures	Yes* (Multi-Engine Configurations only)
(ii) Cruise	
(a) Performance characteristics (speed vs. power)	Yes
(b) Normal and steep turns	Yes
(c) Performance turns	Yes
(d) Approach to stalls, i.e., stall warning (cruise, takeoff/approach, and landing configuration)	Yes
(e) High angle of attack maneuvers (cruise, takeoff/approach, and landing)	Yes
(f) In-flight engine shutdown	Yes
(g) In-flight engine restart	Yes
(iii) Descent	Yes
(a) Normal	Yes
(b) Maximum rate	Yes
(2) **HELICOPTER In-flight Operation**	
(i) Hovering	N/A
(a) Forward	N/A
(b) Rearward	N/A
(c) Sideward	N/A

(d) Turns	N/A
(ii) Climb	N/A
(iii) Cruise	N/A
(a) Performance characteristics	N/A
(b) Turns	N/A
i. Recovery	N/A
ii. Skidding	N/A
iii. Slipping	N/A
(c) In-flight engine shutdown	N/A
(d) In-flight engine restart	N/A
(iv) Descent	N/A
e. Approaches	
(1) Non-precision	Yes
(i) GPS-WAAS	Varies* (Based on Configuration)
(ii) GPS-LAAS	Varies* (Based on Configuration)
(iii) All engines operating	Yes
(iv) One or more engines inoperative	Yes
(v) Approach procedures (NDB, VOR, DME Arc, LOC/BC, LOC, LDA, SDF, ASR, LNAV/VNAV, GPS, & LPV, and additional types when developed and certified)	Yes
(vi) Missed approach (all engines operational, one or more engines inoperative)	Yes
(2) Precision	Yes
(i) PAR – normal	Yes
(ii) ILS	Yes
(iii) GLS	Yes
(iv) Effects of crosswind	Yes
(v) With engine(s) inoperative	Yes
(vi) Missed approach	Yes
(a) Normal	Yes
(b) With engine(s) inoperative	Yes
(c) From steep glide slope	Yes
f. Surface Operations (AIRPLANE-Post Landing)	
(1) Landing roll	Yes
(2) Braking operation	Yes
(3) Reverse thrust operation, if applicable	N/A
g. Any Flight Phase	
(1) Aircraft and power plant systems	Yes
(i) Electrical	Yes
(ii) Flaps (**AIRPLANE**)	Yes
(iii) Fuel and oil	Yes
(iv) Landing gear (**AIRPLANE**)	Yes
(2) Flight management and guidance systems	Yes
(i) Automatic pilot	Yes
(ii) Flight director/system displays	Yes
(iii) Navigation systems	Yes

(iv) Stall warning/avoidance (**AIRPLANE**)	Yes
(v) Multi-function displays	Varies* (Based on Configuration)
(vi) Primary flight displays	Varies* (Based on Configuration)
(3) Airborne procedures	Yes
(i) Holding	Yes
(4) Engine shutdown and parking	Yes
(i) Systems operation	Yes
(ii) Parking brake operation (**AIRPLANE**)	Yes

Any changes or modifications to this device which have not been reviewed, evaluated, and approved in writing by General Aviation and Commercial Division, AFS-800 may terminate FAA approval of this aviation training device.