

K2bU3R3 gate -- does the 2-D limit cycle survive in 3-D at the 59 mm feasible mesh?

quantity	value	units	pre-registered meaning	status
final window 60-80 s peak-to-peak	0.6058	K	<= 0.1 K means DAMPS	measured
preceding window 40-60 s peak-to-peak	1.4414	K	reference for the ratio	measured
ratio final / preceding	0.420	-	<= 0.5 means DAMPS	measured
final window mean	293.5306	K	reported	measured
samples in the final window	100	-	aliasing floor 10 per period	measured
samples in the preceding window	100	-	aliasing floor 10 per period	measured
SURVIVES threshold	p2p >= 0.3 and ratio >= 0.8	-	pre-registered	frozen
DAMPS threshold	p2p <= 0.1 or ratio <= 0.5	-	pre-registered	frozen
planted-zero control	armed; plant recovered	-	detection floor 1.234e-03 K, 81x below the 0.1 K DAMPS floor	measured
outcome	DAMPS	-	the discriminator's answer	graded
VERDICT	GATE REACHED	-	discriminator gate; the value-in-band verdict word does not apply	graded

Thresholds and windows are frozen in K2bU3R3_PREREGISTRATION.md and were fixed before the run. This page recomputes the measured rows through the grade's own reader and refuses if they differ from K2bU3R3_GRADE.txt. The verdict is GATE REACHED. It is not PASS: a survives/damps discriminator has no band for a value to lie inside, so the value-in-band word does not apply to it.