

Post-Quantum ZKP for Privacy-Preserving Authentication and Model Verification in Decentralized CAV

Hasina Andriambelo

Infosys Limited

Paris, France

hasina.andriambelo@infosys.com

Naghmeh Moradpoor

Edinburgh Napier University

Edinburgh, UK

n.moradpoor@napier.ac.uk

Leandros Maglaras

De Montfort University, Gateway House

Leicester, UK

leandros.maglaras@dmu.ac.uk

Abstract—Decentralized and Connected Autonomous Vehicle (CAV) networks offer promising advances in safety, efficiency, and real-time decision-making. However, they face significant challenges in authentication, privacy, and scalability—especially in the face of quantum adversaries. This paper proposes a novel post-quantum secure framework that integrates lattice-based Zero-Knowledge Proofs (ZKPs), optimized Binius proofs, and Multi-Layer Compressed Counting Bloom Filters (ML-CCBF) to enable privacy-preserving authentication and model verification in decentralized CAV environments. Our lattice-based ZKP scheme achieves cryptographic commitments in under $5\mu s$, while Binius proofs verify model integrity in less than 0.17 seconds per update. ML-CCBF ensures scalable membership filtering with 0% false positives across 1000 nodes. Experimental results confirm 100% ZKP soundness, strong resilience against simulated quantum and adaptive attacks, and stable latency under increasing network load. These findings demonstrate that our framework delivers quantum-resilient security, real-time efficiency, and robust scalability, offering a viable solution for trustworthy decentralized intelligence in next-generation vehicular systems.

Index Terms—Federated Learning, Quantum-Resistant Cryptography, Blockchain, Edge Computing, Vehicle-to-Everything (V2X).

I. INTRODUCTION

Connected and Autonomous Vehicle (CAV) networks mark a significant evolution in modern transportation, offering enhanced traffic efficiency, road safety, and user experience. Powered by Vehicle-to-Vehicle (V2V) and Vehicle-to-Infrastructure (V2I) communication, these systems support real-time data exchange to adapt to dynamic conditions such as traffic congestion, accidents, or adverse weather. However, ensuring secure, private, and efficient communication in these decentralized, latency-sensitive networks remains a major challenge.

CAV networks are inherently decentralized, with nodes continuously exchanging sensitive and mission-critical data. This raises pressing concerns regarding authentication, privacy, and the verification of model integrity in real-time. Traditional cryptographic methods such as RSA and Elliptic Curve Cryptography (ECC) struggle in this context: they introduce computational overheads unsuitable for resource-constrained vehicular systems, and they are vulnerable to emerging quantum

attacks [2], [6]. Meanwhile, existing zero-knowledge proof (ZKP) systems like Schnorr or Groth-Sahai [4] offer privacy-preserving authentication but lack scalability for decentralized, high-speed environments like CAVs.

Furthermore, current approaches to decentralized model verification often rely on standard Bloom filters or hash-based checks [5], which suffer from high false-positive rates in large-scale deployments. These methods fall short of the security, efficiency, and reliability demands of real-time vehicular operations. Crucially, many frameworks neglect quantum resilience, leaving authentication protocols vulnerable as quantum computing progresses.

To address these challenges, we propose a novel, post-quantum secure framework that integrates lattice-based cryptography, hybrid zero-knowledge proofs, and advanced membership verification tailored to decentralized CAV networks.

Our key contributions are:

- **Lattice-Based ZKP Authentication:** A quantum-resistant authentication scheme based on structured lattice problems (SIS/LWE), offering strong security and privacy in dynamic, resource-constrained CAV settings.
- **Hybrid Binius-ZKP for Model Verification:** We introduce a hybrid approach combining lattice-based ZKPs with Binius protocols, leveraging FFT-based polynomial commitments and binary field arithmetic to enhance efficiency and quantum resilience.
- **ML-CCBF for Lightweight Verification:** To ensure scalable and low-latency verification, we adopt Multi-Layer Compressed Counting Bloom Filters (ML-CCBF) [10], which provide efficient membership validation while preserving privacy.

Our framework achieves quantum resilience, low computational overhead, and fast verification—core requirements for secure deployment in decentralized CAV systems. By combining post-quantum primitives, efficient proof techniques, and scalable data structures, we fill a critical gap in the literature and advance the state of the art in CAV security.

The remainder of the paper is structured as follows: Section ?? reviews related work and highlights key limitations.

Section ?? introduces relevant background in lattice cryptography, ZKPs, and ML-CCBF. Section ?? presents our proposed architecture. Section ?? discusses implementation and experimental results. Section ?? outlines limitations and future directions. Section ?? concludes the paper.

II. RELATED WORK

The growing adoption of Connected and Autonomous Vehicle (CAV) networks has driven significant research into secure and scalable authentication protocols, particularly in light of the emerging threat posed by quantum computing. This section reviews foundational efforts in three key areas: classical and quantum-resistant cryptographic approaches in vehicular networks, privacy-preserving authentication using Zero-Knowledge Proofs (ZKPs), and lightweight membership verification. We conclude by identifying a critical research gap that motivates this paper.

A. Cryptographic Solutions in Vehicular Networks

Vehicular communication systems—such as those enabling collision avoidance, cooperative driving, and traffic management—rely heavily on robust authentication mechanisms. Classical cryptographic approaches based on Public Key Infrastructure (PKI), RSA, and Elliptic Curve Cryptography (ECC) have historically secured these systems [11], [12]. However, quantum algorithms such as Shor’s [2] threaten the security assumptions underlying these schemes, enabling polynomial-time attacks on both integer factorization and discrete logarithms [6]. As a result, there is growing consensus that existing vehicular security frameworks must transition toward quantum-resistant primitives to ensure future-proof confidentiality and trust [13], [14].

B. Quantum-Resistant Authentication and Zero-Knowledge Proofs

Lattice-based cryptography has emerged as a leading candidate in the field of Post-Quantum Cryptography (PQC), with constructions such as Learning With Errors (LWE) offering provable security against quantum adversaries [7], [8]. These primitives have been applied to authentication protocols in vehicular networks, particularly through the use of lattice-based signatures and challenge-response schemes [15]. In parallel, Zero-Knowledge Proofs (ZKPs) have gained prominence as a means of enabling privacy-preserving authentication—ensuring that identities and credentials can be verified without disclosing underlying data [4], [16]. While lattice-based ZKPs show strong potential in achieving quantum-resistant privacy [17], [18], existing implementations often incur high computational overhead and large proof sizes, making them difficult to deploy in real-time, resource-constrained CAV environments [19].

C. Lightweight Membership Verification Techniques

Scalability and low-latency authentication are particularly critical in decentralized vehicular environments. To address these constraints, research has explored probabilistic data

structures such as Bloom Filters, which offer efficient set membership checks with compact memory usage [5]. However, traditional Bloom Filters suffer from high false-positive rates in large-scale networks. Variants like Counting Bloom Filters (CBF) and Spectral Bloom Filters (SBF) improve accuracy but at the cost of increased complexity [20], [21]. More recently, Multi-Layer Compressed Counting Bloom Filters (ML-CCBFs) have demonstrated improved accuracy and storage efficiency for large-scale distributed verification [10], [22]. Despite these advances, ML-CCBFs have not been integrated with post-quantum or privacy-preserving authentication mechanisms in the context of decentralized CAV systems.

D. Research Gap and Motivation

Although prior work has advanced quantum-resistant cryptography, ZKP-based authentication, and scalable verification mechanisms, these components are rarely unified in a single framework. Most existing efforts either focus on post-quantum security without addressing real-time performance and scalability, or emphasize lightweight authentication without quantum resilience [23], [24]. As CAV networks grow in complexity and scale, there is a pressing need for a holistic solution that integrates post-quantum authentication, efficient zero-knowledge verification, and lightweight membership validation. This paper addresses that gap with a unified architecture designed for secure, scalable, and privacy-preserving operations in decentralized CAV infrastructures.

III. PRELIMINARIES

This section introduces the foundational cryptographic techniques used in our framework: Lattice-Based Cryptography, Multi-Layer Compressed Counting Bloom Filters (ML-CCBF), and Binius Zero-Knowledge Proofs (ZKPs). Each technology contributes distinct advantages in terms of post-quantum security, efficiency, and scalability—crucial for decentralized and resource-constrained environments such as CAV networks.

A. Lattice-Based Cryptography

Lattice-based cryptography is a leading candidate for post-quantum secure cryptographic constructions. A lattice $\mathcal{L}(B)$ is defined as the set of all integer linear combinations of n linearly independent vectors $B = \{\mathbf{b}_1, \dots, \mathbf{b}_n\}$:

$$\mathcal{L}(B) = \left\{ \sum_{i=1}^n a_i \mathbf{b}_i \mid a_i \in \mathbb{Z} \right\}.$$

Cryptographic constructions often rely on hard lattice problems such as the Shortest Vector Problem (SVP) and the Learning With Errors (LWE) problem. The LWE problem is defined as:

$$\mathbf{b} = A\mathbf{s} + \mathbf{e} \pmod{q},$$

where $A \in \mathbb{Z}_q^{m \times n}$ is a public matrix, $\mathbf{s} \in \mathbb{Z}_q^n$ is a secret vector, and $\mathbf{e}$ is a noise vector drawn from a discrete

Gaussian distribution. Recovering s from noisy samples is computationally hard, even for quantum adversaries [7], [8].

Lattice-based schemes also support homomorphic operations, enabling privacy-preserving computation on encrypted data—an essential feature for decentralized systems where sensitive data must remain confidential.

B. Multi-Layer Compressed Counting Bloom Filters (ML-CCBF)

Bloom Filters are probabilistic data structures optimized for fast and memory-efficient membership testing. However, traditional Bloom Filters are limited by their inability to support deletion or precise frequency counting.

ML-CCBF addresses these limitations by organizing multiple Counting Bloom Filter (CBF) layers hierarchically. Each layer contains an array of counters C_i , initialized to zero. When inserting an element x , k independent hash functions $h_1, \dots, h_k$ determine which counters to increment:

$$C_i[h_j(x)] \leftarrow C_i[h_j(x)] + 1, \quad \forall j \in \{1, \dots, k\}.$$

To verify membership:

$$\text{query}(x) = \bigwedge_{j=1}^k (C_i[h_j(x)] > 0).$$

Deletions are supported by decrementing the same counters. The use of compression techniques across layers reduces storage overhead while maintaining high accuracy, making ML-CCBF particularly suitable for real-time, large-scale, decentralized environments like CAV networks [10].

C. Binius Zero-Knowledge Proofs

Traditional ZKP systems like SNARKs and STARKs rely on arithmetic over large prime fields, which can be computationally intensive. Binius improves upon this by operating over binary fields $\mathbb{F}_2 = \{0, 1\}$, taking advantage of hardware-native bitwise operations.

Addition and multiplication in $\mathbb{F}_2$ are defined as:

$$a + b = a \oplus b, \quad a \cdot b = a \wedge b.$$

To improve algebraic expressiveness and security, Binius extends operations to binary field extensions $\mathbb{F}_{2^n}$ using irreducible polynomials $f(x)$:

$$\mathbb{F}_{2^n} \cong \mathbb{F}_2[x]/(f(x)).$$

Elements in $\mathbb{F}_{2^n}$ are polynomials of degree less than n with coefficients in $\mathbb{F}_2$. Arithmetic in these fields—especially multiplication—is optimized via Fast Fourier Transform (FFT)-based algorithms, achieving complexity close to $\mathcal{O}(n \log n)$, as opposed to $\mathcal{O}(n^2)$ in prime fields.

Sparse irreducible polynomials, such as $f(x) = x^n + x^k + 1$, are typically chosen to strike a balance between performance and security. The use of FFT and Merkle tree commitments makes Binius ZKPs particularly efficient for real-time verification in constrained environments like CAVs [9].

IV. PROPOSED FRAMEWORK

This section presents our integrated, post-quantum secure architecture for decentralized CAV networks. The framework comprises three synergistic layers—Lattice-Based ZKP Authentication, Binius ZKP Verification, and Multi-Layer Compressed Counting Bloom Filters (ML-CCBF)—that jointly ensure privacy-preserving authentication, efficient model verification, and scalable membership filtering. The overall workflow is illustrated in Fig. 1, and the cryptographic operations are described through Algorithms 1, 2, and 3.




Fig. 1. Federated learning workflow integrating lattice-based ZKP, Binius proofs, and ML-CCBF verification in decentralized CAV systems.

A. Workflow Integration

The framework supports fully decentralized peer-to-peer model verification across participating CAV nodes. A complete training and verification round proceeds as follows:

- **Local Model Training:** Each vehicle trains a local model using its private data and applies differential privacy mechanisms to preserve confidentiality.
- **Lattice-Based Authentication:** Vehicles generate lattice-based cryptographic commitments to authenticate model updates. These commitments ensure post-quantum secure origin verification without disclosing private parameters.
- **Binius ZKP Verification:** Each node generates Binius ZKPs for its model updates, enabling zero-knowledge

validation of correctness and integrity without revealing underlying data.

- **ML-CCBF Membership Filtering:** A SHA-256 hash of each update is checked against the ML-CCBF structure. New updates are inserted with an associated Binius proof to ensure efficient, tamper-resistant deduplication.
- **Peer-to-Peer Verification:** Model updates, lattice commitments, and Binius proofs are shared across the network. Peers perform decentralized verification across all three layers.
- **Secure Aggregation:** Validated updates are aggregated via secure protocols (e.g., MPC or geometric median) to construct the new global model.

B. Lattice-Based ZKP Authentication Layer

This layer ensures quantum-resistant authentication through cryptographic commitments based on Gaussian sampling in structured lattices. Each participating vehicle independently computes a lattice-based commitment to attest the authenticity of its update.

Algorithm 1 Lattice-Based ZKP Generation and Verification

Require: Secret key s_1 , Public key s_2

Ensure: Commitment proof

- 1: $\sigma \leftarrow 6 \cdot \sqrt{337 \cdot 128}$
 - 2: $y \leftarrow \text{GaussianSampler}(R_q, \sigma, \text{dim} = 128)$
 - 3: $\text{commitment} \leftarrow \text{abdlop_commit}(m_1 = 8, m_2 = 25, \ell = 2, n = 9, N = 1, s_1, s_2, y)$
 - 4: **return** commitment
-

This operation provides a post-quantum secure binding between the model update and the participating node’s identity, ensuring both authenticity and non-repudiation.

C. Binius ZKP Verification Layer

The second layer ensures privacy-preserving verification of model updates using binary field arithmetic. The Binius proof system offers fast, hardware-efficient operations using multilinear polynomial commitments and Merkle tree hashing.

Algorithm 2 Binius ZKP Generation

Require: Evaluations, evaluation point

Ensure: Binius ZKP

- 1: Compute padded evaluation vector and FFT-based extension
 - 2: Generate Merkle tree commitment from extended rows
 - 3: Derive hash-based challenges from Merkle root
 - 4: Perform multilinear polynomial evaluation using tensor products
 - 5: Assemble proof: root, challenge indices, polynomial evaluation, Merkle branches
 - 6: **return** Proof
-

This layer enables zero-knowledge verification of correctness for submitted model updates without revealing the model itself—crucial for preserving privacy in federated learning systems.

D. ML-CCBF Membership Verification Layer

The third layer filters duplicate or replayed updates using ML-CCBF, an efficient data structure supporting scalable, probabilistic membership verification with low false-positive rates. It supports secure insertion and verification via Binius proofs.

Algorithm 3 ML-CCBF Insertion with Proof

Require: Hashed model update

Ensure: Insertion status

- 1: **for** each layer **do**
 - 2: **if** layer.lookup(hash) == False **then**
 - 3: layer.insert(hash)
 - 4: Serialize state and pad to power-of-two
 - 5: $p \leftarrow \text{optimized_binus_proof}(\text{state})$
 - 6: Verify p via $\text{verify_optimized_binus_proof}(p)$
 - 7: **return** True
 - 8: **else**
 - 9: **return** False
 - 10: **end if**
 - 11: **end for**
-

This layer not only improves efficiency by rejecting redundant updates but also ensures insertion correctness via cryptographic proofs—reinforcing security and auditability.

V. EXPERIMENTS AND RESULTS

We evaluate the proposed framework across multiple dimensions: efficiency, soundness, attack resilience, scalability, and accuracy. Experiments were conducted using the Udacity self-driving car dataset [28], using forward-facing sequences. Following [29], five sequences were used for training and one for testing. Data was distributed across silos using a ring-based federated topology [30]. The system ran on an AMD 7950XD CPU with 128 GB RAM, 4 TB SSD, and an NVIDIA RTX 4090 GPU (24 GB VRAM), running Ubuntu 24.04 LTS. The framework is implemented in Python using PyTorch, with custom libraries for zero-knowledge proofs and ML-CCBF logic.

A. Lattice Hardness Evaluation

Goal: Assess the computational efficiency of lattice-based cryptographic operations under the LWE/SIS assumptions.

Process: We executed Gaussian sampling and polynomial commitments within structured lattices (R_q) over multiple iterations.

Results: Commitments consistently executed in under 5 microseconds, as shown in Fig. 2.

Analysis: These low latencies validate the suitability of lattice-based authentication for real-time deployment in vehicular systems.

B. Proof Generation and Verification Efficiency

Goal: Evaluate the computational cost of Binius ZKP generation and verification during model updates.




Fig. 2. Lattice-based ZKP: Commit Time.

Process: Model updates were processed using FFT-accelerated multilinear polynomial commitments and verified via Merkle-based checks.

Results: Average end-to-end verification time remained under 0.17 seconds (Fig. 3).

Analysis: These results demonstrate that Binius ZKPs achieve lightweight proof validation while preserving quantum resistance.




Fig. 3. Optimized Binius ZKP Verification Performance.

C. ZKP Soundness and Completeness

Goal: Validate correctness and robustness of the ZKP protocol through repeated testing.

Process: We performed 1000 proof generation and verification trials under standard and edge-case conditions.

Results: Verification succeeded in all trials with 100% correctness (Fig. 4).

Analysis: The perfect success rate confirms that the ZKP layer satisfies soundness and completeness criteria.

D. Quantum Attack Resistance

Goal: Assess post-quantum robustness of cryptographic primitives against brute-force attacks.

Process: SHA-256-based commitments were evaluated under simulated Grover-accelerated attack models.




Fig. 4. ZKP Soundness and Completeness across trials.

Results: Performance remained stable (2.5 ms per hash), with no observable degradation (Fig. 5).

Analysis: This stability under simulated quantum threats affirms the protocol's resilience and forward secrecy.




Fig. 5. Post-Quantum Resistance under Simulated Attacks.

E. ML-CCBF Membership Verification Accuracy

Goal: Measure the accuracy and false-positive/negative rates of the ML-CCBF filter.

Process: A large batch of known model updates was inserted and queried across multiple filter layers.

Results: No false positives or false negatives were recorded in over 1000 queries (Fig. 6).

Analysis: These results confirm the filter's reliability for duplicate detection and integrity checking in CAV networks.

The experimental results demonstrate that our framework meets the critical requirements of decentralized CAV systems: low-latency post-quantum authentication, scalable and accurate membership verification, and efficient privacy-preserving model validation. The integration of lattice-based ZKPs, optimized Binius proofs, and ML-CCBF yields a synergistic solution that balances security, privacy, and performance. These findings support the feasibility of deploying post-quantum federated learning architectures in real-world vehicular networks, even under adversarial or resource-constrained conditions.




Fig. 6. ML-CCBF Verification Accuracy (0% Error).

VI. FUTURE WORK

While our framework demonstrates strong post-quantum security, efficiency, and scalability, two avenues warrant further investigation:

- **Proof Optimization for Real-Time Systems:** Although our Binius-ZKP and lattice-based schemes are practical, future work could explore adaptive compression techniques and parameter tuning to reduce proof size and latency further—crucial for ultra-low-latency vehicular applications.
- **Large-Scale Deployment Simulation:** Validation in real-world environments, such as digital twin simulations or 5G-enabled vehicular testbeds, would offer deeper insights into latency, fault tolerance, and dynamic network behavior at scale.

VII. CONCLUSION

This paper proposed a unified, post-quantum secure framework for privacy-preserving authentication and model verification in decentralized CAV networks. By integrating lattice-based ZKPs, optimized Binius proofs, and ML-CCBF for lightweight membership verification, our design achieves a rare combination of quantum resilience, privacy, and computational efficiency. Experimental results confirm the system's practicality in terms of verification speed, ZKP soundness, attack resistance, and scalability. This work offers a foundational step toward trustworthy and secure federated intelligence in next-generation transportation systems.

REFERENCES

- [1] L. Chen *et al.*, *Report on Post-Quantum Cryptography*, NIST, NISTIR 8105, 2016.
- [2] P. W. Shor, "Polynomial-time algorithms for prime factorization and discrete logarithms on a quantum computer," *SIAM J. Comput.*, vol. 26, no. 5, pp. 1484–1509, 1997.
- [3] M. Raya and J.-P. Hubaux, "Securing vehicular ad hoc networks," *J. Comput. Security*, vol. 15, no. 1, pp. 39–68, 2007.
- [4] J. Groth and A. Sahai, "Efficient non-interactive proof systems for bilinear groups," in *Proc. EUROCRYPT*, 2008, vol. 4515, pp. 415–432.
- [5] A. Broder and M. Mitzenmacher, "Network applications of Bloom filters: A survey," *Internet Mathematics*, vol. 1, no. 4, pp. 485–509, 2004.

- [6] M. Mosca, "Cybersecurity in an era with quantum computers: Will we be ready?" *IEEE Security & Privacy*, vol. 16, no. 5, pp. 38–41, 2018.
- [7] O. Regev, "On lattices, learning with errors, random linear codes, and cryptography," *J. ACM*, vol. 56, no. 6, Art. no. 34, 2009.
- [8] C. Peikert, "A decade of lattice cryptography," *Found. Trends Theor. Comput. Sci.*, vol. 10, no. 4, pp. 283–424, 2016.
- [9] Binius, "Efficient zero-knowledge proofs for practical deployments," *Cryptology ePrint Archive*, Report 2022/123, 2022.
- [10] D. Guo *et al.*, "Scalable membership verification using multi-layer compressed counting Bloom filters," *IEEE Trans. Netw. Sci. Eng.*, vol. 7, no. 1, pp. 308–320, 2020.
- [11] G. Samara *et al.*, "Security analysis of vehicular ad hoc networks (VANET)," *Int. J. Next-Gener. Netw.*, vol. 4, no. 2, pp. 1–12, 2012.
- [12] Y. Qian and N. Moayeri, "Design of secure and application-oriented VANETs," in *Proc. IEEE VTC Spring*, 2008, pp. 2794–2799.
- [13] A. H. Hussein and M. M. K. El-Fouly, "Impact of quantum computing on cryptography: A survey," *IEEE Access*, vol. 8, pp. 136112–136128, 2020.
- [14] R. Hussain and H. Oh, "Cooperation-aware VANET clouds: Providing secure cloud services to vehicular ad hoc networks," *IEEE Trans. Intell. Transp. Syst.*, vol. 17, no. 10, pp. 2666–2678, 2016.
- [15] A. Bindel *et al.*, "Post-quantum signature schemes for secure VANET communications: A survey," *IEEE Commun. Surv. Tutor.*, vol. 21, no. 3, pp. 2537–2570, 2019.
- [16] F. Benhamouda *et al.*, "Verifiable and zero-knowledge computations on encrypted data: A survey," *Cryptography*, vol. 5, no. 4, Art. no. 27, 2021.
- [17] Y. Yu *et al.*, "Practical lattice-based zero-knowledge proofs for post-quantum authentication," *IEEE Access*, vol. 7, pp. 125719–125732, 2019.
- [18] J. Chen *et al.*, "Efficient lattice-based ring signature with zero-knowledge proofs," *J. Syst. Softw.*, vol. 167, Art. no. 110588, 2020.
- [19] A. Eskandarian *et al.*, "Secure and privacy-preserving vehicular communication using lattice-based cryptography," *IEEE Veh. Technol. Mag.*, vol. 12, no. 3, pp. 66–74, 2017.
- [20] B. Fan *et al.*, "Cuckoo filter: Practically better than Bloom," in *Proc. ACM CoNEXT*, 2014, pp. 75–88.
- [21] D. Eppstein *et al.*, "What's the difference? Efficient set reconciliation without prior context," in *Proc. ACM SIGCOMM*, 2011, pp. 218–229.
- [22] H. Li *et al.*, "Efficient scalable membership verification for vehicular fog computing," *IEEE Internet Things J.*, vol. 7, no. 10, pp. 10367–10375, 2020.
- [23] X. Zhang *et al.*, "Privacy-preserving authentication schemes for VANETs: A comprehensive survey," *IEEE Commun. Surv. Tutor.*, vol. 23, no. 1, pp. 678–711, 2021.
- [24] H. Li *et al.*, "Blockchain-based security architecture for collaborative autonomous vehicles," *IEEE Netw.*, vol. 34, no. 3, pp. 44–51, 2020.
- [25] L. Fan, P. Cao, J. Almeida, and A. Z. Broder, "Summary cache: A scalable wide-area Web cache sharing protocol," *IEEE/ACM Trans. Netw.*, vol. 8, no. 3, pp. 281–293, 2000.
- [26] M. Mitzenmacher, "Compressed Bloom filters," *IEEE/ACM Trans. Netw.*, vol. 10, no. 5, pp. 604–612, 2002.
- [27] V. Buterin, "Binius: Highly efficient proofs over binary fields," 2024. [Online]. Available: <https://vitalik.eth.limo/general/2024/04/29/binius.html>
- [28] Udacity, "An open source self-driving car," 2016. [Online]. Available: <https://www.udacity.com/self-driving-car>
- [29] A. Loquercio, A. I. Maqueda, C. R. del Blanco, and D. Scaramuzza, "Dronet: Learning to fly by driving," *IEEE Robot. Autom. Lett.*, 2018.
- [30] A. Nguyen *et al.*, "Deep federated learning for autonomous vehicles," unpublished.