

# intro\_Python

November 25, 2015

## 1 A Introduction to Python for dummies...

This is part of the Python lecture given by Christophe Morisset at IA-UNAM. More informations at: <http://python-astro.blogspot.mx/>

### 1.0.1 Using Python as a calculator

Using of “print” command is not necessary to obtain a result. Just type some operations and the result is obtain with ENTER.

```
In [1]: 2 + 22
```

```
Out[1]: 24
```

```
In [2]: (2+3)*(3+4)/(5*5)
```

```
Out[2]: 1
```

Python likes the use of spaces to make scripts more readable

```
In [3]: (2+3) * (3+4.) / (5*5)
```

```
Out[3]: 1.4
```

The art of writing good python code is described in the following document: <http://legacy.python.org/dev/peps/pep-0008/>

### 1.0.2 Assignments

Like any other langage, you can assign a value to a variable. This is done with = symbol:

```
In [4]: a = 4
```

A lot of operations can be performed on the variables. The most basics are for example:

```
In [5]: a
```

```
Out[5]: 4
```

```
In [6]: a = a + 1
a
```

```
Out[6]: 5
```

```
In [7]: a *= 4 # similar to a = a * 4
a
```

```
Out[7]: 20
```

```
In [8]: a, b = 1, 3
        a, b
```

```
Out[8]: (1, 3)
```

Some variable name are not available, they are reserved to python itself:

and, as, assert, break, class, continue, def, del, elif, else, except, exec, finally, for, from, global, if, import, in, is, lambda, not, or, pass, print, raise, return, try, while, with, yield

```
In [9]: lambda_ = 2
        file = 3
```

### 1.0.3 Comments

```
In [10]: a = 2 # this is a comment
```

```
In [11]: """ This is a large comment
on multiple lines
ending as it started
"""
```

```
Out[11]: ' This is a large comment\nnon multiple lines\nending as it started\n'
```

### 1.0.4 Types

The types used in Python are: integers, long integers, floats (double prec.), complexes, strings, booleans.

```
In [12]: 2
```

```
Out[12]: 2
```

```
In [13]: 2 / 3 # Take care, this will result in an integer, may not be what you expect. This changes in
```

```
Out[13]: 0
```

```
In [14]: float(2) / 3 # This is the way exact division is performed, adding a dot to promote one of the
```

```
Out[14]: 0.6666666666666666
```

```
In [15]: from __future__ import division
        2 / 3
```

```
Out[15]: 0.6666666666666666
```

Double precision: machine dependent, generally between  $10^{-308}$  and  $10^{308}$ , with 16 significant digits.

The function type gives the type of its argument:

```
In [16]: type(2)
```

```
Out[16]: int
```

```
In [17]: type(2.3)
```

```
Out[17]: float
```

```
In [18]: int(0.8) # truncating
```

```
Out[18]: 0
```

```
In [19]: round(0.8765566777) # nearest, result is float
```

```
Out[19]: 1.0
```

```
In [20]: int(round(0.88766)) # nearest, with the result being an integer:
```

```
Out[20]: 1
```

### 1.0.5 Complex numbers

```
In [21]: a = 1.5 + 0.5j
In [22]: a**2.
Out[22]: (2+1.5j)
In [23]: (1+2j)*(1-2j)
Out[23]: (5+0j)
In [24]: a.real
Out[24]: 1.5
In [25]: (a**3).imag
Out[25]: 3.25
In [26]: a.conjugate() # this is a function, it requires ()
Out[26]: (1.5-0.5j)
```

### 1.0.6 Booleans

Comparison operators are `<`, `<=`, `>`, `>=`, `==`, `!=`

```
In [27]: 5 < 7
Out[27]: True
In [28]: a = 5
         b = 7
In [29]: b < a
Out[29]: False
In [30]: c = 2
In [31]: c < a < b
Out[31]: True
In [32]: a < b and b < c
Out[32]: False
In [33]: res = a < 7
         print(res, type(res))
(True, <type 'bool'>)
In [34]: print int(res)
         print int(not res)
1
0
In [35]: not res is True
Out[35]: False
In [36]: a = True
         print a
True
```

### 1.0.7 Formating strings

```
In [37]: print "Hello world!"
```

Hello world!

```
In [38]: print 'Hello world!'
```

Hello world!

```
In [39]: print "Hello I'm here" # ' inside ""
```

Hello I'm here

```
In [40]: print('Hello') # this is the Python 3 style
```

Hello

```
In [41]: # This is the old fashion way of formating outputs (C-style)
```

```
    a = 7.5
```

```
    b = 'tralala'
```

```
    c = 8.9e-33
```

```
    print('a = %f, b = %s, c = %e' % (a, b, c))
```

a = 7.500000, b = tralala, c = 8.900000e-33

```
In [42]: # The new way is using the format() method of the string object, and {} to define which value
```

```
    print('a = {}, b = {}, c = {}'.format(a,b,c))
```

```
    print('a = {0}, b = {1}, c = {2}'.format(a**2,b,c))
```

```
    print('a = {:.f}, b = {:20s}, c = {:.15.3e}'.format(a,b,c))
```

a = 7.5, b = tralala, c = 8.9e-33

a = 56.25, b = tralala, c = 8.9e-33

a = 7.500000, b = tralala, c = 8.900e-33

Much more on this here: <https://docs.python.org/2/tutorial/inputoutput.html>

### 1.0.8 Strings

```
In [43]: a = "this is a string"
```

```
In [44]: len(a)
```

```
Out[44]: 19
```

A lot of commands can operate on strings. Strings, like ANYTHING in python, are objects. Methods are run on objects by dots:

```
In [45]: a.upper()
```

```
Out[45]: 'THIS IS A STRING'
```

```
In [46]: a.title()
```

```
Out[46]: 'This Is A String'
```

```
In [47]: a.split()
```

```
Out[47]: ['this', 'is', 'a', 'string']
```

```

In [48]: a.split()[1]
Out[48]: 'is'

In [49]: a = "This is a string.  With various sentences."

In [50]: a.split('.')
Out[50]: ['This is a string', '  With various sentences', '']

In [51]: a.split('.')[1].strip() # Here we define the character used to split. The default is space (and
Out[51]: 'With various sentences'

In [52]: a = 'tra'
        b = 'la'
        print ' '.join((a,b,b))
        print '-'.join((a,b,b))
        print ''.join((a,b,b))
        print ' '.join((a,b,b)).split()
        print ' & '.join((a,b,b)) + '\\\\'

tra la la
tra-la-la
tralala
['tra', 'la', 'la']
tra & la & la\\

```

### 1.0.9 Containers: Tuples, Lists and Dictionaries

**list:** a collection of objects. May be of different types. It has an order.

```

In [53]: L = ['red','green','blue'] # squared brackets are used to define lists

In [54]: type(L) # Print the type of L
Out[54]: list

In [55]: L[1]
Out[55]: 'green'

In [56]: L[0] # indexes start at 0 !!!
Out[56]: 'red'

In [57]: L[-1] # last element
Out[57]: 'blue'

In [58]: L[-3]
Out[58]: 'red'

In [59]: L = L + ['black', 'white'] # addition symbol is used to agregate values to a list. See below o

In [60]: print L
['red', 'green', 'blue', 'black', 'white']

```

```

In [61]: L[1:3] # L[start:stop] : elements if index i, where start <= i < stop !! stop not included !!
Out[61]: ['green', 'blue']
In [62]: L[2:] # boudaries can be omitted
Out[62]: ['blue', 'black', 'white']
In [63]: L[-2:]
Out[63]: ['black', 'white']
In [64]: L[::2] # L[start:stop:step] every 2 elements
Out[64]: ['red', 'blue', 'white']
In [65]: L[::-1]
Out[65]: ['white', 'black', 'blue', 'green', 'red']

```

Lists are mutable: their content can be modified.

```

In [66]: L[2] = 'yellow'
          L
Out[66]: ['red', 'green', 'yellow', 'black', 'white']
In [67]: L.append('pink') # append a value at the end
          L
Out[67]: ['red', 'green', 'yellow', 'black', 'white', 'pink']
In [68]: L.insert(2, 'blue') #L.insert(index, object) -- insert object before index
          L
Out[68]: ['red', 'green', 'blue', 'yellow', 'black', 'white', 'pink']
In [69]: L.extend(['magenta', 'purple'])
          L
Out[69]: ['red',
          'green',
          'blue',
          'yellow',
          'black',
          'white',
          'pink',
          'magenta',
          'purple']
In [70]: L.append(['magenta', 'azul'])
          L
Out[70]: ['red',
          'green',
          'blue',
          'yellow',
          'black',
          'white',
          'pink',
          'magenta',
          'purple',
          ['magenta', 'azul']]

```

```
In [71]: L.append(2)
        L
```

```
Out[71]: ['red',
          'green',
          'blue',
          'yellow',
          'black',
          'white',
          'pink',
          'magenta',
          'purple',
          ['magenta', 'azul'],
          2]
```

```
In [72]: L = L[::-1] # reverse order
        L
```

```
Out[72]: [2,
          ['magenta', 'azul'],
          'purple',
          'magenta',
          'pink',
          'white',
          'black',
          'yellow',
          'blue',
          'green',
          'red']
```

```
In [73]: L2 = L[:-3] # cutting the last 3 elements
        print L
        print L2
```

```
[2, ['magenta', 'azul'], 'purple', 'magenta', 'pink', 'white', 'black', 'yellow', 'blue', 'green', 'red']
[2, ['magenta', 'azul'], 'purple', 'magenta', 'pink', 'white', 'black', 'yellow']
```

```
In [74]: L[25] # Out of range leads to error
```

```
-----
IndexError
```

```
Traceback (most recent call last)
```

```
<ipython-input-74-c16babb9288f> in <module>()
----> 1 L[25] # Out of range leads to error
```

```
IndexError: list index out of range
```

```
In [75]: print L
        print L[20:25] # But NO ERROR when slicing.
        print L[20:]
        print L[2:20]
```

```
[2, ['magenta', 'azul'], 'purple', 'magenta', 'pink', 'white', 'black', 'yellow', 'blue', 'green', 'red']
[]
['purple', 'magenta', 'pink', 'white', 'black', 'yellow', 'blue', 'green', 'red']
```

```
In [76]: print L.count('yellow')
```

```
1
```

```
In [77]: L.sort() # One can use TAB to look for the methods (functions that apply to an object)
print L
```

```
[2, ['magenta', 'azul'], 'black', 'blue', 'green', 'magenta', 'pink', 'purple', 'red', 'white', 'yellow']
```

```
In [78]: a = [1,2,3]
b = [10,20,30]
```

```
In [79]: print(a+b) # may not be what you expected, but rather logical too
```

```
[1, 2, 3, 10, 20, 30]
```

```
In [80]: print(a*b) # Does NOT multiply element by element. Numpy will do this job.
```

```
-----
TypeError
```

```
Traceback (most recent call last)
```

```
<ipython-input-80-ddfd21d938fe> in <module>()
----> 1 print(a*b) # Does NOT multiply element by element. Numpy will do this job.
```

```
TypeError: can't multiply sequence by non-int of type 'list'
```

```
In [81]: L = range(4) # Create a list. Notice the parameter is the number of elements, not the last one
L
```

```
Out[81]: [0, 1, 2, 3]
```

```
In [82]: L = range(2, 20, 2) # every 2 integer
L
```

```
Out[82]: [2, 4, 6, 8, 10, 12, 14, 16, 18]
```

The types of the elements of a list are not always the same:

```
In [83]: L = [1, '1', 1.4]
L
```

```
Out[83]: [1, '1', 1.4]
```

Remove the n+1-th element:

```
In [84]: L = range(0,20,2)
print L
del L[5]
print L
```



```
[0, 2, 4, 6, 8, 10, 12, 14, 16, 18]
[0, 2, 4, 6, 8, 12, 14, 16, 18]
```

Slicing: extracting sub-list of a list

```
In [85]: a = [[1, 2, 3], [10, 20, 30], [100, 200, 300]] # Not a 2D table, but rather a table of tables
          print(a)
          print(a[0])
          print(a[1][1])
```

```
[[1, 2, 3], [10, 20, 30], [100, 200, 300]]
[1, 2, 3]
20
```

```
In [86]: print(a[1,1]) # Does NOT work
```

```
-----
TypeError                                Traceback (most recent call last)
```

```
<ipython-input-86-d8214b6adea8> in <module>()
----> 1 print(a[1,1]) # Does NOT work
```

TypeError: list indices must be integers, not tuple

```
In [87]: b = a[1]
          print b
```

```
[10, 20, 30]
```

```
In [88]: b[1] = 999
          print b
```

```
[10, 999, 30]
```

```
In [89]: print a # Changing b changed a !!!
```

```
[[1, 2, 3], [10, 999, 30], [100, 200, 300]]
```

```
In [90]: b[1] is a[1][1]
```

```
Out[90]: True
```

```
In [91]: c = a[1][:] # copy instead of slicing
          print c
          c[0] = 77777
          print c
          print a
```

```
[10, 999, 30]
[77777, 999, 30]
[[1, 2, 3], [10, 999, 30], [100, 200, 300]]
```

tuples: like lists, but immutable

```
In [92]: T = (1,2,3)
         T
```

```
Out[92]: (1, 2, 3)
```

```
In [93]: T2 = 1, 2, 3
         print T2
         type(T2)
```

```
(1, 2, 3)
```

```
Out[93]: tuple
```

```
In [94]: T[1]
```

```
Out[94]: 2
```

tuples are unmutables

```
In [95]: T[1] = 3 # Does NOT work!
```

```
-----
TypeError
```

```
Traceback (most recent call last)
```

```
<ipython-input-95-6dd68cc28786> in <module>()
----> 1 T[1] = 3 # Does NOT work!
```

```
TypeError: 'tuple' object does not support item assignment
```

**Dictionaries** A dictionary is basically an efficient table that maps keys to values. It is an unordered container

```
In [96]: D = {'Christophe': 12, 'Antonio': 15} # defined by {key : value}
```

```
In [97]: D['Christophe'] # access to a value by the key
```

```
Out[97]: 12
```

```
In [98]: D.keys() # list of the dictionary keys
```

```
Out[98]: ['Christophe', 'Antonio']
```

```
In [99]: D['Julio'] = 16 # adding a new entry
```

```
In [100]: print D
```

```
{'Julio': 16, 'Christophe': 12, 'Antonio': 15}
```

### 1.0.10 Blocks

Blocks are defined by indentation. Looks nice and no needs for end :-)

```
In [101]: for i in [1,2,3]: print(i) # compact way, not recommended.
```

```
1
2
3
```

```
In [102]: for cosa in [1,'ff',2]:
           print(cosa)
           print('end')
       print('final end') # end of the indentation means end of the block
```

```
1
end
ff
end
2
end
final end
```

```
In [103]: # defining a dictionary:
```

```
ATOMIC_MASS = {}
ATOMIC_MASS['H'] = 1
ATOMIC_MASS['He'] = 4
ATOMIC_MASS['C'] = 12
ATOMIC_MASS['N'] = 14
ATOMIC_MASS['O'] = 16
ATOMIC_MASS['Ne'] = 20
ATOMIC_MASS['Ar'] = 40
ATOMIC_MASS['S'] = 32
ATOMIC_MASS['Si'] = 28
ATOMIC_MASS['Fe'] = 55.8
```

*# Print the keys and values from the dictionary. As it is not ordered , they come as they want*

```
for key in ATOMIC_MASS.keys():
    print key, ATOMIC_MASS[key]
```

```
C 12
H 1
Si 28
Ne 20
O 16
N 14
S 32
Ar 40
Fe 55.8
He 4
```

```
In [104]: for key in sorted(ATOMIC_MASS): # sorting using the keys
           print('Element: {0:3s} Atomic Mass: {1}'.format(key, ATOMIC_MASS[key]))
```

```
Element: Ar    Atomic Mass: 40
Element: C     Atomic Mass: 12
Element: Fe    Atomic Mass: 55.8
```

```

Element: H      Atomic Mass: 1
Element: He     Atomic Mass: 4
Element: N      Atomic Mass: 14
Element: Ne     Atomic Mass: 20
Element: O      Atomic Mass: 16
Element: S      Atomic Mass: 32
Element: Si     Atomic Mass: 28

```

a key parameter can be used to specify a function to be called on each list element prior to making comparisons. More in sorted function here: <https://wiki.python.org/moin/HowTo/Sorting> or here: <http://www.pythoncentral.io/how-to-sort-a-list-tuple-or-object-with-sorted-in-python/>

```

In [105]: for elem in sorted(ATOMIC_MASS, key = ATOMIC_MASS.get): # sorting using the values
           print('Element: {0:3s} Atomic Mass: {1}'.format(elem, ATOMIC_MASS[elem]))

```

```

Element: H      Atomic Mass: 1
Element: He     Atomic Mass: 4
Element: C      Atomic Mass: 12
Element: N      Atomic Mass: 14
Element: O      Atomic Mass: 16
Element: Ne     Atomic Mass: 20
Element: Si     Atomic Mass: 28
Element: S      Atomic Mass: 32
Element: Ar     Atomic Mass: 40
Element: Fe     Atomic Mass: 55.8

```

```

In [106]: for idx, elem in enumerate(sorted(ATOMIC_MASS, key = ATOMIC_MASS.get)): # adding an index tha
           print('{0:2} Element: {1:2s} Atomic Mass: {2:4.1f}'.format(idx+1, elem, ATOMIC_MASS[elem]))

```

```

1 Element: H      Atomic Mass: 1.0
2 Element: He     Atomic Mass: 4.0
3 Element: C      Atomic Mass: 12.0
4 Element: N      Atomic Mass: 14.0
5 Element: O      Atomic Mass: 16.0
6 Element: Ne     Atomic Mass: 20.0
7 Element: Si     Atomic Mass: 28.0
8 Element: S      Atomic Mass: 32.0
9 Element: Ar     Atomic Mass: 40.0
10 Element: Fe    Atomic Mass: 55.8

```

```

In [107]: for i in range(10):
           if i > 5:
               print i

```

```

6
7
8
9

```

```

In [108]: for i in range(10):
           if i > 5:
               print i
           else:
               print('i lower than five')
           print('END')

```

```

i lower than five
i lower than five
i lower than five
i lower than five
i lower than five
i lower than five
6
7
8
9
END

```

Other commands are: if...elif...else AND while...

### 1.0.11 List and dictionary comprehension

```

In [109]: A = [] # defining an empty list
          for i in range(4):
              A.append(i**2) # filling the list with values
          print A

```

```
[0, 1, 4, 9]
```

```

In [110]: # more compact way to do the same thing
          B = [i**2 for i in range(4)]
          print B

```

```
[0, 1, 4, 9]
```

```

In [111]: # The same is also used for dictionaries
          D = {'squared_{}'.format(k) : k**2 for k in range(10)}
          print D

```

```
{'squared_3': 9, 'squared_2': 4, 'squared_1': 1, 'squared_0': 0, 'squared_7': 49, 'squared_6': 36, 'squared_5': 25, 'squared_4': 16, 'squared_8': 64, 'squared_9': 81}
```

### 1.0.12 Functions, procedures

```

In [112]: def func1(x):
          print(x**3)
          func1(5)

```

```
125
```

```

In [113]: def func2(x):
          """
          Return the cube of the parameter
          """
          return(x**3)
          a = func2(3)

          help(func2)

```

```
Help on function func2 in module __main__:
```

```

func2(x)
    Return the cube of the parameter

```

```
In [115]: #func2() shift-TAB inside the parenthesis
func2?
```

```
In [116]: print(a)
          print(func2(4))
```

27

64

```
In [117]: def func3(x, y, z, a=0, b=1):
          """
          This function has 5 arguments, 2 of them have default values (then not mandatory)
          """
          return a + b * (x**2 + y**2 + z**2)**0.5
          D = func3(3, 4, 5)
          print D
```

7.07106781187

```
In [118]: E = func3(3, 4, 5, 10, 100)
          print E
```

717.106781187

```
In [119]: F = func3(x=3, y=4, z=5, a=10, b=100)
          print F
```

717.106781187

```
In [120]: G = func3(3, 4, 5, a=10, 100) # ERROR!
          print G
```

```
File "<ipython-input-120-a2bc66692446>", line 1
    G = func3(3, 4, 5, a=10, 100) # ERROR!
SyntaxError: non-keyword arg after keyword arg
```

```
In [121]: H = func3(3, 4, 5, a=10, b=100)
          print H
```

717.106781187

```
In [122]: I = func3(z=5, x=3, y=4, a=10, b=100) # quite risky!
          print I
```

717.106781187

Lambda function is used to creat simple (single line) functions:

```
In [123]: J = lambda x, y, z: (x**2 + y**2 + z**2)**0.5
          J(1,2,3)
```

Out[123]: 3.7416573867739413

```
In [124]: print((lambda x,y,z: x+y+z)(0,1,2))
```

3

**Changing the value of variable inside a routine** Parameters to functions are references to objects, which are passed by value. When you pass a variable to a function, python passes the reference to the object to which the variable refers (the value). Not the variable itself. If the value is immutable, the function does not modify the caller's variable. If the value is mutable, the function may modify the caller's variable in-place, if a mutation of the variable is done (not if a new mutable value is assigned):

```
In [125]: def try_to_modify(x, y, z):
           x = 23
           y.append(22)
           z = [29] # new reference
           print('    IN THE ROUTINE')
           print(x)
           print(y)
           print(z)

           # The values of a, b and c are set
           a = 77
           b = [79]
           c = [78]

           print('    INIT')
           print(a)
           print(b)
           print(c)

           try_to_modify(a, b, c)

           print('    AFTER THE ROUTINE')
           print(a)
           print(b)
           print(c)
```

```
INIT
77
[79]
[78]
    IN THE ROUTINE
23
[79, 22]
[29]
    AFTER THE ROUTINE
77
[79, 22]
[78]
```

**Variables from outside (from a level above) are known:**

```
In [126]: a = 5
           def test_a(x):
               print a*x
           test_a(5)
           a = 10
           test_a(5)
           print(a)
```

25  
50  
10

In [127]: *# This works even if a2 is not known when defining the function:*

```
def test_a2(x):  
    print a2*x  
a2 = 10  
test_a2(5)
```

50

Variables from inside are unknown outside:

```
In [128]: def test_g2():  
          g2 = 5  
          print g2  
          test_g2()  
          print g2
```

5

```
-----  
NameError                                Traceback (most recent call last)  
  
  <ipython-input-128-f60224a7598e> in <module>()  
      3     print g2  
      4 test_g2()  
----> 5 print g2
```

NameError: name 'g2' is not defined

Global variable is known outside:

```
In [129]: def test_g3():  
          global g3  
          g3 = 5  
          print g3  
          test_g3()  
          print g3
```

5  
5

Recursivity

```
In [130]: def fact(n):  
          if n <= 0:  
              return 1  
          return n*fact(n-1)  
          print(fact(5))  
          print(fact(20))  
          print(fact(100))
```



120

2432902008176640000

9332621544394415268169923885626670049071596826438162146859296389521759999322991560894146397615651828625

### 1.0.13 Scripting

```
In [131]: %%writefile ex1.py
          # This write the current cell to a file
          def f1(x):
              """
              This is an example of a function, returning x**2
              - parameter: x
              """
              return x**2
```

Overwriting ex1.py

```
In [132]: !cat ex1.py
```

```
# This write the current cell to a file
def f1(x):
    """
    This is an example of a function, returning x**2
    - parameter: x
    """
    return x**2
```

```
In [133]: # load a file in the next cell. Usefull for small scripts.
          %load ex1.py
```

```
In []: # This write the current cell to a file
       def f1(x):
           """
           This is an example of a function, returning x**2
           - parameter: x
           """
           return x**2
```

```
In [134]: # This write the current cell to a file
          def f1(x):
              """
              This is an example of a function, returning x**2
              - parameter: x
              """
              return x**2
```

```
In [135]: import ex1 #this imports a file named ex1.py from the current directory or
          # from one of the directories in the search path
          print ex1.f1(4)
```

16

```
In [136]: from ex1 import f1
          print f1(3)
```

9

```
In [137]: from ex1 import * # DO NOT DO THIS! Very hard to know where f1 is coming from (debugging, nam
print f1(4)
```

16

```
In [138]: import ex1 as tt
print tt.f1(10)
```

100

```
In [139]: %run ex1 # The same as doing a copy-paste of the content of the file.
f1(8)
```

Out[139]: 64

```
In [140]: !pwd
```

/Users/christophemorisset/Google Drive/Pro/Python-MySQL/Notebooks

```
In [141]: !pydoc -w ex1 # ! used to call a Unix command
```

wrote ex1.html

```
In [142]: from IPython.display import HTML
HTML(open('ex1.html').read())
```

Out[142]: <IPython.core.display.HTML at 0x107777050>

Help with TAB or ?

```
In [143]: f1?
```

```
In [144]: help(f1)
```

Help on function f1 in module \_\_main\_\_:

```
f1(x)
    This is an example of a function, returning x**2
    - parameter: x
```

#### 1.0.14 Importing libraries

Not all the power of python is available when we call (i)python. Some additional librairies (included in the python package, or as additional packages, like numpy) can be imported to increase to capacities of python. This is the case of the math library:

```
In [145]: print sin(3.)
```

0.14112000806

```
In [146]: import math
print math.sin(3.)
```

0.14112000806

```
In [147]: math?
```

```
In [148]: math.
```

```
File "<ipython-input-148-186ff497df9b>", line 1
math.
~
```

SyntaxError: invalid syntax

```
In [149]: # We can import all the elements of the library in the current domain name (NOT A GOOD IDEA!!)
          from math import *
          sin(3.)
```

Out[149]: 0.1411200080598672

```
In [150]: # One can look at the contents of a library with dir:
          print(dir(math))
```

```
['__doc__', '__file__', '__name__', '__package__', 'acos', 'acosh', 'asin', 'asinh', 'atan', 'atan2', 'atanh',
```

```
In [151]: # The help command is used to have information on a given function:
          help(math.sin)
```

Help on built-in function sin in module math:

```
sin(...)
    sin(x)
```

Return the sine of x (measured in radians).

```
In [152]: help(log)
```

Help on built-in function log in module math:

```
log(...)
    log(x[, base])
```

Return the logarithm of x to the given base.

If the base not specified, returns the natural logarithm (base e) of x.

```
In [153]: print math.pi
```

3.14159265359

```
In [154]: math.pi = 2.71
```

```
In [155]: print math.pi
```

2.71

```
In [156]: import math
```

```
In [157]: math.pi
```

Out[157]: 2.71

```
In [158]: reload(math)
```

Out[158]: <module 'math' from '/Users/christophemorisset/Ureka/variants/common/lib/python2.7/lib-dynload'

```
In [159]: math.pi
```

```
Out[159]: 3.141592653589793
```

```
In [160]: from math import pi as pa
```

```
In [161]: pa
```

```
Out[161]: 3.141592653589793
```

```
In [162]: math = 2  
          math.pi
```

```
-----  
AttributeError                                Traceback (most recent call last)
```

```
<ipython-input-162-70a02d6227fb> in <module>()  
      1 math = 2  
----> 2 math.pi
```

```
AttributeError: 'int' object has no attribute 'pi'
```

```
In [163]: pa
```

```
Out[163]: 3.141592653589793
```