

intro_Python

June 30, 2017

1 A Introduction to Python for dummies...

This is part of the Python lecture given by Christophe Morisset at IA-UNAM.

```
In [1]: # The following is to know when this notebook has been run and with which python version.
import time, sys
print(time.ctime())
print(sys.version.split('|')[0])
```

```
Fri Jun 30 12:57:36 2017
3.6.1
```

1.0.1 Using Python as a calculator

Using of “print” command is not necessary to obtain a result. Just type some operations and the result is obtain with ENTER.

```
In [1]: 2 + 22
```

```
Out[1]: 24
```

```
In [2]: (2+3)*(3+4)/(5*5)
```

```
Out[2]: 1.4
```

```
In [3]: (2+3) * (3+4.) / (5*5)
```

```
Out[3]: 1.4
```

```
In [4]: # If you are using python 2.X, the default behaviour is not this one.
# Do the following to be sure you are using the python 3.N division:
from __future__ import division
```

Python likes the use of spaces to make scripts more readable

The art of writing good python code is described in the following document:
<http://legacy.python.org/dev/peps/pep-0008/>

1.0.2 Assignments

Like any other langage, you can assign a value to a variable. This is done with = symbol:

```
In [5]: a = 4
```

A lot of operations can be performed on the variables. The most basics are for example:

```
In [6]: a
```

```
Out[6]: 4
```

```
In [7]: a = a + 1  
a
```

```
Out[7]: 5
```

```
In [8]: a *= 4 # similar to a = a * 4  
a
```

```
Out[8]: 20
```

```
In [9]: a, b = 1, 3  
a, b
```

```
Out[9]: (1, 3)
```

Some variable name are not available, they are reserved to python itself: and, as, assert, break, class, continue, def, del, elif, else, except, exec, finally, for, from, global, if, import, in, is, lambda, not, or, pass, print, raise, return, try, while, with, yield

```
In [10]: lambda_ = 2  
file = 3
```

1.0.3 Comments

```
In [11]: a = 2 # this is a comment
```

```
In [12]: """ This is a large comment  
on multiple lines  
ending as it started  
"""
```

```
Out[12]: ' This is a large comment\nnon multiple lines\nending as it started\n'
```

1.0.4 Types

The types used in Python are: integers, long integers, floats (double prec.), complexes, strings, booleans.

Double precision: machine dependent, generally between 10^{-308} and 10^{308} , with 16 significant digits.

The function type gives the type of its argument:

```
In [13]: type(2)
```

```
Out[13]: int
```

```
In [14]: type(2.3)
```

```
Out[14]: float
```

```
In [15]: int(0.8) # truncating
```

```
Out[15]: 0
```

```
In [16]: round(0.8765566777) # nearest, result is integer (was float with python 2.N)
```

```
Out[16]: 1
```

1.0.5 Complex numbers

```
In [17]: a = 1.5 + 0.5j
In [18]: a**2.
Out[18]: (2+1.5j)
In [19]: (1+2j)*(1-2j)
Out[19]: (5+0j)
In [20]: a.real
Out[20]: 1.5
In [21]: (a**3).imag
Out[21]: 3.25
In [22]: a.conjugate() # this is a function, it requires ()
Out[22]: (1.5-0.5j)
```

1.0.6 Booleans

Comparison operators are `<`, `<=`, `>`, `>=`, `==`, `!=`

```
In [23]: 5 < 3
Out[23]: False
In [24]: a = 5
          b = 7
In [25]: b < a
Out[25]: False
In [26]: c = 2
In [27]: c < a < b
Out[27]: True
In [28]: a < b and b < c
Out[28]: False
In [29]: res = a < 7
          print(res, type(res))

True <class 'bool'>
In [30]: print(int(res))
          print(int(not res))

1
0
In [31]: not res is True
Out[31]: False
In [32]: a = True
          print(a)

True
```

1.0.7 Formating strings

```
In [33]: print("Hello world!")
```

Hello world!

```
In [34]: print('Hello world!')
```

Hello world!

```
In [35]: print("Hello I'm here") # ' inside ""
```

Hello I'm here

```
In [36]: # This is the old fashion way of formating outputs (C-style)
```

```
    a = 7.5
```

```
    b = 'tralala'
```

```
    c = 8.9e-33
```

```
    print('a = %f, b = %s, c = %e' % (a, b, c))
```

a = 7.500000, b = tralala, c = 8.900000e-33

```
In [37]: # The new way is using the format() method of the string object, and {} to define which value
```

```
    print('a = {} & b = {} & c = {} \\\\' .format(a,b,c))
```

```
    print('a = {0}, b = {1}, c = {2}' .format(a**2,b,c))
```

```
    print('a = {:.f}, b = {:20s}, c = {:.15.3e}' .format(a,b,c))
```

a = 7.5 & b = tralala & c = 8.9e-33 \\

a = 56.25, b = tralala, c = 8.9e-33

a = 7.500000, b = tralala , c = 8.900e-33

Much more on this here: <https://docs.python.org/3/tutorial/inputoutput.html>

1.0.8 Strings

```
In [38]: a = "this is a string"
```

```
In [39]: len(a)
```

```
Out[39]: 19
```

A lot of commands can operate on strings. Strings, like ANYTHING in python, are objects. Methods are run on objects by dots:

```
In [40]: a.upper()
```

```
Out[40]: 'THIS IS A STRING'
```

```
In [41]: a.title()
```

```
Out[41]: 'This Is A String'
```

```
In [42]: a.split()
```

```
Out[42]: ['this', 'is', 'a', 'string']
```

```
In [43]: a.split()[1]
```

```
Out[43]: 'is'
```

```

In [44]: a = "This is a string.    With various sentences."
In [45]: a.split('.')
Out[45]: ['This is a string', '    With various sentences', '']
In [46]: a.split('.')[1].strip() # Here we define the character used to split. The default is space (and
Out[46]: 'With various sentences'

In [47]: a = 'tra'
        b = 'la'
        print(' '.join((a,b,b)))
        print('-'.join((a,b,b)))
        print(''.join((a,b,b)))
        print(a+b+b)
        print(' '.join((a,b,b)).split())
        print(' & '.join((a,b,b)) + '\\\\')

tra la la
tra-la-la
tralala
tralala
['tra', 'la', 'la']
tra & la & la\\

```

1.0.9 Containers: Tuples, Lists and Dictionaries

list: a collection of objects. May be of different types. It has an order.

```

In [48]: L = ['red', 'green', 'blue'] # squared brackets are used to define lists
In [49]: type(L) # Print the type of L
Out[49]: list

In [50]: L[1]
Out[50]: 'green'

In [51]: L[0] # indexes start at 0 !!!
Out[51]: 'red'

In [52]: L[-1] # last element
Out[52]: 'blue'

In [53]: L[-3]
Out[53]: 'red'

In [54]: L = L + ['black', 'white'] # addition symbol is used to agregate values to a list. See below o
In [55]: print(L)

['red', 'green', 'blue', 'black', 'white']

In [56]: L[1:3] # L[start:stop] : elements if index i, where start <= i < stop !! stop not included !!

```

```

Out[56]: ['green', 'blue']
In [57]: L[2:] # boudaries can be omitted
Out[57]: ['blue', 'black', 'white']
In [58]: L[-2:]
Out[58]: ['black', 'white']
In [59]: L[::2] # L[start:stop:step] every 2 elements
Out[59]: ['red', 'blue', 'white']
In [60]: L[::-1]
Out[60]: ['white', 'black', 'blue', 'green', 'red']

Lists are mutable: their content can be modified.

In [61]: L[2] = 'yellow'
          L
Out[61]: ['red', 'green', 'yellow', 'black', 'white']
In [62]: L.append('pink') # append a value at the end
          L
Out[62]: ['red', 'green', 'yellow', 'black', 'white', 'pink']
In [63]: L.insert(2, 'blue') #L.insert(index, object) -- insert object before index
          L
Out[63]: ['red', 'green', 'blue', 'yellow', 'black', 'white', 'pink']
In [64]: L.extend(['magenta', 'purple'])
          L
Out[64]: ['red',
          'green',
          'blue',
          'yellow',
          'black',
          'white',
          'pink',
          'magenta',
          'purple']
In [65]: L.append(['magenta', 'azul'])
          L
Out[65]: ['red',
          'green',
          'blue',
          'yellow',
          'black',
          'white',
          'pink',
          'magenta',
          'purple',
          ['magenta', 'azul']]

```

```
In [66]: L.append(2)
         L
```

```
Out[66]: ['red',
          'green',
          'blue',
          'yellow',
          'black',
          'white',
          'pink',
          'magenta',
          'purple',
          ['magenta', 'azul'],
          2]
```

```
In [67]: L = L[::-1] # reverse order
         L
```

```
Out[67]: [2,
          ['magenta', 'azul'],
          'purple',
          'magenta',
          'pink',
          'white',
          'black',
          'yellow',
          'blue',
          'green',
          'red']
```

```
In [68]: L2 = L[:-3] # cutting the last 3 elements
         print(L)
         print(L2)
```

```
[2, ['magenta', 'azul'], 'purple', 'magenta', 'pink', 'white', 'black', 'yellow', 'blue', 'green', 'red']
[2, ['magenta', 'azul'], 'purple', 'magenta', 'pink', 'white', 'black', 'yellow']
```

```
In [69]: L[25] # Out of range leads to error
```

```
-----
IndexError                                Traceback (most recent call last)

<ipython-input-69-c16babb9288f> in <module>()
----> 1 L[25] # Out of range leads to error

IndexError: list index out of range
```

```
In [71]: print(L)
         print(L[20:25]) # But NO ERROR when slicing.
         print(L[20:])
         print(L[2:20])
```

```
[2, ['magenta', 'azul'], 'purple', 'magenta', 'pink', 'white', 'black', 'yellow', 'blue', 'green', 'red']
[]
[]
['purple', 'magenta', 'pink', 'white', 'black', 'yellow', 'blue', 'green', 'red']
```

```
In [72]: print(L.count('yellow'))
```

```
1
```

```
In [73]: L2 = L[2:20]
         L2.sort() # One can use TAB to look for the methods (functions that apply to an object)
         print(L2)
```

```
['black', 'blue', 'green', 'magenta', 'pink', 'purple', 'red', 'white', 'yellow']
```

```
In [74]: a = [1,2,3]
         b = [10,20,30]
```

```
In [75]: print(a+b) # may not be what you expected, but rather logical too
```

```
[1, 2, 3, 10, 20, 30]
```

```
In [76]: print(a*b) # Does NOT multiply element by element. Numpy will do this job.
```

```
-----

TypeError                                Traceback (most recent call last)

<ipython-input-76-ddfd21d938fe> in <module>()
----> 1 print(a*b) # Does NOT multiply element by element. Numpy will do this job.
```

```
TypeError: can't multiply sequence by non-int of type 'list'
```

```
In [78]: L = range(4) # Create an iterator. Notice the parameter is the number of elements, not the last element
         print(L) # In python 2, that was a list
         print(list(L))
```

```
range(0, 4)
[0, 1, 2, 3]
```

```
In [79]: L = range(2, 20, 2) # every 2 integer
         print(L)
```

```
range(2, 20, 2)
```

The types of the elements of a list are not always the same:

```
In [80]: L = [1, '1', 1.4]
         L
```

```
Out[80]: [1, '1', 1.4]
```

Remove the n+1-th element:


```
In [81]: L = list(range(0,20,2))
        print(L)
        del(L[5])
        print(L)
```

```
[0, 2, 4, 6, 8, 10, 12, 14, 16, 18]
[0, 2, 4, 6, 8, 12, 14, 16, 18]
```

Slicing: extracting sub-list of a list

```
In [82]: a = [[1, 2, 3], [10, 20, 30], [100, 200, 300]] # Not a 2D table, but rather a table of tables.
        print(a)
        print(a[0])
        print(a[1][1])
```

```
[[1, 2, 3], [10, 20, 30], [100, 200, 300]]
[1, 2, 3]
20
```

```
In [83]: print(a[1,1]) # Does NOT work
```

```
-----
TypeError                                Traceback (most recent call last)

<ipython-input-83-d8214b6adea8> in <module>()
----> 1 print(a[1,1]) # Does NOT work
```

TypeError: list indices must be integers or slices, not tuple

```
In [84]: b = a[1]
        print(b)
```

```
[10, 20, 30]
```

```
In [85]: b[1] = 999 # Changing the value of a single element
        print(b)
```

```
[10, 999, 30]
```

```
In [86]: print(a) # Changing b changed a !!!
```

```
[[1, 2, 3], [10, 999, 30], [100, 200, 300]]
```

```
In [87]: b[1] is a[1][1]
```

```
Out[87]: True
```

```
In [88]: c = a[1][:] # copy instead of slicing
        print(c)
        c[0] = 77777
        print(c)
        print(a)
```

```
[10, 999, 30]
[77777, 999, 30]
[[1, 2, 3], [10, 999, 30], [100, 200, 300]]
```

tuples: like lists, but immutable

```
In [89]: T = (1,2,3)
         T
```

```
Out[89]: (1, 2, 3)
```

```
In [90]: T2 = 1, 2, 3
         print(T2)
         type(T2)
```

```
(1, 2, 3)
```

```
Out[90]: tuple
```

```
In [91]: T[1]
```

```
Out[91]: 2
```

tuples are unmutables

```
In [92]: T[1] = 3 # Does NOT work!
```

```
-----
TypeError                                Traceback (most recent call last)

<ipython-input-92-6dd68cc28786> in <module>()
----> 1 T[1] = 3 # Does NOT work!

TypeError: 'tuple' object does not support item assignment
```

Dictionnaires A dictionary is basically an efficient table that maps keys to values. It is an unordered container

```
In [93]: D = {'Christophe': 12, 'Antonio': 15} # defined by {key : value}
```

```
In [94]: D['Christophe'] # access to a value by the key
```

```
Out[94]: 12
```

```
In [95]: D.keys() # list of the dictionary keys
```

```
Out[95]: dict_keys(['Christophe', 'Antonio'])
```

```
In [96]: D['Yilen'] = 16 # adding a new entry
```

```
In [97]: print(D)
```

```
{'Christophe': 12, 'Antonio': 15, 'Yilen': 16}
```

```
In [98]: print(D[0]) # use the keys to acces the elements. No order in dictionnary.
```

```

-----

KeyError                                Traceback (most recent call last)

<ipython-input-98-035806c13f20> in <module>()
----> 1 print(D[0]) # use the keys to acces the elements. No order in dictionary.

KeyError: 0

```

1.0.10 Blocks

Blocks are defined by indentation. Looks nice and no needs for end :-)

```
In [99]: for i in [1,2,3]: print(i) # compact way, not recommended.
```

```
1
2
3
```

```
In [100]: for cosa in [1,'ff',2]:
           print(cosa)
           print('end')
           print('final end') # end of the indentation means end of the block
```

```
1
end
ff
end
2
end
final end
```

```
In [101]: # defining a dictionary:
```

```

ATOMIC_MASS = {}
ATOMIC_MASS['H'] = 1
ATOMIC_MASS['He'] = 4
ATOMIC_MASS['C'] = 12
ATOMIC_MASS['N'] = 14
ATOMIC_MASS['O'] = 16
ATOMIC_MASS['Ne'] = 20
ATOMIC_MASS['Ar'] = 40
ATOMIC_MASS['S'] = 32
ATOMIC_MASS['Si'] = 28
ATOMIC_MASS['Fe'] = 55.8
# Print the keys and values from the dictionary. As it is not ordered , they come as they wan
for key in ATOMIC_MASS.keys():
    print(key, ATOMIC_MASS[key])

```

```

H 1
He 4
C 12
N 14
O 16

```

```
Ne 20
Ar 40
S 32
Si 28
Fe 55.8
```

```
In [102]: for key in sorted(ATOMIC_MASS): # sorting using the keys
          print('Element: {0:3s} Atomic Mass: {1}'.format(key, ATOMIC_MASS[key]))
```

```
Element: Ar Atomic Mass: 40
Element: C Atomic Mass: 12
Element: Fe Atomic Mass: 55.8
Element: H Atomic Mass: 1
Element: He Atomic Mass: 4
Element: N Atomic Mass: 14
Element: Ne Atomic Mass: 20
Element: O Atomic Mass: 16
Element: S Atomic Mass: 32
Element: Si Atomic Mass: 28
```

a key parameter can be used to specify a function to be called on each list element prior to making comparisons. More in sorted function here: <https://wiki.python.org/moin/HowTo/Sorting> or here: <http://www.pythoncentral.io/how-to-sort-a-list-tuple-or-object-with-sorted-in-python/>

```
In [103]: for elem in sorted(ATOMIC_MASS, key = ATOMIC_MASS.get): # sorting using the values
          print('Element: {0:3s} Atomic Mass: {1}'.format(elem, ATOMIC_MASS[elem]))
```

```
Element: H Atomic Mass: 1
Element: He Atomic Mass: 4
Element: C Atomic Mass: 12
Element: N Atomic Mass: 14
Element: O Atomic Mass: 16
Element: Ne Atomic Mass: 20
Element: Si Atomic Mass: 28
Element: S Atomic Mass: 32
Element: Ar Atomic Mass: 40
Element: Fe Atomic Mass: 55.8
```

```
In [104]: for idx, elem in enumerate(sorted(ATOMIC_MASS, key = ATOMIC_MASS.get)): # adding an index tha
          print('{0:2} Element: {1:2s} Atomic Mass: {2:4.1f}'.format(idx+1, elem, ATOMIC_MASS[elem]))
```

```
1 Element: H Atomic Mass: 1.0
2 Element: He Atomic Mass: 4.0
3 Element: C Atomic Mass: 12.0
4 Element: N Atomic Mass: 14.0
5 Element: O Atomic Mass: 16.0
6 Element: Ne Atomic Mass: 20.0
7 Element: Si Atomic Mass: 28.0
8 Element: S Atomic Mass: 32.0
9 Element: Ar Atomic Mass: 40.0
10 Element: Fe Atomic Mass: 55.8
```

```
In [105]: for i in range(10):
          if i > 5:
              print(i)
```

6
7
8
9

```
In [106]: for i in range(10):
           if i > 5:
               print(i)
           else:
               print('i lower than five')
       print('END')
```

i lower than five
i lower than five
i lower than five
i lower than five
i lower than five
i lower than five
i lower than five

6
7
8
9
END

Other commands are: if...elif...else AND while...

1.0.11 List and dictionary comprehension

```
In [107]: A = [] # defining an empty list
           for i in range(4):
               A.append(i**2) # filling the list with values
           print(A)
```

[0, 1, 4, 9]

```
In [108]: # more compact way to do the same thing
           B = [i**2 for i in range(4)]
           print(B)
```

[0, 1, 4, 9]

```
In [109]: # The same is also used for dictionaries
           D = {'squared_{}'.format(k) : k**2 for k in range(10)}
           print(D)
```

{'squared_0': 0, 'squared_1': 1, 'squared_2': 4, 'squared_3': 9, 'squared_4': 16, 'squared_5': 25, 'squared_6': 36, 'squared_7': 49, 'squared_8': 64, 'squared_9': 81}

1.0.12 Functions, procedures

```
In [110]: def func1(x):
           print(x**3)
           func1(5)
```

125

```

In [111]: def func2(x,
                y):
            """
            Return the cube and the 4th power of the two parameters
            """
            return(x**3, y**4)
            a = func2(3, 5)

            help(func2)

Help on function func2 in module __main__:

func2(x, y)
    Return the cube and the 4th power of the two parameters

In [112]: #func2() shift-TAB inside the parenthesis
            func2?

In [113]: print(a)
            print(func2(4, 6))

(27, 625)
(64, 1296)

In [114]: def func3(x, y, z, a=0, b=1):
            """
            This function has 5 arguments, 2 of them have default values (then not mandatory)
            """
            return a + b * (x**2 + y**2 + z**2)**0.5
            D = func3(3, 4, 5)
            print(D)

7.0710678118654755

In [115]: E = func3(3, 4, 5, 10, 100)
            print(E)

717.1067811865476

In [116]: F = func3(x=3, y=4, z=5, a=10, b=100)
            print(F)

717.1067811865476

In [117]: G = func3(3, 4, 5, a=10, 100) # ERROR!
            print(G)

File "<ipython-input-117-7963f4c1b801>", line 1
G = func3(3, 4, 5, a=10, 100) # ERROR!
              ^
SyntaxError: positional argument follows keyword argument

In [118]: H = func3(3, 4, 5, a=10, b=100)
            print(H)

```

```
717.1067811865476
```

```
In [119]: I = func3(z=5, x=3, y=4, a=10, b=100) # quite risky!
          print(I)
```

```
717.1067811865476
```

Lambda function is used to creat simple (single line) functions:

```
In [120]: J = lambda x, y, z: (x**2 + y**2 + z**2)**0.5
          J(1,2,3)
```

```
Out[120]: 3.7416573867739413
```

```
In [121]: def J(x,y,z):
          return (x**2 + y**2 + z**2)**0.5
          J(1,2,3)
```

```
Out[121]: 3.7416573867739413
```

```
In [122]: print((lambda x,y,z: x+y+z)(0,1,2))
```

```
3
```

Changing the value of variable inside a routine Parameters to functions are references to objects, which are passed by value. When you pass a variable to a function, python passes the reference to the object to which the variable refers (the value). Not the variable itself. If the value is immutable, the function does not modify the caller's variable. If the value is mutable, the function may modify the caller's variable in-place, if a mutation of the variable is done (not if a new mutable value is assigned):

```
In [123]: def try_to_modify(x, y, z):
          x = 23
          y.append(22)
          z = [29] # new reference
          print('    IN THE ROUTINE')
          print(x)
          print(y)
          print(z)

          # The values of a, b and c are set
          a = 77
          b = [79]
          c = [78]

          print('    INIT')
          print(a)
          print(b)
          print(c)

          try_to_modify(a, b, c)

          print('    AFTER THE ROUTINE')
          print(a)
          print(b)
          print(c)
```

```

INIT
77
[79]
[78]
    IN THE ROUTINE
23
[79, 22]
[29]
    AFTER THE ROUTINE
77
[79, 22]
[78]

```

Variables from outside (from a level above) are known:

```

In [124]: a = 5
          def test_a(x):
              print(a*x)
          test_a(5)
          a = 10
          test_a(5)
          print(a)

25
50
10

In [125]: # This works even if a2 is not known when defining the function:
          def test_a2(x):
              print(a2*x)
          a2 = 10
          test_a2(5)

50

```

Variables from inside are unknown outside:

```

In [126]: def test_g2():
          g2 = 5
          print(g2)
          test_g2()
          print(g2)

5

```

```

-----

NameError                                Traceback (most recent call last)

<ipython-input-126-edf2e6190ece> in <module>()
      3     print(g2)
      4 test_g2()
----> 5 print(g2)

NameError: name 'g2' is not defined

```


Global variable is known outside:

```
In [127]: def test_g3():
           global g3
           g3 = 5
           print(g3)
test_g3()
print(g3)
```

5
5

Recursivity

```
In [128]: def fact(n):
           if n <= 0:
               return 1
           return n*fact(n-1)
print(fact(5))
print(fact(20))
print(fact(100))
```

120
2432902008176640000
9332621544394415268169923885626670049071596826438162146859296389521759999322991560894146397615651828625

1.0.13 Scripting

```
In [129]: %%writefile ex1.py
           # This write the current cell to a file
           def f1(x):
               """
               This is an example of a function, returning x**2
               - parameter: x
               """
               return x**2
```

Overwriting ex1.py

```
In [130]: !cat ex1.py
```

```
# This write the current cell to a file
def f1(x):
    """
    This is an example of a function, returning x**2
    - parameter: x
    """
    return x**2
```

```
In [131]: # %load ex1.py
           # This write the current cell to a file
           def f1(x):
               """
               This is an example of a function, returning x**2
               - parameter: x
               """
               return x**2
```

```

In [132]: # This write the current cell to a file
def f1(x):
    """
    This is an example of a function, returning x**2
    - parameter: x
    """
    return x**2

In [133]: # This write the current cell to a file
def f1(x):
    """
    This is an example of a function, returning x**2
    - parameter: x
    """
    return x**2

In [134]: import ex1 #this imports a file named ex1.py from the current directory or
# from one of the directories in the search path
print(ex1.f1(4))

16

In [135]: from ex1 import f1
print(f1(3))

9

In [136]: from ex1 import * # DO NOT DO THIS! Very hard to know where f1 is coming from (debugging, nam
print(f1(4))

16

In [137]: import ex1 as tt
print(tt.f1(10))

100

In [138]: %run ex1 # The same as doing a copy-paste of the content of the file.
f1(8)

Out[138]: 64

In [139]: !pwd

/home/morisset/Google Drive/Pro/Python-MySQL/Notebooks/Notebooks

In [140]: !pydoc -w ex1 # ! used to call a Unix command
wrote ex1.html

In [141]: from IPython.display import HTML
HTML(open('ex1.html').read())

Out[141]: <IPython.core.display.HTML object>

Help with TAB or ?

In [142]: f1?

In [143]: help(f1)

Help on function f1 in module __main__:

f1(x)
    This is an example of a function, returning x**2
    - parameter: x

```

1.0.14 Importing libraries

Not all the power of python is available when we call (i)python. Some additional librairies (included in the python package, or as additional packages, like numpy) can be imported to increase to capacities of python. This is the case of the math library:

```
In [144]: print(sin(3.))
```

```
-----  
NameError                                Traceback (most recent call last)  
  
<ipython-input-144-3774d5a0e3c9> in <module>()  
----> 1 print(sin(3.))  
  
NameError: name 'sin' is not defined
```

```
In [145]: import math  
          print(math.sin(3.))
```

```
0.1411200080598672
```

```
In [146]: math?
```

```
In [147]: math.
```

```
File "<ipython-input-147-186ff497df9b>", line 1  
math.  
^  
SyntaxError: invalid syntax
```

```
In [148]: # We can import all the elements of the library in the current domain name (NOT A GOOD IDEA!!  
          from math import *  
          sin(3.)
```

```
Out[148]: 0.1411200080598672
```

```
In [149]: # One can look at the contents of a library with dir:  
          print(dir(math))
```

```
['__doc__', '__file__', '__loader__', '__name__', '__package__', '__spec__', 'acos', 'acosh', 'asin', 'asinh',
```

```
In [150]: # The help command is used to have information on a given function:  
          help(math.sin)
```

Help on built-in function sin in module math:

```
sin(...)  
    sin(x)
```

Return the sine of x (measured in radians).

```
In [151]: help(log)
```

Help on built-in function log in module math:

```
log(...)
    log(x[, base])
```

Return the logarithm of x to the given base.

If the base not specified, returns the natural logarithm (base e) of x.

```
In [152]: print(math.pi)
```

```
3.141592653589793
```

```
In [153]: math.pi = 2.71
```

```
In [154]: print(math.pi)
```

```
2.71
```

```
In [155]: import math
```

```
In [156]: math.pi
```

```
Out[156]: 2.71
```

```
In [157]: # In python 3 you need to import reload
          from importlib import reload
```

```
In [158]: reload(math)
```

```
Out[158]: <module 'math' from '/home/morisset/anaconda2/envs/py3k6/lib/python3.6/lib-dynload/math.cpython
```

```
In [159]: # In python 2 the value is reset, in python 3 this is not the case!!!
          math.pi
```

```
Out[159]: 2.71
```

```
In [160]: from math import pi as pa
```

```
In [161]: pa
```

```
Out[161]: 2.71
```

```
In [162]: math = 2
          math.pi
```

```
-----
AttributeError                                Traceback (most recent call last)

<ipython-input-162-70a02d6227fb> in <module>()
      1 math = 2
----> 2 math.pi
```

```
AttributeError: 'int' object has no attribute 'pi'
```

```
In [163]: pa
```

```
Out[163]: 2.71
```

```
In [ ]:
```