

Optimization

June 1, 2016

```
In [1]: # Just to know last time this was run:
import time
print time.ctime()
```

Wed Jun 1 17:19:31 2016

1 H Optimizing code writing

This is part of the Python lecture given by Christophe Morisset at IA-UNAM. More informations at: <http://python-astro.blogspot.mx/>

```
In [2]: import numpy as np
from IPython.core.display import Image
```

1.0.1 Profiling the code: CPU usage

```
In [3]: %%writefile test_1_prof.py
```

```
import numpy as np
import os
import urllib2
from scipy.integrate import simpson

class Stel_Spectrum(object):
    """
    This object downloads a file from http://astro.uni-tuebingen.de/~rauch/
    and is able to make some plots.
    """

    spec_count = 0 # This attribute is at the level of the class, not of the object
    def __init__(self, filename=None, T=None, logg=None, verbose=False):
        """
        Initialisation of the Stel_Spectrum object.
        Parameter:
        - filename
        - T: temperature in K, e.g. 150000
```

```

        - logg: e.g. 7.5
        - verbose: if True, some info are printed out
The wl variable is an array of wavelengths in Angstrom.
The fl variable is the flux in erg/s/cm2/A
The variables T and logg are properties: changing them will reload
"""
self.verbose = verbose
if filename is None:
    if T is not None and logg is not None:
        self.__T = T # We need to initialize the hidden values, as
        self.logg = logg
        self.filename = '0{0:06.0f}_{1:.2f}_33_50_02_15.bin_0.1.gz'
    else:
        raise TypeError("T and logg must be given")
else:
    self.filename = filename
    self.__T = float(filename.split('_')[0]) # We need to initialize
    self.logg = float(filename.split('_')[1])
Stel_Spectrum.spec_count += 1
if self.verbose:
    print('Instantiation done')

def dlfile(self):
    """
    Downloading file if not already here. Put it in the current directory
    """
    if not os.path.exists(self.filename):
        if self.verbose:
            print('Downloading {}'.format(self.filename))
        try:
            stel_file = urllib2.urlopen('http://astro.uni-tuebingen.de/{}'.format(
                self.filename))
            output = open(self.filename, 'wb')
            output.write(stel_file.read())
            output.close()
            self.file_found=True
        except:
            if self.verbose:
                print('file {} not found'.format(self.filename))
            self.file_found=False
    else:
        if self.verbose:
            print('{} already on disk'.format(self.filename))
        self.file_found=True

def read_data(self):
    """
    read the data from the file

```

```

"""
if self.file_found:
    data = np.genfromtxt(self.filename, comments='*', names='wl, fl')
    self.fl = data['fl']
    self.wl = data['wl'] # in A
    self.fl /= 1e8 # F LAMBDA GIVEN IN ERG/CM**2/SEC/CM -> erg/s/cm2
    if self.verbose:
        print('Read data from {}'.format(self.filename))
else:
    if self.verbose:
        print('file not found {}'.format(self.filename))
    self.wl = None
    self.fl = None

def plot_spr(self, ax=None, *args, **kwargs):
    """
    Plot the spectrum.
    Parameter:
        - ax: an axis (optionnal). If None or absent, axis is created
        - any extra parameter is passed to ax.plot
    """
    if self.wl is None:
        print('No data to plot')
        return
    if ax is None:
        fig, ax = plt.subplots()
    ax.plot(self.wl, self.fl,
            label='T3={0:.0f}, logg={1}'.format(self.T/1e3, self.logg),
            *args, **kwargs) # Here are the transmissions of extra parameters
    ax.set_yscale('log')
    ax.set_ylim(1e6, 1e14)
    ax.set_xlabel('Wavelength (A)')

def get_integ(self):
    """
    Return the integral of F_lambda over lambda, in erg/s/cm2
    """
    if self.wl is None:
        print('No data')
        return None
    return.simps(self.fl, self.wl) # perform the integral

def __getT(self):
    return self.__T

def __setT(self, value):
    if not isinstance(value, (int, long, float)): # check the type of T
        raise TypeError('T must be an integer or a float')

```

```

        if float(value) not in np.linspace(40000, 190000, 16): # check the
            raise ValueError('T value must be between 40000 and 190000K, by
elif self.__T != value:
    self.__T = value
    self.filename = '0{0:06.0f}_{1:.2f}_33_50_02_15.bin_0.1.gz'.for
    self.dlfile() # will download new data
    self.read_data() # will update the data

def __delT(self):
    print('T is needed')

T = property(__getT, __setT, __delT, "Stellar effective temperature")

def __getlogg(self):
    return self.__logg

def __setlogg(self, value):
    try:
        self.__logg
    except:
        self.__logg = -1
    if not isinstance(value, (int, long, float)):
        raise TypeError('logg must be an integer or a float')
    if float(value) not in (-1., 5., 6., 7., 8., 9.):
        raise ValueError('Error, logg must be 6, 7, 8, or 9')
    self.__logg = None
    elif self.__logg != value:
        self.__logg = value
        self.filename = '0{0:06.0f}_{1:.2f}_33_50_02_15.bin_0.1.gz'.for
        self.dlfile() # will download new data
        self.read_data() # will update the data

def __dellogg(self):
    print('logg is needed')

logg = property(__getlogg, __setlogg, __dellogg, "Stellar logg")

def print_info(self):
    """
    Print out the filename and the number of points
    """
    print self.__repr__()

def __repr__(self):
    """
    This is what is used when calling "print <obj>" or <obj> ENTER
    """
    if self.wl is None:

```

```

        return'Filename: {0}, No data'.format(self.filename)
    else:
        return'Filename: {0}, number of points: {1}'.format(self.filename, len(self.data))

    def __del__(self):
        Stel_Spectrum.spec_count -= 1

    spectra = [] # we create an empty list
    for T in np.linspace(40000, 190000, 4): # this is the list of available temperatures
        spectra.append(Stel_Spectrum(T=T, logg=6, verbose=True)) # we fill the list with spectra
    T = np.array([sp.T for sp in spectra])
    F = np.array([sp.get_integ() for sp in spectra])
    for t, f in zip(T, F):
        print('Temperature = {0:.0f}K, Flux = {1:.2e} erg/s/cm2'.format(t, f))

Overwriting test_1_prof.py

```

In [4]: `%run -t test_1_prof.py`

```

0040000_6.00_33_50_02_15.bin_0.1.gz already on disk
Read data from 0040000_6.00_33_50_02_15.bin_0.1.gz
Instantiation done
0090000_6.00_33_50_02_15.bin_0.1.gz already on disk
Read data from 0090000_6.00_33_50_02_15.bin_0.1.gz
Instantiation done
0140000_6.00_33_50_02_15.bin_0.1.gz already on disk
Read data from 0140000_6.00_33_50_02_15.bin_0.1.gz
Instantiation done
0190000_6.00_33_50_02_15.bin_0.1.gz already on disk
Read data from 0190000_6.00_33_50_02_15.bin_0.1.gz
Instantiation done
Temperature = 40000K, Flux = 4.00e+13 erg/s/cm2
Temperature = 90000K, Flux = 1.05e+15 erg/s/cm2
Temperature = 140000K, Flux = 6.93e+15 erg/s/cm2
Temperature = 190000K, Flux = 2.35e+16 erg/s/cm2

```

```

IPython CPU timings (estimated):
  User      :      0.42 s.
  System    :      0.02 s.
Wall time:   0.45 s.

```

In [5]: `%run -p test_1_prof.py`

```

0040000_6.00_33_50_02_15.bin_0.1.gz already on disk
Read data from 0040000_6.00_33_50_02_15.bin_0.1.gz
Instantiation done
0090000_6.00_33_50_02_15.bin_0.1.gz already on disk

```

```

Read data from 0090000_6.00_33_50_02_15.bin_0.1.gz
Instantiation done
0140000_6.00_33_50_02_15.bin_0.1.gz already on disk
Read data from 0140000_6.00_33_50_02_15.bin_0.1.gz
Instantiation done
0190000_6.00_33_50_02_15.bin_0.1.gz already on disk
Read data from 0190000_6.00_33_50_02_15.bin_0.1.gz
Instantiation done
Temperature = 40000K, Flux = 4.00e+13 erg/s/cm2
Temperature = 90000K, Flux = 1.05e+15 erg/s/cm2
Temperature = 140000K, Flux = 6.93e+15 erg/s/cm2
Temperature = 190000K, Flux = 2.35e+16 erg/s/cm2

```

```
In [6]: # Inserting @profile before some functions leads to detailed report on the
```

```
In [7]: %%writefile test_2_prof.py
```

```

import numpy as np
import os
import urllib2
from scipy.integrate import simpson

class Stel_Spectrum(object):
    """
    This object downloads a file from http://astro.uni-tuebingen.de/~rauch/
    and is able to make some plots.
    """

    spec_count = 0 # This attribute is at the level of the class, not of the

    @profile
    def __init__(self, filename=None, T=None, logg=None, verbose=False):
        """
        Initialisation of the Stel_Spectrum object.
        Parameter:
        - filename
        - T: temperature in K, e.g. 150000
        - logg: e.g. 7.5
        - verbose: if True, some info are printed out
        The wl variable is an array of wavelengths in Angstrom.
        The fl variable is the flux in erg/s/cm2/A
        The variables T and logg are properties: changing them will reload
        """
        self.verbose = verbose
        if filename is None:
            if T is not None and logg is not None:
                self.__T = T # We need to initialize the hidden values, as

```

```

        self.logg = logg
        self.filename = '0{0:06.0f}_{1:.2f}_33_50_02_15.bin_0.1.gz'
    else:
        raise TypeError("T and logg must be given")
else:
    self.filename = filename
    self.__T = float(filename.split('_')[0]) # We need to initialize T
    self.logg = float(filename.split('_')[1])
Stel_Spectrum.spec_count += 1
if self.verbose:
    print('Instantiation done')

@profile
def dlfile(self):
    """
    Downloading file if not already here. Put it in the current directory
    """
    if not os.path.exists(self.filename):
        if self.verbose:
            print('Downloading {}'.format(self.filename))
        try:
            stel_file = urllib2.urlopen('http://astro.uni-tuebingen.de/{}'.format(
                self.filename))
            output = open(self.filename, 'wb')
            output.write(stel_file.read())
            output.close()
            self.file_found=True
        except:
            if self.verbose:
                print('file {} not found'.format(self.filename))
            self.file_found=False
    else:
        if self.verbose:
            print('{} already on disk'.format(self.filename))
        self.file_found=True

@profile
def read_data(self):
    """
    read the data from the file
    """
    if self.file_found:
        data = np.genfromtxt(self.filename, comments='#', names='wl, fl')
        self.fl = data['fl']
        self.wl = data['wl'] # in A
        self.fl /= 1e8 # F LAMBDA GIVEN IN ERG/CM**2/SEC/CM -> erg/s/cm**2
        if self.verbose:
            print('Read data from {}'.format(self.filename))

```

```

else:
    if self.verbose:
        print('file not found {}'.format(self.filename))
    self.wl = None
    self.fl = None

def plot_spr(self, ax=None, *args, **kwargs):
    """
    Plot the spectrum.
    Parameter:
        - ax: an axis (optionnal). If Noe or absent, axis is created
        - any extra parameter is passed to ax.plot
    """
    if self.wl is None:
        print('No data to plot')
        return
    if ax is None:
        fig, ax = plt.subplots()
    ax.plot(self.wl, self.fl,
            label='T3={0:.0f}, logg={1}'.format(self.T/1e3, self.logg),
            *args, **kwargs) # Here are the transmissions of extra para
    ax.set_yscale('log')
    ax.set_ylim(1e6, 1e14)
    ax.set_xlabel('Wavelength (A)')

def get_integ(self):
    """
    Return the integral of Flambda over lambda, in erg/s/cm2
    """
    if self.wl is None:
        print('No data')
        return None
    return.simps(self.fl, self.wl) # perform the integral

def __getT(self):
    return self.__T

def __setT(self, value):
    if not isinstance(value, (int, long, float)): # check the type of t
        raise TypeError('T must be an integer or a float')
    if float(value) not in np.linspace(40000, 190000, 16): # check the
        raise ValueError('T value must be between 40000 and 190000K, by
    elif self.__T != value:
        self.__T = value
        self.filename = '0{0:06.0f}_{1:.2f}_33_50_02_15.bin_0.1.gz'.for
        self.dlfile() # will download new data
        self.read_data() # will update the data

```



```

def __delT(self):
    print('T is needed')

T = property(__getT, __setT, __delT, "Stellar effective temperature")

def __getlogg(self):
    return self.__logg

@profile
def __setlogg(self, value):
    try:
        self.__logg
    except:
        self.__logg = -1
    if not isinstance(value, (int, long, float)):
        raise TypeError('logg must be an integer or a float')
    if float(value) not in (-1., 5., 6., 7., 8., 9.):
        raise ValueError('Error, logg must be 6, 7, 8, or 9')
    self.__logg = None
    elif self.__logg != value:
        self.__logg = value
        self.filename = '0{0:06.0f}_{1:.2f}_33_50_02_15.bin_0.1.gz'.format(
            self.wl, self.__logg)
        self.dlfile() # will download new data
        self.read_data() # will update the data

def __dellogg(self):
    print('logg is needed')

logg = property(__getlogg, __setlogg, __dellogg, "Stellar logg")

def print_info(self):
    """
    Print out the filename and the number of points
    """
    print self.__repr__()

def __repr__(self):
    """
    This is what is used when calling "print <obj>" or <obj> ENTER
    """
    if self.wl is None:
        return 'Filename: {0}, No data'.format(self.filename)
    else:
        return 'Filename: {0}, number of points: {1}'.format(self.filename, self.spec_count)

def __del__(self):
    Stel_Spectrum.spec_count -= 1

```

```

spectra = [] # we create an empty list
for T in np.linspace(40000, 190000, 4): # this is the list of available temperatures
    spectra.append(Stel_Spectrum(T=T, logg=6, verbose=True)) # we fill the list
T = np.array([sp.T for sp in spectra])
F = np.array([sp.get_integ() for sp in spectra])
for t, f in zip(T, F):
    print('Temperature = {0:.0f}K, Flux = {1:.2e} erg/s/cm2'.format(t, f))

```

Overwriting test_2_prof.py

```

In [8]: # Need to pip install line-profiler
! kernprof -l -v test_2_prof.py

```

```

0040000_6.00_33_50_02_15.bin_0.1.gz already on disk
Read data from 0040000_6.00_33_50_02_15.bin_0.1.gz
Instantiation done
0090000_6.00_33_50_02_15.bin_0.1.gz already on disk
Read data from 0090000_6.00_33_50_02_15.bin_0.1.gz
Instantiation done
0140000_6.00_33_50_02_15.bin_0.1.gz already on disk
Read data from 0140000_6.00_33_50_02_15.bin_0.1.gz
Instantiation done
0190000_6.00_33_50_02_15.bin_0.1.gz already on disk
Read data from 0190000_6.00_33_50_02_15.bin_0.1.gz
Instantiation done
Temperature = 40000K, Flux = 4.00e+13 erg/s/cm2
Temperature = 90000K, Flux = 1.05e+15 erg/s/cm2
Temperature = 140000K, Flux = 6.93e+15 erg/s/cm2
Temperature = 190000K, Flux = 2.35e+16 erg/s/cm2
Wrote profile results to test_2_prof.py.lprof
Timer unit: 1e-06 s

```

```

Total time: 1.78263 s
File: test_2_prof.py
Function: __init__ at line 15

```

Line #	Hits	Time	Per Hit	% Time	Line Contents
15					@profile
16					def __init__(self, filename=None):
17					"""
18					Initialisation of the Stel_Spectrum
19					Parameter:
20					- filename
21					- T: temperature in K,
22					- logg: e.g. 7.5
23					- verbose: if True, so

24				
25				
26				
27				
28	4	8	2.0	0.0
29	4	4	1.0	0.0
30	4	2	0.5	0.0
31	4	3	0.8	0.0
32	4	1782513	445628.2	100.0
33	4	57	14.2	0.0
34				
35				
36				
37				
38				
39				
40	4	12	3.0	0.0
41	4	3	0.8	0.0
42	4	25	6.2	0.0

Total time: 0.000108 s
File: test_2_prof.py
Function: dlfile at line 44

Line #	Hits	Time	Per Hit	% Time	Line Contents
=====					

44				
45				
46				
47				
48				
49	4	68	17.0	63.0
50				
51				
52				
53				
54				
55				
56				
57				
58				
59				
60				
61				
62				
63				
64	4	3	0.8	2.8
65	4	35	8.8	32.4

```

The wl variable is an array
The fl variable is the flux
The variables T and logg are
"""
self.verbose = verbose
if filename is None:
    if T is not None and logg is not None:
        self.__T = T # We have T and logg
        self.logg = logg
        self.filename = 'C'
    else:
        raise TypeError("T and logg must be provided")
else:
    self.filename = filename
    self.__T = float(filename.split('.')[0])
    self.logg = float(filename.split('.')[1])
Stel_Spectrum.spec_count += 1
if self.verbose:
    print('Instantiation of Stel_Spectrum object')

```

66	4	2	0.5	1.9	self.file_found=True
----	---	---	-----	-----	----------------------

Total time: 1.78211 s

File: test_2_prof.py

Function: read_data at line 68

Line #	Hits	Time	Per Hit	% Time	Line Contents
68					@profile
69					def read_data(self):
70					"""
71					read the data from the file
72					"""
73	4	3	0.8	0.0	if self.file_found:
74	4	1781582	445395.5	100.0	data = np.genfromtxt(s
75	4	22	5.5	0.0	self.fl = data['fl']
76	4	5	1.2	0.0	self.wl = data['wl'] #
77	4	430	107.5	0.0	self.fl /= 1e8 # F LAN
78	4	4	1.0	0.0	if self.verbose:
79	4	62	15.5	0.0	print('Read data f
80					else:
81					if self.verbose:
82					print('file not fo
83					self.wl = None
84					self.fl = None

Total time: 1.78242 s

File: test_2_prof.py

Function: __setlogg at line 136

Line #	Hits	Time	Per Hit	% Time	Line Contents
136					@profile
137					def __setlogg(self, value):
138	4	13	3.2	0.0	try:
139	4	16	4.0	0.0	self.__logg
140	4	4	1.0	0.0	except:
141	4	2	0.5	0.0	self.__logg = -1
142	4	7	1.8	0.0	if not isinstance(value,
143					raise TypeError('logg
144	4	9	2.2	0.0	if float(value) not in (-1
145					raise ValueError('Error
146					self.__logg = None
147	4	4	1.0	0.0	elif self.__logg != value:
148	4	4	1.0	0.0	self.__logg = value
149	4	35	8.8	0.0	self.filename = '0{0:0
150	4	144	36.0	0.0	self.dlfile() # will c
151	4	1782182	445545.5	100.0	self.read_data() # wil

```
In [9]: # Use the test_1 because @profile is not compatible
        ! python -m cProfile -o test_1_prof.prof test_1_prof.py
```

```
0040000_6.00_33_50_02_15.bin_0.1.gz already on disk
Read data from 0040000_6.00_33_50_02_15.bin_0.1.gz
Instantiation done
0090000_6.00_33_50_02_15.bin_0.1.gz already on disk
Read data from 0090000_6.00_33_50_02_15.bin_0.1.gz
Instantiation done
0140000_6.00_33_50_02_15.bin_0.1.gz already on disk
Read data from 0140000_6.00_33_50_02_15.bin_0.1.gz
Instantiation done
0190000_6.00_33_50_02_15.bin_0.1.gz already on disk
Read data from 0190000_6.00_33_50_02_15.bin_0.1.gz
Instantiation done
Temperature = 40000K, Flux = 4.00e+13 erg/s/cm2
Temperature = 90000K, Flux = 1.05e+15 erg/s/cm2
Temperature = 140000K, Flux = 6.93e+15 erg/s/cm2
Temperature = 190000K, Flux = 2.35e+16 erg/s/cm2
```

```
In [10]: # need to pip install gprof2dot
         # dot is installed by yum install graphviz
         ! gprof2dot -f pstats test_1_prof.prof | dot -Tpng -o test_1-prof.png
```

```
/bin/sh: dot: command not found
```


```
Traceback (most recent call last):
```

```
File "/Users/christophemorriset/anaconda/bin/gprof2dot", line 11, in <module>
    sys.exit(main())
File "/Users/christophemorriset/anaconda/lib/python2.7/site-packages/gprof2dot.py", line 11, in dot.graph(profile, theme)
File "/Users/christophemorriset/anaconda/lib/python2.7/site-packages/gprof2dot.py", line 11, in arrowsize = "%.2f" % theme.edge_arrowsize(weight),
File "/Users/christophemorriset/anaconda/lib/python2.7/site-packages/gprof2dot.py", line 11, in self.attr_list(attrs)
File "/Users/christophemorriset/anaconda/lib/python2.7/site-packages/gprof2dot.py", line 11, in self.id(value)
File "/Users/christophemorriset/anaconda/lib/python2.7/site-packages/gprof2dot.py", line 11, in self.write(s)
File "/Users/christophemorriset/anaconda/lib/python2.7/site-packages/gprof2dot.py", line 11, in self.fp.write(s)
```

```
IOError: [Errno 32] Broken pipe
```

```
In [11]: Image(filename='test_1-prof.png')
```

Out [11]:



```
In [12]: import pstats
p = pstats.Stats('test_1_prof.prof')
p.strip_dirs().sort_stats('time').print_stats(10);
```

Wed Jun 1 17:19:56 2016 test_1_prof.prof

934669 function calls (933646 primitive calls) in 0.752 seconds

Ordered by: internal time

List reduced from 858 to 10 due to restriction <10>

ncalls	totttime	percall	cumtime	percall	filename:lineno(function)
4	0.174	0.043	0.553	0.138	numpyio.py:1259(genfromtxt)
79896	0.113	0.000	0.154	0.000	gzip.py:448(readline)
3	0.092	0.031	0.224	0.075	__init__.py:1(<module>)
79896	0.080	0.000	0.134	0.000	_iotools.py:217(_delimited_splitter)
159608	0.049	0.000	0.049	0.000	_iotools.py:690(_loose_call)
159736	0.040	0.000	0.040	0.000	{method 'split' of 'str' objects}
80256	0.018	0.000	0.018	0.000	{method 'find' of 'str' objects}
80201	0.014	0.000	0.014	0.000	{method 'strip' of 'str' objects}
351	0.013	0.000	0.013	0.000	{built-in method decompress}
19	0.013	0.001	0.013	0.001	{zip}

1.0.2 Profiling the code: RAM memory usage

In [13]: %%**writefile** test_3_prof.py

```
import numpy as np
import os
import urllib2
from scipy.integrate import.simps
from memory_profiler import profile

class Stel_Spectrum(object):
    """
    This object downloads a file from http://astro.uni-tuebingen.de/~rauch
    and is able to make some plots.
    """

    spec_count = 0 # This attribute is at the level of the class, not of th

    @profile
    def __init__(self, filename=None, T=None, logg=None, verbose=False):
        """
        Initialisation of the Stel_Spectrum object.
        Parameter:
        - filename
        - T: temperature in K, e.g. 150000
        - logg: e.g. 7.5
        - verbose: if True, some info are printed out
        The wl variable is an array of wavelengths in Angstrom.
        The fl variable is the flux in erg/s/cm2/A
        The variables T and logg are properties: changing them will reload
        """
```

```

self.verbose = verbose
if filename is None:
    if T is not None and logg is not None:
        self.__T = T # We need to initialize the hidden values, as
        self.logg = logg
        self.filename = '0{0:06.0f}_{1:.2f}_33_50_02_15.bin_0.1.gz'
    else:
        raise TypeError("T and logg must be given")
else:
    self.filename = filename
    self.__T = float(filename.split('_')[0]) # We need to initialize
    self.logg = float(filename.split('_')[1])
Stel_Spectrum.spec_count += 1
if self.verbose:
    print('Instantiation done')

def dlfile(self):
    """
    Downloading file if not already here. Put it in the current directory
    """
    if not os.path.exists(self.filename):
        if self.verbose:
            print('Downloading {}'.format(self.filename))
        try:
            stel_file = urllib2.urlopen('http://astro.uni-tuebingen.de/{}'
                                         self.filename)
            output = open(self.filename, 'wb')
            output.write(stel_file.read())
            output.close()
            self.file_found=True
        except:
            if self.verbose:
                print('file {} not found'.format(self.filename))
            self.file_found=False
    else:
        if self.verbose:
            print('{} already on disk'.format(self.filename))
        self.file_found=True

def read_data(self):
    """
    read the data from the file
    """
    if self.file_found:
        data = np.genfromtxt(self.filename, comments='#', names='wl, fl',
                              delimiter=',')
        self.fl = data['fl']
        self.wl = data['wl'] # in A
        self.fl /= 1e8 # F LAMBDA GIVEN IN ERG/CM**2/SEC/CM -> erg/s/

```



```

        if self.verbose:
            print('Read data from {}'.format(self.filename))
    else:
        if self.verbose:
            print('file not found {}'.format(self.filename))
        self.wl = None
        self.fl = None

def plot_spr(self, ax=None, *args, **kwargs):
    """
    Plot the spectrum.
    Parameter:
        - ax: an axis (optionnal). If Noe or absent, axis is created
        - any extra parameter is passed to ax.plot
    """
    if self.wl is None:
        print('No data to plot')
        return
    if ax is None:
        fig, ax = plt.subplots()
    ax.plot(self.wl, self.fl,
            label='T3={0:.0f}, logg={1}'.format(self.T/1e3, self.logg),
            *args, **kwargs) # Here are the transmissions of extra par
    ax.set_yscale('log')
    ax.set_ylim(1e6, 1e14)
    ax.set_xlabel('Wavelength (A)')

@profile
def get_integ(self):
    """
    Return the integral of Flambda over lambda, in erg/s/cm2
    """
    if self.wl is None:
        print('No data')
        return None
    return.simps(self.fl, self.wl) # perform the integral

def __getT(self):
    return self.__T

def __setT(self, value):
    if not isinstance(value, (int, long, float)): # check the type of
        raise TypeError('T must be an integer or a float')
    if float(value) not in np.linspace(40000, 190000, 16): # check the
        raise ValueError('T value must be between 40000 and 190000K, b
    elif self.__T != value:
        self.__T = value
        self.filename = '0{0:06.0f}_{1:.2f}_33_50_02_15.bin_0.1.gz'.fo

```

```

        self.dlfile() # will download new data
        self.read_data() # will update the data

def __delT(self):
    print('T is needed')

T = property(__getT, __setT, __delT, "Stellar effective temperature")

def __getlogg(self):
    return self.__logg

def __setlogg(self, value):
    try:
        self.__logg
    except:
        self.__logg = -1
    if not isinstance(value, (int, long, float)):
        raise TypeError('logg must be an integer or a float')
    if float(value) not in (-1., 5., 6., 7., 8., 9.):
        raise ValueError('Error, logg must be 6, 7, 8, or 9')
    self.__logg = None
    elif self.__logg != value:
        self.__logg = value
        self.filename = '0{0:06.0f}_{1:.2f}_33_50_02_15.bin_0.1.gz'.format(self.__logg, self.__logg)
        self.dlfile() # will download new data
        self.read_data() # will update the data

def __dellogg(self):
    print('logg is needed')

logg = property(__getlogg, __setlogg, __dellogg, "Stellar logg")

def print_info(self):
    """
    Print out the filename and the number of points
    """
    print self.__repr__()

def __repr__(self):
    """
    This is what is used when calling "print <obj>" or <obj> ENTER
    """
    if self.wl is None:
        return 'Filename: {0}, No data'.format(self.filename)
    else:
        return 'Filename: {0}, number of points: {1}'.format(self.filename, self.wl)

def __del__(self):

```

```
Stel_Spectrum.spec_count -= 1
```

```
sp = Stel_Spectrum(T=100000, logg=6, verbose=True)
print('Temperature = {0:.0f}K, Flux = {1:.2e} erg/s/cm2'.format(sp.T, sp.c
```

Overwriting test_3_prof.py

```
In [14]: # need to pip install -U memory_profiler
        # need to pip install -U psutil
        !python -m memory_profiler test_3_prof.py
```

```
0100000_6.00_33_50_02_15.bin_0.1.gz already on disk
Read data from 0100000_6.00_33_50_02_15.bin_0.1.gz
Instantiation done
Filename: test_3_prof.py
```

Line #	Mem usage	Increment	Line Contents
16	41.5 MiB	0.0 MiB	@profile
17			def __init__(self, filename=None, T=None, logg=None, verbose=False, wl=None, fl=None):
18			"""
19			Initialisation of the Stel_Spectrum object
20			Parameter:
21			- filename
22			- T: temperature in K, e.g. 150000
23			- logg: e.g. 7.5
24			- verbose: if True, some info are printed
25			The wl variable is an array of wavelengths
26			The fl variable is the flux in erg/s/cm2
27			The variables T and logg are properties
28			"""
29	41.5 MiB	0.0 MiB	self.verbose = verbose
30	41.5 MiB	0.0 MiB	if filename is None:
31	41.5 MiB	0.0 MiB	if T is not None and logg is not None:
32	41.5 MiB	0.0 MiB	self.__T = T # We need to initialise T
33	45.2 MiB	3.7 MiB	self.logg = logg
34	45.2 MiB	0.0 MiB	self.filename = '0{0:06.0f}_{1:.0f}.bin'.format(T, logg)
35			else:
36			raise TypeError("T and logg must be None or float")
37			else:
38			self.filename = filename
39			self.__T = float(filename.split('_')[1])
40			self.logg = float(filename.split('_')[2])
41	45.2 MiB	0.0 MiB	Stel_Spectrum.spec_count += 1
42	45.2 MiB	0.0 MiB	if self.verbose:
43	45.2 MiB	0.0 MiB	print('Instantiation done')

Filename: test_3_prof.py

Line #	Mem usage	Increment	Line Contents
104	45.2 MiB	0.0 MiB	@profile
105			def get_integ(self):
106			"""
107			Return the integral of Flambda over lambda
108			"""
109	45.2 MiB	0.0 MiB	if self.wl is None:
110			print('No data')
111			return None
112	45.8 MiB	0.5 MiB	return simps(self.fl, self.wl) # perform

Temperature = 100000K, Flux = 1.79e+15 erg/s/cm²

1.0.3 Debugger

From the terminal

```
In [15]: # ! ipython -m pdb test_1_prof.py # from a terminal
```

Breakpoint

```
In [16]: # import pdb # need to call the debugger at the breakpoint
        # Inserting a pdb.set_trace in the __init__ method to stop the program and
```

```
In [17]: %%writefile test_5_pdb.py
import pdb # This is needed to use the debugger
import numpy as np
import os
import urllib2
from scipy.integrate import simps

class Stel_Spectrum(object):
    """
    This object downloads a file from http://astro.uni-tuebingen.de/~rauch
    and is able to make some plots.
    """

    spec_count = 0 # This attribute is at the level of the class, not of the
    def __init__(self, filename=None, T=None,logg=None, verbose=False):
        """
        Initialisation of the Stel_Spectrum object.
        Parameter:
```

```

        - filename
        - T: temperature in K, e.g. 150000
        - logg: e.g. 7.5
        - verbose: if True, some info are printed out
The wl variable is an array of wavelengths in Angstrom.
The fl variable is the flux in erg/s/cm2/A
The variables T and logg are properties: changing them will reload
"""
pdb.set_trace() # THIS IS A BREAKPOINT
self.verbose = verbose
if filename is None:
    if T is not None and logg is not None:
        self.__T = T # We need to initialize the hidden values, as
        self.logg = logg
        self.filename = '0{0:06.0f}_{1:.2f}_33_50_02_15.bin_0.1.gz'
    else:
        raise TypeError("T and logg must be given")
else:
    self.filename = filename
    self.__T = float(filename.split('_')[0]) # We need to initialize
    self.logg = float(filename.split('_')[1])
Stel_Spectrum.spec_count += 1
if self.verbose:
    print('Instantiation done')

def dlfile(self):
    """
    Downloading file if not already here. Put it in the current directory
    """
    if not os.path.exists(self.filename):
        if self.verbose:
            print('Downloading {}'.format(self.filename))
        try:
            stel_file = urllib2.urlopen('http://astro.uni-tuebingen.de/{}'.format(
                self.filename))
            output = open(self.filename, 'wb')
            output.write(stel_file.read())
            output.close()
            self.file_found=True
        except:
            if self.verbose:
                print('file {} not found'.format(self.filename))
            self.file_found=False
    else:
        if self.verbose:
            print('{} already on disk'.format(self.filename))
        self.file_found=True

```

```

def read_data(self):
    """
    read the data from the file
    """
    if self.file_found:
        data = np.genfromtxt(self.filename, comments='#', names='wl, f')
        self.fl = data['fl']
        self.wl = data['wl'] # in A
        self.fl /= 1e8 # F LAMBDA GIVEN IN ERG/CM**2/SEC/CM -> erg/s/cm**2
        if self.verbose:
            print('Read data from {}'.format(self.filename))
    else:
        if self.verbose:
            print('file not found {}'.format(self.filename))
        self.wl = None
        self.fl = None

def plot_spr(self, ax=None, *args, **kwargs):
    """
    Plot the spectrum.
    Parameter:
        - ax: an axis (optionnal). If Noe or absent, axis is created
        - any extra parameter is passed to ax.plot
    """
    if self.wl is None:
        print('No data to plot')
        return
    if ax is None:
        fig, ax = plt.subplots()
    ax.plot(self.wl, self.fl,
            label='T3={0:.0f}, logg={1}'.format(self.T/1e3, self.logg),
            *args, **kwargs) # Here are the transmissions of extra parameters
    ax.set_yscale('log')
    ax.set_ylim(1e6, 1e14)
    ax.set_xlabel('Wavelength (A)')

def get_integ(self):
    """
    Return the integral of Flambda over lambda, in erg/s/cm2
    """
    if self.wl is None:
        print('No data')
        return None
    return.simps(self.fl, self.wl) # perform the integral

def __getT(self):
    return self.__T

```

```

def __setT(self, value):
    if not isinstance(value, (int, long, float)): # check the type of
        raise TypeError('T must be an integer or a float')
    if float(value) not in np.linspace(40000, 190000, 16): # check the
        raise ValueError('T value must be between 40000 and 190000K, k
    elif self.__T != value:
        self.__T = value
        self.filename = '0{0:06.0f}_{1:.2f}_33_50_02_15.bin_0.1.gz'.fo
        self.dlfile() # will download new data
        self.read_data() # will update the data

def __delT(self):
    print('T is needed')

T = property(__getT, __setT, __delT, "Stellar effective temperature")

def __getlogg(self):
    return self.__logg

def __setlogg(self, value):
    try:
        self.__logg
    except:
        self.__logg = -1
    if not isinstance(value, (int, long, float)):
        raise TypeError('logg must be an integer or a float')
    if float(value) not in (-1., 5., 6., 7., 8., 9.):
        raise ValueError('Error, logg must be 6, 7, 8, or 9')
    self.__logg = None
    elif self.__logg != value:
        self.__logg = value
        self.filename = '0{0:06.0f}_{1:.2f}_33_50_02_15.bin_0.1.gz'.fo
        self.dlfile() # will download new data
        self.read_data() # will update the data

def __dellogg(self):
    print('logg is needed')

logg = property(__getlogg, __setlogg, __dellogg, "Stellar logg")

def print_info(self):
    """
    Print out the filename and the number of points
    """
    print self.__repr__()

def __repr__(self):
    """

```

```

        This is what is used when calling "print <obj>" or <obj> ENTER
        """
        if self.wl is None:
            return 'Filename: {0}, No data'.format(self.filename)
        else:
            return 'Filename: {0}, number of points: {1}'.format(self.filename, self.wl)

    def __del__(self):
        Stel_Spectrum.spec_count -= 1

    sp = Stel_Spectrum(T=100000, logg=6)
    print 'ending'
    print sp.filename

```

Overwriting test_5_pdb.py

The commands that can be used once inside the pdb debugger session are: * l(list) Lists the code at the current position * u(p) Walk up the call stack * d(own) Walk down the call stack * n(ext) Execute the next line (does not go down in new functions) * s(tep) Execute the next statement (goes down in new functions) * bt Print the call stack * a Print the local variables * !command Execute the given Python command (by opposition to pdb commands * break N Set a breakpoint at line number N. If no N, list all the breakpoints * disable N Remove the breakpoint number N * c(ontinue) Run until the next breakpoint or the end of the program * return Continues executing until the function is about to execute a return statement, and then it pauses. This gives you time to look at the return value before the function returns.

In [18]: %run test_5_pdb.py

```

> /Users/christophemorisset/Google Drive/Pro/Python-MySQL/Notebooks/Notebooks/test_5_pdb.py
-> self.verbose = verbose
(Pdb) .c
*** SyntaxError: invalid syntax (<stdin>, line 1)
(Pdb) cont
ending
0100000_6.00_33_50_02_15.bin_0.1.gz

```

In []: