

Computational Graphics: Lecture 12

Alberto Paoluzzi

Tue, Apr 28, 2015

Pyplasm model implementation of curves

```
def circle(r=1):  
    x = lambda p: r*COS(p[0])  
    y = lambda p: r*SIN(p[0])  
    return CONS([x,y])
```

Pyplasm model implementation of curves

```
def sincos(r=1):  
    x = lambda p: r*COS(p[0])  
    y = lambda p: r*SIN(p[0])  
    z = lambda p: PROD([x(p),y(p)])  
    return [x,y,z]
```

Pyplasm model implementation of curves

```
def circle(r=1):  
    def circle0(p):  
        u = p[0]  
        x = r*COS(u)  
        y = r*SIN(u)  
        z = x*y  
        return [x,y,z]  
    return circle0
```

Pyplasm model implementation of curves

```
def dom(interval=1,dmin=0,dmax=1,steps=32):  
    interval = interval*(dmax - dmin)  
    return T(1)(dmin)(INTERVALS(interval)(steps))  
  
VIEW(MAP(circle(1))(dom(1)))  
VIEW(MAP(circle(1))(dom(2*PI)))  
VIEW(MAP(circle(1))(dom(-PI,PI)))  
VIEW(MAP(circle(1))(dom(-PI/2,3*PI/2)))
```

Notable surface classes

Profile product surfaces

```
def PROFILEPRODSURFACE (args):  
    profile_fn,section_fn = args  
  
    def map_fun(point):  
        u,v,w=point  
        profile,section=profile_fn(point),section_fn(point)  
        ret=[profile[0]*section[0],profile[0]*section[1],profile[0]*section[2]]  
        return ret  
    return map_fun
```


Pyplasm model implementation of curves

```

if __name__ == "__main__":
    alpha=BEZIER(S1)([[0.1,0,0],[2,0,0],[0,0,4],[1,0,5]])
    beta =BEZIER(S2)([[0,0,0],[3,-0.5,0],[3,3.5,0],[0,3,0]])
    plasm_config.push(1e-4)
    domain = EMBED(1)(PROD([ Hpc(Grid([20*[1./20]))], Hpc(Grid([20*[1./20]))]))
    out = Plasm.Struct([GMAP(alpha)(domain),MAP(beta )(domain)])
    plasm_config.pop()
    VIEW(out)

```

Ruled surfaces

```
def RULEDSURFACE (args):  
    alpha_fn , beta_fn = args  
  
    def map_fn(point):  
        u,v,w = point  
        alpha,beta=alpha_fn(point),beta_fn(point)  
        ret=[0.0 for i in range(len(alpha))]  
        for K in range(len(ret)): ret[K]=alpha[K]+v*beta[K]  
        return ret  
    return map_fn
```

Pyplasm model implementation of curves

```

if __name__ == "__main__":
    alpha= lambda point: [point[0],point[0],      0 ]
    beta = lambda point: [      -1,      +1, point[0] ]
    #domain= T([1,2])([-1,-1])(Plasm.power(INTERVALS(2)(10),I
    domain = EMBED(1)(PROD([ Hpc(Grid([10*[2./10]])), Hpc(Gr
    domain = MAT([[1,0,0,0],[-1,1,0,0],[-1,0,1,0],[0,0,0,1]])
    plasm_config.push(1e-4)
    VIEW(GMAP(RULEDSURFACE([alpha,beta]))(domain))
    plasm_config.pop()

```

ROTATIONALSURFACE surfaces

```
def ROTATIONALSURFACE (args):  
    profile = args  
  
    def map_fn(point):  
        u,v,w = point  
        f,h,g = profile(point)  
        ret=[f*math.cos(v),f*math.sin(v),g]  
        return ret  
    return map_fn
```

Pyplasm model implementation of curves

```

if __name__ == "__main__":
    profile=BEZIER(S1)([[0,0,0],[2,0,1],[3,0,4]]) # defined in
    plasm_config.push(1e-4)
    #domain=Plasm.power(INTERVALS(1)(10),INTERVALS(2*PI)(30))
    domain = EMBED(1)(PROD([ Hpc(Grid([10*[1./10]])), Hpc(Gr
    out = GMAP(ROTATIONALSURFACE(profile))(domain)
    plasm_config.pop()
    VIEW(out)

```

CYLINDRICALSURFACE surfaces

```
def CYLINDRICALSURFACE (args):  
    alpha_fun    = args[0]  
    beta_fun     = CONS(AA(K)(args[1]))  
    return RULEDSURFACE([alpha_fun, beta_fun])
```

Pyplasm model implementation of curves

```

if __name__ == "__main__":
    alpha=BEZIER(S1)([[1,1,0],[-1,1,0],[1,-1,0],[-1,-1,0]])
    #Udomain=INTERVALS(1)(20)
    #Vdomain=INTERVALS(1)(6)
    #domain=Plasm.power(Udomain,Vdomain)
    domain = EMBED(1)(PROD([ Hpc(Grid([20*[1./20]])), Hpc(Grid([20*[1./20]]))],
    fn = CYLINDRICALSURFACE([alpha,[0,0,1]])
    VIEW(GMAP(fn)(domain))
  
```

CONICALSURFACE surfaces

```
def CONICALSURFACE (args):  
    apex=args[0]  
    alpha_fn    = lambda point: apex  
    beta_fn = lambda point: [ args[1](point)[i]-apex[i] for i  
    return RULEDSURFACE([alpha_fn, beta_fn])
```


Pyplasm model implementation of curves

```
if __name__ == "__main__":
    #domain=Plasm.power(INTERVALS(1)(20),INTERVALS(1)(6))
    domain = EMBED(1)(PROD([ Hpc(Grid([20*[1./20]])), Hpc(Grid([
    beta = BEZIER(S1)([ [1,1,0],[-1,1,0],[1,-1,0],[-1,-1,0] ]))
    out = GMAP(CONICALSURFACE([0,0,1],beta))(domain)
    VIEW(out)
```

Profile product surfaces

```
def CUBICHERMITE (U):
    def CUBICHERMITE0 (args):
        p1_fn , p2_fn , s1_fn , s2_fn = args
        def map_fn(point):
            u=U(point);u2=u*u;u3=u2*u
            p1,p2,s1,s2=[f(point) if callable(f) else f for f
                ret=[0.0 for i in range(len(p1))]
                for i in range(len(ret)):
                    ret[i]+=(2*u3-3*u2+1)*p1[i] + (-2*u3+3*u2)*p2
            return ret
        return map_fn
    return CUBICHERMITE0
```

Pyplasm model implementation of curves

```

if __name__ == "__main__":

    domain=INTERVALS(1)(20)
    out=Plasm.Struct([
        MAP(CUBICHERMITE(S1)([[1,0],[1,1],[ -1, 1],[ 1,0]]))(c1),
        MAP(CUBICHERMITE(S1)([[1,0],[1,1],[ -2, 2],[ 2,0]]))(c2),
        MAP(CUBICHERMITE(S1)([[1,0],[1,1],[ -4, 4],[ 4,0]]))(c3),
        MAP(CUBICHERMITE(S1)([[1,0],[1,1],[ -10,10],[ 10,0]]))(c4)
    ])
    VIEW(out)

    c1=CUBICHERMITE(S1)([[1,0,0],[0,1,0],[0,3,0],[-3,0,0]])
    c2=CUBICHERMITE(S1)([[0.5,0,0],[0,0.5,0],[0,1,0],[-1,0,0]])
    sur3=CUBICHERMITE(S2)([c1,c2,[1,1,1],[-1,-1,-1]])
    #plasm_config.push(1e-4)
    #domain=Plasm.power(INTERVALS(1)(14),INTERVALS(1)(14))

```

Pyplasm model implementation of curves

```
def beta(p):  
    """ cross-section curve """  
    u = p[0]  
    x = COS(u)  
    y = SIN(u)  
    z = 0  
    return [x,y,0]
```

```
VIEW(MAP(beta)(dom(2*PI)))
```

Pyplasm model implementation of curves

```
def alpha(p):  
    """ profile curve """  
    c = bezier([[0,0,0],[4,0,0],[6,0,2],[0,0,4],[2,0,5]])  
    x = c(p)[0]  
    y = c(p)[1]  
    z = c(p)[2]  
    return [x,y,z]
```

```
VIEW(MAP(alpha)(dom(1)))
```

Pyplasm model implementation of curves

```
def profileProduct(alpha,beta):  
    def profileProduct0(p):  
        u,v = p  
        x = beta([u])[0] * alpha([v])[0]  
        y = beta([u])[1] * alpha([v])[0]  
        z = alpha([v])[2]  
        return [x,y,z]  
    return profileProduct0  
  
domain = PROD([dom(interval=2*PI,steps=32),dom(steps=12)])  
  
VIEW(GMAP(profileProduct(alpha,beta))(domain))
```