

Crystal Unit

32.768KHZ

YSX306GA Glass Sealed



Applications

- RTC

Features

- Dimensions: : 8.00 x 3.80 x 2.44mm

- Standard Frequency: 32.768KHz

- Contains Pb in Sealing Glass Exempted
by ROHS Directive




Specifications (规格参数)

Item	Symbol	Specifications
Nominal Frequency 标称频率	f _{nom}	32.768KHz
Load Capacitance 负载电容	CL	7pF, 9pF, 12.5pF, or specify
Frequency Tolerance 频率偏差 (at 25°C)	f _{tol}	±10ppm, ±20ppm, or specify
Parabolic Coefficient 频率温度系数	B	-0.04 * 10 ⁻⁶ / °C ² Max
Operating Temperature 工作温度	T _{use}	-40~+85°C
Storage Temperature 储存温度	T _{stg}	-55~+125°C
Shunt Capacitance 静态电容	C0	2.0pF Max
Level of Drive 激励电平	DL	1.0μW Max
Aging 老化(at 25°C)	f _{age}	±5ppm/year Max

Equivalent Series Resistance (等效串联电阻(ESR))

YSX306GA
50KΩ Max

Dimensions and Recommended Land Pattern (外观尺寸)

Dimensions (Unit: mm)	
 <p>Top View</p>	 <p>Bottom View</p>
 <p>Recommended soldering Pattern</p>	