

Lecture 2: Basics in C++

Jonas Kusch and Martina Prugger

University of Innsbruck

September 28, 2022

Last goals: You are able to

- ✓ understand main advantages and disadvantages of C++
- ✓ set up your project with VS code, git
- ✓ write and compile your own first code with C++
- ✓ use libraries, print outputs to terminal
- ✓ understand types

Last goals: You are able to

- ✓ understand main advantages and disadvantages of C++
- ✓ set up your project with VS code, git
- ✓ write and compile your own first code with C++
- ✓ use libraries, print outputs to terminal
- ✓ understand types

Today's learning goals: You will be able to

- ☐ use conditional statements
- ☐ use loops
- ☐ understand memory management
- ☐ start to use pointers

Last goals: You are able to

- ✓ understand main advantages and disadvantages of C++
- ✓ set up your project with VS code, git
- ✓ write and compile your own first code with C++
- ✓ use libraries, print outputs to terminal
- ✓ understand types

Today's learning goals: You will be able to

- ☐ use conditional statements
- ☐ use loops
- ☐ understand memory management
- ☐ start to use pointers

Ask questions any time!

Vector

- There are more datatypes, which are implemented in standard C++ libraries. Let's start with `std::vector`

```
1 #include <iostream>
2 #include <vector>
3
4 int main(){
5     std::vector<double> v{1, 2, 3};
6     v[2] = 1.0;
7     std::cout<<v[0]<<" "<<v[1]<<" "<<v[2]<<std::endl;
8     return 0;
9 }
```

- Note that you need to put an `std::` in front of the vector (and `cout`, `endl`). This is a namespace which we will cover later.
- indexing starts at 0 in C++!
- `size`, `reserve`, `resize`

Example

```
1 #include <iostream>
2 #include <vector>
3
4 int main(){
5     std::vector<double> v(5);
6     v.reserve(10);
7     v[0] = 1.0;
8     v[2] = 1.0;
9     std::cout<<v.size()<<std::endl;
10    std::cout<< v[0] << " " <<v[1]<< " " <<v[2] <<std::endl;
11
12    return 0;
13 }
```

Task

Write a program which generates two vector $v_1 = [0, 0.5, 1]$ and $v_2 = [0, \sin(0.1), 1]$ of type float. Generate a third vector $v_3 = v_1 + v_2$.

What goes wrong?

```
1 #include <iostream>
2 #include <vector>
3 #include <cmath>
4
5 int main(){
6     std::vector<int> v(2);
7     v[0] = 0;
8     v[1] = 0.1;
9     v[2] = 0.2;
10
11     std::vector<int> v1(2);
12     v1 = v + v;
13
14     std::cout<< v1[0] << " " <<v1[1]<< " " <<v1[2]<<std::endl;
15
16     return 0;
17 }
```


Last goals: You are able to

- ✓ understand main advantages and disadvantages of C++
- ✓ set up your project with VS code, git
- ✓ write and compile your own first code with C++
- ✓ use libraries, print outputs to terminal
- ✓ understand types

Today's learning goals: You will be able to

- ☐ use conditional statements
- ☐ use loops
- ☐ understand memory management
- ☐ start to use pointers

Last goals: You are able to

- ✓ understand main advantages and disadvantages of C++
- ✓ set up your project with VS code, git
- ✓ write and compile your own first code with C++
- ✓ use libraries, print outputs to terminal
- ✓ understand types

Today's learning goals: You will be able to

- use conditional statements
- use loops
- understand memory management
- start to use pointers

Conditionals

- Are you familiar with conditionals in programming languages?

- if, else if, else

```
if( boolean == true ){  
    // statement  
}else if(boolean2 == true){  
    // statement  
}else{  
    // statement  
}
```

- New variables defined inside these environments are unknown to the global scope.

Conditionals

```
#include <iostream>
```

```
int main(){  
    int i = 2, j = 3;  
  
    if( i == j ){  
        i = j - 1;  
    }else if(i == j - 1){  
        i = j;  
    }else{  
        i = j - 1;  
    }  
    std::cout<<i;  
    return 0;  
}
```

conditional

```
#include <iostream>

int main(){
    int i = 3, j = 3;

    if( i == j ){
        i = j - 1;
    }else if(i == j - 1){
        i = j;
    }else{
        i = j - 1;
    }
    std::cout<<i;
    return 0;
}
```

conditional

```
#include <iostream>

int main(){
    int i = 3, j = 3;

    if( i == j ){
        int tmp = j - 1;
        i = tmp;
    }else if(i == j - 1){
        i = j;
    }else{
        i = j - 1;
    }
    std::cout<<i;
    return 0;
}
```

Today's learning goals: You will be able to

- ☒ use conditional statements
- ☐ use loops
- ☐ understand memory management
- ☐ start to use pointers

Today's learning goals: You will be able to

- ☒ use conditional statements
- ☐ use loops
- ☐ understand memory management
- ☐ start to use pointers

Loops

- Are you familiar with loops in programming languages?
- for, while, do while loops

```
for( long i = 0; i < 10; ++i ){  
    // statement  
}  
  
while( boolean == true ){  
    // statement  
}  
  
do{  
    // statement  
}while( boolean == true )
```

- break and continue

Solving an ordinary differential equation

Consider a simple ODE

$$\dot{y}(t) = \sin(y(t))$$

Forward Euler time discretization: Define grid $\{t_1, \dots, t_{N_t}\}$ and define $y^n \simeq y(t_n)$

$$y^{n+1} = y^n + (t_{n+1} - t_n) \sin(y^n)$$

Task

Implement a forward Euler method with equidistant time step size $\Delta t = t_{n+1} - t_n = 0.01$. Store the solution at all time points $t \in [0, 1]$ in a vector and write it to a text file.

Today's learning goals: You will be able to

- ☒ use conditional statements
- ☒ use loops
- ☐ understand memory management
- ☐ start to use pointers


Today's learning goals: You will be able to

- ☒ use conditional statements
- ☒ use loops
- ☐ understand memory management
- ☐ start to use pointers

Addresses

- Every variable has a certain place in memory, called its address.
- Access address via & operator


```
double d = 0.1;  
std::cout<<"Address of d is "<< &d <<std::endl;
```



Now it's up to you...

- What does the code do? Which output do you expect?


```
double a,b;  
std::cout<<"Addresses: "<< &a << " " << &b <<std::endl;  
a = 0.1;  
b = a;  
std::cout<<"Addresses: "<< &a << " " << &b <<std::endl;
```



Now it's up to you...

- What does the code do? Which output do you expect?

```
double a,b;  
std::cout<<"Addresses: "<< &a << " " << &b <<std::endl;  
a = 0.1;  
b = a;  
std::cout<<"Addresses: "<< &a << " " << &b <<std::endl;
```



Now it's up to you...

- What does the code do? Which output do you expect?

```
double a,b;  
std::cout<<"Addresses: "<< &a << " " << &b <<std::endl;  
a = 0.1;  
b = a;  
std::cout<<"Addresses: "<< &a << " " << &b <<std::endl;
```

	...
0x558eef078eb0	<i>a</i> = 0.1
0x558eef078eb8	<i>b</i> = 0.1
	...

Now it's up to you...

- What does the code do? Which output do you expect?

```
double a,b;  
std::cout<<"Addresses: "<< &a << " " << &b <<std::endl;  
a = 0.1;  
b = a;  
std::cout<<"Addresses: "<< &a << " " << &b <<std::endl;
```

	...
0x558eef078eb0	$a = 0.1$
0x558eef078eb8	$b = 0.1$
	...

- Changing the value does not change address!
- Is there a datatype for addresses?

Now it's up to you...

- What does the code do? Which output do you expect?

```
double a,b;  
std::cout<<"Addresses: "<< &a << " " << &b <<std::endl;  
a = 0.1;  
b = a;  
std::cout<<"Addresses: "<< &a << " " << &b <<std::endl;
```


	...
0x558eef078eb0	$a = 0.1$
0x558eef078eb8	$b = 0.1$
	...

- Changing the value does not change address!
- Is there a datatype for addresses?

Pointers

- Datatypes to store an address is a pointer:


```
double a;  
double* p;  
p = &a;  
a = 0.1;  
std::cout<<"Values: "<< a << " " << *p <<std::endl;  
std::cout<<"Addresses: "<< &a << " " << p << " " << &p;
```



Pointers

- Datatypes to store an address is a pointer:


```
double a;  
double* p;  
p = &a;  
a = 0.1;  
std::cout<<"Values: "<< a << " " << *p <<std::endl;  
std::cout<<"Addresses: "<< &a << " " << &p << " " << &b;
```



Pointers

- Datatypes to store an address is a pointer:


```
double a;  
double* p;  
p = &a;  
a = 0.1;  
std::cout<<"Values: "<< a << " " << *p <<std::endl;  
std::cout<<"Addresses: "<< &a << " " << &p << " " << &b;
```



Pointers

- Datatypes to store an address is a pointer:

```
double a;  
double* p;  
p = &a;  
a = 0.1;  
std::cout<<"Values: "<< a << " " << *p <<std::endl;  
std::cout<<"Addresses: "<< &a << " " << p << " " << &p;
```




- Changes of address will change *p.
- Address of p remains the same.
- Pointers depend on data types.
- Dereference with *.

Pointers

- Datatypes to store an address is a pointer:

```
double a;  
double* p;  
p = &a;  
a = 0.1;  
std::cout<<"Values: "<< a << " " << *p <<std::endl;  
std::cout<<"Addresses: "<< &a << " " << p << " " << &p;
```




- Changes of address will change *p.
- Address of p remains the same.
- Pointers depend on data types.
- Dereference with *.

Pointers

- Datatypes to store an address is a pointer:

```
double a;  
double* p;  
p = &a;  
a = 0.1;  
std::cout<<"Values: "<< a << " " << *p <<std::endl;  
std::cout<<"Addresses: "<< &a << " " << p << " " << &p;
```




- Changes of address will change *p.
- Address of p remains the same.
- Pointers depend on data types.
- Dereference with *.

Pointers

- Datatypes to store an address is a pointer:

```
double a;  
double* p;  
p = &a;  
a = 0.1;  
std::cout<<"Values: "<< a << " " << *p <<std::endl;  
std::cout<<"Addresses: "<< &a << " " << p << " " << &p;
```




- Changes of address will change *p.
- Address of p remains the same.
- Pointers depend on data types.
- Dereference with *.

Pointers on pointers

- Datatypes to store an address of a pointer is a double pointer:


```
double a = 1.0, *p = &a, **pp = &p;  
std::cout<<"Values: "<< a << " " << *p << " " << **pp << std::endl;
```



Pointers on pointers

- Datatypes to store an address of a pointer is a double pointer:


```
double a = 1.0, *p = &a, **pp = &p;  
std::cout<<"Values: " << a << " " << *p << " " << **pp << std::endl;
```



Pointers on pointers

- Datatypes to store an address of a pointer is a double pointer:

```
double a = 1.0, *p = &a, **pp = &p;  
std::cout<<"Values: "<< a << " " << *p << " " << **pp << std::endl;
```




- Pointer on pointer is ****pp**.
- You can go on with *****p3**, ...
- Dereference with ******.

Pointers on pointers

- Datatypes to store an address of a pointer is a double pointer:

```
double a = 1.0, *p = &a, **pp = &p;  
std::cout<<"Values: "<< a << " " << *p << " " << **pp << std::endl;
```




- Pointer on pointer is ****pp**.
- You can go on with *****p3**, ...
- Dereference with ******.

Pointers on pointers

- Datatypes to store an address of a pointer is a double pointer:

```
double a = 1.0, *p = &a, **pp = &p;  
std::cout<<"Values: "<< a << " " << *p << " " << **pp << std::endl;
```



- Pointer on pointer is ****pp**.
- You can go on with *****p3**, ...
- Dereference with ******.

Your turn

Task

Write a code which changes the value of an integer `i` from 1 to 2 by using pointers. That is, do not use statements like `i = 2`.

Your turn

Task

Write a code which changes the value of an integer `i` from 1 to 2 by using pointers. That is, do not use statements like `i = 2`.

Task

Change the value to 3 with a pointer on a pointer.

Your turn

Task

Print the memory location of `pp`, `p`, and `i` by only using `pp`.

Your turn

Task

Print the memory location of `pp`, `p`, and `i` by only using `pp`.

Task

Given the code below, make sure that `*one = 1`, `*two = 2`, `*three = 3` without changing the first two lines and without using `i`, `j` and `k`.

```
1 int i = 1, j = 2, k = 3;  
2 int *one = &j, *two = &k, *three = &i;
```

What does the code do?

```
1 #include <iostream>
2
3 int main(){
4     int *i = 1, j = 2;
5     std::cout<< i + j;
6
7     return 0;
8 }
```

What does the code do?

```
1 #include <iostream>
2
3 int main(){
4     int *i = 1, j = 2;
5     std::cout<< i + j;
6
7     return 0;
8 }
```

```
1 #include <iostream>
2
3 int main(){
4     int i = 1, j = 2;
5     int* p = &i;
6     *p = *p + 2;
7     std::cout << i + j;
8
9     return 0;
10 }
```

What does the code do?

```
1 #include <iostream>
2
3 int main(){
4     int i = 1, *p = &i;
5     *p = 2;
6     std::cout << i + *p;
7
8     return 0;
9 }
```

What does the code do?

```
1 #include <iostream>
2
3 int main(){
4     int i = 1, *p = &i;
5     *p = 2;
6     std::cout << i + *p;
7
8     return 0;
9 }
```

```
1 #include <iostream>
2
3 int main(){
4     int i = 1, *p;
5     *p = 2;
6     std::cout << i + *p;
7
8     return 0;
9 }
```

Now it's up to you...

Current learning goals: After homework and self-study

- ✓ use conditional statements
- ✓ use loops
- ✓ understand memory management
- ✓ start to use pointers

Now it's up to you...

Current learning goals: After homework and self-study

- ✓ use conditional statements
- ✓ use loops
- ✓ understand memory management
- ✓ start to use pointers

Now it's up to you...

Current learning goals: After homework and self-study

- ✓ use conditional statements
- ✓ use loops
- ✓ understand memory management
- ✓ start to use pointers

Now it's up to you...

Current learning goals: After homework and self-study

- ✓ use conditional statements
- ✓ use loops
- ✓ understand memory management
- ✓ start to use pointers

Any questions / remarks ? :)

Now it's up to you...

Current learning goals: After homework and self-study

- ✓ use conditional statements
- ✓ use loops
- ✓ understand memory management
- ✓ start to use pointers

Any questions / remarks ? :) {jonas.kusch, martina.prugger}@uibk.ac.at

Now it's up to you...

Current learning goals: After homework and self-study

- ☒ use conditional statements
- ☒ use loops
- ☒ understand memory management
- ☒ start to use pointers

Any questions / remarks ? :) {jonas.kusch, martina.prugger}@uibk.ac.at

Next learning goals:

- ☐ understand heap and stack
- ☐ construct static and dynamic arrays (**new, delete, ...**)
- ☐ start using functions