

Database: Teoria

Aymane Chabbaki

III semestre 2019/2020

Contents

1	Relational Algebra	2
1.1	2
2	SQL	2
2.1	2
3	Functional Dependencies	2
3.1	2
4	Indexes	2
4.1	2
5	Query Cost	2
5.1	Page	2
5.2	Size of a Record	2
5.3	Pages of Relation	3
5.4	Cardinality of a Relation	3
5.5	Cardinality of an Attribute	3
5.6	Records per Page	3
5.7	Relation size	3
5.8	Cost	3
5.9	Scan	3
5.10	Sorting	3
5.11	Indexes	3
6	Transaction	4
6.1	4

1 Relational Algebra

1.1

-

2 SQL

2.1

-

3 Functional Dependencies

3.1

-

4 Indexes

4.1

-

5 Query Cost

5.1 Page

- Every time a Hard Drive is instructed to **read** or **write** something on the disk, it does so by **reading** or **writing units of specific size**.
- This **size** is called a **Page** and has always a **fixed size**.
- The **size of a page** on the disk will be denoted as P .

5.2 Size of a Record

- **Records** of a relation have the **same size**.
- The **size of a record**:
 - indicates how much space, in **bytes**, a **record occupies** when stored on the disk.
 - will be typically **given** or it would be possible to **compute** from the **size of the individual attributes**.
- The **size of a record** of a **relation R** will be denoted as t_R .
- Example:
 - Student(ssn:**int**, credits:**int**, age:**int**, name:**varchar(25)**, surname:**varchar(25)**)
 - Knowing that an **int** variable occupies 4 bytes and a **varchar** variable occupies 1 byte, we have that:

$$t_{Student} = (3 \cdot 4) + (2 \cdot 25) = 62 \text{ bytes}$$

- So the size of each record of Student occupies 62 bytes on the disk.

5.3 Pages of Relation

- When a **page** contains some **data of a relation**, **no records from other relations are allowed** in that page.
- The database try to **fill a page with as many records of the same relations as it can**, and if no more records can fit, then it start saving them in another page.
- All the **pages** that a **relation occupies** on the disk are **full**.
- The **number of pages** that a **relation R occupies** on the disk will be denoted as P_R .

5.4 Cardinality of a Relation

- A relation is a set of records.
- The **cardinality** of a **relation R** will be denoted as $|R|$ (**number of records** a relation has).

5.5 Cardinality of an Attribute

- The **cardinality** of:
 - an **attribute** is the **number of different distinct values** that the attribute has.
 - **two or more attributes** is the **number of different distinct combinations** of the values of these attributes.
- The **cardinality** of:
 - of an attribute A of a relation R , will be denoted as $|R.A|$.
 - of two or more attributes of a **relation** R , will be denoted as $|R.A_1, R.A_2, \dots, R.A_n|$.
- If the attribute is a **key**, the **cardinality** of the attribute is the **same** as the cardinality of the **relation**:
 - If the attribute A is key, then $|R| = |R.A|$, otherwise $|R.A| \leq |R|$.

5.6 Records per Page

-

5.7 Relation size

-

5.8 Cost

-

5.9 Scan

-

5.10 Sorting

-

5.11 Indexes

-

6 Transaction

6.1

-