

AGENEWTECH

M328L

Smart Module Specification_V1.4



Our aim is to provide customers with timely and comprehensive service. For any assistance, please contact our company headquarters:

Wuxi Sunning Technology Co., Ltd. (Abbreviation: Agenew)

No.52, Zone C, Huigu Pioneer Park, Huishan Economic Development Zone, Wuxi

Postal Code: 214174

PhoneNum: +86 0510 8235 0372 Mailbox: Asupport@agenewtech.com

Introduction

AGENEW OFFERS THE DOCUMENT AS A SERVICE TO ITS CUSTOMERS. CUSTOMERS MUST DESIGN THEIR PRODUCTS ACCORDING TO THE SPECIFICATIONS AND PARAMETERS PROVIDED IN THE DOCUMENTS. AGENEW SHALL NOT BE LIABLE FOR ANY DAMAGE CAUSED BY FAILURE TO COMPLY WITH RELEVANT OPERATION OR DESIGN SPECIFICATIONS. AGENEW HAS THE RIGHT TO UPDATE THE DOCUMENT BEFORE IT IS ANNOUNCED.

Disclaimers

AGENEW MAKES EFFORT TO ENSURE THE INTEGRITY, ACCURACY, TIMELINESS OR UTILITY OF THE FUNCTIONS UNDER DEVELOPMENT, BUT DOES NOT EXCLUDE THE POSSIBILITY OF ERRORS OR OMISSIONS OF THE ABOVE FUNCTIONS. UNLESS OTHERWISE SPECIFIED VALID AGREEMENTS, AGENEW MAKES NO IMPLIED OR EXPRESS GUARANTEE FOR THE USE OF FUNCTIONS UNDER DEVELOPMENT. TO THE MAXIMUM EXTENT PERMITTED BY APPLICABLE LAWS, AGENEW SHALL NOT BE LIABLE FOR ANY LOSS OR DAMAGE SUFFERED DUE TO THE USE OF THE FUNCTIONS UNDER DEVELOPMENT, WHETHER SUCH LOSS OR DAMAGE IS FORESEEABLE OR NOT.

Copyright

THE INFORMATION CONTAINED HERE IS PROPRIETARY TECHNICAL INFORMATION OF WUXI SUNNING TECHNOLOGY CO.,LTD. ANY COPIES AND REPRINTS THIS DOCUMENT WITHOUT THE PERMISSION OF AGENEW WILL BEAR LEGAL RESPONSIBILITY.

Copyright © Wuxi Sunning Technology Co., Ltd. 2026. All rights reserved.

About the Document


History

Version	Date	Author	Description
-	2025-03-25	Daniel Wu	Initial
1.0	2025-03-27	Daniel Wu	Controlled
1.1	2025-07-01	Daniel Wu	Update the software version to Android15
1.2	2025-08-19	Xiaochen Huang	Update and supplement interface
1.3	2025-11-30	Daniel Wu	Update WIFI 6E
1.4	2026-03-23	Chen Yun	Change company name

M328L

Smart Computing Power Module

Supports Wi-Fi & BT



M328L is a Wi-Fi smart computing module based on MediaTek's Octa-core MT8371 6nm processor (2×ARM Cortex-A78@2.2GHz + 6×ARM Cortex-A55@2.0GHz) launched by AGENEW, with inbuilt ARM Mali G57 MC2 GPU and NPU 8.0, equipped with Android 15 operating system. Its powerful performance, neon engine processing, 2D/3D graphics acceleration capabilities, fully meet the needs of customers for high-speed and high-computing-power functions in industrial and consumer applications.

M328L supports 2 × 2 Wi-Fi 6E and BT5.3 near-field wireless communication. In addition, M328L also has audio and video input/output interfaces and rich GPIO interfaces, including LCM display modules, touchscreens, cameras, microphones, speakers, UART, USB, I2C, SPI, PCIe, etc. It supports various audio and video codecs. The main screen supports up to UW5K60(5120×2160) @60fps or 4K60(3840×2160) @60fps. AI computing power reaches 10 TOPS.

M328L is a SMT module, with a total of 455 pins, all of which are LGA pins, with a size of 42mm×46mm×2.6mm, which can be embedded in various M2M product applications through the pad, making it widely used in video conferencing, live streaming, gaming, edge computing, robotics, drones, augmented reality/virtual reality (AR/VR), and other terminal products and industries.



Main Advantages

- ✓ Built-in AI unit, support 10T computing power
- ✓ Support Android 15
- ✓ Support 2×2 Wi-Fi 6E & Bluetooth 5.3 short-range wireless communication
- ✓ Support multiple audio and video codecs
- ✓ Main screen supports up to UW5K60(5120×2160) @60fps or 4K60(3840×2160) @60fps
- ✓ Support DP1.4
- ✓ Support 4K@60fps video recording and playback
- ✓ Abundant audio/video input and output interfaces and GPIO interfaces



64-bit Processor (Octa-core)



Wi-Fi 6E 2×2



Support Android 15



10 TOPS



Powerful Multimedia



BT 5.3

AI M328L	
Region/Operator	China
Operating System	Android 15
Memory	128GB UFS 3.1 + 8GB LPDDR5X
Module Dimension (mm)	42 × 46 × 2.6
Packaging	LGA
Temperature Range	
Operation Temperature	Operating temperature range: -20 °C ~ + 80 °C
	Storage temperature range: -40 °C ~ + 90 °C
Certification	
Compulsory Certification	Undetermined
Other Certifications	Undetermined
Features	
AI	10 TOPS
Wi-Fi	Wi-Fi 6E 2×2(MT6637X)
BT	BT 5.3
Video Encoding	4K@30fps
Video Decoding	4K@60fps
USB Firmware Update	●
OTA Firmware Update	●
Electrical Specification	
Operating Voltage	3.4~4.5 V, typical 3.8 V
Consumption (Typical)	200μA @ power off, 5.5mA @ sleep mode, typical
Interface	
LCD	Support up to UW5K60(5120×2160)@60fps or 4K60(3840×2160)@60fps
	2 × 4-lane MIPI DSI, eDP1.4 4-lane, DP1.4 4-lane (Type-C)
Camera	4-lane MIPI CSI
	Support Single camera up to 16MP@30fps
TP	Capacitive touch screen, I2C control
Audio	Lineout Interface (Require external audio amplifier) × 1, headphone × 1, simulated MIC × 4, digital MIC × 2
USB	USB2.0 × 3, USB 3.2 Gen1 × 1, DPoC USB3.2 Gen1 × 1
UART	× 4
SDIO	× 2
ADC	× 2, universal ADC interface
I2C	× 8, for TP, Cameras, Sensors, etc.
SPI	× 6
PWM	× 4
Motor Driven	× 1
I2S	× 2
PCIe	× 1
KEYPAD	× 7,for pow,rst,etc.
GPIO	× 183

AI	M328L
DMIC	× 2
GBE	× 1
eDP	× 1
PCM	× 2
Antenna	Wi-Fi Antenna ×1, Wi-Fi & Bluetooth Antenna ×1