

Class : Data visualization with ggplot

Vidisha Marwaha (A16677246)

Table of contents


Introduction	1
Installing ggplot2	2
A more complicated scatter plot	7
Exploring the gapminder dataset	10
Using Facet Wrap	15

Introduction

Today we will have our first play with the **ggplot2** package - one of the most popular graphics packages on the planet.

There are many plotting systems in R. These include so-called “*base*” plotting/graphics.

```
plot(cars)
```



base plot is generally rather short code and somewhat dull plots - but it is always there for you and is fast for big datasets.

Installing ggplot2

If I want to use **ggplot2** it takes some more work

```
#ggplot(cars)
```

I need to install the package first to my computer. To do this I can use the function `install.packages("ggplot2")`

```
#install.packages("ggplot2")
```

Every time I want to use a package I need to load it up with a `library()` call.

```
library(ggplot2)
```

Now finally I can use ggplot

```
ggplot(cars)
```




Every ggplot has atleast 3 things:

- **data** (the data from with the data you want to plot)
- **aes** (the aesthetic mapping of the data to plot)
- **geom** (how do you want the plot to look, points, lines, etc)


```
head(cars)
```

	speed	dist
1	4	2
2	4	10
3	7	4
4	7	22
5	8	16
6	9	10

```
ggplot(cars) +  
  aes(x=speed, y=dist) +  
  geom_point()
```




```
ggplot(cars) +  
  aes(x=speed, y=dist) +  
  geom_line()
```



Now we smooth the lines using multiple geom inputs...

```
ggplot(cars) +  
  aes(x=speed, y=dist) +  
  geom_point() +  
  geom_smooth()
```

`geom_smooth()` using method = 'loess' and formula = 'y ~ x'




I want a linear model and no standard bounds shown on my plot. I also want nicer axis labels, a title, etc.

```
bp <- ggplot(cars) +
  aes(x=speed, y=dist) +
  geom_point()

bp + geom_smooth(se=FALSE, method="lm") +
  labs(title="Stopping Distance of Old Cars",
       x="Speed (MPH)",
       y="Distance (ft)",
       caption="From the cars dataset") +
  theme_classic()
```

`geom_smooth()` using formula = 'y ~ x'



From the cars dataset

A more complicated scatter plot

Here we make a plot of gene expression data:

```
url <- "https://bioboot.github.io/bimm143_S20/class-material/up_down_expression.txt"
genes <- read.delim(url)
```

```
head(genes)
```

	Gene	Condition1	Condition2	State
1	A4GNT	-3.6808610	-3.4401355	unchanging
2	AAAS	4.5479580	4.3864126	unchanging
3	AASDH	3.7190695	3.4787276	unchanging
4	AATF	5.0784720	5.0151916	unchanging
5	AATK	0.4711421	0.5598642	unchanging
6	AB015752.4	-3.6808610	-3.5921390	unchanging

```
table(genes$State)
```

down	unchanging	up
72	4997	127

```
#genes$State == "up"
```

```
round(sum(genes$State == "up") / nrow(genes) * 100 , 2)
```

```
[1] 2.44
```

```
n.gene <- nrow(genes)
n.up <- sum(genes$State == "up")


up.precent <- n.up/n.gene * 100
round(up.precent, 2)
```

```
[1] 2.44
```

```
myplot <- ggplot(genes) +
  aes(x=Condition1, y=Condition2, col=State) +
  geom_point()
```


Change the colors

```
myplot + scale_colour_manual( values=c("purple","yellow","green") )
```

Change the titles

```
myplot + labs(title="Gene expression changes on Drug Treatment",  
              x="Control (no drug) ",  
              y="Drug Treatment")
```



Exploring the gapminder dataset

Here we will load up the gapminder data set to get practice with plots.

```
# File location online
url <- "https://raw.githubusercontent.com/jennybc/gapminder/master/inst/extdata/gapminder."

gapminder <- read.delim(url)
```

Q. How many entries rows are in this dataset?

```
nrow(gapminder)
```

```
[1] 1704
```

Q. How many columns?

```
ncol(gapminder)
```

```
[1] 6
```

```
head(gapminder)
```

	country	continent	year	lifeExp	pop	gdpPercap
1	Afghanistan	Asia	1952	28.801	8425333	779.4453
2	Afghanistan	Asia	1957	30.332	9240934	820.8530
3	Afghanistan	Asia	1962	31.997	10267083	853.1007
4	Afghanistan	Asia	1967	34.020	11537966	836.1971
5	Afghanistan	Asia	1972	36.088	13079460	739.9811
6	Afghanistan	Asia	1977	38.438	14880372	786.1134

```
table(gapminder$year)
```

1952	1957	1962	1967	1972	1977	1982	1987	1992	1997	2002	2007
142	142	142	142	142	142	142	142	142	142	142	142

Q. How many continents?

```
table(gapminder$continent)
```

Africa	Americas	Asia	Europe	Oceania
624	300	396	360	24

I could use the `unique()` function...

```
length(unique(gapminder$continent))
```

```
[1] 5
```


Q. How many countries are there?

```
length(unique(gapminder$country))
```


```
[1] 142
```

Now we make a plot of gdp per capita on x axis and life expectancy on y axis


```
ggplot(gapminder) +  
  aes(x=gdpPercap, y=lifeExp) +  
  geom_point()
```



```
ggplot(gapminder) +  
  aes(x=gdpPercap, y=lifeExp) +  
  geom_point(alpha=0.5)
```



```
ggplot(gapminder) +  
  aes(x=gdpPerCap, y=lifeExp) +  
  geom_point(col="green")
```



```
#install.packages("dplyr")
library(dplyr)
```

Attaching package: 'dplyr'

The following objects are masked from 'package:stats':

filter, lag

The following objects are masked from 'package:base':

intersect, setdiff, setequal, union


```
gapminder_2007 <- gapminder %>% filter(year==2007)
head(gapminder_2007)
```

	country	continent	year	lifeExp	pop	gdpPercap
1	Afghanistan	Asia	2007	43.828	31889923	974.5803
2	Albania	Europe	2007	76.423	3600523	5937.0295

3	Algeria	Africa	2007	72.301	33333216	6223.3675
4	Angola	Africa	2007	42.731	12420476	4797.2313
5	Argentina	Americas	2007	75.320	40301927	12779.3796
6	Australia	Oceania	2007	81.235	20434176	34435.3674

Plot of 2007 with population and continent date

```
ggplot(gapminder_2007) +
  aes(x=gdpPerCap, y=lifeExp, color=continent, size=pop) +
  geom_point(alpha=0.5)
```



Using Facet Wrap

```
ggplot(gapminder) +
  aes(x=gdpPerCap, y=lifeExp) +
  geom_point() +
  facet_wrap(~continent)
```

