Revision	ECO#	Approved By	Date	Revision History
01	0015681564	Per ECO Approval	1/9/19	In Agile

## iPad Top Modules 80 Digit Serial Number Specification

Apple Inc.	Size: Letter		Scale: NONE	Page 1 of 7
Title: ERS,DISPL MODUI	LE SN FORMAT	T,IPAD	Doc Number: <b>099-157</b> 9	97 Rev: 01

#### 1. PURPOSE

The purpose of this document is to provide an understanding of the 80 digit serial number format specification for all iPad Top Modules.

#### 2. **SCOPE**

This specification applies to all iPad Top Modules products.

#### 3. **RESPONSIBILITY**

The responsibility for complying to iPad Top Module 80 digit serial number specification is the assembly factory for the top module supplier during the barcode printing stage.

#### 4. REFERENCE DOCUMENTS

This is related to the iPad Top Module specification in order of precedence of document authority after (1) the Purchase Order, (2) the Top Module specification, and (3) this Specification.

#### 5. **EQUIPMENT REQUIRED**

Barcode printer that supports the printing of 80-digit serial number according to the Top Module specification without any readability issues on barcode scanners used commonly by FATP sites at both IQC & Top Module input station.

<b>\(\delta\)</b> Apple Inc.	Size: Letter		Scale: NONE	Page 2 of 7
Title: ERS,DISPL MODUI	E SN FORMAT	T,IPAD	Doc Number: <b>099-157</b>	97 Rev: 01

### 6. **xVT Stage Definition**

The following table should be used during xVT stage for printing serial number for xVT stage engineering samples:

Digit	Symbol	Description	Naming Rules	
1	P			
2	Р	Assigned Module/TFT fab code	Assigned and controlled by: factory_code_admin@group.appl	
3	P		e.com	
4	Y	Top Module Year of manufacturing	2013 = "3"	
5	w			
6	w	Top Module Week of manufacturing	1~53	
7	D	Top Module Day of manufacturing	1~7, Sunday = 1	
8	S			
9	S			
10	S	Serial Number (base 34)	0001~9999	
11	S			
12				
ı	EEEE	Apple Assigned EEEE #	Managed by Agile.	
15				
16	A	Engineering Build Name	0~8 Defined by Disp Eng EPM	
17	X	Checksum Character		
18	С		A11, B11, etc. per Display EPMs'	
19	0	Top Module Config in Engineering Builds.	arrangement.	
20	F		In MP, these digits will be reserved and coded as "XXX"	
21	S	SMT Vendor Code	Compeq = "C" Unimicron = "U" Samhan KR/NJ = "W"/"S" Haengsung KR/NJ = "H"/"A" Hankook KR/NJ = "K"/"B" YP = "Y" LGIT = "L" GIS = "G" HDK = "D" TSMT = "J" E-Ong = "E"	

<b>4</b> Apple Inc.	Size: Letter		Scale: NONE	Page 3 of 7
Title: ERS,DISPL MODUI	LE SN FORMAT	Γ,IPAD	Doc Number: <b>099-157</b> 9	<b>97</b> Rev: 01

Digit	Symbol	Description	Naming Rules	
22	М			
23	Т	SMT Date Code	Refer to <b>Section 8.1</b>	
24	В	BA Line ID	0~9, A~Z (excluding alphabets "I", and "O"))	
25	С	CGM Line ID	0~9, A~Z (excluding alphabets "I", and "O"))	
26	С	Cell's Mother Glass Y Position	$0\sim9$ , $A\sim Z$ (excluding alphabets "I", and "O"))	
27	Е	Cell's Mother Glass X Position	$0\sim9$ , $A\sim Z$ (excluding alphabets "I", and "O"))	
28	L			
29	L	Cell's Datecode	Refer to <b>Section 8.1</b>	
30	Р	APR Plate Revision	0~9, A~Z (excluding alphabets "I", and "O"))	
31	E	Models w/ eDP CNT - eDP CNT Vendor  Models w/ eDP Flex - eDP Flex Vendor	Models w/ eDP CNT:  ZDT = "Z"  Fujikura = "F"  Mektec = "M"  Hirose = "H"  Models w/ eDP Flex:  Avary = "A"  Fujikura = "F"  Mektec = "M"	
32	С	CGM models - LAM Line ID  LCM models - Panel Flex	CGM models: 0~9, A~Z (excluding alphabets "I", and "O"))  LCM models: Flexium = "X" YP = "Y"	
33				
1	BLU	BLU 17-digit S/N	Follow same Apple module S/N rule 081-2110	
49			Tale 661 E116	
50	L	LPT LED Vendor/Site		
51	G	LPT Shielding Film Vendor		
52	E	LPT LED Wavelength Bin	Refer to BLU ERS.	
53	L	LPT PCB & SMT Vendor		
54	F	LPT Flex Vendor		
55	С		A11, B11, etc. per Display EPMs'	
56	0	BLU Config in Engineering Builds	arrangement.  In MP, these digits will be	
57	F		reserved and coded as "XXX"	

<b>\(\bigsim\)</b> Apple Inc.	Size: Letter		Scale: NONE	Page 4 of 7
Title: ERS,DISPL MODUI	LE SN FORMAT	Γ,IPAD	Doc Number: <b>099-157</b> 9	<b>97</b> Rev: 01

Digit	Symbol	Description	Naming Rules
58	М	Metal stamping Tool #	
59	P	P-Chassis or insert molding Tool #	Refer to BLU ERS.
60	С	MPC vendor & P-Chassis Cavity #	
61		CGM models - CGS 17-digit S/N	CGM models: Follow same Apple module S/N
I	CGS		rule 081-2110
77	+	LCM models - Reserved	LCM models: Fill with "X"
78	С	CGM models - CGS config	CGM models: A11, B11, etc. per Touch EPMs'
79	0		arrangement.
80	F	LCM models - Reserved	LCM models: Fill with "X"

Apple Inc.	Size: Letter		Scale: NONE	Page 5 of 7
Title: ERS,DISPL MODUI	LE SN FORMAT	T,IPAD	Doc Number: <b>099-157</b> 9	<b>97</b> Rev: 01

<sup>\*</sup>Red text will be printed on 1st row
\*Green text will be printed on 2nd row

# 7. **MP Stage Definition** Follow xVT Stage Definition

<b>Apple Inc.</b>	Size: Letter		Scale: NONE	Page 6 of 7
Title: ERS,DISPL MODUI	LE SN FORMAT	T,IPAD	Doc Number: <b>099-157</b> 9	97 Rev: 01

#### 8. Lookup Tables

This section defines individual lookup tables for encoding / decoding 80-digit serial numbers referred by **Section 6 - xVT Stage Definition** and **Section 7 - MP Stage Definition**.

#### 8.1. SMT (22~23) & Cell (28~29) Date Code

This table denotes  $22nd\sim23rd \& 28th\sim29th$  digit of the 80 digit serial number encoding scheme, where 1st digit is the Month Digit and 2nd digit is the Date Digit, usable code digits are  $0\sim9$ ,  $A\sim Z$  (excluding alphabets "I", and "O")). Year part is excluded on purpose, and can be extracted from 1st digit of YWWD of Top Module - 5th digit of 80 digit serial number.

1st Digit	Month	2nd Digit	Day
1	January	1	1
2	Febuary	2	2
3	March		
4	April	Α	10
5	May	В	11
6	June		
7	July	Н	17
8	August	J	18
9	September		
А	October	N	22
В	November	Р	23
С	December		
		W	30
		Х	31

<b>4</b> Apple Inc.	Size: Letter		Scale: NONE	Page 7 of 7
Title: ERS,DISPL MODUI	LE SN FORMAT	Γ,IPAD	Doc Number: <b>099-157</b> 9	<b>P7</b> Rev: 01