


# C++ Quiz

## PHILOSOPHISING GEEKS



`assert(true);`

Krishna Kumar

# Fun with Type Deduction

- `const int cx = 0;`
- `auto cx2 = cx;`
- `decltype(cx) cx3 = cx;`
- `template <typename T>`  
`void f1(T param);`  
`f1(cx);`
- `template <typename T>`  
`void f1(T& param);`  
`f1(cx);`
- `template <typename T>`  
`void f1(T&& param);`  
`f1(cx);`
- Type? Why? //Type is int
- Type? Why? // Const int
- T's type and why?  
param is a copy of cx – int
- T's type and why?  
Referring to a chunk of memory –  
const int
- T's type and why?  
Neat trick to allow argument  
forwarding – perfect forwarding  
const int&

# Fun with Type Deduction: Solution

- `const int cx = 0;`
- `auto cx2 = cx;`
- `decltype(cx) cx3 = cx;`
- `template <typename T>`  
`void f1(T param);`  
`f1(cx);`
- `template <typename T>`  
`void f1(T& param);`  
`f1(cx);`
- `template <typename T>`  
`void f1(T&& param);`  
`f1(cx);`
- `//Type is int`
- `// Const int`
- T's type and why?
- T's type and why?
- T's type and why?

# Lambda expressions - Type

- `const int cx = 0;`
- `auto lam = [cx] {cx = 10;};`
- `// Compiler generated class`
- `class UptoCompiler {`
  - `private:`
    - `??? cx;`
- `};`
- `// What happens here?`
- `// type? Why?`

# Lambda expressions: Solution

- `const int cx = 0;`
- `auto lam = [cx] {cx = 10;};`
- `// Compiler generated class`
- `class UptoCompiler {`
  - `private:`
    - `??? cx;`
- `};`
- `// Error! Why?`
- `// const int`
- The variable `cx` within `{}` is what is in the compiler generated class.
- To preserve what is being passed to the hidden compiler generated class.
- Programming in 2 scopes!

# Lambda init capture: C++14

- `const int cx = 0;`
- `auto lam = [cx = cx] {cx = 10;};`
- `// Compiler generated class`
- `class UptoCompiler {`
  - `private:`
    - `??? cx;`
  - `Public:`
    - `void operator()() const`
      - `{ cx = 0; }`
    - `...`
- `};`
- `//Error why?`
- `// type? Why?`
- 
-

# Lambda init capture: Solution

- `const int cx = 0;`
- `auto lam = [cx = cx] {cx = 10;};`
- `// Compiler generated class`
- `class UptoCompiler {`
  - `private:`
    - `??? cx;`
  - `Public:`
    - `void operator()() const`
      - `{ cx = 0; }`
    - `...`
- `};`
- `// Error! Why?`
- `// int (acts like a const int!)`
-

# Lambda init capture: mutable

- `const int cx = 0;`
- `auto lam = [cx = cx] mutable {cx = 10;};`
- `auto lam = [cx = cx] ()mutable {cx = 10;};`
- `class UptoCompiler {`
  - `private:`
    - `??? cx;`
  - `Public:`
    - `void operator()() const`
      - `{ cx = 0; }`
    - `...`
- `};`
- `//Error why?`
- `// Standard failed to add empty() for mutable!`
- 
- `Type??`
- `Int (acts like an int)! Phew!`



# Type deduction

For `const int cx = 0;`

Context	Type
<code>auto</code>	<code>int</code>
<code>decltype</code>	<code>const int</code>
<code>template (T param)</code>	<code>int</code>
<code>template (T&amp; param)</code>	<code>const int</code>
<code>template (T&amp;&amp; param)</code>	<code>const int&amp;</code>
<code>lambda (by-value capture)</code>	<code>const int</code>
<code>lambda (init capture)</code> - same as <code>auto</code> !	<code>int</code>

# Type deduction & initialisation

- `int x1 = 0;`  
`int x2(0);`  
`int x3 = {0};`  
`int x4 {0};`
- `auto x1 = 0;`  
`auto x2(0);`  
`auto x3 = {0};`  
`auto x4 {0};`
- `template<typename T>`  
`void f(T param)`  
`f({0});`
  - `// type? Why? - int`
  - `// type? Why? - int`
  - `// type? initializer_list<int>`
  - `// type? initializer_list<int>`
  - `// type? Why?`  
Error!  
No type “{0}”

# auto to explicit type deduction

```
std::map<std::string, int> m;
```

- // Why this is inefficient

```
for (const std::pair<std::string, int>& p : m) ...
```

- // This is optimised

```
for (const auto& p : m) ....
```

# auto or explicit type deduction: solution

- Avoid accidental temporary creation!

```
std::map<std::string, int> m;
```

- // Holds object of type std::pair<**const** std::string, int>
- // Why this is inefficient
- // creates a temp on each iteration std::string is copied

```
for (const std::pair<std::string, int>& p : m) ...
```

- // This is optimised
- // No temporaries are created

```
for (const auto& p : m) ....
```

# Inheritance - should this compile?

- class Base {
  - public:  
void dobasework();
- };
- class Derived : public Base{
  - public:  
void derivedwork() {  
dobasework();  
}
- };

- template <typename T>
- class Base {
  - public:  
void dobasework();
- };
- template <typename T>
- class Derived : public Base<T>{
  - public:  
void derivedwork() {  
dobasework();  
}
- };
- Dependent base class
- Two-phase lookup

# Inheritance - specialisation

- `template <typename T>`
- `class Base {`
  - `public:`  
`void dobasework();`
- `};`
- `template <typename T>`
- `class Derived : public Base<T>{`
  - `public:`  
`void derivedwork() {`  
`dobasework();`  
`}`
- `};`
- `// cont...`

- `// cont...`
- `// Possible future`
- `// no base work`  
`template<>`  
`class Base<int> {};`
- `// Fail!`  
`Derived<int> d;`  
`do.derivedWork();`

# Inheritance – specialisation: solution?

- `template <typename T>`
- `class Base {`
  - `public:`  
`void dobasework();`
- `};`
- `template <typename T>`
- `class Derived : public Base<T>{`
  - `public:`  
`void derivedwork() {`  
`Base<T>::dobasework();`  
`}`
- `};`
- `// Base<T>::` turns off virtual function calls – not relevant here

- `template <typename T>`
- `class Base {`
  - `public:`  
`void dobasework();`
- `};`
- `template <typename T>`
- `class Derived : public Base<T>{`
  - `public:`  
`void derivedwork() {`  
`this->dobasework();`  
`}`
- `};`
- `// Lookup only in the current`

# Templates & function calls

- 1) `template<typename T1, typename T2>  
void f( T1, T2 );`
  - 2) `template<typename T> void f( T );`
  - 3) `template<typename T> void f( T, T );`
  - 4) `template<typename T> void f( T* );`
  - 5) `template<typename T> void f( T*, T );`
  - 6) `template<typename T> void f( T, T* );`
  - 7) `template<typename T> void f( int, T* );`
  - 8) `template<> void f<int>( int );`
  - 9) `void f( int, double );`
  - 10) `void f( int );`
- `int i; double d;`
  - `float ff; complex<double> c;`
  - **non-templates are always preferred over templates**
- a) `f( i );` // invokes?
  - b) `f<int>( i );` // invokes?
  - c) `f( i, i );` // invokes?
  - d) `f( c );` // invokes?
  - e) `f( i, ff );` // invokes?
  - f) `f( i, d );` // invokes?
  - g) `f( c, &c );` // invokes?
  - h) `f( i, &d );` // invokes?
  - i) `f( &d, d );` // invokes?
  - j) `f( &d );` // invokes?
  - k) `f( d, &i );` // invokes?
  - l) `f( &i, &i );` // invokes?



# Templates & function calls

- 1) `template<typename T1, typename T2>`  
`void f( T1, T2 );`
  - 2) `template<typename T> void f( T );`
  - 3) `template<typename T> void f( T, T );`
  - 4) `template<typename T> void f( T* );`
  - 5) `template<typename T> void f( T*, T );`
  - 6) `template<typename T> void f( T, T* );`
  - 7) `template<typename T> void f( int, T* );`
  - 8) `template<> void f<int>( int );`
  - 9) `void f( int, double );`
  - 10) `void f( int );`
- `int i; double d;`
  - `float ff; complex<double> c;`
  - a) `f( i );` // 10
  - b) `f<int>( i );` // 8 – `f<int>` explicit
  - c) `f( i, i );` // 3
  - d) `f( c );` // 2
  - e) `f( i, ff );` // 1 why not 9? only exact match; `ff` is float not double.
  - f) `f( i, d );` // 9
  - g) `f( c, &c );` // 6
  - h) `f( i, &d );` // 7
  - i) `f( &d, d );` // 5
  - j) `f( &d );` // 4
  - k) `f( d, &i );` // 1
  - l) `f( &i, &i );` // 3

# References

- Scott Meyers “The last thing D needs”
- Cracking the C, C++ and Java interview