



MASTER TL5 High Output Eco

MASTER TL5 HO Eco 34=39W/835 UNP

This extremely efficient TL5 lamp (tube diameter 16 mm) saves considerable energy by simple lamp-for-lamp replacement. The TL5 HO Eco lamp is optimized for installations requiring high light output and offers excellent lumen maintenance and color rendering. Application areas vary from offices and industry to schools and retail environments.

Product data

• General Characteristics

Cap-Base	G5
Bulb	T5 [16 mm]
Life to 10% fail	21000 hr
Preheat EL,3h	
Life to 50% fail	25000 hr
Preheat EL,3h	
LSF HF Preheat	99 %
2000h Rated,3h	
LSF HF Preheat	99 %
4000h Rated,3h	
LSF HF Preheat	99 %
6000h Rated,3h	
LSF HF Preheat	99 %
8000h Rated,3h	
LSF HF Preheat	99 %
12000h Rated,3h	
LSF HF Preheat	99 %
16000h Rated,3h	
LSF HF Preheat	94 %
20000h Rated,3h	

• Light Technical Characteristics

Color Code	835 [CCT of 3500K]
Color Rendering Index	85 Ra8
Color Designation (text)	White
Color Temperature	3500 K
Luminous Flux EL 25°C, Rated	3250 Lm
Luminous Flux EL 25°C, Nominal	3250 Lm
Luminous Flux Lamp EL 35°C	3500 Lm

Lum Efficacy Rated HF 25°C	94 Lm/W
Lum Efficacy Rated HF 35°C	102 Lm/W
LLMF HF 2000h Rated	96 %
LLMF HF 4000h Rated	95 %
LLMF HF 6000h Rated	94 %
LLMF HF 8000h Rated	93 %
LLMF HF 12000h Rated	92 %
LLMF HF 16000h Rated	91 %
LLMF HF 20000h Rated	90 %
Design Temperature	35 C
Chromaticity Coordinate X	409 -
Chromaticity Coordinate Y	394 -

• Electrical Characteristics

Lamp Wattage	34 W
Lamp Wattage EL 25°C, Rated	34.6 W
Lamp Wattage EL 25°C, Nominal	34 W
Lamp Wattage EL 35°C	34.2 W
Lamp Voltage EL 25°C	99 V
Lamp Voltage EL 35°C	100 V

MASTER TL5 High Output Eco

Lamp Current EL 25°C	0.350 A
Lamp Current EL 35°C	0.340 A
Dimmable	Yes

• Environmental Characteristics

Energy Efficiency Label (EEL)	A+
Mercury (Hg) Content	1.4 mg
Energy consumption kWh/1000h	38 kWh

• Measuring Conditions

Calibration Current	0.340 A
HF Generator Rated Voltage	215 V
Resistor	330 ohm

• Product Dimensions

Base Face to Base Face A	849.0 (max) mm
--------------------------	----------------

Insertion Length B	853.7 (min), 856.1 (max) mm
Overall Length C	863.2 (max) mm
Diameter D	17 (max) mm

• Product Data



Order code	927992383531
Full product code	927992383531
Full product name	MASTER TL5 HO Eco 34=39W/835 UNP
Order product name	MASTER TL5 HO Eco 34=39W/835 UNP/40
Pieces per pack	1
Packing configuration	40
Packs per outerbox	40
Bar code on pack - EAN1	8718291153559
Bar code on outerbox - EAN3	8718291153566
Logistic code(s) - 12NC	927992383531
ILCOS code	FDH-34/35/1B-L/P-G5-16/850
Net weight per piece	80.500 gr

Warnings and Safety

- A reduction in energy consumption is only achieved with current-controlled gear.

- The lamps operate perfectly with power-controlled gear, but in that case the light output can be up to 10% higher.

Dimensional drawing





G5

MASTER TL5 HO Eco 34=39W/835 UNP

Product	A (Max)	B (Min)	B (Max)	C (Max)	D (Max)
TL5 HO Eco 34=39W/835	849.0	853.7	856.1	863.2	17

Photometric data



© 2013 Koninklijke Philips N.V. (Royal Philips)
All rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. (Royal Philips) or their respective owners.

www.philips.com/lighting

2013, July 4
data subject to change