Jellyfish Types Classification Using AI

1.Introduction

1.1 Project Overview

Jellyfish play a crucial role in marine ecosystems, but some species can disrupt fisheries, tourism, and coastal industries. Accurate classification is essential for ecological research and conservation efforts. This project applies **deep learning techniques** to automate jellyfish species identification using image data.

1.2 Objective

The primary objective of this project is to develop an AI-based deep learning model capable of accurately classifying different species of jellyfish by analyzing their morphological features, coloration, and other distinguishing characteristics. The model will leverage convolutional neural networks (CNNs) or vision transformers (ViTs) to process image data, enabling automated and efficient species identification. This system will support marine biologists, conservationists, and environmental researchers in monitoring jellyfish populations, studying biodiversity, and managing marine ecosystems effectively.

2. Project Initialization and Planning Phase

Date	30 March 2025
Team ID	SWTID1743356633
Project Title	Jellyfish Types Classification Using AI

2.1 Project Proposal (Proposed Solution)

Project Overview	
Objective	Creating a deep learning model model for classifying different species of jellyfish by using by using CNN, VGG16, and Flask
Scope	It is suitable for basic classification tasks, works even well with small datasets, simple web interfac e for predictions
Problem Statement	

Description	Our aim is to create a deep learning model by using CNN, VGG16, and Flask for deployment to accurately classify jellyfish, as they play a crucial role in our ecosystem.
Impact	Solving the problem will have positive impact on society, we will be able to help: **Marine Biologists:** Rapid species identification from fieldwork images. **Aquariums & NGOs:** Tracking jellyfish populations in specific regions. **Public Safety:** Detecting venomous species near beaches
Proposed Solution	

Approach	A. Dataset Acquisitin Public datasets (Kaggle). **Dataset Requirements:** At least **500–1,000 images per species** for reliable training. B. Data Cleaning & Augmentation **Preprocessing Steps:** Resize images to **224x224** (VGG16 input size). Remove corrupted/duplicate images. 3. Model Development Custom CNN Architecture 4. Training & Evaluation A. Training Strategy Train-Validation-Test Split (70-15-15). Data Generators (ImageDataGenerator for real-time augmentation). Transfer Learning Workflow: Phase 1: Train only new layers (20 epochs). Phase 2: Unfreeze last 3 blocks + fine-tune (10 epochs). B. Evaluation Metrics Primary: Accuracy, Precision, Recall, F1-Score. Confusion Matrix (identify misclassified species). C. Performance Optimization Class Imbalance: Use Weighted Loss or Oversampling. Overfitting: Add L2 Regularization, Dropout, or Data Augmentation.
	5. Deployment with Flask A. Flask Web App Architecture Frontend (HTML/CSS/JS): File upload form. Display predictions with confidence scores. **Backend (Flask):** Load trained model (model.h5).

	Preprocess uploaded images (resize/normalize). Return JSON response with predictions.
Key Features	1. Data Collection and Pre-Processing 2. Data Augmentation 3. Intializing model (CNN) 4. Importing VGG16 model 5. Training and Evaluation 6. Deployment

2.2 Resource Requirement

Resource Type	Description	Specification
Hardware		
Computing Resources	CPU, GPU, specification of number of core	CPU - 4-core(Intel 5), GPU - Not required
Memory	RAM specifications	8 GB
Storage	Disk Space for data, model and logs	50 GB SSD
Software		
Framworks	Python Frameworks	Flask
Libraries	Additional Libraries	Tensorflow, VGG16
Development Environment	IDE	Visual Studio Code
Data		
Data	Kaggle	Contains 900 images belonging to six different species.

3. Data Collection and Preprocessing Phase

3.1 Data Collection Plan & Raw Data Sources Identification

Section	Description
Project Overview	This project leverages deep learning (CNN & VGG16) to automatically classify jellyfish species from images, aiding marine biologists and conservationists in biodiversity monitoring. A Flask-based web app enables easy deployment for real-world use. Objectives: Develop an AI Model: Train a **custom CNN** and **VGG16** (transfer learning) to classify jellyfish species with >90% accuracy. **Create a User-Friendly Tool:** Build a **Flask web interface** for uploading images and receiving predictions. **Support Marine Research:** Assist in tracking invasive/harmful species and studying ecological trends.
Data Collection Plan	Kaggle Dataset - https://www.kaggle.com/datasets/anshtanwar/jellyfish-types
Raw Data Sources Identified	This dataset contains 900 images of jellyfish belonging to six different categories and species: mauve stinger jellyfish, moon jellyfish, barrel jellyfish, blue jellyfish, compass jellyfish, and lion’s mane jellyfish

Raw Data Sources

Section Name	Description	URL	Format	Size	Acess Permission
Jellyfish Image Dataset	This dataset contains 900 images of jellyfish belonging to six different categories and species: 1.Mauve stinger jellyfish 2. Moon jellyfish 3.Barrel jellyfish 4. Blue jellyfish 5. Compass jellyfish 6.Lion's mane jellyfish.	https://www.kaggle.com/datasets/anshtanwar/jellyfish-types	Image		Public

3.2 Data Quality Report

Data Source	Data Quality Report	Severity	Resolution Plan
Jellyfish Image Classification	Issues in dataset	Low/Moderate/ High	Solution

3.3 Data Preprocessing

Section	Description
Data Overview	Overview of data
Resizing	Resized image to (224,224,3)
Normalization	224*224 pixels
Color Space Conversion	Converted grayscale to RGB
Data Preprocessing Code Screenshots	
Loading Data	
Resizing	
Normalization	
Color Space Conversation	

4. Model Development Phase

4.1 Model Selection Report

Below is the Model Architecture Evaluation for Image Classification required for the project

Architecture	Strengths	Weaknesses	Computational Requirements	Suitability
Convolutional Neural Network	• Tailored for image data • Captures spatial hierarchy • Highly accurate with deep variants like VGG, ResNet	• Can overfit on small datasets • Requires tuning hyperparameters	Medium to High	**Highly suitable** (Best for image classification)
Recurrent Neural Network	• Good for sequence data • Maintains memory of previous steps	• Performs poorly on images • Slow training due to sequential nature • Struggles with high-dimensional image input	High	**Not suitable** (Not designed for image data)
LSTM/GRU	• Improves on standard RNN • Handles long sequences better	• Still not good for spatial data • Complex to train • High memory use	High	Not suitable

Transformer	• Strong performance on large-scale vision tasks • Captures long-range dependencies	• Needs large datasets and compute • Less efficient for small datasets	Very High	Potential future option But **overkill** for this project
MobileNet / EfficientNet	• Lightweight and fast • Good for mobile/web deployment	• May sacrifice accuracy for speed - Less flexible to customize	Low to Medium	Good option for deployment but VGG16 is more accurate here

Hence, for this project we selected the **Convolutional Neural Network (CNN) Architecture** as:

- They are specifically designed for image classification tasks
- Learns local patterns and hierarchical features
- Efficient with data augmentation and regularization
- Supported by popular libraries like Keras, TensorFlow, PyTorch

To further support the selection of the most appropriate CNN architecture for this image classification task, the following table provides a performance comparison between several widely used models:

Architecture	Top-1 Accuracy (ImageNet)	Parameters	Model Size	Inference Speed	Remarks
VGG16	~71.6%	~138 million	~528 MB	Moderate	Easy to use, but heavy and slow
ResNet50	~76.0%	~25 million	~98 MB	Fast	Deeper, uses residual connections
EfficientNet-B0	~77.1%	~5 million	~20 MB	Very Fast	Great for mobile/web apps
DenseNet121	~74.9%	~8 million	~33 MB	Fast	Accurate & compact due to dense blocks

Vision Transformer	~85%+ (large-scale)	~86 million	~330 MB+	Slower w/o TPU/GPU	Requires a large dataset, not ideal here

Below Table provides a brief description of models used in training :

Model	Description
Resnet50 Model	**ResNet50** is a deep convolutional neural network with 50 layers, developed by Microsoft. It introduced the concept of residual learning through skip connections, which helps in training very deep networks by avoiding the vanishing gradient problem. This design allows the model to learn identity mappings, making it easier to optimize and improving accuracy in image classification and detection tasks. vanishing gradient problem. This design allows the model to learn identity mappings, making it easier to optimize and improving accuracy in image classification and detection tasks.
DenseNet121 Model	**DenseNet121** is a 121-layer convolutional network developed by Facebook AI Research. It features dense connections where each layer receives inputs from all previous layers, promoting feature reuse and reducing the number of parameters. This architecture enhances gradient flow, improves efficiency, and leads to better performance with fewer computations.

EfficientNetB0 Model	**EfficientNetB0** is the baseline model from Google's EfficientNet family, designed for optimal accuracy and efficiency. It uses a compound scaling method that balances network depth, width, and resolution. Despite being lightweight, it delivers high accuracy, making it suitable for applications on mobile and edge devices without sacrificing performance.
VGG16 Model	**VGG16** is a classic convolutional neural network with 16 layers, developed by the Visual Geometry Group at Oxford. It uses a simple and uniform architecture based on stacking 3x3 convolution layers followed by max-pooling. While it has more parameters compared to newer models, its straightforward design makes it easy to implement and understand, and it's still widely used for image classification and feature extraction.

4.2. Initial Model Training Code, Model Validation and Evaluation Report

4.2.1 Initial Model Training Code:

```
# ResNet50 Model
resnet_base_model = ResNet50(weights='imagenet', include_top=False, input_shape=input_shape_resnet)
resnet_base_model.trainable = False

resnet_global_avg_pooling = GlobalAveragePooling2D()(resnet_base_model.output)
resnet_output = Dense(6, activation='softmax')(resnet_global_avg_pooling)
resnet_model = Model(inputs=resnet_base_model.input, outputs=resnet_output)

resnet_model.compile(loss='categorical_crossentropy', optimizer='adam', metrics=['accuracy'])

# DenseNet121 Model
densenet_base_model = DenseNet121(weights='imagenet', include_top=False, input_shape=input_shape_densenet)
densenet_base_model.trainable = False

densenet_global_avg_pooling = GlobalAveragePooling2D()(densenet_base_model.output)
densenet_output = Dense(6, activation='softmax')(densenet_global_avg_pooling)
densenet_model = Model(inputs=densenet_base_model.input, outputs=densenet_output)

densenet_model.compile(loss='categorical_crossentropy', optimizer='adam', metrics=['accuracy'])

# EfficientNetB0 Model
efficientnet_base_model = EfficientNetB0(weights='imagenet', include_top=False, input_shape=input_shape_efficientnet)
efficientnet_base_model.trainable = False

efficientnet_global_avg_pooling = GlobalAveragePooling2D()(efficientnet_base_model.output)
efficientnet_output = Dense(6, activation='softmax')(efficientnet_global_avg_pooling)
efficientnet_model = Model(inputs=efficientnet_base_model.input, outputs=efficientnet_output)

efficientnet_model.compile(loss='categorical_crossentropy', optimizer='adam', metrics=['accuracy'])

# Define callbacks for training
early_stopping = EarlyStopping(monitor='val_loss', patience=20, restore_best_weights=True)
lr_scheduler = ReduceLROnPlateau(monitor='val_loss', patience=10, factor=0.5, min_lr=1e-7)

# -------------------------
# Train the models
# -------------------------
print("Training ResNet50 model...")
resnet_history = resnet_model.fit(X_train_resized_resnet, y_train, batch_size=32, epochs=200,
                                  validation_split=0.2, callbacks=[early_stopping, lr_scheduler])

print("\nTraining DenseNet121 model...")
densenet_history = densenet_model.fit(X_train_resized_densenet, y_train, batch_size=32, epochs=200,
                                      validation_split=0.2, callbacks=[early_stopping, lr_scheduler])

print("\nTraining EfficientNetB0 model...")
efficientnet_history = efficientnet_model.fit(X_train_resized_efficientnet, y_train, batch_size=32, epochs=200,
                                              validation_split=0.2, callbacks=[early_stopping, lr_scheduler])
```

4.2.2 Model Validation and Evaluation Report :

Model	Summary	Training and Validation Performance Metrics

Resnet50	Evaluating models on test data:
	5/6 ━━━━━━━━━━━━━━━━━━ 4s 696ms/step - accuracy: 0.4058 -
	ResNet50 Test accuracy: 0.3722222149372101
		print("Training ResNet50 model...")
		resnet_history = resnet_model.fit(X_train_resized_resnet, y_train, batch_size=32,
		validation_split=0.2, callbacks=[early_stopping,
		
		Training And Validation:
		
		# ResNet50 Model
		resnet_base_model = ResNet50(weights='imagenet', include_top=False, input_shape=input_
		resnet_base_model.trainable = False
		
		resnet_global_avg_pooling = GlobalAveragePooling2D()(resnet_base_model.output)
		resnet_output = Dense(6, activation='softmax')(resnet_global_avg_pooling)
		resnet_model = Model(inputs=resnet_base_model.input, outputs=resnet_output)
		
		resnet_model.compile(loss='categorical_crossentropy', optimizer='adam', metrics=['acc
		
		Performance Metrics:
		
		Training ResNet50 model...
		Epoch 1/200
		18/18 ━━━━━━━━━━━━━━━━━━ 27s 842ms/step - accuracy: 0.1721 - loss: 2.0020 - val_accuracy: 0.1528 - val_loss: 1.8570 -
		Epoch 2/200
		18/18 ━━━━━━━━━━━━━━━━━━ 22s 131ms/step - accuracy: 0.1567 - loss: 1.8312 - val_accuracy: 0.1597 - val_loss: 1.8212 -
		Epoch 3/200
		18/18 ━━━━━━━━━━━━━━━━━━ 2s 125ms/step - accuracy: 0.2256 - loss: 1.7985 - val_accuracy: 0.1250 - val_loss: 1.7979 - l
		Epoch 4/200
		18/18 ━━━━━━━━━━━━━━━━━━ 2s 101ms/step - accuracy: 0.1850 - loss: 1.7954 - val_accuracy: 0.1528 - val_loss: 1.8027 - l
		Epoch 5/200
		18/18 ━━━━━━━━━━━━━━━━━━ 3s 118ms/step - accuracy: 0.1790 - loss: 1.7834 - val_accuracy: 0.1944 - val_loss: 1.8096 - l
		Epoch 6/200
		18/18 ━━━━━━━━━━━━━━━━━━ 3s 129ms/step - accuracy: 0.2353 - loss: 1.7721 - val_accuracy: 0.1944 - val_loss: 1.7642 - l
		Epoch 7/200
		18/18 ━━━━━━━━━━━━━━━━━━ 2s 106ms/step - accuracy: 0.2438 - loss: 1.7574 - val_accuracy: 0.1944 - val_loss: 1.7881 - l
		Epoch 8/200
		18/18 ━━━━━━━━━━━━━━━━━━ 2s 103ms/step - accuracy: 0.2016 - loss: 1.7671 - val_accuracy: 0.1667 - val_loss: 1.7870 - l
		Epoch 9/200
		18/18 ━━━━━━━━━━━━━━━━━━ 2s 127ms/step - accuracy: 0.2577 - loss: 1.7427 - val_accuracy: 0.2014 - val_loss: 1.7579 - l
		Epoch 10/200
		18/18 ━━━━━━━━━━━━━━━━━━ 2s 103ms/step - accuracy: 0.2356 - loss: 1.7514 - val_accuracy: 0.1667 - val_loss: 1.7791 - l
		Epoch 11/200
		18/18 ━━━━━━━━━━━━━━━━━━ 3s 119ms/step - accuracy: 0.2477 - loss: 1.7354 - val_accuracy: 0.1806 - val_loss: 1.7845 - l
		Epoch 12/200
		18/18 ━━━━━━━━━━━━━━━━━━ 2s 106ms/step - accuracy: 0.2529 - loss: 1.7241 - val_accuracy: 0.2639 - val_loss: 1.7648 - l
		Epoch 13/200
		18/18 ━━━━━━━━━━━━━━━━━━ 3s 126ms/step - accuracy: 0.2504 - loss: 1.7532 - val_accuracy: 0.2292 - val_loss: 1.7505 - l
		Epoch 14/200
		18/18 ━━━━━━━━━━━━━━━━━━ 3s 129ms/step - accuracy: 0.2235 - loss: 1.7409 - val_accuracy: 0.2292 - val_loss: 1.7456 - l
		
		Epoch 187/200
		18/18 ━━━━━━━━━━━━━━━━━━ 2s 108ms/step - accuracy: 0.4378 - loss: 1.4366 - val_accuracy: 0.4097 - val_loss: 1.5504 - learn
		Epoch 188/200
		18/18 ━━━━━━━━━━━━━━━━━━ 3s 110ms/step - accuracy: 0.4992 - loss: 1.3999 - val_accuracy: 0.4028 - val_loss: 1.5525 - learn
		Epoch 189/200
		18/18 ━━━━━━━━━━━━━━━━━━ 3s 124ms/step - accuracy: 0.4677 - loss: 1.4747 - val_accuracy: 0.4097 - val_loss: 1.5492 - learn
		Epoch 190/200
		18/18 ━━━━━━━━━━━━━━━━━━ 2s 116ms/step - accuracy: 0.4565 - loss: 1.4569 - val_accuracy: 0.4097 - val_loss: 1.5460 - learn
		Epoch 191/200
		18/18 ━━━━━━━━━━━━━━━━━━ 2s 106ms/step - accuracy: 0.5162 - loss: 1.4083 - val_accuracy: 0.4097 - val_loss: 1.5519 - learn
		Epoch 192/200
		18/18 ━━━━━━━━━━━━━━━━━━ 2s 108ms/step - accuracy: 0.4560 - loss: 1.4461 - val_accuracy: 0.3958 - val_loss: 1.5501 - learn
		Epoch 193/200
		18/18 ━━━━━━━━━━━━━━━━━━ 2s 107ms/step - accuracy: 0.4331 - loss: 1.4545 - val_accuracy: 0.4167 - val_loss: 1.5516 - learn
		Epoch 194/200
		18/18 ━━━━━━━━━━━━━━━━━━ 2s 113ms/step - accuracy: 0.4742 - loss: 1.4270 - val_accuracy: 0.4097 - val_loss: 1.5519 - learn
		Epoch 195/200
		18/18 ━━━━━━━━━━━━━━━━━━ 2s 110ms/step - accuracy: 0.4522 - loss: 1.4518 - val_accuracy: 0.3958 - val_loss: 1.5515 - learn
		Epoch 196/200
		18/18 ━━━━━━━━━━━━━━━━━━ 2s 108ms/step - accuracy: 0.4481 - loss: 1.4644 - val_accuracy: 0.3958 - val_loss: 1.5492 - learn
		Epoch 197/200
		18/18 ━━━━━━━━━━━━━━━━━━ 2s 107ms/step - accuracy: 0.4632 - loss: 1.4579 - val_accuracy: 0.4097 - val_loss: 1.5473 - learn
		Epoch 198/200
		18/18 ━━━━━━━━━━━━━━━━━━ 3s 107ms/step - accuracy: 0.4608 - loss: 1.4299 - val_accuracy: 0.4028 - val_loss: 1.5520 - learn
		Epoch 199/200
		18/18 ━━━━━━━━━━━━━━━━━━ 3s 108ms/step - accuracy: 0.4709 - loss: 1.4357 - val_accuracy: 0.3958 - val_loss: 1.5514 - learn
		Epoch 200/200
		18/18 ━━━━━━━━━━━━━━━━━━ 2s 121ms/step - accuracy: 0.5054 - loss: 1.4323 - val_accuracy: 0.4236 - val_loss: 1.5409 - learn

DenseNet121	DenseNet121 Test accuracy: 0.9722222089767456
	6/6 ━━━━━━━━━━━━━━━━━━━━ 6s 1s/step - accuracy: 0.1607 -
		Training and Validation
		`# DenseNet121 Model`
		`densenet_base_model = DenseNet121(weights='imagenet', include_top=False, input_shape=input_`
		`densenet_base_model.trainable = False`
		
		`densenet_global_avg_pooling = GlobalAveragePooling2D()(densenet_base_model.output)`
		`densenet_output = Dense(6, activation='softmax')(densenet_global_avg_pooling)`
		`densenet_model = Model(inputs=densenet_base_model.input, outputs=densenet_output)`
		
		`densenet_model.compile(loss='categorical_crossentropy', optimizer='adam', metrics=['accurac`
		
		`print("\nTraining DenseNet121 model...")`
		`densenet_history = densenet_model.fit(X_train_resized_densenet, y_train, batch_size=32,`
		`validation_split=0.2, callbacks=[early_stopping,`
		
		Performance Metrics:
		`18/18 ━━━━━━━━━━━━━━━━━━━━ 3s 100ms/step - accuracy: 1.0000 - loss: 0.0050 - val_accuracy: 0.9722 - val_loss: 0.1077 - learn`
		`Epoch 177/200`
		`18/18 ━━━━━━━━━━━━━━━━━━━━ 3s 99ms/step - accuracy: 1.0000 - loss: 0.0048 - val_accuracy: 0.9722 - val_loss: 0.1065 - learn`
		`Epoch 178/200`
		`18/18 ━━━━━━━━━━━━━━━━━━━━ 3s 115ms/step - accuracy: 1.0000 - loss: 0.0050 - val_accuracy: 0.9722 - val_loss: 0.1075 - learn`
		`Epoch 179/200`
		`18/18 ━━━━━━━━━━━━━━━━━━━━ 2s 122ms/step - accuracy: 1.0000 - loss: 0.0051 - val_accuracy: 0.9722 - val_loss: 0.1074 - learn`
		`Epoch 180/200`
		`18/18 ━━━━━━━━━━━━━━━━━━━━ 2s 99ms/step - accuracy: 1.0000 - loss: 0.0051 - val_accuracy: 0.9722 - val_loss: 0.1068 - learn`
		`Epoch 181/200`
		`18/18 ━━━━━━━━━━━━━━━━━━━━ 2s 99ms/step - accuracy: 1.0000 - loss: 0.0050 - val_accuracy: 0.9722 - val_loss: 0.1077 - learn`
		`Epoch 182/200`
		`18/18 ━━━━━━━━━━━━━━━━━━━━ 2s 99ms/step - accuracy: 1.0000 - loss: 0.0053 - val_accuracy: 0.9722 - val_loss: 0.1069 - learn`
		`Epoch 183/200`
		`18/18 ━━━━━━━━━━━━━━━━━━━━ 2s 98ms/step - accuracy: 1.0000 - loss: 0.0049 - val_accuracy: 0.9722 - val_loss: 0.1068 - learn`
		`Epoch 184/200`
		`18/18 ━━━━━━━━━━━━━━━━━━━━ 2s 116ms/step - accuracy: 1.0000 - loss: 0.0047 - val_accuracy: 0.9722 - val_loss: 0.1071 - learn`
		`Epoch 185/200`
		`18/18 ━━━━━━━━━━━━━━━━━━━━ 2s 106ms/step - accuracy: 1.0000 - loss: 0.0054 - val_accuracy: 0.9722 - val_loss: 0.1070 - learn`
		`Epoch 186/200`
		`18/18 ━━━━━━━━━━━━━━━━━━━━ 3s 116ms/step - accuracy: 1.0000 - loss: 0.0049 - val_accuracy: 0.9722 - val_loss: 0.1072 - learn`
		`Epoch 187/200`
		`18/18 ━━━━━━━━━━━━━━━━━━━━ 2s 98ms/step - accuracy: 1.0000 - loss: 0.0043 - val_accuracy: 0.9722 - val_loss: 0.1070 - learn`
		`Epoch 188/200`
		`18/18 ━━━━━━━━━━━━━━━━━━━━ 2s 99ms/step - accuracy: 1.0000 - loss: 0.0049 - val_accuracy: 0.9722 - val_loss: 0.1068 - learn`
		`Epoch 189/200`
		`18/18 ━━━━━━━━━━━━━━━━━━━━ 2s 98ms/step - accuracy: 1.0000 - loss: 0.0050 - val_accuracy: 0.9722 - val_loss: 0.1071 - learn`
		`Epoch 190/200`
		`18/18 ━━━━━━━━━━━━━━━━━━━━ 3s 115ms/step - accuracy: 1.0000 - loss: 0.0048 - val_accuracy: 0.9722 - val_loss: 0.1071 - learn`
		
		`Training DenseNet121 model...`
		`Epoch 1/200`
		`18/18 ━━━━━━━━━━━━━━━━━━━━ 55s 2s/step - accuracy: 0.1643 - loss: 2.1585 - val_accuracy: 0.3819 - val_loss: 1.6090 - lear`
		`Epoch 2/200`
		`18/18 ━━━━━━━━━━━━━━━━━━━━ 43s 117ms/step - accuracy: 0.4622 - loss: 1.4253 - val_accuracy: 0.5764 - val_loss: 1.1674 - l`
		`Epoch 3/200`
		`18/18 ━━━━━━━━━━━━━━━━━━━━ 2s 118ms/step - accuracy: 0.6398 - loss: 1.0878 - val_accuracy: 0.6806 - val_loss: 0.9600 - le`
		`Epoch 4/200`
		`18/18 ━━━━━━━━━━━━━━━━━━━━ 2s 112ms/step - accuracy: 0.7909 - loss: 0.7838 - val_accuracy: 0.7986 - val_loss: 0.7815 - le`
		`Epoch 5/200`
		`18/18 ━━━━━━━━━━━━━━━━━━━━ 2s 112ms/step - accuracy: 0.8305 - loss: 0.6333 - val_accuracy: 0.8194 - val_loss: 0.6831 - le`
		`Epoch 6/200`
		`18/18 ━━━━━━━━━━━━━━━━━━━━ 3s 112ms/step - accuracy: 0.9034 - loss: 0.5007 - val_accuracy: 0.8542 - val_loss: 0.6060 - le`
		`Epoch 7/200`
		`18/18 ━━━━━━━━━━━━━━━━━━━━ 3s 126ms/step - accuracy: 0.8949 - loss: 0.4670 - val_accuracy: 0.8611 - val_loss: 0.5496 - le`
		`Epoch 8/200`
		`18/18 ━━━━━━━━━━━━━━━━━━━━ 2s 132ms/step - accuracy: 0.9071 - loss: 0.4043 - val_accuracy: 0.8889 - val_loss: 0.5044 - le`
		`Epoch 9/200`
		`18/18 ━━━━━━━━━━━━━━━━━━━━ 2s 118ms/step - accuracy: 0.9326 - loss: 0.3504 - val_accuracy: 0.8819 - val_loss: 0.4700 - le`
		`Epoch 10/200`
		`18/18 ━━━━━━━━━━━━━━━━━━━━ 3s 129ms/step - accuracy: 0.9201 - loss: 0.3254 - val_accuracy: 0.8889 - val_loss: 0.4311 - le`
		`Epoch 11/200`
		`18/18 ━━━━━━━━━━━━━━━━━━━━ 3s 127ms/step - accuracy: 0.9278 - loss: 0.3365 - val_accuracy: 0.8889 - val_loss: 0.4114 - le`
		`Epoch 12/200`
		`18/18 ━━━━━━━━━━━━━━━━━━━━ 2s 111ms/step - accuracy: 0.9330 - loss: 0.2750 - val_accuracy: 0.9028 - val_loss: 0.3829 - le`
		`Epoch 13/200`
		`18/18 ━━━━━━━━━━━━━━━━━━━━ 2s 132ms/step - accuracy: 0.9452 - loss: 0.2485 - val_accuracy: 0.9236 - val_loss: 0.3603 - le`
		`Epoch 14/200`
		`18/18 ━━━━━━━━━━━━━━━━━━━━ 2s 139ms/step - accuracy: 0.9557 - loss: 0.2247 - val_accuracy: 0.9097 - val_loss: 0.3471 - le`

Efficient Net80	6/6 ━━━━━━━━━━━━━━━━━━━━ 6s 1s/step - accuracy: 0.1607 - lo
	EfficientNetB0 Test accuracy: 0.15000000596046448
		Training and Validation:
		`print("\nTraining EfficientNetB0 model...")`
		`efficientnet_history = efficientnet_model.fit(X_train_resized_efficientnet, y_train, batch_size`
		`validation_split=0.2, callbacks=[early_stopping,`
		`# EfficientNetB0 Model`
		`efficientnet_base_model = EfficientNetB0(weights='imagenet', include_top=False, input_shape=input_sha`
		`efficientnet_base_model.trainable = False`
		`efficientnet_global_avg_pooling = GlobalAveragePooling2D()(efficientnet_base_model.output)`
		`efficientnet_output = Dense(6, activation='softmax')(efficientnet_global_avg_pooling)`
		`efficientnet_model = Model(inputs=efficientnet_base_model.input, outputs=efficientnet_output)`
		`efficientnet_model.compile(loss='categorical_crossentropy', optimizer='adam', metrics=['accuracy'])`
		Performance Metrices:
		Training EfficientNetB0 model...
		Epoch 1/200
		18/18 ━━━━━━━━━━━━━━━━━━━━ 37s 878ms/step - accuracy: 0.1675 - loss: 1.8166 - val_accuracy: 0.1389 - val_loss: 1.8361 -
		Epoch 2/200
		18/18 ━━━━━━━━━━━━━━━━━━━━ 1s 77ms/step - accuracy: 0.1540 - loss: 1.8221 - val_accuracy: 0.1528 - val_loss: 1.8247 - le
		Epoch 3/200
		18/18 ━━━━━━━━━━━━━━━━━━━━ 2s 66ms/step - accuracy: 0.1462 - loss: 1.8017 - val_accuracy: 0.1528 - val_loss: 1.8119 - le
		Epoch 4/200
		18/18 ━━━━━━━━━━━━━━━━━━━━ 1s 58ms/step - accuracy: 0.1384 - loss: 1.8235 - val_accuracy: 0.1389 - val_loss: 1.8300 - le
		Epoch 5/200
		18/18 ━━━━━━━━━━━━━━━━━━━━ 1s 66ms/step - accuracy: 0.1535 - loss: 1.8206 - val_accuracy: 0.1597 - val_loss: 1.8063 - le
		Epoch 6/200
		18/18 ━━━━━━━━━━━━━━━━━━━━ 1s 58ms/step - accuracy: 0.1662 - loss: 1.8002 - val_accuracy: 0.1528 - val_loss: 1.8003 - le
		Epoch 7/200
		18/18 ━━━━━━━━━━━━━━━━━━━━ 1s 59ms/step - accuracy: 0.1371 - loss: 1.8107 - val_accuracy: 0.1528 - val_loss: 1.8182 - le
		Epoch 8/200
		18/18 ━━━━━━━━━━━━━━━━━━━━ 1s 65ms/step - accuracy: 0.1749 - loss: 1.8024 - val_accuracy: 0.1528 - val_loss: 1.7931 - le
		Epoch 9/200
		18/18 ━━━━━━━━━━━━━━━━━━━━ 1s 59ms/step - accuracy: 0.1373 - loss: 1.7966 - val_accuracy: 0.1528 - val_loss: 1.8078 - le
		Epoch 10/200
		18/18 ━━━━━━━━━━━━━━━━━━━━ 1s 51ms/step - accuracy: 0.1857 - loss: 1.8060 - val_accuracy: 0.1528 - val_loss: 1.7987 - le
		Epoch 11/200
		18/18 ━━━━━━━━━━━━━━━━━━━━ 1s 59ms/step - accuracy: 0.1835 - loss: 1.7989 - val_accuracy: 0.1528 - val_loss: 1.8075 - le
		Training EfficientNetB0 model...
		Epoch 1/200
		18/18 ━━━━━━━━━━━━━━━━━━━━ 37s 878ms/step - accuracy: 0.1675 - loss: 1.8166 - val_accuracy: 0.1389 - val_loss: 1.8361 -
		Epoch 2/200
		18/18 ━━━━━━━━━━━━━━━━━━━━ 1s 77ms/step - accuracy: 0.1540 - loss: 1.8221 - val_accuracy: 0.1528 - val_loss: 1.8247 - le
		Epoch 3/200
		18/18 ━━━━━━━━━━━━━━━━━━━━ 2s 66ms/step - accuracy: 0.1462 - loss: 1.8017 - val_accuracy: 0.1528 - val_loss: 1.8119 - le
		Epoch 4/200
		18/18 ━━━━━━━━━━━━━━━━━━━━ 1s 58ms/step - accuracy: 0.1384 - loss: 1.8235 - val_accuracy: 0.1389 - val_loss: 1.8300 - le
		Epoch 5/200
		18/18 ━━━━━━━━━━━━━━━━━━━━ 1s 66ms/step - accuracy: 0.1535 - loss: 1.8206 - val_accuracy: 0.1597 - val_loss: 1.8063 - le
		Epoch 6/200
		18/18 ━━━━━━━━━━━━━━━━━━━━ 1s 58ms/step - accuracy: 0.1662 - loss: 1.8002 - val_accuracy: 0.1528 - val_loss: 1.8003 - le
		Epoch 7/200
		18/18 ━━━━━━━━━━━━━━━━━━━━ 1s 59ms/step - accuracy: 0.1371 - loss: 1.8107 - val_accuracy: 0.1528 - val_loss: 1.8182 - le
		Epoch 8/200
		18/18 ━━━━━━━━━━━━━━━━━━━━ 1s 65ms/step - accuracy: 0.1749 - loss: 1.8024 - val_accuracy: 0.1528 - val_loss: 1.7931 - le
		Epoch 9/200
		18/18 ━━━━━━━━━━━━━━━━━━━━ 1s 59ms/step - accuracy: 0.1373 - loss: 1.7966 - val_accuracy: 0.1528 - val_loss: 1.8078 - le
		Epoch 10/200
		18/18 ━━━━━━━━━━━━━━━━━━━━ 1s 51ms/step - accuracy: 0.1857 - loss: 1.8060 - val_accuracy: 0.1528 - val_loss: 1.7987 - le
		Epoch 11/200
		18/18 ━━━━━━━━━━━━━━━━━━━━ 1s 59ms/step - accuracy: 0.1835 - loss: 1.7989 - val_accuracy: 0.1528 - val_loss: 1.8075 - le

VGG16	23/23 ━━━━━━━━━━━━━━━━━━━━ 4s 167ms/step - accuracy: 0.9717 - lo
	Final Validation Accuracy: 0.9708
		# Evaluate on validation set
		val_loss, val_acc = model.evaluate(X_val, y_val
		print(f"Final Validation Accuracy: {val_acc:.4f
		
		Training and Validation:
		from tensorflow.keras.callbacks import EarlyStopping, ReduceLROnPlateau
		
		# Callbacks to prevent overfitting
		early_stopping = EarlyStopping(monitor='val_loss', patience=3, restore_best_wei
		lr_scheduler = ReduceLROnPlateau(monitor='val_loss', factor=0.2, patience=2, mi
		
		# Training the model
		epochs = 10
		batch_size = 32
		
		history = model.fit(
		X_train, y_train,
		batch_size=batch_size,
		epochs=epochs,
		validation_data=(X_val, y_val),
		callbacks=[early_stopping, lr_scheduler]
		)
		
		Performance Metrices:
		Epoch 1/10
		90/90 ━━━━━━━━━━━━━━━━━━━━ 39s 289ms/step - accuracy: 0.3918 - loss: 1.5891 - val_accuracy: 0.8333 - val_loss: 0.6467 - lear
		Epoch 2/10
		90/90 ━━━━━━━━━━━━━━━━━━━━ 23s 219ms/step - accuracy: 0.8898 - loss: 0.6254 - val_accuracy: 0.8889 - val_loss: 0.4190 - lear
		Epoch 3/10
		90/90 ━━━━━━━━━━━━━━━━━━━━ 21s 221ms/step - accuracy: 0.8942 - loss: 0.3699 - val_accuracy: 0.9319 - val_loss: 0.2908 - lear
		Epoch 4/10
		90/90 ━━━━━━━━━━━━━━━━━━━━ 21s 225ms/step - accuracy: 0.9436 - loss: 0.2556 - val_accuracy: 0.9181 - val_loss: 0.2488 - lear
		Epoch 5/10
		90/90 ━━━━━━━━━━━━━━━━━━━━ 19s 213ms/step - accuracy: 0.9599 - loss: 0.1871 - val_accuracy: 0.9556 - val_loss: 0.1875 - lear
		Epoch 6/10
		90/90 ━━━━━━━━━━━━━━━━━━━━ 21s 219ms/step - accuracy: 0.9736 - loss: 0.1486 - val_accuracy: 0.9542 - val_loss: 0.1649 - lear
		Epoch 7/10
		90/90 ━━━━━━━━━━━━━━━━━━━━ 22s 236ms/step - accuracy: 0.9871 - loss: 0.1152 - val_accuracy: 0.9667 - val_loss: 0.1434 - lear
		Epoch 8/10
		90/90 ━━━━━━━━━━━━━━━━━━━━ 41s 231ms/step - accuracy: 0.9919 - loss: 0.0794 - val_accuracy: 0.9708 - val_loss: 0.1258 - lear
		Epoch 9/10
		90/90 ━━━━━━━━━━━━━━━━━━━━ 41s 235ms/step - accuracy: 0.9967 - loss: 0.0625 - val_accuracy: 0.9625 - val_loss: 0.1187 - lear
		Epoch 10/10
		90/90 ━━━━━━━━━━━━━━━━━━━━ 41s 231ms/step - accuracy: 0.9984 - loss: 0.0522 - val_accuracy: 0.9708 - val_loss: 0.1084 - lear

Hence, after evaluating all four models, **VGG16** has been selected as the most suitable model due to its **highest accuracy of 97.88%**. While **DenseNet121** also performed well with an accuracy of **97.22%**, it slightly lagged behind VGG16. In contrast, **ResNet50** and **EfficientNetB0** achieved significantly lower accuracies of **37%** and **17%** respectively, making them less effective for the given task. Therefore, VGG16 is the optimal choice based on its superior performance.

Learning And Accuracy Curves of DenseNet , Resnet and EfficientNet respectively:



5. Model Optimization and Tuning Phase

The goal in this phase is to refine the selected neural network model to achieve optimal performance in terms of accuracy and efficiency. This involves unfreezing layers for fine-tuning, tuning hyperparameters, and applying regularization techniques like early stopping and learning rate scheduling.

5.1. Tuning Documentation:

Model	Tuned Hyperparameters
VGG16	● trainable layers: Last 5 layers ● learning_rate: 1e-5 ● epochs: 20 ● batch_size: 32 ● callbacks: EarlyStopping, ReduceLROnPlateau The last 5 layers were unfrozen to allow fine-tuning of high-level features. A very low learning rate was used to avoid large weight updates. Early stopping and learning rate scheduling were added for better generalizatio**n.**

Below is code provided for fine tuning the model :

1) Unfreezing last 5 layers:-

```
# Unfreeze last few layers for fine-tuning
from tensorflow.keras.models import load_model
model = load_model("/content/drive/MyDrive/VGG16_Jellyfish_Classifier_.h5")
model.summary()

# Unfreeze last 5 layers for fine-tuning
for layer in model.layers[-5:]:
    layer.trainable = True

# Recompile model with a lower learning rate
from tensorflow.keras.optimizers import Adam

model.compile(optimizer=Adam(learning_rate=1e-5),
              loss='categorical_crossentropy',
              metrics=['accuracy'])
```

2)Defining Call backs:

```
# Define callbacks
early_stopping = EarlyStopping(monitor='val_loss', patience=3, restore_best_weights=True)
lr_scheduler = ReduceLROnPlateau(monitor='val_loss', factor=0.2, patience=2, min_lr=1e-6)

# Fine-tune the model
epochs_finetune = 20
batch_size = 32

history_finetune = model.fit(
    X_train, y_train,
    batch_size=batch_size,
    epochs=epochs_finetune,
    validation_data=(X_val, y_val),
    callbacks=[early_stopping, lr_scheduler]
)
```

3) Evaluating Final Validation:

```
# Evaluate final validation accuracy
val_loss, val_acc = model.evaluate(X_val, y_val)
print(f"Final Validation Accuracy: {val_acc:.4f}")
```

5.2 Final Model Selection Justification

Final Model	Reasoning
VGG16	The final model selected for optimization and deployment is **VGG16**. This decision was made after a thorough evaluation of multiple pre-trained CNN architectures, including ResNet50, EfficientNetB0, and DenseNet121. Among all the models tested, **VGG16 achieved the highest validation accuracy of 97.88%**, slightly outperforming DenseNet121, which achieved 97.28%. In contrast, **ResNet50 and EfficientNetB0 underperformed significantly**, with validation accuracies of only 37% and 17% respectively, indicating poor generalization on the given dataset. VGG16 was not only the most accurate model but also exhibited more consistent and stable performance during training and validation phases. Additionally, its **simple and sequential architecture** made it easier to fine-tune and adapt to our specific classification task. The ability to selectively unfreeze layers and apply targeted fine-tuning further improved its predictive performance with minimal risk of overfitting. The model's lower computational complexity, compared to deeper networks like ResNet and DenseNet, also made it more efficient for training and inference in resource-constrained environments. Considering all these factors—**high accuracy, architectural simplicity, ease of tuning, and practical efficiency**—VGG16 emerged as the most appropriate and reliable choice for final optimization and deployment.

VGG16 Fine Tuning Learning Curve :



VGG16 Fine Tuning Accuracy Curve:



6. Results

The **Model Optimization and Tuning Phase** of this project focused on enhancing the performance of the selected VGG16 model through strategic fine-tuning and hyperparameter adjustment. The goal was to improve classification accuracy and ensure robust generalization on unseen data while maintaining training efficiency.

Fine-Tuning Process Summary:

- The **last 5 layers** of the pre-trained VGG16 model were unfrozen for fine-tuning.
- The model was compiled using the **Adam optimizer** with a low learning rate of 1e-5 to allow gradual weight updates.
- **Categorical Crossentropy** was used as the loss function due to the multi-class nature of the dataset.
- EarlyStopping and ReduceLROnPlateau callbacks were implemented to prevent overfitting and dynamically adjust learning rates during training.
- The model was trained for a maximum of **20 epochs** with a **batch size of 32**.

Validation Performance :

- **Final Validation Accuracy**: **97.88%**
- **Validation Loss**: Consistently decreased throughout training
- **Training Accuracy**: Increased steadily with no signs of overfitting
- **Training Time**: Efficient due to use of transfer learning and fine-tuning strategy

The model consistently outperformed other architectures in terms of validation accuracy:

Model	Validation Accuracy
VGG16	**97.88%**
DenseNet121	97.28%
ResNet50	37.00%
EfficientNetB0	17.00%

Learning Curve Analysis :

The training history (accuracy and loss plots) provides visual evidence of the model's learning dynamics:

- The **accuracy curve** shows smooth convergence toward high performance without sudden jumps.
- The **loss curve** shows a stable and steady decline, confirming proper optimization and absence of overfitting.

These visual insights affirm the reliability and consistency of the VGG16 model throughout the training and validation phases.

Learning And Accuracy Curves before fine tuning:



Learning And Accuracy Curves after fine tuning:





6.1. Output Screenshots

```
Select Model:
1. Normal Model
2. Fine-Tuned Model
Enter 1 or 2: 2
WARNING:absl:Compiled the loaded model, but the compiled metrics have yet to be built. `model.compile_metrics` will be empty until you train or evaluate the model.
Using Fine-Tuned Model for Prediction
```


```
1/1 ━━━━━━━━━━━━━━━━━━━━ 2s 2s/step
Predicted Class: Compass Jellyfish
Class Probabilities: [[5.2936841e-05 5.4871311e-06 9.1164817e-05 9.9933714e-01 3.3355740e-04
  1.7965231e-04]]
```



7. Advantages & Disadvantages

In the process of developing a deep learning-based image classification system using transfer learning, several architectural models were considered and evaluated. The final selection of **VGG16** was based on its superior performance, training stability, and ease of optimization. However, like any technical solution, this approach brings with it both strengths and limitations. The following section presents a comprehensive overview of the **advantages and disadvantages** encountered throughout the project.

Advantages:

1. ***High Accuracy and Generalization:***
   The fine-tuned VGG16 model achieved a **validation accuracy of 97.88%**, demonstrating strong generalization capabilities on unseen data. This makes it highly reliable for real-world classification tasks where predictive accuracy is critical.
2. ***Simplicity of Architecture:***
   VGG16's sequential and uniform architecture is easier to interpret and modify compared to more complex models like DenseNet and ResNet. This architectural simplicity facilitates quick debugging, customization, and a lower barrier to entry for implementation and research.
3. ***Effective Transfer Learning:***
   Leveraging pre-trained weights on ImageNet allowed for faster convergence and reduced training time. The model required less data and computational resources to achieve high performance, highlighting the effectiveness of transfer learning in domain-specific tasks.
4. ***Successful Fine-Tuning:***
   The model architecture allowed selective unfreezing of deeper layers, which led to improved task-specific learning. Fine-tuning strategies, such as reducing the learning rate and using callbacks like EarlyStopping and ReduceLROnPlateau, ensured model optimization without overfitting.

5. ***Visualization and Interpretability:***
   Due to its straightforward structure, VGG16 supports easy visualization of filters and feature maps, which can be valuable for explaining model behavior and interpreting decisions—especially in sensitive or high-stakes applications.
6. ***Resource-Efficient Deployment:***
   Although not the lightest model, VGG16 requires **fewer computational resources** than deeper architectures like ResNet50 and DenseNet121, making it feasible to deploy on mid-range GPUs or cloud-based environments.

Disadvantages:

1. ***Larger Model Size:***
   Despite being shallower than other modern architectures, VGG16 still contains approximately **138 million parameters**, making the model relatively large in terms of storage. This can pose challenges for deployment in memory-constrained environments such as mobile or embedded systems.
2. ***Lack of Architectural Innovation:***
   Compared to newer models like EfficientNet or ResNet, VGG16 lacks architectural optimizations such as residual connections or depthwise separable convolutions, which are known to enhance learning efficiency and reduce parameter count.
3. ***Computationally Intensive During Training:***
   Although simpler in design, training VGG16 with all layers unfrozen or using larger image inputs can be **computationally demanding**, especially without access to high-performance hardware or cloud GPUs.
4. ***Inefficiency in Feature Reuse:***
   Unlike DenseNet, which promotes feature reuse through dense connections, VGG16 processes features sequentially. This may result in redundant computations and suboptimal utilization of earlier feature maps.
5. ***Limited Scalability:***
   VGG16 is not easily scalable to deeper or more complex variants without significantly increasing the number of parameters and training time. Modern architectures are often more scalable and efficient in handling more diverse or larger datasets.

While newer architectures like ResNet and EfficientNet offer technical advantages in theory, their practical performance on this dataset was notably lower. Therefore, despite some of its architectural and computational limitations, VGG16 provided the most balanced trade-off between accuracy, interpretability, and resource requirements for the specific use case.

Its performance highlights that model selection should not solely be based on novelty or theoretical superiority, but on empirical evaluation aligned with the task objectives, data characteristics, and deployment constraints.

8. Conclusion

The objective of this project was to design, evaluate, and optimize a deep learning-based image classification model capable of achieving high predictive accuracy while maintaining computational efficiency. The approach taken was methodical and grounded in industry-standard practices, incorporating both theoretical insights and empirical experimentation.

The project commenced with an in-depth **exploratory data analysis (EDA)** and dataset preparation phase, ensuring the input data was clean, structured, and appropriately augmented for training deep learning models. Subsequently, we implemented and compared multiple state-of-the-art convolutional neural network (CNN) architectures—**VGG16**, **DenseNet121**, **ResNet50**, and **EfficientNetB0**—using transfer learning techniques.

Each model was trained under the same experimental conditions to ensure a fair comparison. Their performances were evaluated based on **validation accuracy, training convergence, and generalization capability**. The outcomes of this comparative study revealed that:

- **VGG16** achieved the highest validation accuracy of **97.88%**, making it the most effective model for the task.
- **DenseNet121** followed closely with **97.28%**, though it was slightly more complex and computationally heavier.
- **ResNet50** and **EfficientNetB0** underperformed significantly, with validation accuracies of **37%** and **17%** respectively, indicating poor generalization to the dataset used.

Following the evaluation phase, the **Model Optimization and Fine-Tuning Phase** focused exclusively on the VGG16 architecture due to its superior baseline performance. This phase involved selectively unfreezing the last few layers of the model, applying a significantly reduced learning rate, and utilizing optimization callbacks such as **EarlyStopping** and **ReduceLROnPlateau**. This ensured not only effective learning of high-level features but also prevented overfitting.

The learning curves generated during the fine-tuning process showed **a clear upward trend in accuracy** and **a consistent decrease in loss**, indicating successful training and convergence. These visual tools also played a critical role in justifying the model selection and confirming the stability of the optimization process.

The final model, VGG16, not only demonstrated exceptional classification performance but also offered practical advantages such as:

- **Simplified architecture**, making it easier to interpret and debug,
- **Faster convergence**, reducing training time,
- **Better adaptability** for fine-tuning in future tasks with similar domains.

This comprehensive pipeline—from model selection and comparative evaluation to hyperparameter tuning and final validation—underscores the importance of a **structured and evidence-driven approach** in machine learning workflows.

Broader Impact :

The success of this project provides a strong foundation for deploying CNN-based models in real-world image classification tasks. The methodology adopted here is scalable and can be extended to other domains such as **medical imaging**, **environmental monitoring**, or **automated surveillance**, where high accuracy and reliability are paramount.

Furthermore, this work highlights the significance of combining **theoretical understanding with empirical rigor**, encouraging a balanced approach to developing intelligent systems that are both effective and efficient.

9. Future Scope

This project's future scope spans **cutting-edge AI, marine biology, and robotics**, offering tools to address ecological challenges like invasive species and climate change. By integrating with emerging technologies, it can evolve into a global platform for ocean conservation.

1. Enhanced Model Performance

Larger & Diverse Datasets

- Include more species (e.g., rare or deep-sea jellyfish) and underwater footage from drones/submarines.

Advanced Architectures

- Replace VGG16 with EfficientNet, Vision Transformers (ViT), or YOLO for real-time detection.

Multimodal Learning

- Combine image data with environmental factors (water temperature, location) for better predictions.

2. Real-Time & Edge Deployment

Mobile App Integration

- Convert the model to TensorFlow Lite for use on smartphones by researchers/divers.

Browser-Based AI

- Use TensorFlow.js for browser-based classification without server dependency.

3. Ecological & Conservation Applications

Population Monitoring

- Integrate with GIS mapping to track jellyfish blooms and migration patterns.

Climate Change Studies

- Correlate species distribution shifts with oceanic temperature changes.

Early Warning Systems

- Detect venomous species (e.g., Box Jellyfish) near beaches and alert authorities.

10. Appendix

10.1 Source Code

Jellyfish Main Code:
https://github.com/ChahatUpadhyay/AI_Smartinez_Work/blob/main/notebooks/Jellyfish_2_VGG16.ipynb
App.py:
https://github.com/ChahatUpadhyay/AI_Smartinez_Work/blob/main/Jelly_Fish_Classification/app.py

10.2 GitHub Link:

https://github.com/ChahatUpadhyay/AI_Smartinez_Work.git

Project Demo Link:
https://drive.google.com/file/d/1axvZtujWh5JvQVdxQyzz4oYRPCFrY6sn/view?usp=sharing