

SF BELIDA Chaina

Formation : BTS Services Informatiques aux Organisations Option SLAM

Année : 2026

Établissement : Paris Ynov Campus

Encadrant : Madame EL KHADAR

1. Présentation

Symfony est un **framework PHP** moderne et puissant utilisé pour créer des applications web professionnelles. Il repose sur une architecture, offre de nombreux **composants réutilisables**, une **sécurité avancée**, et une **grande flexibilité**.

Grâce à sa stabilité et sa communauté active, Symfony est largement utilisé dans les projets d'entreprise.

1.1 Créer le projet

```
composer create-project symfony/skeleton nom_du_projet
```

→ Télécharge et configure le projet automatiquement.

```

C:\Users\chain>composer create-project symfony/skeleton sf-slam1
Creating a "symfony/skeleton" project at "./sf-slam1"
Installing symfony/skeleton (v8.0.99)
  - Downloading symfony/skeleton (v8.0.99)
  - Installing symfony/skeleton (v8.0.99): Extracting archive
Created project in C:\Users\chain\sf-slam1
Loading composer repositories with package information
Updating dependencies
Lock file operations: 1 install, 0 updates, 0 removals
  - Locking symfony/flex (v2.10.0)
Writing lock file
Installing dependencies from lock file (including require-dev)
Package operations: 1 install, 0 updates, 0 removals
  - Downloading symfony/flex (v2.10.0)
  - Installing symfony/flex (v2.10.0): Extracting archive
Generating autoload files
1 package you are using is looking for funding.
Use the `composer fund` command to find out more!

Run composer recipes at any time to see the status of your Symfony recipes.

Loading composer repositories with package information
Restricting packages listed in "symfony/symfony" to "8.0.*"
Updating dependencies
Lock file operations: 30 installs, 0 updates, 0 removals
  - Locking psr/cache (3.0.0)
  - Locking psr/container (2.0.2)
  - Locking psr/event-dispatcher (1.0.0)
  - Locking psr/log (3.0.2)
  - Locking symfony/cache (v8.0.10)

```

```

Use the `composer fund` command to find out more!

Symfony operations: 4 recipes (bbedf4b77e7e21d359db99ef452ea697)
  - Configuring symfony/flex (>=2.4): From github.com/symfony/recipes:main
  - Configuring symfony/framework-bundle (>=7.4): From github.com/symfony/recipes:main
  - Configuring symfony/console (>=5.3): From github.com/symfony/recipes:main
  - Configuring symfony/routing (>=7.4): From github.com/symfony/recipes:main
Executing script cache:clear [OK]
Executing script assets:install public [OK]

What's next?

Some files have been created and/or updated to configure your new packages.
Please review, edit and commit them: these files are yours.

symfony/framework-bundle instructions:

* Run your application:
  1. Go to the project directory
  2. Create your code repository with the git init command
  3. Download the Symfony CLI at https://symfony.com/download to install a development web server

* Read the documentation at https://symfony.com/doc

No security vulnerability advisories found.

No security vulnerability advisories found.

C:\Users\chain>

```

1.2 Se placer dans le dossier du projet

```
cd nom_du_projet
```

```
C:\Users\chain>cd sf-slam1  
C:\Users\chain\sf-slam1>|
```

2. Installer le pack webapp

Le squelette de base est très léger. Pour une application web complète (Twig, Doctrine, formulaires...), on installe le pack **webapp**.

Après installation, de nouveaux dossiers peuvent apparaître, par exemple :

- `assets/`
- `migrations/`
- `templates/`
- `tests/`
- `translations/`

2.1 Installation complète

```
composer require webapp
```

→ Ajoute les modules essentiels au développement web.

```
C:\Users\chain>cd sf-slam1
```

```
C:\Users\chain\sf-slam1>composer require webapp
```

```
./composer.json has been updated
```

```
Running composer update symfony/webapp-pack
```

```
Loading composer repositories with package information
```

```
Restricting packages listed in "symfony/symfony" to "8.0.*"
```

```
Updating dependencies
```

```
Lock file operations: 102 installs, 0 updates, 0 removals
```

- Locking composer/semver (3.4.4)
- Locking doctrine/collections (2.6.0)
- Locking doctrine/dbal (4.4.3)
- Locking doctrine/deprecations (1.1.6)
- Locking doctrine/doctrine-bundle (3.2.2)
- Locking doctrine/doctrine-migrations-bundle (4.0.0)
- Locking doctrine/event-manager (2.1.1)
- Locking doctrine/inflector (2.1.0)
- Locking doctrine/instantiator (2.1.0)
- Locking doctrine/lexer (3.0.1)
- Locking doctrine/migrations (3.9.7)
- Locking doctrine/orm (3.6.5)
- Locking doctrine/persistence (4.2.0)
- Locking doctrine/sql-formatter (1.5.4)
- Locking egulias/email-validator (4.0.4)
- Locking monolog/monolog (3.10.0)
- Locking myclabs/deep-copy (1.13.4)
- Locking nikic/php-parser (v5.7.0)
- Locking phar-io/manifest (2.0.4)

```

* To send messages to a transport and handle them asynchronously:

1. Update the MESSENGER_TRANSPORT_DSN env var in .env if needed
   and framework.messenger.transports.async in config/packages/messenger.yaml;
2. (if using Doctrine) Generate a Doctrine migration bin/console doctrine:migration:diff
   and execute it bin/console doctrine:migration:migrate
3. Route your message classes to the async transport in config/packages/messenger.yaml.

* Read the documentation at https://symfony.com/doc/current/messenger.html

symfony/mailer instructions:

* You're ready to send emails.

* If you want to send emails via a supported email provider, install
  the corresponding bridge.
  For instance, composer require mailgun-mailer for Mailgun.

* If you want to send emails asynchronously:

1. Install the messenger component by running composer require messenger;
2. Add 'Symfony\Component\Mailer\Messenger\SendEmailMessage': amqp to the
   config/packages/messenger.yaml file under framework.messenger.routing
   and replace amqp with your transport name of choice.

* Read the documentation at https://symfony.com/doc/master/mailer.html

No security vulnerability advisories found.
C:\Users\chain\sف-slam1>

```

3. (Optionnel) Initialiser Git

Bonne pratique : versionner le projet dès le début avec Git.

Le fichier `.gitignore` est déjà pré-configuré par Symfony.

3.1 Initialiser le dépôt

```
git init
```

```

C:\Users\chain\sف-slam1>git init
Initialized empty Git repository in C:/Users/chain/sف-slam1/.git/

```

→ Le fichier `.gitignore` est déjà configuré par Symfony.

4. Lancer le serveur de développement

PHP intègre un serveur web léger, parfait pour tester en local.

- Cette commande démarre le serveur sur le port **8000**.
- Le dossier `public/` est la **racine web** du projet.

```
C:\Users\chain\sف-slam1>git init
Initialized empty Git repository in C:/Users/chain/sف-slam1/.git/

C:\Users\chain\sف-slam1>php -S 127.0.0.1:8000 -t public
[Mon May 18 19:23:13 2026] PHP 8.5.3 Development Server (http://127.0.0.1:8000) started
```

4.1 Démarrer le serveur

```
php -S 127.0.0.1:8000 -t public
```

