CHAPTER 1

INTRODUCTION

1. INTRODUCTION

Scene text is the text that appears in an image captured by a camera in an outdoor environment. Scene-text detection in natural-scene images is an important technique because scene texts contain location information like names of places and buildings, but many difficulties still remain regarding practical use. Text embedded in natural scene images provide rich semantic information about the scene, which is of great value for content-based image. The goal of scene text extraction is to identify and isolate text element in a picture. Indexing and retrieval applications Text characters embedded in images and video sequences represents a variety of rich source of information. Text information in scene image servings as important clue for many computer vision applications. Text component in an image is of particular interest, as it is easy to understand by both humans as well as machines.

It is a procedure that checks for text existing in natural images, and if present, then to locate each instance of a text. The text in images provides rich and precise high-level semantic information; therefore, it becomes vital for many possible applications like scene understanding, image and video retrieval, and content-based recommendation systems. As a result, the text detection of natural scenes has widely attracted consideration in the Computer Vision and Image Understanding Community. However, the detection and recognition of scene text in natural images with unconstrained environments remains a challenging problem in computer vision. First, a text image background is very complex, and some region components like signs, bricks, and grass are hard to distinguish from text. Secondly, scene text can be diversified and usually exits in different colors, fonts, orientations, languages, and scales in natural images. Furthermore, there exist strongly confusing factors, such as non-uniform illumination, strong exposure, low contrast, blurring, low resolution, and conclusion, which bring hard challenges for the text detection task. The ability to robustly read text in unconstrained scenes can significantly help with numerous real-world applications.

Detecting text regions amidst diverse backgrounds involves deploying advanced algorithms and deep learning models capable of distinguishing text from non-text elements in images characterized by varied colors, patterns, and clutter. This ensures accurate identification even in complex scenes. Handling variations in appearance such as fonts, sizes, and orientations requires robust algorithms that can adapt to diverse scenarios, ensuring reliable text recognition across different contexts. Overcoming occlusions and distortions involves developing algorithms that can interpret text even when partially obscured or affected by perspective changes,

ensuring precise extraction of textual information from natural scene images. Achieving real-time processing involves optimizing computational resources for swift detection and interpretation of text in dynamic environments, enhancing applications like augmented reality and autonomous driving. Seamless integration with downstream applications involves feeding recognized text into processes such as translation and document analysis, thereby enhancing user interaction and operational efficiency in real-world contexts.

Text detection, as a prerequisite of the subsequent processes, plays a critical role in the whole procedure of textual information extraction and understanding. The text recognition techniques have been through wide research, with propositional effective methods that provide the demanded accuracy. Text detection approaches can be divided into two main categories (a) sliding window-based approaches (b) connected components-based approaches. There are three main methods used in text detection: color-based method, ntexture-based method and stroke-based method. Previous text detection approaches have already obtained promising performances on various benchmarks in this field.

The most successful of these is the Optical-Character-Recognition method for recognizing printed text in scanned documents. Optical Character Recognition is a significant area of research in artificial intelligence, computer vision, pattern recognition, and machine learning. It was also one of the earliest fields of artificial technology research and has emerged as a mature technology. It began back in 1913 when Dr. Edmund Fournier d'Albe invented the Optophone to scan and convert text into sound for visually impaired people. Since then, this technology has experienced multiple developmental phases.

In the 1990s, the technology became prominent with the digitization of historical newspapers. In addition, the emergence of smartphones and electronic documents also lead to further advancements in Optical Character Recognition(OCR) technology. It is still, however, hard for computers to detect and recognize the so-called scene text, which is text in natural-scene images, because in scene text, many interference factors exist in appearance. Optical Character Recognition remains a challenging problem when text occurs in unconstrained environments, like natural scenes, due to geometrical distortions, complex backgrounds, and diverse fonts.

The technology still holds an immense potential due to the various use-cases of deep learning-based OCR like building license plate readers, digitizing invoices, digitizing menus, digitizing ID cards. For almost two decades, optical character

recognition systems have been widely used to provide automated text entry into computerized systems.

Connected component-based methods extract character candidates from images by connected component analysis accompanied by assembling character hopefuls into content; extra checks may be led to expel false positives. Extraction is performed using stroke width transform (SWT) approach and connected component analysis. The Pytesseract package provides all the tools required for the extraction of text from image.

OCR (Optical Character Recognition) is a technology that enables the conversion of scanned images or handwritten documents into editable and searchable data. It automates the process of recognizing printed or handwritten text characters within digital images or documents, making them machine-readable. OCR systems utilize pattern recognition algorithms to analyse the shapes and structures of characters, enabling accurate extraction and interpretation of textual information. This technology is essential in various applications such as document digitization, automated data entry, and accessibility tools for converting text from physical forms into digital formats efficiently.

The text detection project is done using an OpenCV file for image processing and PyTesseractfor detecting text and many other things. So, we are going to detect images and convert into textual data that is inputted into a new file.

CHAPTER 2

SCOPE OF THE STUDY

2. SCOPE

The text recognition problem in natural images is extensive. This report is only concerned with recognizing text in horizontal and multi-oriented natural images. The scope of text detection and recognition in natural scene images using OCR and PyTesseract is extensive and justified by its potential to address real-world challenges and applications. Natural scene images present diverse complexities, including varied lighting conditions, diverse font styles, and complex backgrounds, making the need for robust text detection and recognition methodologies critical.

- **Varied Lighting Conditions**

Natural scenes are often captured in different lighting environments, from bright sunlight to dimly lit areas. These variations can significantly affect the visibility and clarity of text in images. Robust text detection and recognition methodologies must be able to preprocess and normalize these images to maintain consistent performance. Techniques such as contrast adjustment, histogram equalization, and shadow removal are essential to tackle these lighting variations.

- **Diverse Font Styles and Sizes**

Unlike printed documents, text in natural scenes can appear in numerous fonts, sizes, and orientations. This diversity poses a challenge for text recognition systems as they must generalize well across a wide range of textual representations. OCR systems, particularly those using machine learning and deep learning, must be trained on extensive datasets that include varied fonts and sizes to accurately detect and recognize text regardless of its appearance.

- **Complex Backgrounds**

Natural scenes often contain backgrounds with textures, colors, and objects that can obscure or interfere with text. Detecting text in such environments requires advanced techniques to isolate text from the background. Methods like edge detection, connected components analysis, and region-based segmentation are crucial in differentiating text from complex backgrounds. Furthermore, deep learning models can be trained to learn features that distinguish text from noise, enhancing detection accuracy.

- **Real-World Applications**

The practical applications of text detection and recognition in natural scenes are vast. In smart cities, these technologies can improve transportation systems through

automatic traffic sign recognition and license plate reading, enhancing both navigation and law enforcement. In retail, recognizing storefront signs and advertisements can enable location-based services and targeted marketing. For visually impaired individuals, assistive technologies can use text recognition to read out signs and labels, significantly improving their interaction with the environment.

- **Integration with PyTesseract**

Using PyTesseract, an OCR tool that integrates well with Python, provides a flexible and powerful solution for recognizing text in natural scenes. PyTesseract leverages Tesseract's capabilities while allowing for extensive preprocessing and post-processing of images using Python's robust libraries, such as OpenCV. This combination allows for the development of highly customized and effective text recognition systems.

CHAPTER 3

METHODOLOGY

3. METHODOLOGY

3.1 STD (Scene text detection):

Scene text detection is to locate text in complex scene images.

Examples of STD include text detection in various contexts, such as books, ID cards, tickets, intelligent traffic scenarios, such as road signs, license plate recognition, etc.



Figure 1. Scene text detection process

Figure 1 gives a formal overview of the text detection process. We have summarized a unified three-stage framework that most existing models fit into.

<u>The three stages as follows:</u>

Visualization of an example flow of scene text detection.

- **<u>Transformation</u>:** In this stage, the input image is transformed into a new one using a spatial transformation network framework, while any text contained in it is rectified. The rectification process facilitated subsequent stages. It is powered by a flexible thin-plate spline (TPS) transformation, which can handle a variety of text irregularities and diverse aspect ratios of text lines.
- **<u>Feature Extraction:</u>** This stage maps the input image to a representation that focuses on the attributes relevant for character features, such as font, color, size, and background. With convolutional networks entering a phase of rapid development after AlexNet's success at the 2012 ImageNet competition, Visual Geometry Group Network (VGGNet), GoogleNet ,RestNet and DetNetare are often used as a feature extractor.
- **<u>Prediction:</u>** Predicts the position of the text in the image, usually expressed as a coordinate point.Text detection in natural scene images is much more difficult than text detection in scanned document images because of the diversity of the

forms the text may occur in. The main features of the scene text are summarized below:

-Multiple languages may be mixed.

-Characters may occur in different sizes, fonts, colors, brightness, contrast, etc.

-Text lines may be horizontal, vertical, curved, rotated, twisted, or in other patterns.

-The text area in the image may also be distorted (perspective, affine transformation), suffer defects, blurring, or other phenomena.

-The background of scene images is extremely diverse, and text may appear on a plane, surface, or folded surface; the text region may be near complex interference textures, or non-text areas may have textures that approximate text, such as sand, grass, fences, brick walls, etc.

3.2 Optical Character Recognition:

OCR (Optical Character Recognition) in other words, OCR systems transform a two-dimensional image of text, that could contain machine printed or handwritten text from its image representation into machine-readable text. Optical Character Recognition is the solution that is flexible and recognizes printed characters from scanned documents/ image or photograph.



Figure 2. Image to text conversion using OCR

Advanced OCR software also supports handwritten text recognition. OCR as a process generally consists of several sub-processes to perform as accurately as possible. The subprocesses are:

- Preprocessing of the Image
- Text Localization
- Character Segmentation
- Character Recognition
- Post Processing

Basically, it is how a document/image is scanned using Optical Character Recognition software and has its character of various fonts and sizes recognized. More importantly, it involves recognized characters being further converted into machine-encoded texts that are capable of being edited or saved in files of any desirable format.

3.3 Tesseract OCR:

Tesseract is an open-source OCR engine, available under the Apache 2.0 license. It supports a wide variety of languages. It can be used directly or, for programmers, using an API to extract printed text from images. It doesn't have a built-in GUI, but there are several available from the 3rdParty page. Wrappers for many languages and frameworks are available at GitHub, and thus, Tesseract can be used. Tesseract can be used either together with the existing analysis of layout to recognize text within a large document or in conjunction with an external text detector for recognizing text from an image of a single text line.



Figure 3. OCR Process Flow

Tesseract 4.00 introduces a new neural network subsystem that is configured as a text line recognizer. This new system has its origin in the OCRopus LSTM-based implementation in Python but was redesigned for Tesseract in C++. Actually, the neural network subsystem of Tesseract pre-dates TensorFlow and, similarly, has been engineered to be compatible with it. This is because there exists a network description language called Variable Graph Specification Language, VGSL, also available for use under TensorFlow. To recognize an image containing a single character, we typically use a Convolutional Neural Network (CNN). Text of arbitrary length is a sequence of characters, and such problems are solved using RNNs (Recurrent Neural Network) and LSTM (Long Short-term Memory) is a popular form of RNN

3.3.1 Installing Tesseract OCR:

Installing tesseract on Windows is easy with the precompiled binaries. Do not forget to edit "path" environment variable and add tesseract path. For Linux or Mac installation it is installed with few commands.

After the installation verify that everything is working by typing command in the terminal or cmd:

$ tesseract --version

You can install the python wrapper for tesseract after this using pip.
$ pip install PyTesseract

The Tesseract library comes with a useful salary-command-line-driven tool called tesseract. We leverage this utility to carry out OCR on images. The result, finally, will be stored in a text file. We are able to integrate Tesseract into our C++ or Python code if we want to; for this, we are going to use Tesseract's API.

3.3.2 PyTesseract:

PyTesseract is one of the most used OCR libraries for Python applications. The simplest application of it is in extracting text from images, documents, and such other sources of information to make it accessible and usable for many text analytics and data processing purposes. It is a powerful tool because PyTesseract is a Python package for optical character recognition that is very good at turning images of printed or handwritten text into machine-readable text data. The different formats

in which it processes images are for extracting text from them. It supports most image types, like scanned documents, photographs, and screenshots.

Features & capabilities	**Description**
Text Extraction	Extracts text from image including scanned documents, photographs, and screenshots.
Cross-Platform Compatibility	Works seamlessly on Windows, macOS, and Linux systems
Python Integration	Easily integrated into python application for streamlined text extraction and data analysis
Multilingual Support	Supports recognition of text in multiple languages and scripts.
Active Community	Benefits from regular updates, bug fixes, and improvements due to an engaged open-source developer community

Table 1: Features of PyTesseract

3.3.3 Working of PyTesseract:

When you feed PyTesseract with an image containing text, it first rigorously analyzes the image to understand exactly how it is structured and laid out in terms of the text. After that, it detects the single words and even characters—noting which are in different fonts or styles. Finally, PyTesseract transforms the identified text into a format that can easily be read and processed by your Python program. It can modify the contrast of the image, reduce any noise, and make the text more readable. In other words, PyTesseract separates the text from all irrelevant parts of the picture, focusing only on the words and sentences you are trying to extract. Subsequently, after doing this processing, PyTesseract generates the recognized text as simple output, which you can leverage toward in-built data analysis, language processing, or any other operation of your choice.



Figure 4. Tesseract flow

CHAPTER 4

ANALYSIS AND INTERPRETATION

4. ANALYSIS AND INTERPRETATION

4.1 Image Preprocessing:

Preprocessing acts as a step that may be used to enhance the quality of an input image. This step is necessary for removal or reduction of various types of ambiguities and noises that may appear during the process of scanning/clicking of an image and paper conditions in such a way that the image is precisely and effectively processable by the OCR. A noisy image is more prone to be misread by an OCR model.

- **Noise removal:**

Image analysis systems benefit from the reduction of noise in the preprocessing stage this can provide a substantial improvement in the reliability and robustness of the feature extraction and recognition stages of the OCR system. A common manifestation of noise in binary images takes the form of isolated pixels, salt-and-pepper noise or speckle noise, thus; the processing of removing this type of noise is called filling.

In grey- level images or median filters and low-pass filters such as average or Gaussian blur filters proved to eliminate isolated pixel noise. In grey-level images or median filters and low-pass filters such as average or Gaussian blur filters proved to eliminate isolated pixel noise.

The order in which we have implemented the various steps involved in the preprocessing tool are outlined in the above diagram and a brief description of the methods is given below.



Figure 5. Architectural design

4.2 Resizing:

In this step, the input image is resized so as to increase its resolution. Its done in order to give a constant display of dimension throughout the process so that different dimension of images can be displayed at one dimension.

4.3 Unsharp Masking:

In mask processing, a pixel value is computed from the pixel value in the original image and the values of pixels in its vicinity; it forms a more expensive operation compared to simple point processing but is more powerful. Application of a mask to an input image of certain dimensions produces an output image of the same size as the input. This step aims to enhance text details and edges by using an unsharp masking filter. Sharpness describes the clarity of detail in a photo (document text in our case) and can be a valuable tool for emphasizing texture . This method is used to sharpen the blurry edge of the characters present in the image.

Here, we can control the blend between the filter and the threshold. The parameters used in this method are described below

- Radius: defines the size of the area to sample.
- Sigma: defines the standard deviation.
- Amount: controls the sharpening ability of the filter.
- if amount > 1, more sharpening filter is used.
- if amount < 1, less sharpening filter is used.



Figure 6. Sample images from the dataset

- Thresholding: if thresholding is greater than 0, it reduces the sharpening quality

The value of the amount parameter plays an important role in sharpening the image but we should not take a very large value of the amount (i.e., more sharpening) since it will result in unwanted noise in the image which can adversely affect the accuracy of the Tesseract model.

4.4 Level:

Level method is used to enhance the color of an image by controlling the black and white boundaries of an image. We define the following parameters to set the level. 1. Level range gives two values white points and black points. So, for example, if white = 0.2 and black = 0.8 then we will have a level range [.2, .8]. Now, colors darker than the black point i.e., greater than 0.8 are set to 0 and colors brighter than the white point i.e., less than 0.2 are set to the maximum value. 2. Gamma (γ) is used to change the intensity of an image. A pixel is modified as pixel(1/γ). Higher the γ value (more than 1), lower the intensity of the resulting pixel.

4.5 Color Conversion:

Here, conversion of colored images into RGB is done by the OCR. The localization of text using RGB background is favorable to some software applications in recognizing textual character present in an image. The conversion is done from BGR (Blue Green Red) into RGB (Red Green Blue).



Figure 7. Conversion from BGR to RGB

4.6 Adaptive Thresholding:

As the name suggests, it adapts the threshold value for each pixel based on their neighborhood. The area of the neighboring pixels is defined by passing width and height arguments and an offset argument is used to apply a +/− value to the current pixel. The method has following parameters.

- Width gives the width of surrounding pixels.

- Height gives the height of surrounding pixels.
- Offset is used to change the current value of the pixels that can be added or subtracted from the current pixel.

4.7 Character Segmentation:

Character segmentation is considered as one of the main steps in pre-processing, especially in cursive scripts such as Arabic, Urdu and other scripts where characters are connected together. Therefore, many techniques have been developed for character segmentation, most of which are script-specific and thus cannot work with other scripts. Character segmentation is even required in printed handwritten documents due to the touching of characters when written by hand. For example, printed Latin characters can be easily segmented using both horizontal and vertical histogram profiles; however, smaller fonts and those containing serifs may be troublemakers to joining, which will need further processing to solve the touching problem.

4.8 Image size normalization:

As a result of the character segmentation stage, isolated characters are ready to be passed into the feature extraction stage; therefore, the isolated characters have to be normalized into a specific size that can be decided empirically or experimentally depending on the exact application and the feature extraction or the classification techniques used. Then features are extracted from all the characters with the same size in order to provide data uniformity.

4.9 Thinning and Skeletonization:

Skeletonization is a method used to thin out binary image foreground regions to a skeletal remnant that largely preserves the extent and connectivity of the original region but allows most of the original foreground pixels to be removed. It is easy to see that the skeleton can be defined as the loci of centres of bi-tangent circles which lie entirely within the foreground region under consideration, and can be explained with the use of the rectangular shape in figure



Figure 8. Skeletonization Method

The two fundamental techniques to generate the skeleton of an object are basic thinning and medial axis transforms. Thinning is a morphological operation that is used to remove selected foreground pixels from binary images, somewhat like erosion or opening. Thinning is an erosive data reduction process that will reduce an object until it is one pixel wide, returning a skeleton of the object. This enables easy recognition of features, such as characters.



Figure 9. Text Detection Process Involved In Skeletonization Method

The medial axis transform is similar to measuring the Euclidean distance of any pixel in an object to the edge of the object; hence, it constitutes every point within an object that happens to be equidistant to more than one edge of an object.(Russ, 2007)

4.10 Character Recognition:

PyTesseract segments the image first into text lines and later into single characters using methods such as adaptive thresholding and connected component analysis.

Character identification is done by models trained using Tesseract with feature extraction and pattern matching. Newer models like the Long Short-Term Memory network are used for better precision. This output is further fine-tuned by some post-processing to correct any errors and ensure coherent and readable text.

- **Pattern Recognition:**

  Pattern recognition is an important step in OCR. It occurs when the OCR software has been "trained" on examples of text in different fonts and formats. Imagine the OCR program being shown all the possible fonts—serif, sans-serif, hand-painted, bold, italic, and so on. Character recognition is then learned by comparing what it sees in the scanned document or image against such templates. Each of these different combinations of shape, scale, and font is called a glyph. A glyph represents some character, say 'A', 'b', or '7', in some style. As the OCR system encounters characters within the image scanned, it gets compared to the system's internal database of glyphs. One desires maximum match.

- **Getting boxes around text**:

  The PyTesseract library provides a convenient function in plotting the recognizing text /characters in an image. It returns detailed information about the detected text, including bounding box coordinates. The (x, y, w, h) values represent the top-left corner coordinates and the width and height of each bounding box.

By utilize statistical regions to merge to cut apart with remove be scarcely text the zone and based on as the standard of high similarity, color similarity, region distance and the horizontal alignment of giving a definition to group areas, thereby come pretreatment image:

High similarity is defined

$$\frac{\max(HEIGHT_1, HEIGHT_2)}{\min(HEIGHT_1, HEIGHT_2)} < T_{height_sim},$$

As HEIGHT wherein $_1$ And HEIGHT $_2$It is the height in two zones;

Color similarity is defined as

$$D(c_1, c_2) = \sqrt{\left(\overset{\‾}{R_1} - \overset{\‾}{R_2}\right)^2 + \left(\overset{\‾}{G_1} - \overset{\‾}{G_2}\right)^2 + \left(\overset{\‾}{B_1} - \overset{\‾}{B_2}\right)^2} < T_{coloc},$$

Wherein

$$\mathbf{c}_1 = \left[\overline{R_1} \quad \overline{G_1} \quad \overline{B_1}\right]$$

With

$$\mathbf{c}_2 = \left[\overline{R_2} \quad \overline{G_2} \quad \overline{B_2}\right]$$

It is the average color in two zones;

Region distance is defined as $D_{Region} < T_{Region}$,

D where in $_{Region}$ Be the horizontal range in two zones, and

Horizontal alignment is defined as $D_{Top} < T_{Align}$Perhaps $D_{Bottom} < T_{Align}$, D wherein $_{Top}$And D_{Bottom}It is the vertical range between coboundary and the lower boundary;

Carry out characteristic extraction procedure to describe each remaining area, wherein each feature is by this regional stroke feature, edge feature and fill factor, curve factor character representation; And

Figure 10. Input Image



Figure 11. Detected Image

4.11 File writing:

The recognized character which are represented as plain output during the process of text detection is transferred to a separate file indicating the output that is shown by the PyTesseract. This process in Python involves a sequence of actions to ensure data is correctly written to a file. Python provides inbuilt functions for creating, writing and reading files. There are two types of files that can be handled in python, normal text files and binary files (written in binary language, 0s and 1s). The file should exist in the same directory as the python program file, else the full address of the file should be written in place of filename.

4.11.1 Steps involved

- **Opening the File**:
  The process starts by opening a file using the build-in-function of Python, which requires specifying the file name and the mode (such as write, append, or exclusive creation).
  - 'w': Write mode (overwrites the file if it exists)
  - 'a': Append mode (writes to the end of the file)
  - 'x': Exclusive creation (fails if the file already exists)
  - 'b': Binary mode (for non-text files)
  - 't': Text mode (default mode)

  This step prepares the file for writing operations

- **Writing Data**:

  Once the file is opened, data obtained from the text detection process can be written into the specified file path. This stage transfers the data from the program to the file. This stored data can help for referencing the accuracy.

- **Closing the File**:
  After writing, the file must be closed. Closing the file ensures that all data is properly saved and that system resources are released. It finalizes the writing process.

- **Context Management:**
  For better resource management and to avoid potential issues with forgetting to close files, a context manager can be used. This automatically handles the opening and closing of the file, providing a cleaner and more reliable way to manage file operations.

CHAPTER 5

OBJECTIVES OF THE STUDY

5. OBJECTIVES OF THE STUDY

5.1 To detect the text in natural scene image:

Basically, it aims at accurately locating and segmenting a text region against complex backgrounds. A fundamental challenge includes dealing with several variations in the appearance of the text, lighting conditions, and geometric distortions. Robust algorithms—mostly inspired by deep learning—will ensure real-time processing and low false detections for applications such as augmented reality, automatic sign translation, and scene understanding that enable enhanced interaction with visual environments.

5.2 To recognize the text in scene image:

Intrinsic text in natural scene images is recognized by detecting the text regions and identifying them against cluttered and highly diversified backgrounds. State-of-the-art computer vision techniques and deep learning models are used to handle font changes, sizes, orientations, and lighting variations. Correct recognition of text gives rise to applications like augmented reality, automated sign translation, and better scene understanding for autonomous systems or smart devices.

CHAPTER 6

CONCLUSION

6. CONCLUSION

In this work, we used Tesseract OCR for the purpose of OCRing different texts. In order to evaluate the accuracy of the model, we took sample images from five different books. For each of these images, we obtained the OCRed text using the Tesseract model trained on the specific language. In order to evaluate the efficiency of this model, compared with various image preprocessing techniques, we manually corrected the text files to match the input images. Obtaining these ground truth files took a significant amount of time. The time and effort needed to manually correct the OCR results can be significantly improved if we can apply appropriate preprocessing techniques.

Text detection and recognition in natural scene images, powered by Optical Character Recognition (OCR) and the Python library PyTesseract, practiced today is arguably among the most important developments within the discipline of computer vision. It provides an avenue for accurately detecting and interpreting texts located within intricate scenes of visuals through the application of high-end algorithms and deep learning models. It powered applications ranging from accessibility for visually challenged persons to automating document analysis or real-time translation within augmented reality systems. The integration of OCR with PyTesseract puts a footprint on the path of evolution toward efficient and scalable solutions able to handle multilingual text, varied fonts, and challenging light conditions. Such capabilities not only realize smooth business operations with increased productivity but also offer fertile ground for innovation in the development of autonomous systems, smart devices, and beyond. As these technologies further evolve, their impact remains profound to societal inclusivity, operational efficiency, and technological advancement—promising further improvement in how we perceive, interact with, and utilize textual information in our increasingly digital world.

CHAPTER 7

LEARNING OUTCOME OF THE PROJECT

7. LEARNING OUTCOME OF THE PROJECT

Detecting and recognising text involves a very delicate procedure, which detects a number of varying fonts, contrasts, font sizes, alignments, and colors. Each of these elements makes it challenging to establish a single solution. An additional challenge is the fact that humans are regarded as a benchmark for determining whether the algorithm functions in a similar manner to our eyes and brain, as at times there are challenges related to the detection and recognition of text in videos and images.

The main aim of the research presented in this thesis was to develop a robust text detection and recognition system from natural images with high accuracy and recall, which would be used as the target of the experiments.

Analyze the literature review on text detection and recognition from natural images, which can explain the methods used and identify the features of each method. Review and compare traditional and current deep learning-based algorithms for detecting and recognising text in natural images. Furthermore, Demonstrate the evaluation protocols and the state-of-art existing benchmarks. Identify the most significant challenges and applications. Develop algorithms to identify the location and recognise text in natural images. Generate a new dataset, which can fill the gap of character annotation, multi-orientation, and curved text. Furthermore, develop image augmentation methods and tools on the bounding-box level to provide more samples for training, thus reducing the manual annotations of a large number of new images. Implement the proposed methodologies and algorithms and carry out an experiment on the proposed dataset. Evaluate the proposed methods and compare the results with the previous methods.

References:

[1]Preprocessing Techniques in Character Recognition by **Yasser Alginhi**

[2]TextField **:** Learning A Deep Direction Field for Irregular Scene Text Detection by Yongchao Xu, Yukang Wang

[3]Robust Text Detection in Natural Scene Images Xu-Cheng Yin, Xuwang Yin, Kaizhu Huang, and Hong-Wei Hao

[4]R. Smith, "An Overview of the Tesseract OCR Engine", Proceedings of IEEE International Conference on Document Analysis and Recognition, pp. 1-14, 2007

[5]EAST: An Efficient and Accurate Scene Text Detector Xinyu Zhou, Cong Yao, He Wen, Yuzhi Wang, Shuchang Zhou, Weiran He, and Jiajun Liang Megvii Technology Inc., Beijing, China {zxy, yaocong, wenhe, wangyuzhi, zsc, hwr, liangjiajun}@megvii.com

[6]Text localization for image and video OCR
CN102144236A - Text localization for image and video OCR - Google Patents

[7]Github, "GitHub tesseract-ocr/tessdata: Trained Models with Support for Legacy and LSTM OCR Engine", Available at https://github.com/tesseract-ocr/tessdata, Accessed at 2021

[8]PyTesseract: A brief guide to Python-tesseract **Ashutosh Saitwal**
Founder CEO - KlearStack AI

[9]OCR using PyTesseract and OpenCV by **Filip Zelic** & **Anuj Sable**

[10]Text Recognition In Natural Scene Images Using Machine Learning

[11]Localizing and segmenting text in Images and videos
Rainer Lienhart, Member, IEEE, and Axel Wernicke