

# Deep Learning - Theory and Practice

*IE 643  
Lecture 4*

August 7, 2025.


# 1 Perceptron Convergence

# Convergence of Perceptron Training

# Perceptron Convergence - Geometric Intuition


- What are some natural assumptions to expect the perceptron training to converge?
- Let us first motivate such assumptions through geometric intuition.

# Perceptron Convergence - Geometric Intuition




- Can the data be separated by a hyperplane?

# Perceptron Convergence - Geometric Intuition




- **First assumption:** At least the data should be such that the samples with label 1 can be separated by a hyperplane from samples with label  $-1$ .

# Perceptron Convergence - Geometric Intuition




- **First assumption:** At least the data should be such that the samples with label 1 can be separated by a hyperplane from samples with label  $-1$ .
- **Is this assumption sufficient?**


# Perceptron Convergence - Geometric Intuition




# Perceptron Convergence - Geometric Intuition




# Perceptron Convergence - Geometric Intuition




# Perceptron Convergence - Geometric Intuition




## Perceptron Convergence - Geometric Intuition




## Perceptron Convergence - Geometric Intuition




# Perceptron Convergence - Geometric Intuition




## Perceptron Convergence - Geometric Intuition



# Perceptron Convergence - Geometric Intuition



# Perceptron Convergence - Geometric Intuition



- **Refined assumption:** We not only want the data to be separated but the separation should be **good enough!**

# Perceptron Convergence - Separability Assumption

## Linear Separability Assumption

Let  $D = \{(x^t, y^t)\}_{t=1}^{\infty}$  denote the training data where  $x^t \in \mathbb{R}^d$ ,  $y^t \in \{+1, -1\}$ ,  $\forall t = 1, 2, \dots$ . Then there exist  $\mathbb{R}^d \ni w^* \neq 0$ ,  $\gamma > 0$ , such that:

$$\begin{aligned}\langle w^*, x^t \rangle &> \gamma \text{ where } y^t = 1, \\ \langle w^*, x^t \rangle &< -\gamma \text{ where } y^t = -1.\end{aligned}$$

# Perceptron Convergence - Separability Assumption

## Linear Separability Assumption

Let  $D = \{(x^t, y^t)\}_{t=1}^{\infty}$  denote the training data where  $x^t \in \mathbb{R}^d$ ,  $y^t \in \{+1, -1\}$ ,  $\forall t = 1, 2, \dots$ . Then there exist  $\mathbb{R}^d \ni w^* \neq 0$ ,  $\gamma > 0$ , such that:

$$y^t \langle w^*, x^t \rangle > \gamma.$$

# Perceptron Convergence - Mistake Bound

- We will try to derive useful bounds on the number of mistakes that a perceptron can commit during its training.
- **Assumption on data:** Linear Separability
- Assume that  $T$  rounds of training have been completed in perceptron training. **Assume  $T$  to be some large number.**
- Assume that  $M$  mistakes are made by the perceptron in these  $T$  rounds. (Obviously,  $M \leq T$ .)
- We ask if the number of mistakes  $M$  can be bounded by some suitable quantity.

# Perceptron Convergence - Mistake Bound

- We begin the analysis by considering an arbitrary round  $t \in \{1, 2, \dots, T\}$  where a mistake is made by the perceptron.

# Perceptron Convergence - Mistake Bound

- We begin the analysis by considering an arbitrary round  $t \in \{1, 2, \dots, T\}$  where a mistake is made by the perceptron.
- **Recall:** During this  $t$ -th round:
  - ▶ Perceptron computes  $\hat{y}^t = \text{sign}(\langle w^t, x^t \rangle)$ .

# Perceptron Convergence - Mistake Bound

- We begin the analysis by considering an arbitrary round  $t \in \{1, 2, \dots, T\}$  where a mistake is made by the perceptron.
- **Recall:** During this  $t$ -th round:
  - ▶ Perceptron computes  $\hat{y}^t = \text{sign}(\langle w^t, x^t \rangle)$ .
  - ▶  $\hat{y}^t \neq y^t$ .

# Perceptron Convergence - Mistake Bound

- We begin the analysis by considering an arbitrary round  $t \in \{1, 2, \dots, T\}$  where a mistake is made by the perceptron.
- **Recall:** During this  $t$ -th round:
  - ▶ Perceptron computes  $\hat{y}^t = \text{sign}(\langle w^t, x^t \rangle)$ .
  - ▶  $\hat{y}^t \neq y^t$ .
  - ▶ Perceptron update:  $w^{t+1} = w^t + y^t x^t$ .

# Perceptron Convergence - Mistake Bound

- We begin the analysis by considering an arbitrary round  $t \in \{1, 2, \dots, T\}$  where a mistake is made by the perceptron.
- **Recall:** During this  $t$ -th round:
  - ▶ Perceptron computes  $\hat{y}^t = \text{sign}(\langle w^t, x^t \rangle)$ .
  - ▶  $\hat{y}^t \neq y^t$ .
  - ▶ Perceptron update:  $w^{t+1} = w^t + y^t x^t$ .
- Now from linear separability assumption, we have  $w^* \neq 0$  such that  $y^t \langle w^*, x^t \rangle > \gamma$ .

# Perceptron Convergence - Mistake Bound

- We begin the analysis by considering an arbitrary round  $t \in \{1, 2, \dots, T\}$  where a mistake is made by the perceptron.
- **Recall:** During this  $t$ -th round:
  - ▶ Perceptron computes  $\hat{y}^t = \text{sign}(\langle w^t, x^t \rangle)$ .
  - ▶  $\hat{y}^t \neq y^t$ .
  - ▶ Perceptron update:  $w^{t+1} = w^t + y^t x^t$ .
- Now from linear separability assumption, we have  $w^* \neq 0$  such that  $y^t \langle w^*, x^t \rangle > \gamma$ .
- **First step:** To bound the difference  $\langle w^*, w^{t+1} \rangle - \langle w^*, w^t \rangle$ .

## Perceptron Convergence - Mistake Bound

- We begin the analysis by considering an arbitrary round  $t \in \{1, 2, \dots, T\}$  where a mistake is made by the perceptron.
- **Recall:** During this  $t$ -th round:
  - ▶ Perceptron computes  $\hat{y}^t = \text{sign}(\langle w^t, x^t \rangle)$ .
  - ▶  $\hat{y}^t \neq y^t$ .
  - ▶ Perceptron update:  $w^{t+1} = w^t + y^t x^t$ .
- Now from linear separability assumption, we have  $w^* \neq 0$  such that  $y^t \langle w^*, x^t \rangle > \gamma$ .
- Now we can write

$$\langle w^*, w^{t+1} \rangle - \langle w^*, w^t \rangle = \langle w^*, w^t + y^t x^t \rangle - \langle w^*, w^t \rangle$$

# Perceptron Convergence - Mistake Bound

- We begin the analysis by considering an arbitrary round  $t \in \{1, 2, \dots, T\}$  where a mistake is made by the perceptron.
- Recall:** During this  $t$ -th round:
  - Perceptron computes  $\hat{y}^t = \text{sign}(\langle w^t, x^t \rangle)$ .
  - $\hat{y}^t \neq y^t$ .
  - Perceptron update:  $w^{t+1} = w^t + y^t x^t$ .
- Now from linear separability assumption, we have  $w^* \neq 0$  such that  $y^t \langle w^*, x^t \rangle > \gamma$ .
- Now we can write

$$\begin{aligned}\langle w^*, w^{t+1} \rangle - \langle w^*, w^t \rangle &= \langle w^*, w^t + y^t x^t \rangle - \langle w^*, w^t \rangle \\ &= \langle w^*, w^t \rangle + \langle w^*, y^t x^t \rangle - \langle w^*, w^t \rangle \quad (\text{how?})\end{aligned}$$

# Perceptron Convergence - Mistake Bound

- We begin the analysis by considering an arbitrary round  $t \in \{1, 2, \dots, T\}$  where a mistake is made by the perceptron.
- Recall:** During this  $t$ -th round:
  - Perceptron computes  $\hat{y}^t = \text{sign}(\langle w^t, x^t \rangle)$ .
  - $\hat{y}^t \neq y^t$ .
  - Perceptron update:  $w^{t+1} = w^t + y^t x^t$ .
- Now from linear separability assumption, we have  $w^* \neq 0$  such that  $y^t \langle w^*, x^t \rangle > \gamma$ .
- Now we can write

$$\begin{aligned}\langle w^*, w^{t+1} \rangle - \langle w^*, w^t \rangle &= \langle w^*, w^t + y^t x^t \rangle - \langle w^*, w^t \rangle \\ &= \langle w^*, w^t \rangle + \langle w^*, y^t x^t \rangle - \langle w^*, w^t \rangle \\ &= \langle w^*, y^t x^t \rangle\end{aligned}$$

# Perceptron Convergence - Mistake Bound

- We begin the analysis by considering an arbitrary round  $t \in \{1, 2, \dots, T\}$  where a mistake is made by the perceptron.
- Recall:** During this  $t$ -th round:
  - Perceptron computes  $\hat{y}^t = \text{sign}(\langle w^t, x^t \rangle)$ .
  - $\hat{y}^t \neq y^t$ .
  - Perceptron update:  $w^{t+1} = w^t + y^t x^t$ .
- Now from linear separability assumption, we have  $w^* \neq 0$  such that  $y^t \langle w^*, x^t \rangle > \gamma$ .
- Now we can write

$$\begin{aligned}
 \langle w^*, w^{t+1} \rangle - \langle w^*, w^t \rangle &= \langle w^*, w^t + y^t x^t \rangle - \langle w^*, w^t \rangle \\
 &= \langle w^*, w^t \rangle + \langle w^*, y^t x^t \rangle - \langle w^*, w^t \rangle \\
 &= \langle w^*, y^t x^t \rangle \\
 &= y^t \langle w^*, x^t \rangle \quad (\text{how?})
 \end{aligned}$$

# Perceptron Convergence - Mistake Bound

- We begin the analysis by considering an arbitrary round  $t \in \{1, 2, \dots, T\}$  where a mistake is made by the perceptron.
- Recall:** During this  $t$ -th round:
  - Perceptron computes  $\hat{y}^t = \text{sign}(\langle w^t, x^t \rangle)$ .
  - $\hat{y}^t \neq y^t$ .
  - Perceptron update:  $w^{t+1} = w^t + y^t x^t$ .
- Now from linear separability assumption, we have  $w^* \neq 0$  such that  $y^t \langle w^*, x^t \rangle > \gamma$ .
- Now we can write

$$\begin{aligned}
 \langle w^*, w^{t+1} \rangle - \langle w^*, w^t \rangle &= \langle w^*, w^t + y^t x^t \rangle - \langle w^*, w^t \rangle \\
 &= \langle w^*, w^t \rangle + \langle w^*, y^t x^t \rangle - \langle w^*, w^t \rangle \\
 &= \langle w^*, y^t x^t \rangle \\
 &= y^t \langle w^*, x^t \rangle > \gamma
 \end{aligned}$$

# Perceptron Convergence - Mistake Bound

- We begin the analysis by considering an arbitrary round  $t \in \{1, 2, \dots, T\}$  where a mistake is made by the perceptron.
- **Recall:** During this  $t$ -th round:
  - ▶ Perceptron computes  $\hat{y}^t = \text{sign}(\langle w^t, x^t \rangle)$ .
  - ▶  $\hat{y}^t \neq y^t$ .
  - ▶ Perceptron update:  $w^{t+1} = w^t + y^t x^t$ .
- Now from linear separability assumption, we have  $w^* \neq 0$  such that  $y^t \langle w^*, x^t \rangle > \gamma$ .
- Now we can write

$$\langle w^*, w^{t+1} \rangle - \langle w^*, w^t \rangle > \gamma.$$

# Perceptron Convergence - Mistake Bound

- Now when no mistake is made in round  $t$ , we have  $w^{t+1} = w^t$ .
- Hence  $\langle w^*, w^{t+1} \rangle - \langle w^*, w^t \rangle = 0$ .

# Perceptron Convergence - Mistake Bound

## Recall our assumptions:

- Assume that the  $T$  rounds of training have been completed in perceptron training. **Assume  $T$  to be some large number.**
- Assume that  $M$  mistakes are made by the perceptron in these  $T$  rounds. (Obviously,  $M \leq T$ .)

# Perceptron Convergence - Mistake Bound

$$\sum_{t=1}^T \langle w^*, w^{t+1} \rangle - \langle w^*, w^t \rangle = \sum_{\substack{t \in \{1, \dots, T\}, \\ t: \text{mistake is made} \\ \text{at round } t}} \langle w^*, w^{t+1} \rangle - \langle w^*, w^t \rangle + \sum_{\substack{t \in \{1, \dots, T\}, \\ t: \text{no mistake is made} \\ \text{at round } t}} \langle w^*, w^{t+1} \rangle - \langle w^*, w^t \rangle$$

# Perceptron Convergence - Mistake Bound

$$\begin{aligned}
 \sum_{t=1}^T \langle w^*, w^{t+1} \rangle - \langle w^*, w^t \rangle &= \sum_{\substack{t \in \{1, \dots, T\}, \\ t: \text{mistake is made} \\ \text{at round } t}} \langle w^*, w^{t+1} \rangle - \langle w^*, w^t \rangle + \\
 &\quad \sum_{\substack{t \in \{1, \dots, T\}, \\ t: \text{no mistake is made} \\ \text{at round } t}} \langle w^*, w^{t+1} \rangle - \langle w^*, w^t \rangle \\
 &= \sum_{\substack{t \in \{1, \dots, T\}, \\ t: \text{mistake is made} \\ \text{at round } t}} \langle w^*, w^{t+1} \rangle - \langle w^*, w^t \rangle + 0 \text{ (how?)}
 \end{aligned}$$

# Perceptron Convergence - Mistake Bound

$$\begin{aligned} \sum_{t=1}^T \langle w^*, w^{t+1} \rangle - \langle w^*, w^t \rangle &= \sum_{\substack{t \in \{1, \dots, T\}, \\ t: \text{mistake is made} \\ \text{at round } t}} \langle w^*, w^{t+1} \rangle - \langle w^*, w^t \rangle \\ &> M\gamma \text{ (how?)} \end{aligned}$$

# Perceptron Convergence - Mistake Bound

Also note:

$$\sum_{t=1}^T \langle w^*, w^{t+1} \rangle - \langle w^*, w^t \rangle = \langle w^*, w^{T+1} \rangle \text{ (homework!)}$$

# Perceptron Convergence - Mistake Bound

Hence we have:

$$\sum_{t=1}^T \langle w^*, w^{t+1} \rangle - \langle w^*, w^t \rangle > M\gamma$$
$$\implies \langle w^*, w^{T+1} \rangle > M\gamma$$

# Perceptron Mistake Bound - An upper bound

# Perceptron Convergence - Mistake Bound

Now we will handle the inner product term:

$$\langle w^*, w^{T+1} \rangle > M\gamma$$

# Perceptron Convergence - Mistake Bound

Now we will handle the inner product term:

$$\langle w^*, w^{T+1} \rangle > M\gamma$$

- From Cauchy-Schwarz inequality we have,  
 $\langle w^*, w^{T+1} \rangle \leq \|w^*\|_2 \|w^{T+1}\|_2$ . (Homework: Prove this inequality!)
- **Note:**  $\|w^{T+1}\|_2$  denotes the Euclidean  $\ell_2$  norm of  $w^{T+1}$ .

# Perceptron Convergence - Mistake Bound

Now we will handle the inner product term:

$$\langle w^*, w^{T+1} \rangle > M\gamma$$

- From Cauchy-Schwarz inequality we have,  
 $\langle w^*, w^{T+1} \rangle \leq \|w^*\|_2 \|w^{T+1}\|_2$ . (Homework: Prove this inequality!)
- **Note:**  $\|w^{T+1}\|_2$  denotes the Euclidean  $\ell_2$  norm of  $w^{T+1}$ .
- We will now see how to bound  $\|w^{T+1}\|_2$ .

# Perceptron Convergence - Mistake Bound

- Again we consider an arbitrary round  $t \in \{1, 2, \dots, T\}$  where a mistake is made by the perceptron.

# Perceptron Convergence - Mistake Bound

- Again we consider an arbitrary round  $t \in \{1, 2, \dots, T\}$  where a mistake is made by the perceptron.
- Recall:** During this  $t$ -th round:
  - ▶ Perceptron computes  $\hat{y}^t = \text{sign}(\langle w^t, x^t \rangle)$ .

# Perceptron Convergence - Mistake Bound

- Again we consider an arbitrary round  $t \in \{1, 2, \dots, T\}$  where a mistake is made by the perceptron.
- Recall:** During this  $t$ -th round:
  - Perceptron computes  $\hat{y}^t = \text{sign}(\langle w^t, x^t \rangle)$ .
  - $\hat{y}^t \neq y^t$ .

# Perceptron Convergence - Mistake Bound

- Again we consider an arbitrary round  $t \in \{1, 2, \dots, T\}$  where a mistake is made by the perceptron.
- Recall:** During this  $t$ -th round:
  - Perceptron computes  $\hat{y}^t = \text{sign}(\langle w^t, x^t \rangle)$ .
  - $\hat{y}^t \neq y^t$ .
  - Perceptron update:  $w^{t+1} = w^t + y^t x^t$ .

# Perceptron Convergence - Mistake Bound

- Again we consider an arbitrary round  $t \in \{1, 2, \dots, T\}$  where a mistake is made by the perceptron.
- Recall:** During this  $t$ -th round:
  - Perceptron computes  $\hat{y}^t = \text{sign}(\langle w^t, x^t \rangle)$ .
  - $\hat{y}^t \neq y^t$ .
  - Perceptron update:  $w^{t+1} = w^t + y^t x^t$ .

Now, we have

$$\|w^{t+1}\|_2^2 = \|w^t + y^t x^t\|_2^2$$

# Perceptron Convergence - Mistake Bound

- Again we consider an arbitrary round  $t \in \{1, 2, \dots, T\}$  where a mistake is made by the perceptron.
- Recall:** During this  $t$ -th round:
  - Perceptron computes  $\hat{y}^t = \text{sign}(\langle w^t, x^t \rangle)$ .
  - $\hat{y}^t \neq y^t$ .
  - Perceptron update:  $w^{t+1} = w^t + y^t x^t$ .

Now, we have

$$\begin{aligned}\|w^{t+1}\|_2^2 &= \|w^t + y^t x^t\|_2^2 \\ &= \|w^t\|_2^2 + \|y^t x^t\|_2^2 + 2\langle w^t, y^t x^t \rangle\end{aligned}$$

# Perceptron Convergence - Mistake Bound

- Again we consider an arbitrary round  $t \in \{1, 2, \dots, T\}$  where a mistake is made by the perceptron.
- Recall:** During this  $t$ -th round:
  - Perceptron computes  $\hat{y}^t = \text{sign}(\langle w^t, x^t \rangle)$ .
  - $\hat{y}^t \neq y^t$ .
  - Perceptron update:  $w^{t+1} = w^t + y^t x^t$ .

Now, we have

$$\begin{aligned}
 \|w^{t+1}\|_2^2 &= \|w^t + y^t x^t\|_2^2 \\
 &= \|w^t\|_2^2 + \|y^t x^t\|_2^2 + 2\langle w^t, y^t x^t \rangle \\
 &= \|w^t\|_2^2 + \|x^t\|_2^2 + 2y^t \langle w^t, x^t \rangle
 \end{aligned}$$

# Perceptron Convergence - Mistake Bound

- Again we consider an arbitrary round  $t \in \{1, 2, \dots, T\}$  where a mistake is made by the perceptron.
- Recall:** During this  $t$ -th round:
  - Perceptron computes  $\hat{y}^t = \text{sign}(\langle w^t, x^t \rangle)$ .
  - $\hat{y}^t \neq y^t$ .
  - Perceptron update:  $w^{t+1} = w^t + y^t x^t$ .

Now, we have

$$\begin{aligned}
 \|w^{t+1}\|_2^2 &= \|w^t + y^t x^t\|_2^2 \\
 &= \|w^t\|_2^2 + \|y^t x^t\|_2^2 + 2\langle w^t, y^t x^t \rangle \\
 &= \|w^t\|_2^2 + \|x^t\|_2^2 + 2y^t \langle w^t, x^t \rangle \\
 \implies \|w^{t+1}\|_2^2 &\leq \|w^t\|_2^2 + \|x^t\|_2^2 \quad (\text{How?})
 \end{aligned}$$

# Perceptron Convergence - Mistake Bound

- Again we consider an arbitrary round  $t \in \{1, 2, \dots, T\}$  where a mistake is made by the perceptron.
- Recall:** During this  $t$ -th round:
  - Perceptron computes  $\hat{y}^t = \text{sign}(\langle w^t, x^t \rangle)$ .
  - $\hat{y}^t \neq y^t$ .
  - Perceptron update:  $w^{t+1} = w^t + y^t x^t$ .

Now, we have

$$\begin{aligned}
 \|w^{t+1}\|_2^2 &= \|w^t + y^t x^t\|_2^2 \\
 &= \|w^t\|_2^2 + \|y^t x^t\|_2^2 + 2\langle w^t, y^t x^t \rangle \\
 &= \|w^t\|_2^2 + \|x^t\|_2^2 + 2y^t \langle w^t, x^t \rangle \\
 \implies \|w^{t+1}\|_2^2 &\leq \|w^t\|_2^2 + \|x^t\|_2^2 \quad (\text{How?})
 \end{aligned}$$

Thus  $\|w^{t+1}\|_2^2 - \|w^t\|_2^2 \leq \|x^t\|_2^2$ .

# Perceptron Convergence - Mistake Bound

## Assumption on boundedness of $\|x^t\|_2$

We shall assume further that  $\forall t = 1, 2, \dots$ , the  $\ell_2$  norm (or length) of  $x^t$  is bounded, which is denoted as:

$$\|x^t\|_2 \leq R \quad \forall t = 1, 2, \dots$$

# Perceptron Convergence - Mistake Bound

## Assumption on boundedness of $\|x^t\|_2$

We shall assume further that  $\forall t = 1, 2, \dots$ , the  $\ell_2$  norm (or length) of  $x^t$  is bounded, which is denoted as:

$$\|x^t\|_2 \leq R \quad \forall t = 1, 2, \dots$$

- This is yet another assumption to help our analysis.
- Bounded  $\|x^t\|_2$  is not very unrealistic, however finding a suitable value for  $R$  might be difficult.

# Perceptron Convergence - Mistake Bound

## Assumption on boundedness of $\|x^t\|_2$

We shall assume further that  $\forall t = 1, 2, \dots$ , the  $\ell_2$  norm (or length) of  $x^t$  is bounded, which is denoted as:

$$\|x^t\|_2 \leq R \quad \forall t = 1, 2, \dots$$

- This is yet another assumption to help our analysis.
- Bounded  $\|x^t\|_2$  is not very unrealistic, however finding a suitable value for  $R$  might be difficult.
- This is where normalizing all  $x^t$  might help, so that  $\|x^t\|_2 \leq 1$  can be assumed.
- **Note:** The set  $\{x \in \mathbb{R}^d : \|x\|_2 \leq 1\}$  is called a **unit ball** in  $\mathbb{R}^d$ .

# Perceptron Convergence - Mistake Bound

We thus have

$$\|w^{t+1}\|_2^2 - \|w^t\|_2^2 \leq \|x^t\|_2^2 \implies \|w^{t+1}\|_2^2 - \|w^t\|_2^2 \leq R^2.$$

## Perceptron Convergence - Mistake Bound

We thus have

$$\|w^{t+1}\|_2^2 - \|w^t\|_2^2 \leq \|x^t\|_2^2 \implies \|w^{t+1}\|_2^2 - \|w^t\|_2^2 \leq R^2.$$

Again, summing  $\|w^{t+1}\|_2^2 - \|w^t\|_2^2$  over  $t = 1, \dots, T$  we get

# Perceptron Convergence - Mistake Bound

We thus have

$$\|w^{t+1}\|_2^2 - \|w^t\|_2^2 \leq \|x^t\|_2^2 \implies \|w^{t+1}\|_2^2 - \|w^t\|_2^2 \leq R^2.$$

Again, summing  $\|w^{t+1}\|_2^2 - \|w^t\|_2^2$  over  $t = 1, \dots, T$  we get

$$\sum_{i=1}^T \|w^{t+1}\|_2^2 - \|w^t\|_2^2 = \sum_{\substack{t \in \{1, \dots, T\}, \\ t: \text{mistake is made} \\ \text{at round } t}} \|w^{t+1}\|_2^2 - \|w^t\|_2^2 + \sum_{\substack{t \in \{1, \dots, T\}, \\ t: \text{no mistake is made} \\ \text{at round } t}} \|w^{t+1}\|_2^2 - \|w^t\|_2^2$$

# Perceptron Convergence - Mistake Bound

We thus have

$$\|w^{t+1}\|_2^2 - \|w^t\|_2^2 \leq \|x^t\|_2^2 \implies \|w^{t+1}\|_2^2 - \|w^t\|_2^2 \leq R^2.$$

Again, summing  $\|w^{t+1}\|_2^2 - \|w^t\|_2^2$  over  $t = 1, \dots, T$  we get

$$\begin{aligned} \sum_{i=1}^T \|w^{t+1}\|_2^2 - \|w^t\|_2^2 &= \sum_{\substack{t \in \{1, \dots, T\}, \\ t: \text{mistake is made} \\ \text{at round } t}} \|w^{t+1}\|_2^2 - \|w^t\|_2^2 + \\ &\quad \sum_{\substack{t \in \{1, \dots, T\}, \\ t: \text{no mistake is made} \\ \text{at round } t}} \|w^{t+1}\|_2^2 - \|w^t\|_2^2 \\ &= \sum_{\substack{t \in \{1, \dots, T\}, \\ t: \text{mistake is made} \\ \text{at round } t}} \|w^{t+1}\|_2^2 - \|w^t\|_2^2 \end{aligned}$$

# Perceptron Convergence - Mistake Bound

We thus have

$$\|w^{t+1}\|_2^2 - \|w^t\|_2^2 \leq \|x^t\|_2^2 \implies \|w^{t+1}\|_2^2 - \|w^t\|_2^2 \leq R^2.$$

Again, summing  $\|w^{t+1}\|_2^2 - \|w^t\|_2^2$  over  $t = 1, \dots, T$  we get

$$\begin{aligned} \sum_{i=1}^T \|w^{t+1}\|_2^2 - \|w^t\|_2^2 &= \sum_{\substack{t \in \{1, \dots, T\}, \\ t: \text{mistake is made} \\ \text{at round } t}} \|w^{t+1}\|_2^2 - \|w^t\|_2^2 + \\ &\quad \sum_{\substack{t \in \{1, \dots, T\}, \\ t: \text{no mistake is made} \\ \text{at round } t}} \|w^{t+1}\|_2^2 - \|w^t\|_2^2 \\ &= \sum_{\substack{t \in \{1, \dots, T\}, \\ t: \text{mistake is made} \\ \text{at round } t}} \|w^{t+1}\|_2^2 - \|w^t\|_2^2 \leq MR^2 \text{ (How?)} \end{aligned}$$

# Perceptron Convergence - Mistake Bound

Thus we have

$$\sum_{i=1}^T \|w^{t+1}\|_2^2 - \|w^t\|_2^2 \leq MR^2.$$

# Perceptron Convergence - Mistake Bound

Thus we have

$$\sum_{i=1}^T \|w^{t+1}\|_2^2 - \|w^t\|_2^2 \leq MR^2.$$

On the other hand we get:

$$\sum_{i=1}^T \|w^{t+1}\|_2^2 - \|w^t\|_2^2 = \|w^{T+1}\|_2^2. \text{ (Homework!)}$$

# Perceptron Convergence - Mistake Bound

Thus we have

$$\sum_{i=1}^T \|w^{t+1}\|_2^2 - \|w^t\|_2^2 \leq MR^2.$$

On the other hand we get:

$$\sum_{i=1}^T \|w^{t+1}\|_2^2 - \|w^t\|_2^2 = \|w^{T+1}\|_2^2. \text{ (Homework!)}$$

Combining both, we get

$$\|w^{T+1}\|_2^2 \leq MR^2.$$

# Perceptron Convergence - Mistake Bound

Thus we have

$$\sum_{i=1}^T \|w^{t+1}\|_2^2 - \|w^t\|_2^2 \leq MR^2.$$

On the other hand we get:

$$\sum_{i=1}^T \|w^{t+1}\|_2^2 - \|w^t\|_2^2 = \|w^{T+1}\|_2^2. \text{ (Homework!)}$$

Combining both, we get

$$\|w^{T+1}\|_2^2 \leq MR^2.$$

Thus we have bounded  $\|w^{T+1}\|_2$ .

# Perceptron Convergence - Mistake Bound

**Recall:** We wanted to handle the inner product term:

$$\langle w^*, w^{T+1} \rangle > M\gamma$$

# Perceptron Convergence - Mistake Bound

**Recall:** We wanted to handle the inner product term:

$$\langle w^*, w^{T+1} \rangle > M\gamma$$

Then using Cauchy-Schwarz inequality we had

$$M\gamma < \langle w^*, w^{T+1} \rangle \leq \|w^*\|_2 \|w^{T+1}\|_2$$

# Perceptron Convergence - Mistake Bound

**Recall:** We wanted to handle the inner product term:

$$\langle w^*, w^{T+1} \rangle > M\gamma$$

Then using Cauchy-Schwarz inequality we had

$$\begin{aligned} M\gamma &< \langle w^*, w^{T+1} \rangle \leq \|w^*\|_2 \|w^{T+1}\|_2 \\ \implies M^2\gamma^2 &< \|w^*\|_2^2 \|w^{T+1}\|_2^2 \end{aligned}$$

# Perceptron Convergence - Mistake Bound

**Recall:** We wanted to handle the inner product term:

$$\langle w^*, w^{T+1} \rangle > M\gamma$$

Then using Cauchy-Schwarz inequality we had

$$\begin{aligned} M\gamma &< \langle w^*, w^{T+1} \rangle \leq \|w^*\|_2 \|w^{T+1}\|_2 \\ \implies M^2\gamma^2 &< \|w^*\|_2^2 \|w^{T+1}\|_2^2 \end{aligned}$$

Using the bound  $\|w^{T+1}\|_2^2 \leq MR^2$  we obtain:

# Perceptron Convergence - Mistake Bound

**Recall:** We wanted to handle the inner product term:

$$\langle w^*, w^{T+1} \rangle > M\gamma$$

Then using Cauchy-Schwarz inequality we had

$$\begin{aligned} M\gamma &< \langle w^*, w^{T+1} \rangle \leq \|w^*\|_2 \|w^{T+1}\|_2 \\ \implies M^2\gamma^2 &< \|w^*\|_2^2 \|w^{T+1}\|_2^2 \end{aligned}$$

Using the bound  $\|w^{T+1}\|_2^2 \leq MR^2$  we obtain:

$$M^2\gamma^2 < \|w^*\|_2^2 MR^2$$

# Perceptron Convergence - Mistake Bound

**Recall:** We wanted to handle the inner product term:

$$\langle w^*, w^{T+1} \rangle > M\gamma$$

Then using Cauchy-Schwarz inequality we had

$$\begin{aligned} M\gamma &< \langle w^*, w^{T+1} \rangle \leq \|w^*\|_2 \|w^{T+1}\|_2 \\ \implies M^2\gamma^2 &< \|w^*\|_2^2 \|w^{T+1}\|_2^2 \end{aligned}$$

Using the bound  $\|w^{T+1}\|_2^2 \leq MR^2$  we obtain:

$$\begin{aligned} M^2\gamma^2 &< \|w^*\|_2^2 MR^2 \\ \implies M &< \frac{\|w^*\|_2^2 R^2}{\gamma^2} \end{aligned}$$

# Perceptron Convergence - Mistake Bound

**Recall:** We wanted to handle the inner product term:

$$\langle w^*, w^{T+1} \rangle > M\gamma$$

Then using Cauchy-Schwarz inequality we had

$$\begin{aligned} M\gamma &< \langle w^*, w^{T+1} \rangle \leq \|w^*\|_2 \|w^{T+1}\|_2 \\ \implies M^2\gamma^2 &< \|w^*\|_2^2 \|w^{T+1}\|_2^2 \end{aligned}$$

Using the bound  $\|w^{T+1}\|_2^2 \leq MR^2$  we obtain:

$$\begin{aligned} M^2\gamma^2 &< \|w^*\|_2^2 MR^2 \\ \implies M &< \frac{\|w^*\|_2^2 R^2}{\gamma^2} \end{aligned}$$

Thus, assuming that  $\|w^*\|_2$  and  $R$  can be controlled, the number of mistakes  $M$  is inversely proportional to  $\gamma$ , which determines the closeness of the data points to the separating hyperplane.

# Perceptron Convergence - Mistake Bound

## References:

- **H.D. Block:** The perceptron: A model for brain functioning.  
*Reviews of Modern Physics* 34, 123-135 (1962).
- **A.B.J. Novikoff:** On convergence proofs on perceptrons. In:  
*Proceedings of the Symposium on the Mathematical Theory of Automata*, vol. XII, pp. 615-622 (1962).

# Perceptron Convergence - Mistake Bound

Two questions remain:

# Perceptron Convergence - Mistake Bound

Two questions remain:

- How do we compute  $w^*$  and  $\gamma$ ?
- What is the intuition behind the Perceptron update rule?

# Perceptron Convergence - Mistake Bound

Two questions remain:

- How do we compute  $w^*$  and  $\gamma$ ?
- What is the intuition behind the Perceptron update rule?

Try to find answers to these questions!