

Title: Git Hands-On Lab 2 - Git Ignore**Problem Statement:****Objectives:**

- Explain git ignore
- Explain how to ignore unwanted files using git ignore

In this hands-on lab, I learnt how to:

- Implement git ignore command to ignore unwanted files and folders\

Prerequisites:

- Setting up Git environment
- Integrate notepad++ as a default editor
- A Git repository in the local system and a remote repository in GitLab
-

Create a “.log” file and a log folder in the working directory of Git. Update the .gitignore file in such a way that on committing, these files (.log extensions and log folders) are ignored. Verify if the git status reflects the same about working directory, local repository and git repository.

Step-by-Step Instructions

1. Create a “.log” file (e.g., echo "log content" > file.log) and a log folder (e.g., mkdir log) in the working directory of Git.

```
pchai@Chaitanya MINGW32 ~/GitDemo (master)
$ git ~/GitDemo
git: 'C:/Users/pchai/GitDemo' is not a git command. See 'git --help'.

pchai@Chaitanya MINGW32 ~/GitDemo (master)
$ cd ~/GitDemo

pchai@Chaitanya MINGW32 ~/GitDemo (master)
$ echo "temporary log content">deug.log

pchai@Chaitanya MINGW32 ~/GitDemo (master)
$ mkdir -p log

pchai@Chaitanya MINGW32 ~/GitDemo (master)
$ echo "application log">log/app.log

pchai@Chaitanya MINGW32 ~/GitDemo (master)
$ ls -l
total 10
-rw-r--r-- 1 pachai 197609 6224 Aug 10 05:16 README.md
-rw-r--r-- 1 pachai 197609 22 Aug 10 05:21 deug.log
drwxr-xr-x 1 pachai 197609 0 Aug 10 05:24 log/
-rw-r--r-- 1 pachai 197609 31 Aug 9 21:24 welcome.txt

pchai@Chaitanya MINGW32 ~/GitDemo (master)
$ ls -l log/
total 1
-rw-r--r-- 1 pachai 197609 16 Aug 10 05:24 app.log

pchai@Chaitanya MINGW32 ~/GitDemo (master)
$ echo '*log'>log/.gitignore
*log/.gitignore

pchai@Chaitanya MINGW32 ~/GitDemo (master)
$ ^C

pchai@Chaitanya MINGW32 ~/GitDemo (master)
$ echo '*log'>.gitignore

pchai@Chaitanya MINGW32 ~/GitDemo (master)
$ echo 'log/'>>.gitignore
```

2. Update the .gitignore file to ignore .log files and log folder (e.g., add *.log and log/ to .gitignore).

```

MINGW32/c/Users/pchai/GitDemo
pchai@Chaitanya MINGW32 ~/GitDemo (master)
$ git check-ignore -v deug.log
.gitignore:1:*log      deug.log

pchai@Chaitanya MINGW32 ~/GitDemo (master)
$ git check-ignore -v .log/deug.log
.gitignore:1:*log      .log/deug.log

```

3. Commit the changes (e.g., git add .gitignore and git commit -m "Update gitignore").

```

MINGW32/c/Users/pchai/GitDemo
pchai@Chaitanya MINGW32 ~/GitDemo (master)
$ cat .gitignore
*log
log/

pchai@Chaitanya MINGW32 ~/GitDemo (master)
$ git status
On branch master
Your branch is ahead of 'origin/master' by 2 commits.
(use "git push" to publish your local commits)

Untracked files:
  (use "git add <file>..." to include in what will be committed)
    .gitignore

nothing added to commit but untracked files present (use "git add" to track)

pchai@Chaitanya MINGW32 ~/GitDemo (master)
$ git add .gitignore
warning: in the working copy of '.gitignore', LF will be replaced by CRLF the next time Git
touches it

pchai@Chaitanya MINGW32 ~/GitDemo (master)
$ git commit -m "Ass .gitignore to ignore .log files"
[master 22be986] Ass .gitignore to ignore .log files
1 file changed, 2 insertions(+)
create mode 100644 .gitignore

```

4. Verify if the git status reflects that .log files and log folder are ignored in working directory, local repository, and git repository by executing git status.

```

create mode 100644 .gitignore

pchai@Chaitanya MINGW32 ~/GitDemo (master)
$ git status
On branch master
Your branch is ahead of 'origin/master' by 3 commits.
(use "git push" to publish your local commits)

nothing to commit, working tree clean

pchai@Chaitanya MINGW32 ~/GitDemo (master)
$ ^C

pchai@Chaitanya MINGW32 ~/GitDemo (master)
$ ^C

pchai@Chaitanya MINGW32 ~/GitDemo (master)

```