* Huffman Codes (Variable size coding)

Ex: Message :- B C C A B B D D A E C C B B A E D D C C (len = 20)
i/p

General way :- Ascii char of each symbol (8 bit)

$20 \times 8 = 160$ bits (to send)

Char	freq count	Own code (3 bit)
A	3	0 0 0
B	6	0 0 1
C	6	0 1 0
D		0 1 1
E		1 0 0

5 char

fixed sized code

$2^1 = 2$
$2^2 = 4$
$2^3 = 8$ //

- total size of msg = $20 \times 3 = 60$ bits (Ascii)
- total bits for table ⇒ 5×8 bits $= 40$
  5×3 bits $= 15$ (own code)
  + = 55 bits

* Final size of msg = $60 + 55 = 115$ bits

60 ↑ msg, 55 ↑ table

* Variable size Coding (Huffman coding)
↳ optimal merge pattern tree

Msg → B C C A B B D D A E C C B B A E D D C C

10 11 11 001 10 10 11 11

Char	freq count	code (Variable size code)	
A	3	001	3×3 = 9
B	5	10	5×2 = 10
C	6	11	6×2 = 12
D	4	01	4×2 = 8
E	2	000	2×3 = 6
	20 bits	12 bits	

(Ascii)

5 × 8 = 40 bits

Msg size ⇒ 45 bits

* left child taken as 0
* rt child taken as 1

* Total ⇒ 40 + 12
table size = 52 bits



optimal merge pattern tree

Huffman code →

arrange the i/p char in asc order seq

(Huffman coding)

45 bits 52 bits

Msg size	Table

= 97 bits (Final size)

Relation ① More the no of times a char occurs in an i/p text ⟶ lesser is the size of Huffman code