



STAGE 3

INSTRUCTIONS

Hit the following URL to check the code

LOCALHOST:8089/STAGE3.HTML

INDEX.JS



```

X express = require('express');
var app = express();

app.get("/test",(request, response)=>{
response.send("<h1>Executing Test Handler</h1>");
});

app.get("/hello",(request, response)=>{
var data = "";
var times = request.query.times;
var message = request.query.message;
times = (times === undefined )? 5 : parseInt(times);
message = (message === undefined )?"Hello" : message;
for(var i = 0; i <times ; i++){
data += "<h1>"+message+ "</h1>";
}
response.send(data);
});

app.get("/jsonendpoint1",(request, response)=>{
response.setHeader('Content-Type', 'application/json');
response.send(JSON.stringify({x:1,y:2}));
});

app.get("/jsonendpoint2",(request, response)=>{
response.setHeader('Content-Type', 'application/json');
response.send(JSON.stringify({message: "I Love AJAX",times:3}));
});

app.listen(8089,()=>{
console.log("Express server started at port 8089");
});

app.use(express.static("public"));
console.log("Staring Stage3");

```

STAGE3.HTML

```
X DOCTYPE html>  
<html>  
  <head>  
    <title>ExpressJs AJAX Stage3</title>  
    <meta charset="UTF-8">  
    <meta name="viewport" content="width=device-width,  
initial-scale=1.0">  
    <style>  
      textarea {  
        background-color: black;  
        color: white;  
        height: 300px;  
        width: 400px;  
      }  
      button{  
        background-color: green;  
        color: white;  
        padding:20px;  
      }  
      form{  
        background-color: khaki;  
        color: black;  
        padding:20px;  
      }  
    </style>  
    <script>  
      function run1() {  
        console.log("Entering AJAX run");  
        var xhttp = new XMLHttpRequest();  
        xhttp.onreadystatechange = () => {  
          if (xhttp.readyState === XMLHttpRequest.DONE  
&& xhttp.status === 200) {  
            console.log(xhttp.responseText);  
            document.getElementById("ta").value =  
xhttp.responseText;  
          }  
        };  
        xhttp.open("GET", "/jsonendpoint1", true);
```



```
xhttp.send();
console.log("Leaving run");
}

function run2() {
    console.log("Entering AJAX run");
    var xhttp = new XMLHttpRequest();
    xhttp.onreadystatechange = () => {
        if (xhttp.readyState === XMLHttpRequest.DONE
        && xhttp.status === 200) {
            console.log(xhttp.responseText);
            document.getElementById("ta").value =
xhttp.responseText;
            var data = JSON.parse(xhttp.responseText);
            document.getElementById("message").value =
data.message;
            document.getElementById("times").value =
data.times;
        }
    };
    xhttp.open("GET", "/jsonendpoint2", true);
    xhttp.send();
    console.log("Leaving AJAX run");
}

</script>
</head>
<body>
    <h1>HTML Page with AJAX</h1>
    <br>
    <button onclick="run1()"> GetAjaxData </button>
    <br>
    <br>
    <textarea id="ta" style="width:300;height:300">
        This is some static content in textarea
    </textarea>
    <br>
    <br>
    <button onclick="run2()"> Populate Form </button>
    <br>
    <br>
```



```
<form action="/hello">
  <table>
    <tr>
      <td>
        <label style="padding-right:10px"> Message
      </td>
      <td>
        <input name="message" value="0"
id="message" type="text"/>
      </td>
    </tr>
    <tr>
      <td>
        <label style="padding-right:10px"> Times
      </td>
      <td>
        <input name="times" value="0" id="times"
type="text"/>
      </td>
    </tr>
    <tr>
      <td>
        <input type="submit" value="Submit"/>
      </td>
    </tr>
  </table>
</form>
</body>
</html>
```

Add : 25, Patel Shopping Center, Sai Nath Road, Malad (west) ,Opp malad subway , Mumbai 64 Contact : 9820396074, 022-28809398, 9820860292
Copyright © 2011-2020 Rajesh Patkar, All rights reserved.

