



# Amazon.com 273

## Address

### POST Add Address

http://localhost:3000/write/customer/profile/address/1

#### BODY raw

```
{
  "name": "kowshhal",
  "address1": "190 ryland street",
  "address2": "Apt 5312",
  "city": "san Jose",
  "state": "california",
  "country": "United Sttes",
  "zipCode": "95110",
  "phoneNumber": "6693007583"
}
```

#### Example Request

Add Address

```
curl --location --request POST 'http://localhost:3000/write/customer/profile/address/1' \
--data-raw '{
  "name": "kowshhal",
  "address1": "190 ryland street",
  "address2": "Apt 5312",
  "city": "san Jose",
  "state": "california",
  "country": "United Sttes",
  "zipCode": "95110",
  "phoneNumber": "6693007583"
}
```

[Documentation Settings](#)

[View More](#)

## DEL delete address

http://localhost:3000/write/customer/profile/address/1

### Example Request

delete address

```
curl --location --request DELETE 'http://localhost:3000/write/customer/profile/address/1'
```

## PUT update Address

http://localhost:3000/write/customer/profile/address/1/1

### BODY raw

```
{
  "name": "kowshhal",
  "address1": "190 ryland street",
  "address2": "Apt 5312",
  "city": "san Jose",
  "state": "california",
  "country": "United States of Americ",
  "zipCode": "95110",
  "phoneNumber": "6693007583"
}
```



## Example Request

update Address

```
curl --location --request PUT 'http://localhost:3000/write/customer/profile/address/1/1' \
--data-raw '{
  "name": "kowshhal",
  "address1": "190 ryland street",
  "address2": "Apt 5312",
  "city": "san Jose",
  "state": "california",
  "country": "United States of Americ",
  "zipCode": "95110",
  "phoneNumber": "6693007583"
}
```

[View More](#)

# Signup

## POST signup

`http://localhost:3000/write/signup`

## BODY raw

```
{
  "name": "kowshhal",
  "email": "kowshhhal@gmail.com",
  "password": "qwerty",
  "userType": "customer"
}
```

## Example Request

signup

```
curl --location --request POST 'http://localhost:3000/write/signup' \  
--data-raw '{  
  "name": "kowshhal",  
  "email": "kowshhhal@gmail.com",  
  "password": "qwerty",  
  "userType": "customer"  
}'
```

[Documentation Settings](#) ▼

## POST SignUp

http://localhost:3000/write/signup

### HEADERS

#### Content-Type

application/json

### BODY raw

```
{  
  "name": "Apple",  
  "email": "apple@apple.com",  
  "password": "qwerty",  
  "userType": "seller"  
}
```

### Example Request

#### SignUp

```
curl --location --request POST 'http://localhost:3000/write/signup' \  
--header 'Content-Type: application/json' \  
--data-raw '{  
  "name": "Apple",  
  "email": "apple@apple.com",  
  "password": "qwerty",  
  "userType": "seller"  
}'
```



# Login

## POST login

http://localhost:3000/write/login

### BODY raw

```
{  
  "email": "kowshhhal@gmail.com",  
  "password": "qwerty"  
}
```

### Example Request

login

```
curl --location --request POST 'http://localhost:3000/write/login' \  
--data-raw '{  
  "email": "kowshhhal@gmail.com",  
  "password": "qwerty"  
}'
```

## POST Login

http://localhost:3000/write/login

### HEADERS

#### Content-Type

application/json

### BODY raw

```
{  
  "email": "appple@appple.com",  
  "password": "qwerty"  
}
```

[Documentation Settings](#)

#### Example Request

Login

```
curl --location --request POST 'http://localhost:3000/write/login' \  
--header 'Content-Type: application/json' \  
--data-raw '{  
  "email": "appple@appple.com",  
  "password": "qwerty"  
}'
```

## Card

### PUT Update Card

<http://localhost:3000/write/customer/profile/cards/1>

#### BODY raw

```
{  
  "name": "kowshhal",  
  "cardNumber": "989887798989",  
  "expirationDate": "05/2024",  
  "cvv": "457"  
}
```

#### Example Request

Update Card

≡ `curl --location --request PUT 'http://localhost:3000/write/customer/profile/cards/1' \`  
`--data-raw '{`  
 `"name": "kowshhal",`  
 `"cardNumber": "989887798989",`  
 `"expirationDate": "05/2024",`  
 `"cvv": "457"`  
`}`

Documentation Settings ▼

## DEL Delete Card

`http://localhost:3000/write/customer/profile/cards/1`

### Example Request

Delete Card

```
curl --location --request DELETE 'http://localhost:3000/write/customer/profile/cards/1'
```

## POST Add Card

`http://localhost:3000/write/customer/profile/cards/1`

### BODY raw

```
{  
  "name": "kowshhal",  
  "cardNumber": "989887798989",  
  "expirationDate": "05/2024",  
  "cvv": "456"  
}
```

### Example Request

Add Card

≡ `curl --location --request POST 'http://localhost:3000/write/customer/profile/cards/1' \`  
`--data-raw '{`  
 `"name": "kowshhal",`  
 `"cardNumber": "989887798989",`  
 `"expirationDate": "05/2024",`  
 `"cvv": "456"`  
`}`

Documentation Settings ▼

# Customer Profile

## GET get profile

`https://jkinwl2fhd.execute-api.us-west-2.amazonaws.com/prod/read/customer/profile/1`

### Example Request

get profile

`curl --location --request GET 'https://jkinwl2fhd.execute-api.us-west-2.amazonaws.com/prod/read/`

## PUT update profile

`http://localhost:3000/read/customer/profile/1`

### Example Request

update profile

`curl --location --request PUT 'http://localhost:3000/read/customer/profile/1'`





# comments

## POST add comments

```
http://localhost:3000/write/comments/1/1
```

### BODY raw

```
{  
  "comment": "its a good item"  
}
```

### Example Request

add comments

```
curl --location --request POST 'http://localhost:3000/write/comments/1/1' \  
--data-raw '{  
  "comment": "its a good item"  
}'
```

## PUT update comments

```
http://localhost:3000/write/comments/1
```

### BODY raw

```
{  
  "comment": "its an Awesome item"  
}
```

### Example Request

[Documentation Settings](#) ▼

update comments

```
curl --location --request PUT 'http://localhost:3000/write/comments/1' \  
--data-raw '{  
  "comment":"its an Awesome item"  
}'
```

## DEL delete comments

http://localhost:3000/write/comments/1

### Example Request

delete comments

```
curl --location --request DELETE 'http://localhost:3000/write/comments/1'
```

## GET get comments by customer id

http://localhost:3000/read/customer/comments/1

### Example Request

get comments by customer id

```
curl --location --request GET 'http://localhost:3000/read/customer/comments/1'
```

## GET Get comments by product id

http://localhost:3000/read/customer/comments/product/1



## Example Request

Get comments by product id

```
curl --location --request GET 'http://localhost:3000/read/customer/comments/product/1'
```

# cart

## POST create product in cart

```
http://localhost:3000/write/customer/cart/1/1
```

## BODY raw

```
{
  "quantity": "3",
  "flag": "0",
  "gift": "0"
}
```

## Example Request

create product in cart

```
curl --location --request POST 'http://localhost:3000/write/customer/cart/1/1' \
--data-raw '{
  "quantity": "3",
  "flag": "0",
  "gift": "0"
}'
```

## PUT update a product in cart

http://localhost:3000/write/customer/cart/1/1

Documentation Settings ▼

BODY raw

```
{  
  "flag": "1"  
}
```

Example Request

update a product in cart

```
curl --location --request PUT 'http://localhost:3000/write/customer/cart/1/1' \  
--data-raw '{  
  "flag": "1"  
}'
```

## DEL delete a product in cart

http://localhost:3000/write/customer/cart/1/1

Example Request

delete a product in cart

```
curl --location --request DELETE 'http://localhost:3000/write/customer/cart/1/1'
```

## GET get a cart by customer Id

http://localhost:3000/read/customer/cart/1



## Example Request

get a cart by customer Id

```
curl --location --request GET 'http://localhost:3000/read/customer/cart/1'
```

## GET Save to later get by Id

http://localhost:3000/read/customer/cart/saveToLater/1

## Example Request

Save to later get by Id

```
curl --location --request GET 'http://localhost:3000/read/customer/cart/saveToLater/1'
```

# Votes

## POST Add ratings

http://localhost:3000/write/customer/profile/votes/1/2

## BODY raw

```
{  
  "rating": "3"  
}
```

### Example Request

[Documentation Settings](#) ▼

Add ratings

```
curl --location --request POST 'http://localhost:3000/write/customer/profile/votes/1/2' \  
--data-raw '{  
  "rating": "3"  
}'
```

## PUT Update rating

http://localhost:3000/write/customer/profile/votes/1

BODY raw

```
{  
  "rating": "4"  
}
```

### Example Request

Update rating


```
curl --location --request PUT 'http://localhost:3000/write/customer/profile/votes/1' \  
--data-raw '{  
  "rating": "4"  
}'
```

## GET Get votes by customer id

http://localhost:3000/read/customer/votes/1

### Example Request

Get votes by customer id

 `curl --location --request GET 'http://localhost:3000/read/customer/votes/1'`[Documentation Settings](#) ▼

# product

## POST Create Products

`http://localhost:3000/write/products/1`

### HEADERS

#### Content-Type

`application/json`

### BODY raw

```
{
  "productName": "Iphone X",
  "sellerName": "Apple",
  "price": "1000",
  "description": "Iphone SE 2020",
  "categoryId": "1",
  "inventory": "100"
}
```

### Example Request

#### Create Products

```
curl --location --request POST 'http://localhost:3000/write/products/1' \
--header 'Content-Type: application/json' \
--data-raw '{
  "productName": "Iphone X",
  "sellerName": "Apple",
  "price": "1000",
  "description": "Iphone SE 2020",
  "categoryId": "1",
  "inventory": "100"
}'
```



## GET get product by id

```
http://localhost:3000/read/products/1
```

### Example Request

```
get product by id
```

```
curl --location --request GET 'http://localhost:3000/read/products/1'
```

## GET Get All Products

```
http://localhost:3000/read/products/
```

### Example Request

```
Get All Products
```

```
curl --location --request GET 'http://localhost:3000/read/products/'
```

## GET get products by seller Id

```
http://localhost:3000/read/seller/product/1
```

### Example Request

```
get products by seller Id
```



≡ curl --location --request GET 'http://localhost:3000/read/seller/product/1' Documentation Settings ▼

## PUT Update Product

http://localhost:3000/write/products/3

### BODY raw

```
{
  "productName": "Iphone X",
  "sellerName": "Apple",
  "price": "1000",
  "description": "Iphone SE 2020",
  "categoryId": "1",
  "inventory": "1000"
}
```

### Example Request

#### Update Product

```
curl --location --request PUT 'http://localhost:3000/write/products/3' \
--data-raw '{
  "productName": "Iphone X",
  "sellerName": "Apple",
  "price": "1000",
  "description": "Iphone SE 2020",
  "categoryId": "1",
  "inventory": "1000"
}'
```

## DEL Delete product

http://localhost:3000/write/products/3

Example Request

Documentation Settings ▼

Delete product

```
curl --location --request DELETE 'http://localhost:3000/write/products/3'
```

# seller

## GET Get all Seller profile

http://localhost:3000/read/seller/profile/

Example Request

Get all Seller profile

```
curl --location --request GET 'http://localhost:3000/read/seller/profile/'
```

# Category

## GET Get category

http://localhost:3000/read/admin/category

Example Request

Get category

≡ curl --location --request GET 'http://localhost:3000/read/admin/category' Documentation Settings ▼

## POST Create Category

http://localhost:3000/write/admin/category

### HEADERS

#### Content-Type

application/json

### BODY raw

```
{
  "categoryName": "electronics"
}
```

### Example Request

#### Create Category

```
curl --location --request POST 'http://localhost:3000/write/admin/category' \
--header 'Content-Type: application/json' \
--data-raw '{
  "categoryName": "electronics"
}'
```

## PUT Update Category

### BODY raw

```
{
  "categoryName": "electronics"
}
```



## Example Request

Update Category

```
curl --location --request PUT '' \  
--data-raw '{  
  "categoryName": "electronics"  
}'
```

## GET get category by Id

```
http://localhost:3000/read/admin/category/1
```

## Example Request

get category by Id

```
curl --location --request GET 'http://localhost:3000/read/admin/category/1'
```

# Orders

## PUT Update order by Seller

```
http://localhost:3000/write/seller/orders/5e9f7cbb982ce2721f4dfdc4
```

## HEADERS

**Content-Type**

application/json

## BODY raw

```
{
  "productId": "1",
  "orderStatus": "open",
  "orderUpdateItem": {
    "deliveryStatus": "shipped"
  }
}
```

[Documentation Settings](#)

#### Example Request

Update order by Seller

```
curl --location --request PUT 'http://localhost:3000/write/seller/orders/5e9f7cbb982ce2721f4dfdc4' \
--header 'Content-Type: application/json' \
--data-raw '{
  "productId": "1",
  "orderStatus": "open",
  "orderUpdateItem": {
    "deliveryStatus": "shipped"
  }
}'
```

## GET Get All orders by Admin

<http://localhost:3000/read/admin/orders>

#### Example Request

Get All orders by Admin

```
curl --location --request GET 'http://localhost:3000/read/admin/orders'
```

## GET Get Order by Id

<http://localhost:3000/read/customer/orders/5e9f7cbb982ce2721f4dfdc4>



## Example Request

Get Order by Id

```
curl --location --request GET 'http://localhost:3000/read/customer/orders/5e9f7cbb982ce2721f4dfc'
```

## POST Create Orders

```
http://localhost:3000/write/customer/orders/1
```

## HEADERS

**Content-Type**

application/json

## BODY raw

```
{
  "customerId": "1",
  "customerName": "Yash",
  "billing": {
    "name": "Yash",
    "cardNumber": "4242424242424242",
    "totalPrice": "100"
  },
  "shippingAddress": {
    "addressId": "1",
```

[View More](#)

## Example Request

Create Orders

```
curl --location --request POST 'http://localhost:3000/write/customer/orders/1' \
--header 'Content-Type: application/json' \
--data-raw '{
  "customerId": "1",
  "customerName": "Yash",
  "billing": {
    "name": "Yash",
    "cardNumber": "4242424242424242",
    "totalPrice": "100"
  },
  "totalPrice": "100"
}
```

[Documentation Settings](#) ▼

[View More](#)

## GET Get Order by customer Id

http://localhost:3000/read/customer/orders/1

### Example Request

Get Order by customer Id

```
curl --location --request GET 'http://localhost:3000/read/customer/orders/1'
```

# Stats

## GET Top 5 Sellers

http://localhost:3000/read/admin/stats/top/seller

### Example Request

Top 5 Sellers

```
curl --location --request GET 'http://localhost:3000/read/admin/stats/top/seller'
```



## GET Top 5 Customers

```
http://localhost:3000/read/admin/stats/top/customer
```

### Example Request

Top 5 Customers

```
curl --location --request GET 'http://localhost:3000/read/admin/stats/top/customer'
```

# upload

## PUT upload customer pic

```
http://localhost:3000/write/customer/profile/1
```

BODY formdata

**upl**


### Example Request

upload customer pic

```
curl --location --request PUT 'http://localhost:3000/write/customer/profile/1' \  
--form 'upl=@/path/to/file'
```

## PUT Upload seller pic



 `http://localhost:3000/write/seller/profile/1`[Documentation Settings](#) ▼

BODY formdata

**upl**

## Example Request

Upload seller pic

```
curl --location --request PUT 'http://localhost:3000/write/seller/profile/1' \  
--form 'upl=@/path/to/file'
```