

Language processing: introduction to compiler construction

Andy D. Pimentel

Computer Systems Architecture group

andy@science.uva.nl

<http://www.science.uva.nl/~andy/taalverwerking.html>

About this course

- This part will address compilers for programming languages
- Depth-first approach
 - Instead of covering all compiler aspects very briefly, we focus on particular compiler stages
 - Focus: optimization and compiler back issues
- This course is complementary to the compiler course at the VU
- Grading: (heavy) practical assignment and one or two take-home assignments

About this course (cont'd)

- Book
 - Recommended, not compulsory: Seti, Aho and Ullman, "Compilers Principles, Techniques and Tools" (the Dragon book)
 - Old book, but still more than sufficient
 - Copies of relevant chapters can be found in the library
- Sheets are available at the website
- Idem for practical/take-home assignments, deadlines, etc.

Topics

- Compiler introduction
 - General organization
- Scanning & parsing
 - From a practical viewpoint: LEX and YACC
- Intermediate formats
- Optimization: techniques and algorithms
 - Local/peephole optimizations
 - Global and loop optimizations
 - Recognizing loops
 - Dataflow analysis
 - Alias analysis

Topics (cont'd)

- Code generation
 - Instruction selection
 - Register allocation
 - Instruction scheduling: improving ILP
- Source-level optimizations
 - Optimizations for cache behavior


Compilers: general organization

Compilers: organization




- Frontend
 - Dependent on source language
 - Lexical analysis
 - Parsing
 - Semantic analysis (e.g., type checking)

Compilers: organization (cont'd)



- Optimizer
 - Independent part of compiler
 - Different optimizations possible
 - IR to IR translation
 - Can be very computational intensive part

Compilers: organization (cont'd)




- Backend
 - Dependent on target processor
 - Code selection
 - Code scheduling
 - Register allocation
 - Peephole optimization

Frontend

Introduction to parsing
using LEX and YACC

Overview

- Writing a compiler is difficult requiring lots of time and effort
- Construction of the scanner and parser is routine enough that the process may be automated



YACC

- What is YACC ?
 - **Tool which will produce a parser for a given grammar.**
 - YACC (Yet Another Compiler Compiler) is a program designed to compile a LALR(1) grammar and to produce the source code of the syntactic analyzer of the language produced by this grammar
 - Input is a grammar (rules) and actions to take upon recognizing a rule
 - Output is a C program and optionally a header file of tokens

LEX

- Lex is a scanner generator
 - Input is description of patterns and actions
 - Output is a C program which contains a function `yylex()` which, when called, matches patterns and performs actions per input
 - Typically, the generated scanner performs lexical analysis and produces tokens for the (YACC-generated) parser

LEX and YACC: a team

LEX
yylex()


YACC
yyparse()

How to work ?

Input programs

12 + 26

LEX and YACC: a team




Availability

- lex, yacc on most UNIX systems
- bison: a yacc replacement from GNU
- flex: *fast lexical* analyzer
- BSD yacc
- Windows/MS-DOS versions exist

YACC

Basic Operational Sequence



YACC File Format

Definitions

%%

Rules

%%

Supplementary Code

The identical LEX format was
actually taken from this...

Rules Section

- Is a grammar
- Example

```
expr : expr '+' term | term;  
term : term '*' factor | factor;  
factor : '(' expr ')' | ID | NUM;
```

Rules Section

- Normally written like this
- Example:

```
expr    : expr '+' term
        | term
        ;

term     : term '*' factor
        | factor
        ;

factor  : '(' expr ')'
        | ID
        | NUM
        ;
```

Definitions Section

Example

```
%{  
#include <stdio.h>  
#include <stdlib.h>  
%}  
%token ID NUM  
%start expr
```

This is called a
terminal

The start
symbol
(non-terminal)

Sidebar

- LEX produces a function called `yylex()`
- YACC produces a function called `yyparse()`
- `yyparse()` expects to be able to call `yylex()`
- How to get `yylex()`?
- Write your own!
- If you don't want to write your own: Use LEX!!!

Sidebar

```
int yylex()  
{  
    if(it's a num)  
        return NUM;  
    else if(it's an id)  
        return ID;  
    else if(parsing is done)  
        return 0;  
    else if(it's an error)  
        return -1;  
}
```

Semantic actions

```
expr : expr '+' term      { $$ = $1 + $3; }
    | term                { $$ = $1; }
    ;

term : term '*' factor    { $$ = $1 * $3; }
    | factor              { $$ = $1; }
    ;

factor : '(' expr ')'     { $$ = $2; }
      | ID
      | NUM
      ;
```


Semantic actions (cont'd)

\$1 


```
expr : expr '+' term      { $$ = $1 + $3; }  
      | term                { $$ = $1; }  
      ;  
  
term : term '*' factor     { $$ = $1 * $3; }  
      | factor              { $$ = $1; }  
      ;  
  
factor : '(' expr ')'      { $$ = $2; }  
        | ID  
        | NUM  
        ;
```

Semantic actions (cont'd)

```
expr : expr '+' term    { $$ = $1 + $3; }
      | term             { $$ = $1; }
      ;


term  : term '*' factor  { $$ = $1 * $3; }
      | factor           { $$ = $1; }
      ;

factor : '(' expr ')'    { $$ = $2; }
        | ID
        | NUM
        ;
```



Semantic actions (cont'd)

```
expr : expr '+' term      { $$ = $1 + $3; }  
    | term                 { $$ = $1; }  
    ;  
term : term '*' factor    { $$ = $1 * $3; }  
    | factor               { $$ = $1; }  
    ;  
factor : '(' expr ')'      { $$ = $2; }  
    | ID  
    | NUM  
    ;
```



Default: $$$ = \1 ;


Bored, lonely? Try this!

```
yacc -d gram.y
```

- Will produce:

```
y.tab.h
```

Look at this and you'll
never be unhappy again!



```
yacc -v gram.y
```

- Will produce:

```
y.output
```

Shows "State Machine"®



Example: LEX

```
%{
#include <stdio.h>
#include "y.tab.h"
%}

id      [_a-zA-Z][_a-zA-Z0-9]*
wspc    [ \t\n]+
semi    [;]
comma   [,]

%%

int      { return INT; }
char     { return CHAR; }
float    { return FLOAT; }
{comma}  { return COMMA; }      /* Necessary? */
{semi}   { return SEMI; }
{id}     { return ID; }
{wspc}   { ; }
```

Example: Definitions

```
%{  
#include <stdio.h>  
#include <stdlib.h>  
%}  
%start  line  
%token  CHAR, COMMA, FLOAT, ID, INT, SEMI  
%%
```

Example: Rules

```
/* This production is not part of the "official"  
 * grammar. It's primary purpose is to recover from  
 * parser errors, so it's probably best if you leave  
 * it here. */
```

```
line : /* lambda */  
    | line decl  
    | line error {  
        printf("Failure :-(\n");  
        yyerrok;  
        yyclearin;  
    }  
    ;
```

Example: Rules

```
decl : type ID list { printf("Success!\n"); } ;
```

```
list : COMMA ID list  
      | SEMI  
      ;
```

```
type : INT | CHAR | FLOAT  
      ;
```

```
%%
```


Example: Supplementary Code

```
extern FILE *yyin;
main()
{
    do {
        yyparse();
    } while(!feof(yyin));
}
yyerror(char *s)
{
    /* Don't have to do anything! */
}
```

Bored, lonely? Try this!

```
yacc -d decl.y
```

- Produced

```
y.tab.h
```

```
# define CHAR 257
```

```
# define COMMA 258
```

```
# define FLOAT 259
```

```
# define ID 260
```

```
# define INT 261
```

```
# define SEMI 262
```

Symbol attributes

- Back to attribute grammars...
- Every symbol can have a value
 - Might be a numeric quantity in case of a number (42)
 - Might be a pointer to a string ("Hello, World!")
 - Might be a pointer to a symbol table entry in case of a variable
- When using LEX we put the value into `yylval`
 - In complex situations `yylval` is a union
- Typical LEX code:

```
[0-9]+      {yylval = atoi(yytext); return NUM}
```

Symbol attributes (cont'd)

- YACC allows symbols to have multiple types of value symbols

```
%union {  
    double dval;  
    int     vblno;  
    char*   strval;  
}
```

Symbol attributes (cont'd)

```
%union {  
    double dval;  
    int     vblno;  
    char*   strval;  
}
```

yacc -d



```
y.tab.h  
...  
extern YYSTYPE yylval;
```

```
[0-9]+ { yylval.vblno = atoi(yytext);  
        return NUM;}  
[A-z]+ { yylval.strval = strdup(yytext);  
        return STRING;}
```



LEX file
include "y.tab.h"

Precedence / Association

```
expr: expr '-' expr
     | expr '*' expr
     | expr '<' expr
     | '(' expr ')'
     ...
;
```

(1) $1 - 2 - 3$

(2) $1 - 2 * 3$

1. $1-2-3 = (1-2)-3$? or $1-(2-3)$?

Define '-' operator is left-association.

2. $1-2*3 = 1-(2*3)$

Define "*" operator is precedent to "-" operator

Precedence / Association

```
%left  '+' '-'  
%left  '*' '/'  
%noassoc UMINUS
```

```
expr : expr '+' expr { $$ = $1 + $3; }  
    | expr '-' expr { $$ = $1 - $3; }  
    | expr '*' expr { $$ = $1 * $3; }  
    | expr '/' expr { if($3==0)  
                        yyerror("divide 0");  
                        else  
                        $$ = $1 / $3;  
                      }  
    | '-' expr %prec UMINUS { $$ = -$2; }
```

Precedence / Association

%right '='

%left '<' '>' NE LE GE

%left '+' '-'

%left '*' '/'




highest precedence

Big trick

Getting YACC & LEX to work together!

LEX & YACC



Building Example

- Suppose you have a lex file called `scanner.l` and a yacc file called `decl.y` and want `parser`
- Steps to build...

```
lex scanner.l
```

```
yacc -d decl.y
```

```
gcc -c lex.yy.c y.tab.c
```

```
gcc -c parser lex.yy.o y.tab.o -ll
```

Note: scanner should include in the definitions section: `#include "y.tab.h"`

YACC

- Rules may be recursive
- Rules may be ambiguous
- Uses bottom-up Shift/Reduce parsing
 - Get a token
 - Push onto stack
 - Can it be reduced (How do we know?)
 - If yes: Reduce using a rule
 - If no: Get another token
- YACC cannot look ahead more than one token

Shift and reducing

```
stmt: stmt ';' stmt  
      | NAME '=' exp
```

```
stack:  
<empty>
```

```
exp: exp '+' exp  
     | exp '-' exp  
     | NAME  
     | NUMBER
```

```
input:  
a = 7; b = 3 + a + 2
```

Shift and reducing

```
stmt: stmt ';' stmt
      | NAME '=' exp
```

```
exp: exp '+' exp
     | exp '-' exp
     | NAME
     | NUMBER
```

SHIFT!

stack:

NAME

input:

= 7; b = 3 + a + 2

Shift and reducing

```
stmt: stmt ';' stmt
      | NAME '=' exp
```

```
exp: exp '+' exp
     | exp '-' exp
     | NAME
     | NUMBER
```

SHIFT!

stack:

NAME '='

input:

7; b = 3 + a + 2

Shift and reducing

```
stmt: stmt ';' stmt
      | NAME '=' exp
```

```
exp: exp '+' exp
     | exp '-' exp
     | NAME
     | NUMBER
```

SHIFT!

stack:

NAME '=' 7

input:

; b = 3 + a + 2

Shift and reducing

```
stmt: stmt ';' stmt
      | NAME '=' exp
```

```
exp: exp '+' exp
     | exp '-' exp
     | NAME
     | NUMBER
```

REDUCE!

stack:

NAME '=' exp

input:

; b = 3 + a + 2

Shift and reducing

```
stmt: stmt ';' stmt
      | NAME '=' exp
```

```
exp: exp '+' exp
     | exp '-' exp
     | NAME
     | NUMBER
```

REDUCE!

stack:

stmt

input:

; b = 3 + a + 2

Shift and reducing

```
stmt: stmt ';' stmt
      | NAME '=' exp
```

```
exp: exp '+' exp
     | exp '-' exp
     | NAME
     | NUMBER
```

SHIFT!

stack:

stmt ';'

input:

b = 3 + a + 2

Shift and reducing

```
stmt: stmt ';' stmt
      | NAME '=' exp
```

```
exp: exp '+' exp
     | exp '-' exp
     | NAME
     | NUMBER
```

SHIFT!

stack:

stmt ';' NAME

input:

= 3 + a + 2

Shift and reducing

```
stmt: stmt ';' stmt
      | NAME '=' exp
```

```
exp: exp '+' exp
     | exp '-' exp
     | NAME
     | NUMBER
```

SHIFT!

stack:

stmt ';' NAME '='

input:

3 + a + 2

Shift and reducing

```
stmt: stmt ';' stmt
      | NAME '=' exp
```

```
exp: exp '+' exp
     | exp '-' exp
     | NAME
     | NUMBER
```

SHIFT!

stack:

```
stmt ';' NAME '='
NUMBER
```

input:

```
+ a + 2
```

Shift and reducing

```
stmt: stmt ';' stmt
      | NAME '=' exp
```

```
exp: exp '+' exp
     | exp '-' exp
     | NAME
     | NUMBER
```

REDUCE!

```
stack:
stmt ';' NAME '='
exp
```

```
input:
+ a + 2
```

Shift and reducing

```
stmt: stmt ';' stmt
      | NAME '=' exp
```

```
exp: exp '+' exp
     | exp '-' exp
     | NAME
     | NUMBER
```

SHIFT!

stack:

```
stmt ';' NAME '='
exp '+'
```

input:

```
a + 2
```


Shift and reducing

```
stmt: stmt ';' stmt
      | NAME '=' exp
```

```
exp: exp '+' exp
     | exp '-' exp
     | NAME
     | NUMBER
```

SHIFT!

stack:

```
stmt ';' NAME '='
exp '+' NAME
```

input:
+ 2

Shift and reducing

```
stmt: stmt ';' stmt
      | NAME '=' exp
```

```
exp: exp '+' exp
     | exp '-' exp
     | NAME
     | NUMBER
```

REDUCE!

stack:

```
stmt ';' NAME '='
exp '+' exp
```

input:
+ 2

Shift and reducing

```
stmt: stmt ';' stmt
      | NAME '=' exp
```

```
exp: exp '+' exp
     | exp '-' exp
     | NAME
     | NUMBER
```

REDUCE!

```
stack:
stmt ';' NAME '='
exp
```

```
input:
+ 2
```

Shift and reducing

```
stmt: stmt ';' stmt
      | NAME '=' exp
```

```
exp: exp '+' exp
     | exp '-' exp
     | NAME
     | NUMBER
```

SHIFT!

stack:

```
stmt ';' NAME '='
exp '+'
```

input:
2

Shift and reducing

```
stmt: stmt ';' stmt
      | NAME '=' exp
```

```
exp: exp '+' exp
     | exp '-' exp
     | NAME
     | NUMBER
```

SHIFT!

stack:

```
stmt ';' NAME '='
exp '+' NUMBER
```

input:
<empty>

Shift and reducing

```
stmt: stmt ';' stmt
      | NAME '=' exp
```

```
exp: exp '+' exp
     | exp '-' exp
     | NAME
     | NUMBER
```

REDUCE!

```
stack:
stmt ';' NAME '='
exp '+' exp
```

```
input:
<empty>
```

Shift and reducing

```
stmt: stmt ';' stmt
      | NAME '=' exp
```

```
exp: exp '+' exp
     | exp '-' exp
     | NAME
     | NUMBER
```

REDUCE!

stack:

```
stmt ';' NAME '='
exp
```

input:
<empty>

Shift and reducing

```
stmt: stmt ';' stmt
      | NAME '=' exp
```

```
exp: exp '+' exp
     | exp '-' exp
     | NAME
     | NUMBER
```

REDUCE!

```
stack:
stmt ';' stmt
```

```
input:
<empty>
```


Shift and reducing

```
stmt: stmt ';' stmt
      | NAME '=' exp
```

```
exp: exp '+' exp
     | exp '-' exp
     | NAME
     | NUMBER
```

REDUCE!

stack:

stmt

input:
<empty>

Shift and reducing

```
stmt: stmt ';' stmt  
      | NAME '=' exp
```

```
exp: exp '+' exp  
     | exp '-' exp  
     | NAME  
     | NUMBER
```

DONE!

stack:

stmt

input:

<empty>

IF-ELSE Ambiguity

- Consider following rule:

```
stmt:  
  IF expr stmt  
  | IF expr stmt ELSE stmt  
  ...
```

Following state : **IF expr IF expr stmt . ELSE stmt**

- Two possible derivations:

```
IF expr IF expr stmt . ELSE stmt  
IF expr IF expr stmt ELSE . stmt  
IF expr IF expr stmt ELSE stmt .  
      IF expr stmt
```

```
IF expr IF expr stmt . ELSE stmt  
      IF expr stmt . ELSE stmt  
IF expr stmt ELSE . stmt  
IF expr stmt ELSE stmt .
```

IF-ELSE Ambiguity

- It is a shift/reduce conflict
- YACC will always do shift first
- Solution 1 : re-write grammar

```
stmt      : matched
           | unmatched
           ;
matched: other_stmt
        | IF expr THEN matched ELSE matched
        ;
unmatched: IF expr THEN stmt
          | IF expr THEN matched ELSE unmatched
          ;
```

IF-ELSE Ambiguity

- Solution 2:

```
%nonassoc IFX  
%nonassoc ELSE
```

```
stmt:
```

```
    IF expr stmt %prec IFX  
    | IF expr stmt ELSE stmt
```

the rule has the
same precedence as
token IFX

Shift/Reduce Conflicts

- **shift/reduce conflict**
 - occurs when a grammar is written in such a way that a decision between shifting and reducing can not be made.
 - e.g.: IF-ELSE ambiguity
- To resolve this conflict, **YACC will choose to shift**

Reduce/Reduce Conflicts

- ***Reduce/Reduce Conflicts:***
start : expr | stmt
 ;
expr : CONSTANT;
stmt : CONSTANT;
- YACC (Bison) resolves the conflict by reducing using the rule that occurs earlier in the grammar. **NOT GOOD!!**
- So, modify grammar to eliminate them

Error Messages

- Bad error message:
 - Syntax error
 - Compiler needs to give programmer a good advice
- It is better to track the line number in LEX:

```
void yyerror(char *s)
{
    fprintf(stderr, "line %d: %s\n", yylineno, s);
}
```


Recursive Grammar

- Left recursion

```
list:  
    item  
    | list ',' item  
    ;
```

- Right recursion

```
list:  
    item  
    | item ',' list  
    ;
```

- LR parser prefers left recursion
- LL parser prefers right recursion

YACC Example

- Taken from LEX & YACC
- Simple calculator

```
a = 4 + 6
```

```
a
```

```
a=10
```

```
b = 7
```

```
c = a + b
```

```
c
```

```
c = 17
```

```
pressure = (78 + 34) * 16.4
```

```
$
```

Grammar

```
expression ::= expression '+' term |  
              expression '-' term |  
              term
```

```
term          ::= term '*' factor |  
                term '/' factor |  
                factor
```

```
factor        ::= '(' expression ')' |  
                '-' factor |  
                NUMBER |  
                NAME
```

parser.h

```

/*
 *Header for calculator program
 */

#define NSYMS 20 /* maximum number
                  of symbols */

struct symtab {
    char *name;
    double value;
} symtab[NSYMS];

struct symtab *symlook();

```

parser.h

0	name	value
1	name	value
2	name	value
3	name	value
4	name	value
5	name	value
6	name	value
7	name	value
8	name	value
9	name	value
10	name	value
11	name	value
12	name	value
13	name	value
14	name	value

•
•
•

parser.y

```
%{  
#include "parser.h"  
#include <string.h>  
%}  
  
%union {  
    double dval;  
    struct symtab *symp;  
}  
%token <symp> NAME  
%token <dval> NUMBER  
  
%type <dval> expression  
%type <dval> term  
%type <dval> factor  
%%
```

parser.y

```

statement_list:  statement '\n'
                |  statement_list statement '\n'
                ;

statement:  NAME '=' expression      { $1->value = $3; }
          |  expression              { printf("= %g\n", $1); }
          ;

expression: expression '+' term { $$ = $1 + $3; }
          | expression '-' term { $$ = $1 - $3; }
          | term
          ;

```

parser.y


```

term:  term '*' factor { $$ = $1 * $3; }
      |  term '/' factor { if($3 == 0.0)
                           yyerror("divide by zero");
                           else
                             $$ = $1 / $3;
                           }
      |  factor
      ;

```

```

factor: '(' expression ')' { $$ = $2; }
       | '-' factor        { $$ = -$2; }
       | NUMBER
       | NAME               { $$ = $1->value; }
       ;

```

%%

parser.y

```

/* look up a symbol table entry, add if not present */
struct symtab *symlook(char *s) {
    char *p;
    struct symtab *sp;
    for(sp = symtab; sp < &symtab[NSYMS]; sp++) {
        /* is it already here? */
        if(sp->name && !strcmp(sp->name, s))
            return sp;
        if(!sp->name) { /* is it free */
            sp->name = strdup(s);
            return sp;
        }
        /* otherwise continue to next */
    }
    yyerror("Too many symbols");
    exit(1); /* cannot continue */
} /* symlook */

```

parser.y

```
yyerror(char *s)
{
    printf( "yyerror: %s\n", s);
}
```

```
typedef union  
{  
    double dval;  
    struct symtab *symp;  
} YYSTYPE;
```

```
extern YYSTYPE yylval;
```

```
# define NAME 257
```

```
# define NUMBER 258
```

y.tab.h

calclexer.l

```
%{  
#include "y.tab.h"  
#include "parser.h"  
#include <math.h>  
%}  
%%
```

calclex.er.l

```

%%
([0-9]+|([0-9]*\.[0-9]+)([eE][-+]?[0-9]+)?) {
    yylval.dval = atof(yytext);
    return NUMBER;
}

[ \t] ;          /* ignore white space */

[A-Za-z][A-Za-z0-9]* { /* return symbol pointer */
    yylval.symp = symlook(yytext);
    return NAME;
}

"$" { return 0; /* end of input */ }

\n|. return yytext[0];
%%

```

calclex.er.l

Makefile

Makefile

```
LEX = lex
```

```
YACC = yacc
```

```
CC = gcc
```

```
calcu:      y.tab.o lex.yy.o
```

```
    $(CC) -o calcu y.tab.o lex.yy.o -ly -ll
```

```
y.tab.c y.tab.h: parser.y
```

```
    $(YACC) -d parser.y
```

```
y.tab.o: y.tab.c parser.h
```

```
    $(CC) -c y.tab.c
```

```
lex.yy.o: y.tab.h lex.yy.c
```

```
    $(CC) -c lex.yy.c
```

```
lex.yy.c: calclexer.l parser.h
```

```
    $(LEX) calclexer.l
```

```
clean:
```

```
    rm *.o
```

```
    rm *.c
```

```
    rm calcu
```

YACC Declaration Summary

- '%start'** Specify the grammar's start symbol
- '%union'** Declare the collection of data types that semantic values may have
- '%token'** Declare a terminal symbol (token type name) with no precedence or associativity specified
- '%type'** Declare the type of semantic values for a nonterminal symbol

YACC Declaration Summary

'%right' Declare a terminal symbol (token type name) that is right-associative

'%left' Declare a terminal symbol (token type name) that is left-associative

'%nonassoc' Declare a terminal symbol (token type name) that is nonassociative (using it in a way that would be associative is a syntax error, e.g.:
 $x \text{ op. } y \text{ op. } z$ is syntax error)