Practical-13

Date:_____

AIM: The price of a product changes constantly. It is important to maintain the history of the prices of the products.Create a trigger to update the 'product_price_history' table when the price of the product is updated in the 'product' table.

Input :-

i). Create the product and product_price_history table :-

```
// Product Table
CREATE TABLE product (
    product_id NUMBER PRIMARY KEY,
    product_name VARCHAR2(100),
    price NUMBER(10,2)
);
// Product_Price_History Table
CREATE TABLE product_price_history (
    history_id NUMBER PRIMARY KEY GENERATED BY DEFAULT AS
                                  IDENTITY,
    product_id NUMBER,
    old_price NUMBER(10,2),
    new_price NUMBER(10,2),
    change_date TIMESTAMP DEFAULT CURRENT_TIMESTAMP,
    FOREIGN KEY (product_id) REFERENCES product(product_id)
);
```

ii). Create the Trigger :-

```
CREATE OR REPLACE TRIGGER trg_update_product_price
AFTER UPDATE OF price ON product
FOR EACH ROW
BEGIN
    INSERT INTO product_price_history (product_id, old_price,
                                       new_price)
    VALUES (:OLD.product_id, :OLD.price, :NEW.price);
END;
```

iii). Insert and fetch data :-

```
INSERT INTO product (product_id, product_name, price) VALUES
                    (1, 'Product A', 100.00);
INSERT INTO product (product_id, product_name, price) VALUES
                    (2, 'Product B', 150.00);

SELECT * FROM product ;
```

Output :-

product_id	product_name	price
1	Product A	100.00
2	Product B	150.00

iv). Update and fetch data :-

```
UPDATE product
SET price = 120.00
WHERE product_id = 1 ;

SELECT * FROM product ;
SELECT * FROM product_price_history ;
```

Output :-

// Product Table

product_id	product_name	price
1	Product A	120.00
2	Product B	150.00

history_id	product_id	old_price	new_price	change_date
1	1	100.00	120.00	2024-10-13 14:30:00