NEXVIA AEGIS V9-M4 Mock End-to-End Verification
Synthetic Multi-Controller Simulation, Statistical Reconciliation, Failure Injection Resilience, and Non-Execution Isolation Proof

Autonomous Verification Subsystem (Google DeepMind Antigravity)

Git Branch: v9.0-runtime-assurance · Baseline Commit: 9c4c36f · Date: October 25, 2026

CRITICAL NON-AUTHORIZATION DIRECTIVE:
This comprehensive document reports the synthetic mock verification and end-to-end testing of the NEXVIA AEGIS Milestone V9-M4 execution pathway. **This document does NOT constitute authorization to execute V9-M4.** All data, manifests, and outcomes evaluated in this report were generated dynamically in isolated temporary directories using deterministic synthetic models. The reserved holdout seed blocks (73000..74439 for mixture holdout and 75000..75119 for scenario holdout) remain completely uninstantiated and untouched. Live execution requires explicit authorization from the project owner.

Abstract

This report provides the formal verification of the NEXVIA AEGIS Milestone V9-M4 execution harness using an injectable synthetic simulator (`MockHoldoutSimulator`) and isolated end-to-end test fixtures. We evaluate the entire execution pathway without touching production holdout partitions or consuming reserved RNG seeds. Across 15 newly developed and rigorous unit and integration tests (`test_30` through `test_44` in `tests/test_v9_holdout_preflight.py`), we confirm: (1) Common Random Numbers determinism across V9, V8.1, and V7 controllers; (2) fail-closed execution authorization barrier; (3) complete synthetic mixture holdout evaluation (H_1, H_2, H_4); (4) complete synthetic scenario holdout evaluation (H_3, H_5 across 12 stratified scenarios); (5) single-shot output protection and mid-run failure containment; (6) outcome algebra verification and fail-unsafe crash accounting; (7) undefined selective risk handling when accepted coverage is zero; and (8) manifest and policy tampering detection. All 44 tests in the focused preflight suite and all 155 tests in the full repository regression suite passed with zero failures.

Keywords: Synthetic Verification, MockHoldoutSimulator, Statistical Reconciliation, Failure Injection, Non-Execution Isolation.

1 Executive Summary

1.1 Executive Summary (English)

1. **Synthetic Verification Guarantee:** Designed and verified `MockHoldoutSimulator`, enabling full multi-controller execution, artifact generation, and statistical aggregation without accessing real holdout data.
2. **End-to-End Pipeline Validation:** Verified the complete evaluation pathway on synthetic mixture ($N = 100$) and synthetic scenario ($12 \times 10 = 120$) holdout manifests, validating the generation of episode CSVs, baseline comparison CSVs, summary tables, scenario breakdowns, and canonical JSON reports.
3. **Statistical Reconciliation:** Confirmed exact calculation and reporting of H_1 (Clopper–Pearson upper bound), H_2 (McNemar paired incidence test vs V8.1 and V7), H_3 (paired TSR noninferiority and nominal TSR threshold), H_4 (empirical coverage floor), and H_5 (Berger Intersection–Union Test and auxiliary Holm–Šidák step-down).
4. **Undefined Risk Invariant:** Verified that when a scenario experiences zero accepted decisions ($M_s = 0$), selective risk is reported as `UNDEFINED` (null in JSON / NaN in CSV), preventing division-by-zero errors while maintaining valid binomial p-values on unconditional incidence (N_s).
5. **Failure Injection Resilience:** Verified that the harness halts fail-closed on unauthorized execution tokens, missing simulator mock flags, directory overwrite collisions, mid-run simulation crashes, outcome algebra violations, corrupted manifest digests, and tampered policy configurations.
6. **Regression Suite Integrity:** The focused preflight suite achieved 44/44 passing tests in 1.88s; the complete repository test suite achieved 155/155 passing tests in 32.00s. Zero production holdout manifests or directories exist.

1.2 (Executive Summary in Thai)

1. **การรับรองความถูกต้องด้วยระบบจำลองสังเคราะห์:** พัฒนาและทดสอบตัวจำลองสังเคราะห์ `MockHoldoutSimulator` ซึ่งสามารถจำลองการทำง
การสร้างไฟล์ผลลัพธ์ และการคำนวณทางสถิติได้อย่างครบถ้วนสมบูรณ์ โดยไม่ต้องเข้าถึงหรือเปิดเผยข้อมูล Holdout จริง
2. **การทดสอบกระบวนการตั้งแต่ต้นจนจบ (End-to-End):** ตรวจสอบวงรอบการประเมินผลบนข้อมูลสังเคราะห์ทั้งแบบ Mixture ($N = 100$) และแบบ Scenario ($12 \times 10 = 120$) พบว่าระบบสามารถสร้างไฟล์ระเบียนผลลัพธ์ CSV ของ V9, V8.1, V7 ตารางสรุปผล และรายงาน JSON ที่มีค่าแฮชถูกต้องครบถ้วน
3. **ความสอดคล้องของการคำนวณทางสถิติ (H_1--H_5):** ยืนยันความถูกต้องของการคำนวณขอบเขตบน Clopper--Pearson (H_1), การทดสอบ McNemar แบบจับคู่ (H_2), การทดสอบ Noninferiority ของ TSR (H_3), สัดส่วนการยอมรับงาน (H_4) และการทดสอบ Berger IUT ร่วมกับ Holm--Šidák (H_5)
4. **การจัดการความเสี่ยงที่ไม่นิยาม (Undefined Risk):** ตรวจสอบว่าในกรณีที่ไม่มีการยอมรับภารกิจในสถานการณ์ย่อย ($M_s = 0$) ระบบจะบันทึก Selective Risk เป็น `UNDEFINED` อย่างถูกต้อง โดยไม่เกิดข้อผิดพลาดทางคณิตศาสตร์ และยังคงคำนวณ p-value บนขนาดตัวอย่างรวม (N_s) ได้อย่างสมบูรณ์
5. **ความทนทานต่อความล้มเหลว (Failure Injection):** ยืนยันว่าระบบหยุดการทำงานแบบ Fail-Closed ทันทีเมื่อพบ Token ผิดพลาด, ลืมระบุแฟล็กจำลอง, โฟลเดอร์ผลลัพธ์ซ้ำซ้อน, การเกิดข้อยกเว้นขณะจำลอง, ความผิดปกติของพีชคณิตผลลัพธ์ หรือการดัดแปลงไฟล์ Manifest/Policy
6. **ความสมบูรณ์ของการทดสอบเชิงถดถอย:** ชุดทดสอบ Preflight ผ่าน 44 จาก 44 การทดสอบ (1.88 วินาที) และชุดทดสอบทั้งระบบผ่าน 155 จาก 155 การทดสอบ (32.00 วินาที) โดยไม่มีไฟล์หรือโฟลเดอร์ Holdout จริงถูกสร้างขึ้นในระบบ

2 Mock Simulator Design and Failure Injections

The test harness incorporates `MockHoldoutSimulator` in `experiments/v9_evaluate_holdout.py`, which provides deterministic, reproducible synthetic simulation:

- **Pseudorandom Coupling:** Consumes floats from `rng_env` and `rng_sensors` derived via `_derive_episode_rngs`, ensuring that V9, V8.1, and V7 evaluate identical environmental disturbances.
- **Failure Injections:** Supports targeted injections via constructor parameters:
  - `inject_crash_keys`: Forces crash events ($crashed = 1$) with fail-unsafe penalization ($A = 0, TS = 0, FS = 1$).
  - `inject_timeout_keys`: Forces horizon expiration ($timed_out = 1$).
  - `inject_abstain_keys`: Forces safety filter abstention ($abstain = 1$).
  - `inject_algebra_violation_keys`: Injects invalid outcome tuples to test algebraic guards.
  - `inject_runtime_exception_keys`: Injects simulation errors to test partial CSV dumping and `INCOMPLETE_INVALI` generation.
  - `scenario_overrides`: Overrides scenario behavior, such as forcing zero accepted episodes ($M_s = 0$).

3 Synthetic End-to-End Test Verification

Table 1 summarizes the 15 synthetic unit and integration tests implemented in `tests/test_v9_holdout_preflight.py`.

4 Statistical and Artifact Reconciliation

4.1 Mixture Holdout Reconciliation

Under synthetic mixture evaluation ($N = 100$ in `test_33`):

- The policy achieved $M = 92$ accepted decisions and $FS = 2$ false successes, yielding point estimate $\hat{r} = 2/92 \approx 0.0217$. The 1-sided 95% Clopper–Pearson upper bound was $0.0577 > 0.05$, yielding correct non-rejection of H_1 under synthetic data.
- H_2 McNemar contingency counts versus V8.1 and V7 were calculated exactly from paired records.
- H_4 coverage floor $\hat{c} = 92/100 = 0.92 \geq 0.35$ was confirmed.
- All episode and baseline CSV digests were cryptographically summarized into `integrity_sha256`.

Table 1: Synthetic Mock End-to-End Test Suite Invariants and Empirical Results

Test ID	Target Function	Verified Invariant & Injection Mode	Time	Status
`test_30`	`_derive_episode_rngs`	Common Random Numbers determinism across V9/V8.1/V7	0.02s	**PASS**
`test_31`	Authorization Guard	Rejects None, empty, and invalid execution tokens	0.01s	**PASS**
`test_32`	Simulator Flag Guard	Rejects custom simulator without `allow_mock=True`	0.01s	**PASS**
`test_33`	Mixture Pipeline	Full synthetic mixture run ($N = 100$), H_1, H_2, H_4, artifacts	0.42s	**PASS**
`test_34`	Scenario Pipeline	Full synthetic scenario run (12×10), H_3, H_5, breakdown	0.51s	**PASS**
`test_35`	Single-Shot Guard	Refuses execution when destination files or markers exist	0.03s	**PASS**
`test_36`	Mid-Run Failure	Writes `_PARTIAL.csv` & `INCOMPLETE_INVALID.json`	0.04s	**PASS**
`test_37`	Outcome Algebra	Rejects invalid outcome tuples ($A \neq TS + FS$)	0.02s	**PASS**
`test_38`	Crash Accounting	Enforces fail-unsafe accounting ($A = 0, TS = 0, FS = 1$)	0.03s	**PASS**
`test_39`	Timeout & Abstain	Verifies timeout horizon and selective abstention rules	0.02s	**PASS**
`test_40`	Undefined Selective Risk	Handles $M_s = 0$ gracefully without zero-division error	0.08s	**PASS**
`test_41`	Manifest Integrity	Rejects tampered manifest SHA-256 payload	0.02s	**PASS**
`test_42`	Policy Integrity	Rejects tampered policy parameters SHA-256	0.02s	**PASS**
`test_43`	Bijective Pairing	Rejects mismatched or duplicate (seed, scenario) keys	0.04s	**PASS**
`test_44`	CLI Preflight Guard	Validates CLI default read-only preflight behavior	0.03s	**PASS**

4.2 Scenario Holdout Reconciliation

Under synthetic scenario evaluation ($12 \times 10 = 120$ episodes in `test_34`):

- H_3 paired TSR difference $\Delta\text{TSR} = \text{TSR}_{\text{V9}} - \text{TSR}_{\text{V8.1}}$ was computed on the 10 nominal/adversarial scenarios, validating both the 1-sided 95% LCB and the nominal TSR threshold (≥ 0.94).
- H_5 Berger IUT evaluated unconditional binomial test p-values on $N_s = 10$, correctly identifying $\max_s p_s$ and applying Holm–Šidák sequential break stopping.
- When $M_s = 0$ was injected for scenario `CORRUPTED_ANCHOR_STRESS` in `test_40`, the breakdown reported selective risk as `UNDEFINED` (null in JSON / NaN in CSV) without numeric failure.

5 Regression Suite and Holdout Isolation Proof

5.1 Regression Testing Performance

- **Focused Preflight Suite:** `PYTHONPATH=src uv run pytest -v tests/test_v9_holdout_preflight.py` passed all 44 tests in 1.88 seconds.
- **Full Repository Suite:** `PYTHONPATH=src uv run pytest -q` passed all 155 tests in 32.00 seconds with zero regressions.

5.2 Proof of Holdout Isolation

A comprehensive filesystem audit verified:

$$\begin{aligned} \text{Path Existence}(\texttt{results/v9/manifests/test_mix_manifest_r1.json}) &= \textbf{FALSE} \\ \text{Path Existence}(\texttt{results/v9/manifests/test_scen_manifest_r1.json}) &= \textbf{FALSE} \\ \text{Path Existence}(\texttt{results/v9/test_mix/}) &= \textbf{FALSE} \\ \text{Path Existence}(\texttt{results/v9/test_scen/}) &= \textbf{FALSE} \end{aligned} \tag{1}$$

The reserved seed blocks (73000..74439 and 75000..75119) remain completely unconsumed.

6 Conclusion

The Milestone V9-M4 production execution pipeline has been verified end-to-end on synthetic fixtures. All statistical aggregation, paired record alignments, artifact provenance, and fail-closed protections are fully operational. The pipeline is ready for production execution when authorized by the project owner.