



Applied Machine Learning

Lecture 11 Neural Network

Ekarat Rattagan, Ph.D.

Slides adapted from Andrew NG


Outline

1. Non-linear hypotheses
2. Model representation I
3. Model representation II
4. Examples and intuitions I
5. Examples and intuitions II
6. Multi-class classification
7. Cost function
8. Backpropagation algorithm

Neural Networks: Representation

Non-linear
hypotheses

Non-linear Classification




x_1 = size
 x_2 = # bedrooms
 x_3 = # floors
 x_4 = age
...
 x_{100}

$$g(\theta_0 + \theta_1 x_1 + \theta_2 x_2 + \theta_3 x_1 x_2 + \theta_4 x_1^2 x_2 + \theta_5 x_1^3 x_2 + \theta_6 x_1 x_2^2 + \dots)$$

What is this?

You see this:



But the camera sees this:

194	210	201	212	199	213	215	195	178	158	182	209
180	189	190	221	209	205	191	167	147	115	129	163
114	126	140	188	176	165	152	140	170	106	78	88
87	103	115	154	143	142	149	153	173	101	57	57
102	112	106	131	122	138	152	147	128	84	58	66
94	95	79	104	105	124	129	113	107	87	69	67
68	71	69	98	89	92	98	95	89	88	76	67
41	56	68	99	63	45	60	82	58	76	75	65
20	43	69	75	56	41	51	73	55	70	63	44
50	50	57	69	75	75	73	74	53	68	59	37
72	59	53	66	84	92	84	74	57	72	63	42
67	61	58	65	75	78	76	73	59	75	69	50

Computer Vision: Car detection



Cars






Not a car

Testing:




What is this?





Learning
Algorithm



50 x 50 pixel images \rightarrow 2500 pixels
 $n = 2500$ (7500 if RGB)


$$x = \begin{bmatrix} \text{pixel 1 intensity} \\ \text{pixel 2 intensity} \\ \vdots \\ \text{pixel 2500 intensity} \end{bmatrix}$$

Quadratic features ($x_i \times x_j$): ≈ 3 million features


Neural Networks: Representation

Model
representation I


Neuron in the brain



Neurons in the brain




Neuron model: Logistic unit




$$x = \begin{bmatrix} x_0 \\ x_1 \\ x_2 \\ x_3 \end{bmatrix} \quad \theta = \begin{bmatrix} \theta_0 \\ \theta_1 \\ \theta_2 \\ \theta_3 \end{bmatrix}$$

Sigmoid (logistic) activation function.

Neural Network



Neural Network



$a_i^{(j)}$ = “activation” of unit i in layer j

$\Theta^{(j)}$ = matrix of weights controlling function mapping from layer j to layer $j + 1$

$$a_1^{(2)} = g(\Theta_{10}^{(1)} x_0 + \Theta_{11}^{(1)} x_1 + \Theta_{12}^{(1)} x_2 + \Theta_{13}^{(1)} x_3)$$

$$a_2^{(2)} = g(\Theta_{20}^{(1)} x_0 + \Theta_{21}^{(1)} x_1 + \Theta_{22}^{(1)} x_2 + \Theta_{23}^{(1)} x_3)$$

$$a_3^{(2)} = g(\Theta_{30}^{(1)} x_0 + \Theta_{31}^{(1)} x_1 + \Theta_{32}^{(1)} x_2 + \Theta_{33}^{(1)} x_3)$$


$$h_{\Theta}(x) = a_1^{(3)} = g(\Theta_{10}^{(2)} a_0^{(2)} + \Theta_{11}^{(2)} a_1^{(2)} + \Theta_{12}^{(2)} a_2^{(2)} + \Theta_{13}^{(2)} a_3^{(2)})$$

If network has s_j units in layer j , s_{j+1} units in layer $j + 1$, then $\Theta^{(j)}$ will be of dimension $s_{j+1} \times (s_j + 1)$.

Neural Networks: Representation

Model
representation II

Forward propagation: Vectorized implementation



$$a_1^{(2)} = g(\Theta_{10}^{(1)} x_0 + \Theta_{11}^{(1)} x_1 + \Theta_{12}^{(1)} x_2 + \Theta_{13}^{(1)} x_3)$$

$$a_2^{(2)} = g(\Theta_{20}^{(1)} x_0 + \Theta_{21}^{(1)} x_1 + \Theta_{22}^{(1)} x_2 + \Theta_{23}^{(1)} x_3)$$

$$a_3^{(2)} = g(\Theta_{30}^{(1)} x_0 + \Theta_{31}^{(1)} x_1 + \Theta_{32}^{(1)} x_2 + \Theta_{33}^{(1)} x_3)$$

$$h_{\Theta}(x) = g(\Theta_{10}^{(2)} a_0^{(2)} + \Theta_{11}^{(2)} a_1^{(2)} + \Theta_{12}^{(2)} a_2^{(2)} + \Theta_{13}^{(2)} a_3^{(2)})$$

$$x = \begin{bmatrix} x_0 \\ x_1 \\ x_2 \\ x_3 \end{bmatrix} \quad z^{(2)} = \begin{bmatrix} z_1^{(2)} \\ z_2^{(2)} \\ z_3^{(2)} \end{bmatrix}$$

$$z^{(2)} = \Theta^{(1)} x$$


$$a^{(2)} = g(z^{(2)})$$

$$\text{Add } a_0^{(2)} = 1 \text{ .}$$

$$z^{(3)} = \Theta^{(2)} a^{(2)}$$

$$h_{\Theta}(x) = a^{(3)} = g(z^{(3)})$$

Neural Network learning its own features




Neural Networks: Representation

Examples and
intuitions I

Non-linear classification example: XOR/XNOR

x_1, x_2 are binary (0 or 1).



$$y = x_1 \text{ XOR } x_2$$



$$x_1 \text{ XNOR } x_2$$

$$\text{NOT } (x_1 \text{ XOR } x_2)$$


Simple example: AND

$$x_1, x_2 \in \{0, 1\}$$

$$y = x_1 \text{ AND } x_2$$



Example: OR function




x_1	x_2	$h_{\Theta}(x)$
0	0	
0	1	
1	0	
1	1	

Neural Networks: Representation

Examples and intuitions II

Negation:




$$h_{\Theta}(x) = g(10 - 20x_1)$$


x_1	$h_{\Theta}(x)$
0	
1	

(NOT x_1) AND (NOT x_2)


Putting it together: x_1 XNOR x_2



x_1 AND x_2



$(\text{NOT } x_1)$ AND $(\text{NOT } x_2)$




x_1 OR x_2



x_1	x_2	$a_1^{(2)}$	$a_2^{(2)}$	$h_{\Theta}(x)$
0	0			
0	1			
1	0			
1	1			

Neural Network intuition



Neural Networks: Representation

Multi-class
classification

Multiple output units: One-vs-all.



Pedestrian




Car



Motorcycle



Truck




$$h_{\Theta}(x) \in \mathbb{R}^4$$

Want $h_{\Theta}(x) \approx \begin{bmatrix} 1 \\ 0 \\ 0 \\ 0 \end{bmatrix}$, $h_{\Theta}(x) \approx \begin{bmatrix} 0 \\ 1 \\ 0 \\ 0 \end{bmatrix}$, $h_{\Theta}(x) \approx \begin{bmatrix} 0 \\ 0 \\ 1 \\ 0 \end{bmatrix}$, etc.

when pedestrian when car when motorcycle

Multiple output units: One-vs-all.



$$h_{\Theta}(x) \in \mathbb{R}^4$$

Want $h_{\Theta}(x) \approx \begin{bmatrix} 1 \\ 0 \\ 0 \\ 0 \end{bmatrix}$, $h_{\Theta}(x) \approx \begin{bmatrix} 0 \\ 1 \\ 0 \\ 0 \end{bmatrix}$, $h_{\Theta}(x) \approx \begin{bmatrix} 0 \\ 0 \\ 1 \\ 0 \end{bmatrix}$, etc.
when pedestrian when car when motorcycle


Training set: $(x^{(1)}, y^{(1)}), (x^{(2)}, y^{(2)}), \dots, (x^{(m)}, y^{(m)})$

$y^{(i)}$ one of $\begin{bmatrix} 1 \\ 0 \\ 0 \\ 0 \end{bmatrix}$, $\begin{bmatrix} 0 \\ 1 \\ 0 \\ 0 \end{bmatrix}$, $\begin{bmatrix} 0 \\ 0 \\ 1 \\ 0 \end{bmatrix}$, $\begin{bmatrix} 0 \\ 0 \\ 0 \\ 1 \end{bmatrix}$
pedestrian car motorcycle truck

Neural Networks: Learning

Cost function

Neural Network (Classification)



Layer 1 Layer 2 Layer 3 Layer 4

Binary classification

$y = 0$ or 1

1 output unit

$$\{(x^{(1)}, y^{(1)}), (x^{(2)}, y^{(2)}), \dots, (x^{(m)}, y^{(m)})\}$$

$L =$ total no. of layers in network

$s_l =$ no. of units (not counting bias unit) in layer l

Multi-class classification (K classes)

$y \in \mathbb{R}^K$ E.g. $\begin{bmatrix} 1 \\ 0 \\ 0 \\ 0 \end{bmatrix}$, $\begin{bmatrix} 0 \\ 1 \\ 0 \\ 0 \end{bmatrix}$, $\begin{bmatrix} 0 \\ 0 \\ 1 \\ 0 \end{bmatrix}$ $\begin{bmatrix} 0 \\ 0 \\ 0 \\ 1 \end{bmatrix}$
pedestrian car motorcycle truck

K output units

Cost function

Logistic regression:

$$J(\theta) = -\frac{1}{m} \left[\sum_{i=1}^m y^{(i)} \log h_{\theta}(x^{(i)}) + (1 - y^{(i)}) \log(1 - h_{\theta}(x^{(i)})) \right] + \frac{\lambda}{2m} \sum_{j=1}^n \theta_j^2$$

Neural network:

$$h_{\Theta}(x) \in \mathbb{R}^K \quad (h_{\Theta}(x))_i = i^{th} \text{ output}$$

$$J(\Theta) = -\frac{1}{m} \left[\sum_{i=1}^m \sum_{k=1}^K y_k^{(i)} \log(h_{\Theta}(x^{(i)}))_k + (1 - y_k^{(i)}) \log(1 - (h_{\Theta}(x^{(i)}))_k) \right] \\ + \frac{\lambda}{2m} \sum_{l=1}^{L-1} \sum_{i=1}^{s_l} \sum_{j=1}^{s_{l+1}} (\Theta_{ji}^{(l)})^2$$

Neural Networks: Learning

Backpropagation
algorithm

Gradient computation

$$J(\Theta) = -\frac{1}{m} \left[\sum_{i=1}^m \sum_{k=1}^K y_k^{(i)} \log h_{\theta}(x^{(i)})_k + (1 - y_k^{(i)}) \log(1 - h_{\theta}(x^{(i)})_k) \right] \\ + \frac{\lambda}{2m} \sum_{l=1}^{L-1} \sum_{i=1}^{s_l} \sum_{j=1}^{s_{l+1}} (\Theta_j^{(l)})^2$$

$$\min_{\Theta} J(\Theta)$$

Need code to compute:

- $J(\Theta)$
- $\frac{\partial}{\partial \Theta_{ij}^{(l)}} J(\Theta)$

Gradient computation

Given one training example (x, y) :

Forward propagation:

$$a^{(1)} = x$$

$$z^{(2)} = \Theta^{(1)} a^{(1)}$$


$$a^{(2)} = g(z^{(2)}) \quad (\text{add } a_0^{(2)})$$

$$z^{(3)} = \Theta^{(2)} a^{(2)}$$

$$a^{(3)} = g(z^{(3)}) \quad (\text{add } a_0^{(3)})$$

$$z^{(4)} = \Theta^{(3)} a^{(3)}$$

$$a^{(4)} = h_{\Theta}(x) = g(z^{(4)})$$



Gradient computation: Backpropagation algorithm


Intuition: $\delta_j^{(l)}$ = “error” of node j in layer l .

For each output unit (layer $L = 4$)

$$\delta_j^{(4)} = a_j^{(4)} - y_j$$

$$\delta^{(3)} = (\Theta^{(3)})^T \delta^{(4)} \quad g'(z^{(3)})$$

$$\delta^{(2)} = (\Theta^{(2)})^T \delta^{(3)} \quad g'(z^{(2)})$$



Backpropagation algorithm

Training set $\{(x^{(1)}, y^{(1)}), \dots, (x^{(m)}, y^{(m)})\}$

Set $\Delta_{ij}^{(l)} = 0$ (for all l, i, j).

For $i = 1$ to m

Set $a^{(1)} = x^{(i)}$

Perform forward propagation to compute $a^{(l)}$ for $l = 2, 3, \dots, L$

Using $y^{(i)}$, compute $\delta^{(L)} = a^{(L)} - y^{(i)}$

Compute $\delta^{(L-1)}, \delta^{(L-2)}, \dots, \delta^{(2)}$

$$\Delta_{ij}^{(l)} := \Delta_{ij}^{(l)} + a_j^{(l)} \delta_i^{(l+1)}$$

$$D_{ij}^{(l)} := \frac{1}{m} \Delta_{ij}^{(l)} + \lambda \Theta_{ij}^{(l)} \text{ if } j \neq 0$$

$$D_{ij}^{(l)} := \frac{1}{m} \Delta_{ij}^{(l)} \text{ if } j = 0$$




$$\frac{\partial}{\partial \Theta_{ij}^{(l)}} J(\Theta) = D_{ij}^{(l)}$$

Neural Networks: Learning

Putting it
together

Training a neural network

Pick a network architecture (connectivity pattern between neurons)



No. of input units: Dimension of features $x^{(i)}$

No. output units: Number of classes

Reasonable default: 1 hidden layer, or if >1 hidden layer, have same no. of hidden units in every layer (usually the more the better)