

exp_5.1.1 | Arduino 1.8.19

File Edit Sketch Tools Help

exp_5.1.1

```
int x0,x1,x2,x3,x4,x5,x6,x7,x8,x9;
int delay_time=200;

void setup() {
  //configure pin2 as an input and enable the internal pull-up resistor
  pinMode(12, INPUT_PULLUP);
  pinMode(1,OUTPUT);

  pinMode(2,OUTPUT);
  pinMode(3,OUTPUT);
  pinMode(4,OUTPUT);
  pinMode(5,OUTPUT);
  pinMode(6,OUTPUT);
  pinMode(7,OUTPUT);
}

void loop() {
  //read the pushbutton value into a variable
  int sensorVal = digitalRead(12);

  if (sensorVal == LOW) {
    x0=true;
  }
  while(x0){
    zero();
    sensorVal = digitalRead(12);
    if (sensorVal == LOW) {
      x1=true;
      x0=false;
    }
  }
  while(x1){
    one();
    sensorVal = digitalRead(12);
    if (sensorVal == HIGH) {

```

Done compiling.

Sketch uses 2174 bytes (6%) of program storage space. Maximum is 32256 bytes.
Global variables use 29 bytes (1%) of dynamic memory, leaving 2019 bytes for local variables. Maximum is 2048 bytes.

229

Arduino Uno

3 37°C
Mostly cloudy

Search

ENG
IN

14:54
01-08-2026

