



Exercise 30.1: Working with User Accounts

1. Examine `/etc/passwd` and `/etc/shadow`, comparing the fields in each file, especially for the normal user account. What is the same and what is different?
2. Create a `user1` account using **useradd**.
3. Login as `user1` using `ssh`. You can just do this with:

```
$ ssh user1@localhost
```

It should fail because you need a password for `user1`; it was never established.

4. Set the password for `user1` to `user1pw` and then try to login again as `user1`.
5. Look at the new records which were created in the `/etc/passwd`, `/etc/group` and the `/etc/shadow` files.
6. Look at the `/etc/default/useradd` file and see what the current defaults are set to. Also look at the `/etc/login.defs` file.
7. Create a user account for `user2` which will use the **Korn** shell (**ksh**) as its default shell. (if you do not have `/bin/ksh` install it or use the **C** shell at `/bin/csh`.) Set the password to `user2pw`.
8. Look at `/etc/shadow`. What is the current expiration date for the `user1` account?
9. Use **chage** to set the account expiration date of `user1` to December 1, 2013.
Look at `/etc/shadow` to see what the new expiration date is.
10. Use **usermod** to lock the `user1` account.
Look at `/etc/shadow` and see what has changed about `user1`'s password. Reset the password to `userp1` on the account to complete this exercise.

✓ Solution 30.1

1.

```
$ sudo grep student /etc/passwd /etc/shadow
```

```
/etc/passwd:student:x:1000:100:LF Student:/home/student:/bin/bash
/etc/shadow:student:$6$jtoFVPICHhba$iGFFU08ctr0GoistJ4/30DrNLi1FS66qnn0VbS6Mvm
luKI08SgbzT5.Ic0Ho5j/S0dCagZmF2RgzTvzLb11H0:16028:0:99999:7:::
```

(You can use any normal user name in the place of `student`.) About the only thing that matches is the user name field.

2.

```
$ sudo useradd user1
```

3.

```
$ ssh user1@localhost
```

```
user1@localhost's password:
```

Note you may have to first start up the **sshd** service as in:

```
$ sudo service sshd restart
```

or

```
$ sudo systemctl restart sshd.service
```

4.

```
$ sudo passwd user1
```

```
Changing password for user user1.
New password:
```

```
5. $ sudo grep user1 /etc/passwd /etc/shadow

/etc/passwd:user1:x:1001:100::/home/user1:/bin/bash
/etc/shadow:user1:$6$0BE1mPMw$CIc7urbQ9ZSnyiniV0eJxKqLFu8fz4whfEexVem2
TFpucuWRN1CCHZ19XGhj4qVujslRIS.P4aCXd/y1U4utv.:16372:0:99999:7:::
```

6. On either **RHEL 7** or **openSUSE** systems for example:

```
$ cat /etc/default/useradd

# useradd defaults file
GROUP=100
HOME=/home
INACTIVE=-1
EXPIRE=
SHELL=/bin/bash
SKEL=/etc/skel
CREATE_MAIL_SPOOL=yes
```

```
$ cat /etc/login.defs
```

```
....
```

We don't reproduce the second file as it is rather longer, but examine it on your system.

```
7. $ sudo useradd -s /bin/ksh user2
$ sudo passwd user2

Changing password for user user2.
New password:
```

```
8. $ sudo grep user1 /etc/shadow

user1:$6$0BE1mPMw$CIc7urbQ9ZSnyiniV0eJxKqLFu8fz4whfEexVem2TFpucuWRN1CCHZ
19XGhj4qVujslRIS.P4aCXd/y1U4utv.:16372:0:99999:7:::
```

There should be no expiration date.

```
9. $ sudo chage -E 2013-12-1 user1
$ sudo grep user1 /etc/shadow

user1:$6$0BE1mPMw$CIc7urbQ9ZSnyiniV0eJxKqLFu8fz4whfEexVem2TFpucuWRN1CCHZ
19XGhj4qVujslRIS.P4aCXd/y1U4utv.:16372:0:99999:7:::16040:
```

```
10. $ sudo usermod -L user1

$ sudo passwd user1
```