Integration / system test command output

Source commit: 93ef68f21d0fba21945c7cb0f675dc7b9ba9f667

Tracked source changes: no

Generated from actual command output; test counts in separate commands may overlap.

Frontend test output includes component, service and integration suites.

==

COMMAND: npm run test:integration -- --reporter=verbose --reporter=junit --outputFile=reports/integration-junit.xml

Started UTC: 2026-11-06T14:54:18.001Z

> se-jackfruit-security-foundation@0.1.0 test:integration

> vitest run backend/tests/integration --reporter=verbose --reporter=junit --outputFile=reports/integration-junit.xml

RUN v5.0.3 D:/SEMESTERS/SEM5_2025/SE-JACKFRUIT

✓ backend/tests/integration/team-sprint2.test.ts > connects real Question creation, Quiz discovery, trusted submission and persisted attempt without answer leakage 354ms

✓ backend/tests/integration/team-sprint2.test.ts > enforces actual Quiz moderation, excludes discovery/submission and preserves existing attempt history 371ms

✓ backend/tests/integration/team-sprint2.test.ts > makes moderated Questions unavailable through real Quiz reads and trusted scoring 276ms

✓ backend/tests/integration/team-sprint2.test.ts > rejects malformed Quiz filters, forged scores and Admin submissions 399ms

✓ backend/tests/integration/team-sprint2.test.ts > deduplicates racing retries of one submission, rejects changed answers and permits a fresh repeat attempt 466ms

✓ backend/tests/integration/team-sprint2.test.ts > retains history and retry identity after reconnect and after moderation without exposing post-submission keys through history 677ms

✓ backend/tests/integration/team-sprint2.test.ts > supports the submitted SAD download path with the same authenticated PDF bytes and removal denial 550ms

stdout | backend/tests/integration/team-sprint2.test.ts > serves real Quiz retrieval and trusted submissions for 10 concurrent Student sessions

Real Quiz load: 10 sessions, 20 requests, p90 166ms (paired retrieval + submission).

✓ backend/tests/integration/team-sprint2.test.ts > serves real Quiz retrieval and trusted submissions for 10 concurrent Student sessions 2219ms

stdout | backend/tests/integration/team-sprint2.test.ts > serves real Quiz retrieval and trusted submissions for 50 concurrent Student sessions

Real Quiz load: 50 sessions, 100 requests, p90 904ms (paired retrieval + submission).

✓ backend/tests/integration/team-sprint2.test.ts > serves real Quiz retrieval and trusted submissions for 50 concurrent Student sessions 9772ms

✓ backend/tests/integration/sprint2.test.ts > lists only enabled moderation resources and rejects student/anonymous administration 216ms

✓ backend/tests/integration/sprint2.test.ts > removes material atomically and closes both search and download while retaining recoverable data 310ms

✓ backend/tests/integration/sprint2.test.ts > requires explicit confirmation and validates identifiers, missing/repeated removals and query limits 195ms

✓ backend/tests/integration/sprint2.test.ts > searches all material metadata and combines keyword with a subject filter 177ms

✓ backend/tests/integration/sprint2.test.ts > lists searchable subjects from available materials only 186ms

✓ backend/tests/integration/sprint2.test.ts > returns selected material metadata by identifier and rejects invalid or unavailable identifiers 147ms

✓ backend/tests/integration/sprint2.test.ts > validates safe searches and download options, escapes regex and paginates 238ms

✓ backend/tests/integration/sprint2.test.ts > uses owner-supplied question and quiz moderation adapters behind the same admin gate 282ms

✓ backend/tests/integration/sprint2.test.ts > handles missing PDF storage safely and makes revoked administrator access ineffective 245ms

stdout | backend/tests/integration/sprint2.test.ts > keeps normal protected operations within three seconds for 10 concurrent authenticated sessions

NFR scoped smoke: 10 sessions, 20 authenticated requests; p90=119ms

✓ backend/tests/integration/sprint2.test.ts > keeps normal protected operations within three seconds for 10 concurrent authenticated sessions 1162ms

stdout | backend/tests/integration/sprint2.test.ts > keeps normal protected operations within three seconds for 50 concurrent authenticated sessions

NFR scoped smoke: 50 sessions, 100 authenticated requests; p90=348ms

✓ backend/tests/integration/sprint2.test.ts > keeps normal protected operations within three seconds for 50 concurrent authenticated sessions 4146ms

✓ backend/tests/integration/sprint2.test.ts > persists removal and existing authentication after runtime recreation and database reconnect 277ms

✓ backend/tests/integration/admin-provisioning.test.ts > creates an administrator in the configured named database using the existing bcrypt helper 199ms

✓ backend/tests/integration/admin-provisioning.test.ts > repeats safely without overwriting an existing admin password or name 124ms

✓ backend/tests/integration/admin-provisioning.test.ts > handles concurrent provisioning with one account and no password reset 135ms

✓ backend/tests/integration/admin-provisioning.test.ts > rejects an existing student rather than promoting them 95ms

✓ backend/tests/integration/admin-provisioning.test.ts > does not reactivate a disabled administrator 68ms

✓ backend/tests/integration/admin-provisioning.test.ts > rejects missing/invalid provisioning input without writes 7ms

✓ backend/tests/integration/admin-provisioning.test.ts > rejects missing/invalid provisioning input without writes 4ms

✓ backend/tests/integration/admin-provisioning.test.ts > rejects missing/invalid provisioning input without writes 7ms

✓ backend/tests/integration/admin-provisioning.test.ts > rejects missing/invalid provisioning input without writes 5ms

✓ backend/tests/integration/admin-provisioning.test.ts > rejects missing/invalid provisioning input without writes 8ms

✓ backend/tests/integration/admin-provisioning.test.ts > rejects missing/invalid provisioning input without writes 3ms

✓ backend/tests/integration/admin-provisioning.test.ts > requires an explicit development/test confirmation and disables production 2ms

✓ backend/tests/integration/admin-provisioning.test.ts > runs the real CLI only against disposable MongoDB, uses its database, exits cleanly and prints no secrets 1325ms

✓ backend/tests/integration/admin-provisioning.test.ts > refuses the CLI before connecting when production or confirmation is invalid 572ms

✓ backend/tests/integration/admin-provisioning.test.ts > exits cleanly after a database-connected CLI refusal without promoting a Student or leaking input 762ms

✓ backend/tests/integration/admin-provisioning.test.ts > uses the common login and server-verified RBAC for real Question Bank creation and persistence 465ms

✓ backend/tests/integration/quizzes.test.ts > Quiz API integration (CSMQ-48 / SRS CSMQ-F-030) > IT-M2-QUIZ-01: authenticated student creates a valid quiz from existing Question Bank questions 182ms

✓ backend/tests/integration/quizzes.test.ts > Quiz API integration (CSMQ-48 / SRS CSMQ-F-030) > IT-M2-QUIZ-02: rejects unauthenticated requests with 401 Unauthorized 28ms

✓ backend/tests/integration/quizzes.test.ts > Quiz API integration (CSMQ-48 / SRS CSMQ-F-030) > IT-M2-QUIZ-03: rejects quiz creation with empty questions array 142ms

✓ backend/tests/integration/quizzes.test.ts > Quiz API integration (CSMQ-48 / SRS CSMQ-F-030) > IT-M2-QUIZ-04: rejects quiz creation with unknown question IDs not in Question Bank 146ms

✓ backend/tests/integration/quizzes.test.ts > Quiz API integration (CSMQ-48 / SRS CSMQ-F-030) > IT-M2-QUIZ-05: rejects quiz creation with duplicate question IDs in the selection 151ms

✓ backend/tests/integration/quizzes.test.ts > Quiz API integration (CSMQ-48 / SRS CSMQ-F-030) > IT-M2-QUIZ-06: rejects quiz creation with missing required fields (title, subject) 132ms

✓ backend/tests/integration/quizzes.test.ts > Quiz API integration (CSMQ-48 / SRS CSMQ-F-030) > IT-M2-QUIZ-07: rejects unexpected extra fields ensuring students cannot add/edit questions 134ms

✓ backend/tests/integration/quizzes.test.ts > Quiz API integration (CSMQ-48 / SRS CSMQ-F-030) > IT-M2-QUIZ-08: authenticated student retrieves quiz by ID and receives student-safe payload with zero answer leakage 144ms

✓ backend/tests/integration/quizzes.test.ts > Quiz API integration (CSMQ-48 / SRS CSMQ-F-030) > IT-M2-QUIZ-09: returns 404 for non-existent quiz and 400 for malformed quiz ID 134ms

✓ backend/tests/integration/quizzes.test.ts > Quiz API integration (CSMQ-48 / SRS CSMQ-F-030) > IT-M2-QUIZ-10: moderation interface lists active quizzes and soft-deletes a quiz 136ms

✓ backend/tests/integration/quizzes.test.ts > Quiz API integration (CSMQ-48 / SRS CSMQ-F-030) > IT-M2-QUIZ-11: GET /api/quizzes returns all active quizzes with metadata and question count 190ms

✓ backend/tests/integration/quizzes.test.ts > Quiz API integration (CSMQ-48 / SRS CSMQ-F-030) > IT-M2-QUIZ-12: GET /api/quizzes?search=... filters quizzes by title keyword case-insensitively 285ms

✓ backend/tests/integration/quizzes.test.ts > Quiz API integration (CSMQ-48 / SRS CSMQ-F-030) > IT-M2-QUIZ-13: GET /api/quizzes?subject=... filters quizzes by subject case-insensitively 240ms

✓ backend/tests/integration/quizzes.test.ts > Quiz API integration (CSMQ-48 / SRS CSMQ-F-030) > IT-M2-QUIZ-14: GET /api/quizzes?search=...&subject=... applies combined filters 299ms

✓ backend/tests/integration/quizzes.test.ts > Quiz API integration (CSMQ-48 / SRS CSMQ-F-030) > IT-M2-QUIZ-15: GET /api/quizzes returns empty list when nothing matches search or subject 342ms

✓ backend/tests/integration/quizzes.test.ts > Quiz API integration (CSMQ-48 / SRS CSMQ-F-030) > IT-M2-QUIZ-16: GET /api/quizzes excludes soft-deleted/moderated quizzes 252ms

✓ backend/tests/integration/quizzes.test.ts > Quiz API integration (CSMQ-48 / SRS CSMQ-F-030) > IT-M2-QUIZ-17: GET /api/quizzes never leaks question options, questions array, or correctAnswer 207ms

✓ backend/tests/integration/local-demo.test.ts > serves protected APIs and SPA routes, preserving sessions, questions and removal across actual MongoDB restarts 2995ms

✓ backend/tests/integration/local-demo.test.ts > fails before starting a database when the frontend build is missing 3ms

✓ backend/tests/integration/security.test.ts > IT-M4-01 / TC-Auth-01..03 MongoDB-backed account integration > registers, normalizes email, hashes the password, logs in and reads protected context 159ms

✓ backend/tests/integration/security.test.ts > IT-M4-01 / TC-Auth-01..03 MongoDB-backed account integration > rejects duplicate emails with a controlled response, including a concurrent registration race 126ms

✓ backend/tests/integration/security.test.ts > IT-M4-01 / TC-Auth-01..03 MongoDB-backed account integration > rejects malformed data and privilege escalation 7ms

✓ backend/tests/integration/security.test.ts > IT-M4-01 / TC-Auth-01..03 MongoDB-backed account integration > rejects malformed data and privilege escalation 6ms

✓ backend/tests/integration/security.test.ts > IT-M4-01 / TC-Auth-01..03 MongoDB-backed account integration > rejects malformed data and privilege escalation 9ms

✓ backend/tests/integration/security.test.ts > IT-M4-01 / TC-Auth-01..03 MongoDB-backed account integration > rejects malformed data and privilege escalation 9ms

✓ backend/tests/integration/security.test.ts > IT-M4-01 / TC-Auth-01..03 MongoDB-backed account integration > rejects malformed data and privilege escalation 11ms

✓ backend/tests/integration/security.test.ts > IT-M4-01 / TC-Auth-01..03 MongoDB-backed account integration > rejects malformed data and privilege escalation 6ms

✓ backend/tests/integration/security.test.ts > IT-M4-01 / TC-Auth-01..03 MongoDB-backed account integration > uses the same error for wrong passwords and unknown or disabled accounts 300ms

✓ backend/tests/integration/security.test.ts > IT-M4-01 / TC-Auth-01..03 MongoDB-backed account integration > revokes only the active session on logout and rejects replay after recreating the app 248ms

✓ backend/tests/integration/security.test.ts > IT-M4-01 / TC-Auth-01..03 MongoDB-backed account integration > persists sessions across a database reconnect and refuses expired sessions before TTL cleanup 131ms

✓ backend/tests/integration/security.test.ts > IT-M4-01 / TC-Auth-01..03 MongoDB-backed account integration > rejects missing, random, malformed and revoked credentials, including query-string tokens 127ms

✓ backend/tests/integration/security.test.ts > IT-M4-01 / TC-Auth-01..03 MongoDB-backed account integration > rejects deleted or disabled users without waiting for session expiry 126ms

✓ backend/tests/integration/security.test.ts > IT-M4-01 / TC-Auth-01..03 MongoDB-backed account integration > rate limits authentication attempts 118ms

✓ backend/tests/integration/security.test.ts > IT-M4-02/03 / TC-Sec-02/03 teammate route contracts > protects the upload route before its handler receives multipart bytes 129ms

✓ backend/tests/integration/security.test.ts > IT-M4-02/03 / TC-Sec-02/03 teammate route contracts > denies a student at Add Question and allows an administrator; role changes take effect immediately 131ms

✓ backend/tests/integration/security.test.ts > IT-M4-02/03 / TC-Sec-02/03 teammate route contracts > protects the attempt prototype and supplies the student context 155ms

✓ backend/tests/integration/questions.test.ts > Question API integration (CSMQ-23 / IT-M2-01..02) > IT-M2-01: admin can create a question and it persists to MongoDB with creator attached 224ms

✓ backend/tests/integration/questions.test.ts > Question API integration (CSMQ-23 / IT-M2-01..02) > IT-M2-02: student role is rejected from creating questions with 403 Forbidden 141ms

✓ backend/tests/integration/questions.test.ts > Question API integration (CSMQ-23 / IT-M2-01..02) > rejects unauthenticated requests to create questions with 401 Unauthenticated 7ms

✓ backend/tests/integration/questions.test.ts > Question API integration (CSMQ-23 / IT-M2-01..02) > CSMQ-24: rejects invalid payload with 400 and clear error message 126ms

✓ backend/tests/integration/questions.test.ts > Question API integration (CSMQ-23 / IT-M2-01..02) > IT-M2-03: admin can list questions and apply subject/topic/difficulty filters 188ms

✓ backend/tests/integration/questions.test.ts > Question API integration (CSMQ-23 / IT-M2-01..02) > IT-M2-04: student can access /api/quiz-questions and receives student-safe payload without correctAnswer 251ms

✓ backend/tests/integration/questions.test.ts > Question API integration (CSMQ-23 / IT-M2-01..02) > IT-M2-05: student responses and stored question answers map to Member 3 evaluateQuiz contract for accurate scoring 277ms

✓ backend/tests/integration/questions.test.ts > Question API integration (CSMQ-23 / IT-M2-01..02) > supports quizId, title, and subject filters on /api/quiz-questions 342ms

✓ backend/tests/integration/question-moderation.test.ts > moderates the actual Question model, excludes both read APIs and preserves persisted attempt references 320ms

✓ backend/tests/integration/question-moderation.test.ts > requires current admin role, confirmation and valid identifiers; removal is atomic 316ms

✓ backend/tests/integration/question-moderation.test.ts > discovers integrated modules and rejects malicious query/body fields 330ms

✓ backend/tests/integration/question-moderation.test.ts > persists question moderation and sessions after runtime recreation and database reconnect 405ms

✓ backend/tests/integration/attempt-api.test.ts > CSMQ-40: Production Quiz Attempt API > submits, evaluates and persists an authenticated attempt 203ms

✓ backend/tests/integration/attempt-api.test.ts > CSMQ-40: Production Quiz Attempt API > rejects unauthenticated submissions 13ms

✓ backend/tests/integration/attempt-api.test.ts > CSMQ-40: Production Quiz Attempt API > rejects non-student accounts 141ms

✓ backend/tests/integration/attempt-api.test.ts > CSMQ-40: Production Quiz Attempt API > rejects invalid quiz IDs 154ms

✓ backend/tests/integration/attempt-api.test.ts > CSMQ-40: Production Quiz Attempt API > rejects client-supplied scores and user IDs 134ms

✓ backend/tests/integration/attempt-api.test.ts > CSMQ-40: Production Quiz Attempt API > rejects questions outside the selected quiz 177ms

✓ backend/tests/integration/attempt-api.test.ts > CSMQ-40: Production Quiz Attempt API > rejects invalid answer options 166ms

✓ backend/tests/integration/attempt-api.test.ts > CSMQ-40: Production Quiz Attempt API > rejects removed quizzes 131ms

✓ backend/tests/integration/runtime.test.ts > CSMQ-14/15 authenticated PDF upload and validation integration > registers, logs in, persists a real PDF and metadata, then rejects upload after logout 341ms

✓ backend/tests/integration/runtime.test.ts > CSMQ-14/15 authenticated PDF upload and validation integration > rejects unauthenticated upload before accepting file data 18ms

✓ backend/tests/integration/runtime.test.ts > CSMQ-14/15 authenticated PDF upload and validation integration > rejects missing metadata, missing files, non-PDFs, forged PDFs, and oversized files with controlled errors 271ms

✓ backend/tests/integration/runtime.test.ts > CSMQ-14/15 authenticated PDF upload and validation integration > rejects unknown/malicious metadata, extra files, and oversized text fields 156ms

✓ backend/tests/integration/runtime.test.ts > CSMQ-14/15 authenticated PDF upload and validation integration > enforces the student upload role using the database role 137ms

✓ backend/tests/integration/runtime.test.ts > CSMQ-14/15 authenticated PDF upload and validation integration > removes uploaded bytes if saving metadata fails and returns a safe error 133ms

✓ backend/tests/integration/runtime.test.ts > CSMQ-14/15 authenticated PDF upload and validation integration > rejects a PDF with no pages 132ms

✓ backend/tests/integration/runtime.test.ts > CSMQ-14/15 authenticated PDF upload and validation integration > enforces account hash storage and handles missing or malformed identity lookups 11ms

✓ backend/tests/integration/bulk-moderation.test.ts > bulk materials removal enforces roles/confirmation, retains audit/history and covers hidden items 204ms

✓ backend/tests/integration/bulk-moderation.test.ts > bulk questions removal enforces roles/confirmation, retains audit/history and covers hidden items 116ms

✓ backend/tests/integration/bulk-moderation.test.ts > bulk quizzes removal enforces roles/confirmation, retains audit/history and covers hidden items 90ms

✓ backend/tests/integration/quiz-contract-cross-module.test.ts > Quiz Cross-Module Contract & Comprehensive Integration (CSMQ-53) > verifies end-to-end quiz creation, persistence, model-level lookup, and safe retrieval 189ms

✓ backend/tests/integration/quiz-contract-cross-module.test.ts > Quiz Cross-Module Contract & Comprehensive Integration (CSMQ-53) > verifies cross-module contract with Karan's evaluateQuiz and QuizAttempt model without remapping 149ms

✓ backend/tests/integration/quiz-contract-cross-module.test.ts > Quiz Cross-Module Contract & Comprehensive Integration (CSMQ-53) > verifies moderation removal compatibility (softDeleteQuizById and deleteQuizById) 169ms

✓ backend/tests/integration/quiz-attempt.test.ts > QuizAttempt integration > evaluates an authenticated student attempt and persists it in MongoDB 162ms

✓ backend/tests/integration/quiz-attempt.test.ts > QuizAttempt integration > rejects an unauthenticated attempt before anything is persisted 8ms

✓ backend/tests/integration/quiz-attempt.test.ts > QuizAttempt integration > uses the authenticated user instead of a client supplied userId 127ms

✓ backend/tests/integration/quiz-attempt.test.ts > QuizAttempt integration > rejects a non-student account through the application role middleware 165ms

✓ backend/tests/integration/csmq45-history-isolation.test.ts > CSMQ-45 / real MongoDB student isolation and history > returns only the signed-in student history, including persisted quiz details 47ms

✓ backend/tests/integration/csmq45-history-isolation.test.ts > CSMQ-45 / real MongoDB student isolation and history > never returns student A data to student B 12ms

✓ backend/tests/integration/csmq45-history-isolation.test.ts > CSMQ-45 / real MongoDB student isolation and history > does not allow query parameters to change the authenticated identity 10ms

✓ backend/tests/integration/csmq45-history-isolation.test.ts > CSMQ-45 / real MongoDB student isolation and history > rejects unauthenticated access to history 4ms

✓ backend/tests/integration/csmq45-history-isolation.test.ts > CSMQ-45 / real MongoDB student isolation and history > returns the empty history state for a new student 7ms

✓ backend/tests/integration/csmq45-history-isolation.test.ts > CSMQ-45 / real MongoDB student isolation and history > respects page size and total counts without cross-user leakage 6ms

✓ backend/tests/integration/attempt-repository.test.ts > CSMQ-40: MongoDB attempt repository > fetches a quiz and its trusted questions 82ms

✓ backend/tests/integration/attempt-repository.test.ts > CSMQ-40: MongoDB attempt repository > evaluates and persists a real quiz attempt 60ms

✓ backend/tests/integration/attempt-repository.test.ts > CSMQ-40: MongoDB attempt repository > rejects a nonexistent quiz without saving 28ms

✓ backend/tests/integration/attempt-repository.test.ts > CSMQ-40: MongoDB attempt repository > rejects a removed quiz without saving 8ms

✓ backend/tests/integration/attempt-repository.test.ts > CSMQ-40: MongoDB attempt repository > rejects invalid options without persisting 7ms

✓ backend/tests/integration/csmq45-submission-acceptance.test.ts > CSMQ-45 / production POST /api/attempts acceptance > saves a server-evaluated correct/incorrect result under the authenticated student 44ms

✓ backend/tests/integration/csmq45-submission-acceptance.test.ts > CSMQ-45 / production POST /api/attempts acceptance > counts an omitted question as unanswered rather than incorrect 5ms

✓ backend/tests/integration/csmq45-submission-acceptance.test.ts > CSMQ-45 / production POST /api/attempts acceptance > rejects an unauthenticated submission without saving 4ms

✓ backend/tests/integration/csmq45-submission-acceptance.test.ts > CSMQ-45 / production POST /api/attempts acceptance > rejects invalid quiz ID without persisting 4ms

✓ backend/tests/integration/csmq45-submission-acceptance.test.ts > CSMQ-45 / production POST /api/attempts acceptance > rejects invalid question ID without persisting 3ms

✓ backend/tests/integration/csmq45-submission-acceptance.test.ts > CSMQ-45 / production POST /api/attempts acceptance > rejects invalid option without persisting 4ms

✓ backend/tests/integration/csmq45-submission-acceptance.test.ts > CSMQ-45 / production POST /api/attempts acceptance > rejects duplicate question response without persisting 3ms

✓ backend/tests/integration/csmq45-submission-acceptance.test.ts > CSMQ-45 / production POST /api/attempts acceptance > does not let client-supplied userId override the session identity 3ms

✓ backend/tests/integration/csmq45-submission-acceptance.test.ts > CSMQ-45 / production POST /api/attempts acceptance > rejects forged score/percentage values supplied by the client 3ms

Test Files 16 passed (16)

Tests 131 passed (131)

Start at 20:24:18

Duration 64.64s (tests 84%, import 15%, transform 1%)

JUNIT report written to D:/SEMESTERS/SEM5_2025/SE-JACKFRUIT/reports/integration-junit.xml

Finished UTC: 2026-11-06T14:55:23.385Z

Exit code: 0

==

COMMAND: npm run test:browser --prefix frontend

Started UTC: 2026-11-06T14:55:23.385Z

> frontend@0.0.0 test:browser

> playwright test

Running 21 tests using 1 worker

(node:1688) Warning: The 'NO_COLOR' env is ignored due to the 'FORCE_COLOR' env being set.

(Use `node --trace-warnings ...` to show where the warning was created)

vite v8.3.4 building client environment for production...

transforming...

✓ 74 modules transformed.

rendering chunks...

computing gzip size...

node_modules/.cache/e2e-production/index.html 0.67 kB │ gzip: 0.41 kB

node_modules/.cache/e2e-production/assets/index-DNSOORnA.css 77.79 kB │ gzip: 15.04 kB

node_modules/.cache/e2e-production/assets/index-sdxlfAj4.js 379.53 kB │ gzip: 112.82 kB

✓ built in 275ms

✓ 1 [chrome] › e2e\moderation.spec.ts:22:1 › bulk material moderation confirms hidden scope, supports cancellation and retains PDF audit data (1.9s)

✓ 2 [chrome] › e2e\moderation.spec.ts:90:1 › complete Student attempt, result, history and subject performance survive Quiz moderation (2.8s)

✓ 3 [chrome] › e2e\moderation.spec.ts:174:1 › real Quiz creation, discovery, trusted API scoring and confirmed Quiz moderation integrate (1.5s)

✓ 4 [chrome] › e2e\moderation.spec.ts:217:1 › student uploads, administrator confirms removal and removed content cannot be downloaded (3.2s)

✓ 5 [chrome] › e2e\moderation.spec.ts:292:1 › student loads the 26th search match and keeps the search after another upload (1.2s)

✓ 6 [chrome] › e2e\moderation.spec.ts:327:1 › Admin dashboard integrates real Question Bank moderation, responsive navigation and Student denial (2.0s)

✓ 7 [chrome] › e2e\moderation.spec.ts:394:1 › ten isolated browser sessions concurrently upload, create quizzes, submit and read their own history (9.9s)

(node:34064) Warning: The 'NO_COLOR' env is ignored due to the 'FORCE_COLOR' env being set.

(Use `node --trace-warnings ...` to show where the warning was created)

vite v8.3.4 building client environment for production...

transforming...

✓ 74 modules transformed.

rendering chunks...

computing gzip size...

node_modules/.cache/e2e-production/index.html 0.67 kB │ gzip: 0.41 kB

node_modules/.cache/e2e-production/assets/index-DNSOORnA.css 77.79 kB │ gzip: 15.04 kB

node_modules/.cache/e2e-production/assets/index-sdxlfAj4.js 379.53 kB │ gzip: 112.82 kB

✓ built in 261ms

✓ 8 [edge] › e2e\moderation.spec.ts:22:1 › bulk material moderation confirms hidden scope, supports cancellation and retains PDF audit data (1.3s)

✓ 9 [edge] › e2e\moderation.spec.ts:90:1 › complete Student attempt, result, history and subject performance survive Quiz moderation (2.9s)

✓ 10 [edge] › e2e\moderation.spec.ts:174:1 › real Quiz creation, discovery, trusted API scoring and confirmed Quiz moderation integrate (1.3s)

✓ 11 [edge] › e2e\moderation.spec.ts:217:1 › student uploads, administrator confirms removal and removed content cannot be downloaded (3.4s)

✓ 12 [edge] › e2e\moderation.spec.ts:292:1 › student loads the 26th search match and keeps the search after another upload (1.2s)

✓ 13 [edge] › e2e\moderation.spec.ts:327:1 › Admin dashboard integrates real Question Bank moderation, responsive navigation and Student denial (1.9s)

✓ 14 [edge] › e2e\moderation.spec.ts:394:1 › ten isolated browser sessions concurrently upload, create quizzes, submit and read their own history (10.6s)

(node:36072) Warning: The 'NO_COLOR' env is ignored due to the 'FORCE_COLOR' env being set.

(Use `node --trace-warnings ...` to show where the warning was created)

vite v8.3.4 building client environment for production...

transforming...

✓ 74 modules transformed.

rendering chunks...

computing gzip size...

node_modules/.cache/e2e-production/index.html 0.67 kB │ gzip: 0.41 kB

node_modules/.cache/e2e-production/assets/index-DNSOORnA.css 77.79 kB │ gzip: 15.04 kB

node_modules/.cache/e2e-production/assets/index-sdxIfAj4.js 379.53 kB │ gzip: 112.82 kB

✓ built in 1.87s

✓ 15 [firefox] › e2e\moderation.spec.ts:22:1 › bulk material moderation confirms hidden scope, supports cancellation and retains PDF audit data (11.8s)

✓ 16 [firefox] › e2e\moderation.spec.ts:90:1 › complete Student attempt, result, history and subject performance survive Quiz moderation (4.8s)

✓ 17 [firefox] › e2e\moderation.spec.ts:174:1 › real Quiz creation, discovery, trusted API scoring and confirmed Quiz moderation integrate (1.7s)

✓ 18 [firefox] › e2e\moderation.spec.ts:217:1 › student uploads, administrator confirms removal and removed content cannot be downloaded (3.4s)

✓ 19 [firefox] › e2e\moderation.spec.ts:292:1 › student loads the 26th search match and keeps the search after another upload (1.5s)

✓ 20 [firefox] › e2e\moderation.spec.ts:327:1 › Admin dashboard integrates real Question Bank moderation, responsive navigation and Student denial (2.2s)

✓ 21 [firefox] › e2e\moderation.spec.ts:394:1 › ten isolated browser sessions concurrently upload, create quizzes, submit and read their own history (15.9s)

21 passed (2.3m)

Finished UTC: 2026-11-06T14:57:41.278Z

Exit code: 0

REPORT COMMAND EXIT CODE: 0