

▼ Import Required Libraries



```
import numpy as np
import pandas as pd

from sklearn.model_selection import train_test_split

import matplotlib.pyplot as plt
import seaborn as sns
```

```
df=pd.read_csv("/content/titanic_toy.csv",usecols=['Age','Fare','Survived'])
```

```
df.sample(5)
```

	Age	Fare	Survived	
639	NaN	16.1000	0	
326	61.0	6.2375	0	
627	21.0	77.9583	1	
887	19.0	30.0000	1	
665	32.0	73.5000	0	

▼ Feature–Target Split & Train–Test Split

```
x=df.drop(columns='Survived')
y=df['Survived']
```

```
x_train,x_test,y_train,y_test=train_test_split(x,y,test_size=0.2,random_state=0)
```

▼ Create Imputed Feature Copies

```
x_train['age_imputed']=x_train['Age']
x_test['age_imputed']=x_test['Age']
x_train['fare_imputed']=x_train['Fare']
x_test['fare_imputed']=x_test['Fare']
```

Missing Value Imputation (Random Sampling)

```
x_train['age_imputed'][x_train['age_imputed'].isnull()]=x_train['Age'].dropna().sample(x_train['age_imputed'].isnull().sum())
x_test['age_imputed'][x_test['age_imputed'].isnull()]=x_test['Age'].dropna().sample(x_test['age_imputed'].isnull().sum())
x_train['fare_imputed'][x_train['fare_imputed'].isnull()]=x_train['Fare'].dropna().sample(x_train['fare_imputed'].isnull().sum())
x_test['fare_imputed'][x_test['fare_imputed'].isnull()]=x_test['Fare'].dropna().sample(x_test['fare_imputed'].isnull().sum())
```

/tmp/ipython-input-3530151679.py:1: FutureWarning: ChainedAssignmentError: behaviour will change in the future. You are setting values through chained assignment. Currently this works in certain cases, but it is deprecated. A typical example is when you are setting values in a column of a DataFrame, like:

```
df["col"][row_indexer] = value
```

Use `df.loc[row_indexer, "col"] = values` instead, to perform the assignment in a single step

See the caveats in the documentation: https://pandas.pydata.org/pandas-docs/stable/user_guide

```
x_train['age_imputed'][x_train['age_imputed'].isnull()]=x_train['Age'].dropna().sample(x_train['age_imputed'].isnull().count())
```

/tmp/ipython-input-3530151679.py:2: FutureWarning: ChainedAssignmentError: behaviour will change in a future version. You are setting values through chained assignment. Currently this works in certain cases, but A typical example is when you are setting values in a column of a DataFrame, like:

```
df["col"][row_indexer] = value
```

Use `df.loc[row_indexer, "col"] = values` instead, to perform the assignment in a single step

See the caveats in the documentation: https://pandas.pydata.org/pandas-docs/stable/user_guide

```
x_test['age_imputed'][x_test['age_imputed'].isnull()]=x_test['Age'].dropna().sample(x_test['age_imputed'].isnull().count())
```

/tmp/ipython-input-3530151679.py:3: FutureWarning: ChainedAssignmentError: behaviour will change in a future version. You are setting values through chained assignment. Currently this works in certain cases, but A typical example is when you are setting values in a column of a DataFrame, like:

```
df["col"][row_indexer] = value
```

Use `df.loc[row_indexer, "col"] = values` instead, to perform the assignment in a single step

See the caveats in the documentation: https://pandas.pydata.org/pandas-docs/stable/user_guide

```
x_train['fare_imputed'][x_train['fare_imputed'].isnull()]=x_train['Fare'].dropna().sample(x_train['fare_imputed'].isnull().count())
```

/tmp/ipython-input-3530151679.py:4: FutureWarning: ChainedAssignmentError: behaviour will change in a future version. You are setting values through chained assignment. Currently this works in certain cases, but A typical example is when you are setting values in a column of a DataFrame, like:

```
df["col"][row_indexer] = value
```

Use `df.loc[row_indexer, "col"] = values` instead, to perform the assignment in a single step

See the caveats in the documentation: https://pandas.pydata.org/pandas-docs/stable/user_guide

```
x_test['fare_imputed'][x_test['fare_imputed'].isnull()]=x_test['Fare'].dropna().sample(x_test['fare_imputed'].isnull().count())
```

x_train

	Age	Fare	age_imputed	fare_imputed	
140	NaN	15.2458	36.0	15.2458	
439	31.0	10.5000	31.0	10.5000	
817	31.0	37.0042	31.0	37.0042	
378	20.0	NaN	20.0	26.5500	
491	21.0	7.2500	21.0	7.2500	
...	
835	39.0	83.1583	39.0	83.1583	
192	19.0	7.8542	19.0	7.8542	
629	NaN	7.7333	28.0	7.7333	
559	36.0	17.4000	36.0	17.4000	
684	60.0	39.0000	60.0	39.0000	

712 rows × 4 columns



Distribution Comparison: Before vs After Imputation

```
sns.distplot(x_train['Age'],label='Original',hist=False)
sns.distplot(x_train['age_imputed'],label='Imputes',hist=False)
plt.legend()
plt.show()
```

/tmp/ipython-input-2255413705.py:1: UserWarning:

`distplot` is a deprecated function and will be removed in seaborn v0.14.0.

Please adapt your code to use either `displot` (a figure-level function with similar flexibility) or `kdeplot` (an axes-level function for kernel density plots).

For a guide to updating your code to use the new functions, please see

<https://gist.github.com/mwaskom/de44147ed2974457ad6372750bbe5751>

```
sns.distplot(x_train['Age'],label='Original',hist=False)
```

/tmp/ipython-input-2255413705.py:2: UserWarning:


`distplot` is a deprecated function and will be removed in seaborn v0.14.0.

Please adapt your code to use either `displot` (a figure-level function with similar flexibility) or `kdeplot` (an axes-level function for kernel density plots).

For a guide to updating your code to use the new functions, please see

<https://gist.github.com/mwaskom/de44147ed2974457ad6372750bbe5751>

```
sns.distplot(x_train['age_imputed'],label='Imputes',hist=False)
```



```
sns.distplot(x_train['Fare'],label="Original",hist=False)
sns.distplot(x_train['fare_imputed'],label="Imputed",hist=False)
plt.legend()
plt.show()
```

```
/tmp/ipython-input-4221924458.py:1: UserWarning:
```

`distplot` is a deprecated function and will be removed in seaborn v0.14.0.

Please adapt your code to use either `displot` (a figure-level function with similar flexibility) or `kdeplot` (an axes-level function for kernel density plots).

For a guide to updating your code to use the new functions, please see <https://gist.github.com/mwaskom/de44147ed2974457ad6372750bbe5751>


```
sns.distplot(x_train['Fare'],label="Original",hist=False)
/tmp/ipython-input-4221924458.py:2: UserWarning:
```

`distplot` is a deprecated function and will be removed in seaborn v0.14.0.

Please adapt your code to use either `displot` (a figure-level function with similar flexibility) or `kdeplot` (an axes-level function for kernel density plots).


For a guide to updating your code to use the new functions, please see <https://gist.github.com/mwaskom/de44147ed2974457ad6372750bbe5751>

```
sns.distplot(x_train['fare_imputed'],label="Imputed",hist=False)
```




```
x_train[['Age','age_imputed']].boxplot()
```

<Axes: >



```
x_train[['Fare', 'fare_imputed']].boxplot()
```

<Axes: >



Start coding on [generate](#) with AI.